

CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

Label Printer

MODEL NUMBER: EP71, P71, P71A, P71B, P71C, P71S, P71T, GTP71, GTP71E, GTP71F, GTP71G, GTP71H, GP71, GP71T, GP71U, GP71V, GP71W, GP71X, GP71Y, EP71, EP71R, P71-3R, P71A-3R, P71S-3R, GTP71-3R, GTP71G-3R, GTP71H-3R, GP71-3R, GP71T-3R, GP71U-3R, EP71-3R, EP71R-3R, AP71, AP71A, AP71S, AP71T, AP71P, AP71-3R, AP71A-3R, AP71S-3R, AP71T-3R, BP71, BP71S, BP71-3R, BP71S-3R, W1610, W1610A, W1610B, W1610S, W1610P, W1610, W1610A-3R, W1610B-3R, W1610S-3R, W1610P-3R, M400B, M400B-S, M400B-T, M400B-P, M400B-A, M400B-3R, M400B-S3R, M400B-T3R, M400B-P3R, M400B-A3R, EM7B, EM7B-S, EM7B-P, EM7B-3R, EM7B-S3R, EM7B-P3R, PB7, PB7A, PB7B, PB7H, PB7G, PB7-3R, PB7A-3R, PB7B-3R, PB7H-3R, PB7G-3R

REPORT NUMBER: E04A26040684F00101

ISSUE DATE: August 17, 2026

FCC ID: 2BLKN-EP71

Prepared for

**Chongqing Pinsheng Technology Co., Ltd.
7Floor, No.5 middle Huangshan Avenue, North New Zone, Chongqing**

Prepared by

Guangdong Global Testing Technology Co., Ltd.

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park,
Dongguan city, Guangdong, People's Republic of China, 523808**

This report is based on a single evaluation of the submitted sample(s) of the above mentioned product, it does not imply an assessment of the production of the products.

This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	August 17, 2026	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2020, Clause 11.9.1.2	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020, Clause 11.8.1 or 11.8.2	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2020, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2020, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020, Clause 11.12	FCC Part 15.247(d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

Note:

1. For ISED, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 standards.
2. N/A: In this whole report not applicable.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 Issue 4> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>8</i>
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	<i>9</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>MAXIMUM CONDUCTED OUTPUT POWER</i>	<i>10</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>10</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>10</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>11</i>
5.8. <i>SETUP DIAGRAM</i>	<i>11</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	12
7. ANTENNA PORT TEST RESULTS	14
7.1. <i>Conducted Output Power.....</i>	<i>14</i>
7.2. <i>6dB Bandwidth and 99% Occupied Bandwidth</i>	<i>15</i>
7.3. <i>Power Spectral Density.....</i>	<i>17</i>
7.4. <i>Conducted Band edge and spurious emission</i>	<i>18</i>
7.5. <i>Duty Cycle</i>	<i>20</i>
8. RADIATED TEST RESULTS.....	21
8.1. <i>Radiated Band edge and Spurious Emission</i>	<i>26</i>
9. ANTENNA REQUIREMENT	38
10. AC POWER LINE CONDUCTED EMISSION	40

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Chongqing Pinsheng Technology Co., Ltd.
Address: 7Floor, No.5 middle Huangshan Avenue, North New Zone, Chongqing

Manufacturer Information

Company Name: Chongqing Pinsheng Technology Co., Ltd.
Address: 7Floor, No.5 middle Huangshan Avenue, North New Zone, Chongqing

EUT Information

Product Description: Label Printer
Model: EP71
Series Model: P71, P71A, P71B, P71C, P71S, P71T, GTP71, GTP71E, GTP71F, GTP71G, GTP71H, GP71, GP71T, GP71U, GP71V, GP71W, GP71X, GP71Y, EP71, EP71R, P71-3R, P71A-3R, P71S-3R, GTP71-3R, GTP71G-3R, GTP71H-3R, GP71-3R, GP71T-3R, GP71U-3R, EP71-3R, EP71R-3R, AP71, AP71A, AP71S, AP71T, AP71P, AP71-3R, AP71A-3R, AP71S-3R, AP71T-3R, BP71, BP71S, BP71-3R, BP71S-3R, W1610, W1610A, W1610B, W1610S, W1610P, W1610, W1610A-3R, W1610B-3R, W1610S-3R, W1610P-3R, M400B, M400B-S, M400B-T, M400B-P, M400B-A, M400B-3R, M400B-S3R, M400B-T3R, M400B-P3R, M400B-A3R, EM7B, EM7B-S, EM7B-P, EM7B-3R, EM7B-S3R, EM7B-P3R, PB7, PB7A, PB7B, PB7H, PB7G, PB7-3R, PB7A-3R, PB7B-3R, PB7H-3R, PB7G-3R
Brand: WEWIN, JINGJING, MAKEID
Sample Received Date: June 18, 2026
Sample Status: Normal
Sample ID: A26040684 001
Date of Tested: June 18, 2026 to July 16, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass

Prepared By:



Ekko Wu

Project Engineer

Checked By:



Alan He

Laboratory Leader

Approved By:



Alan He

Laboratory Manager



2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 4, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2020, ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 6947.01) Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1343) Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules ISED (Company No.: 30714) Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		Label Printer
Model		EP71
Series Model		P71, P71A, P71B, P71C, P71S, P71T, GTP71, GTP71E, GTP71F, GTP71G, GTP71H, GP71, GP71T, GP71U, GP71V, GP71W, GP71X, GP71Y, EP71, EP71R, P71-3R, P71A-3R, P71S-3R, GTP71-3R, GTP71G-3R, GTP71H-3R, GP71-3R, GP71T-3R, GP71U-3R, EP71-3R, EP71R-3R, AP71, AP71A, AP71S, AP71T, AP71P, AP71-3R, AP71A-3R, AP71S-3R, AP71T-3R, BP71, BP71S, BP71-3R, BP71S-3R, W1610, W1610A, W1610B, W1610S, W1610P, W1610, W1610A-3R, W1610B-3R, W1610S-3R, W1610P-3R, M400B, M400B-S, M400B-T, M400B-P, M400B-A, M400B-3R, M400B-S3R, M400B-T3R, M400B-P3R, M400B-A3R, EM7B, EM7B-S, EM7B-P, EM7B-3R, EM7B-S3R, EM7B-P3R, PB7, PB7A, PB7B, PB7H, PB7G, PB7-3R, PB7A-3R, PB7B-3R, PB7H-3R, PB7G-3R
Model Difference		All models are the same except for the model names, colors, Resolution, Brands.
Hardware Version		V1.0
Software Version		V1.0
Ratings		5V 1.4A; 7.4V 2600mAh 19.24Wh
Power Supply	AC	120V/60Hz
	DC	5V
	Battery	7.4V 2600mAh 19.24Wh

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth 5.4
Bluetooth Mode:	Bluetooth LE
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Normal Test Voltage:	5 V
Note:	The Antenna Gain was provided by customer, and this information may affect the validity of the results, customer should be responsible for this.

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470

2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2466	/	/

5.3. MAXIMUM CONDUCTED OUTPUT POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
GFSK(1Mbps)	2402 ~ 2480	0-39[40]	0.01	/

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK(1Mbps)	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software Version		BR BlueletSuite_v6.3		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	1	7	7	7

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	PCB	1.4

Test Mode	Transmit and Receive Mode	Description
GFSK(1Mbps)	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5.7. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.


Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo	T14	/	GTG Support
E-1	Adapter	Xiaomi	MDY-11-EX	N/A	GTG Support

5.8. SETUP DIAGRAM

Radiated emissions:



AC Power Line Conducted Emission:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2025/08/25	2026/08/24
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2025/08/25	2026/08/24
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2025/08/25	2026/08/24
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2025/08/25	2026/08/24
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2025/08/25	2026/08/24
temperature humidity chamber	Espec	SH-241	SH-241-2014	2025/08/25	2026/08/24
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESCI3	101144	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2025/08/23	2026/08/22
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2025/09/20	2028/09/19
Biconilog Antenna	ETS	3142E	00243651	2025/02/22	2028/02/21
Loop Antenna	ETS	6502	00243668	2025/02/22	2028/02/21
RF Cable	TIMES Microwave	LMR240UF-NMMN-14M	N/A	2025/08/23	2026/08/22
RF Cable	TIMES Microwave	HF205-NMMN-11.00M	N/A	2025/08/23	2026/08/22
RF Cable	JCT	JCT-06S-NJ-NJ-2.5M	N/A	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2025/08/23	2026/08/22
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-1G1850	HYPA21003	2025/08/23	2026/08/22

Horn antenna	ETS	3117	00246069	2025/02/22	2028/02/21
Pre-Amplifier	HzEMC	HPA-184057	HYP A21004	2025/08/23	2026/08/22
Horn antenna	ETS	3116C	00246265	2025/02/22	2028/02/21
RF Filter Bank	HzEMC	HSW-F18	HSWF2218E01	2025/08/23	2026/08/22
RF Filter Bank	HzEMC	HPF18	HPF2218E02	2025/08/23	2026/08/22
RF Cable	TIMES Microwave	HF205-NMNM- 7.00M	N/A	2025/08/23	2026/08/22
RF Cable	TIMES Microwave	HF205-NMNM- 2.50M	N/A	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2025/08/23	2026/08/22
LISN/AMN	Rohde & Schwarz	ENV216	102843	2025/08/23	2026/08/22
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 6.3.2	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor and meter or Spectrum analyzer (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 6.3.1(a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.8.1 or 11.8.2 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission or The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100$ kHz, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.10.2.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
FCC Part 15.247(d)	Conducted Band edge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.11.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1G

The setting of the spectrum analyzer


RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


TEST SETUP**TEST ENVIRONMENT**

Temperature	22.5°C	Relative Humidity	63%
Atmosphere Pressure	101kPa		

TEST RESULTS**8.1. RADIATED BAND EDGE AND SPURIOUS EMISSION**

Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

All modes have been tested and the worst result as bellow:




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	48.43	49.15	30.50	-18.65	40.00	9.50	PK	Vertical	PASS
2	59.10	54.58	34.53	-20.05	40.00	5.47	PK	Vertical	PASS
3	71.71	45.66	23.96	-21.70	40.00	16.04	PK	Vertical	PASS
4	143.49	51.62	33.40	-18.22	43.50	10.10	PK	Vertical	PASS
5	167.74	51.78	32.81	-18.97	43.50	10.69	PK	Vertical	PASS
6	255.04	47.74	27.56	-20.18	46.00	18.44	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2402
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	60.07	44.25	24.05	-20.20	40.00	15.95	PK	Horizontal	PASS
2	95.96	42.45	19.54	-22.91	43.50	23.96	PK	Horizontal	PASS
3	120.21	44.73	24.26	-20.47	43.50	19.24	PK	Horizontal	PASS
4	143.49	58.64	40.42	-18.22	43.50	3.08	PK	Horizontal	PASS
5	167.74	57.06	38.09	-18.97	43.50	5.41	PK	Horizontal	PASS
6	288.02	48.75	29.51	-19.24	46.00	16.49	PK	Horizontal	PASS


Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

Project Information

EUT Model I	P71	Channel	2402
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	1940.31	54.81	45.04	-9.77	74.00	28.96	PK	Vertical	PASS
2	2401.80	52.64	44.11	-8.53	74.00	29.89	PK	Vertical	PASS
3	2958.65	52.00	44.64	-7.36	74.00	29.36	PK	Vertical	PASS
4	4800.60	61.62	50.29	-11.33	74.00	23.71	PK	Vertical	PASS
5	7976.66	50.22	42.23	-7.99	74.00	31.77	PK	Vertical	PASS
6	10507.50	48.38	42.88	-5.50	74.00	31.12	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2402
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2145.05	55.93	46.88	-9.05	74.00	27.12	PK	Horizontal	PASS
2	2401.80	54.30	45.77	-8.53	74.00	28.23	PK	Horizontal	PASS
3	2841.28	52.63	44.70	-7.93	74.00	29.30	PK	Horizontal	PASS
4	4800.60	63.29	51.96	-11.33	74.00	22.04	PK	Horizontal	PASS
5	7156.39	49.82	41.87	-7.95	74.00	32.13	PK	Horizontal	PASS
6	10357.45	48.46	42.64	-5.82	74.00	31.36	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2440
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2141.05	54.37	45.33	-9.04	74.00	28.67	PK	Vertical	PASS
2	2512.50	55.63	47.15	-8.48	74.00	26.85	PK	Vertical	PASS
3	3490.16	56.51	42.41	-14.10	74.00	31.59	PK	Vertical	PASS
4	4880.63	61.75	50.62	-11.13	74.00	23.38	PK	Vertical	PASS
5	6066.02	50.26	42.25	-8.01	74.00	31.75	PK	Vertical	PASS
6	10832.61	48.51	43.39	-5.12	74.00	30.61	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2440
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2142.38	55.89	46.84	-9.05	74.00	27.16	PK	Horizontal	PASS
2	2512.50	54.69	46.21	-8.48	74.00	27.79	PK	Horizontal	PASS
3	2998.00	52.25	45.24	-7.01	74.00	28.76	PK	Horizontal	PASS
4	4880.63	63.70	52.57	-11.13	74.00	21.43	PK	Horizontal	PASS
5	5630.88	50.39	41.18	-9.21	74.00	32.82	PK	Horizontal	PASS
6	8306.77	49.25	41.39	-7.86	74.00	32.61	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2480
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2143.71	54.07	45.02	-9.05	74.00	28.98	PK	Vertical	PASS
2	2504.50	61.39	52.98	-8.41	74.00	21.02	PK	Vertical	PASS
3	2981.33	51.57	44.60	-6.97	74.00	29.40	PK	Vertical	PASS
4	4955.65	62.96	51.59	-11.37	74.00	22.41	PK	Vertical	PASS
5	7221.41	49.53	41.48	-8.05	74.00	32.52	PK	Vertical	PASS
6	10857.62	48.82	43.70	-5.12	74.00	30.30	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2480
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2146.38	56.11	47.07	-9.04	74.00	26.93	PK	Horizontal	PASS
2	2504.50	59.30	50.89	-8.41	74.00	23.11	PK	Horizontal	PASS
3	2976.66	52.44	45.39	-7.05	74.00	28.61	PK	Horizontal	PASS
4	4960.65	63.31	51.97	-11.34	74.00	22.03	PK	Horizontal	PASS
5	7921.64	50.11	42.06	-8.05	74.00	31.94	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


Band Edge

All modes have been tested and the worst result as bellow:

Project Information

EUT Model	P71	Channel	2402
Test Mode	BT	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph



Suspected Data List


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2382.31	28.26	50.83	22.57	74.00	23.17	PK	Vertical	PASS
2	2390.00	26.43	49.15	22.72	74.00	24.85	PK	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2402
Test Mode	BT	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**


NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2383.67	28.40	51.00	22.60	74.00	23.00	PK	Horizontal	PASS
2	2390.00	25.80	48.52	22.72	74.00	25.48	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2480
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	24.49	47.64	23.15	74.00	26.36	PK	Vertical	PASS
2	2504.25	32.34	55.43	23.09	74.00	18.57	PK	Vertical	PASS

Final Data List


NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Pol	Verdict
1	2504.02	23.09	26.43	49.52	54.00	4.48	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Project Information

EUT Model	P71	Channel	2480
Test Mode	BLE	Operating Mode	TX
Bandwidth	1MHZ	Power Level	/
Environment	Temp: 22.5°C; Humi:63%	Test Date	2026-07-02
Note	/	Engineer	Ren

Test Graph**Suspected Data List**

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	24.37	47.52	23.15	74.00	26.48	PK	Horizontal	PASS
2	2504.08	30.54	53.63	23.09	74.00	20.37	PK	Horizontal	PASS

Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Pol	Verdict
1	2504.01	23.09	25.58	48.67	54.00	5.33	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Standard	Requirement
RSS-Gen issue 5 6.8.	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list. For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested. For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location: This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

	Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.
--	---

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	23.2°C	Relative Humidity	52%
Atmosphere Pressure	101kPa		

TEST RESULTS

Phase: N

Mode: BLE 1M 2480MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2175	28.34	9.65	37.99	62.91	-24.92	QP
2	0.2175	3.87	9.65	13.52	52.91	-39.39	AVG
3	0.4110	21.16	9.63	30.79	57.63	-26.84	QP
4	0.4110	5.27	9.63	14.90	47.63	-32.73	AVG
5	0.8250	12.79	9.65	22.44	56.00	-33.56	QP
6	0.8250	2.85	9.65	12.50	46.00	-33.50	AVG
7	1.8870	10.01	9.66	19.67	56.00	-36.33	QP
8	1.8870	-2.77	9.66	6.89	46.00	-39.11	AVG
9	6.8595	15.39	9.89	25.28	60.00	-34.72	QP
10	6.8595	0.13	9.89	10.02	50.00	-39.98	AVG
11	22.2405	8.97	10.48	19.45	60.00	-40.55	QP
12	22.2405	-3.47	10.48	7.01	50.00	-42.99	AVG



Phase: L1

Mode: BLE 1M 2480MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1770	30.21	9.69	39.90	64.63	-24.73	QP
2	0.1770	4.80	9.69	14.49	54.63	-40.14	AVG
3	0.4110	19.55	9.60	29.15	57.63	-28.48	QP
4	0.4110	4.78	9.60	14.38	47.63	-33.25	AVG
5	0.9645	11.83	9.65	21.48	56.00	-34.52	QP
6	0.9645	-1.74	9.65	7.91	46.00	-38.09	AVG
7	1.9185	10.23	9.73	19.96	56.00	-36.04	QP
8	1.9185	-2.02	9.73	7.71	46.00	-38.29	AVG
9	4.7760	10.20	9.83	20.03	56.00	-35.97	QP
10	4.7760	-3.53	9.83	6.30	46.00	-39.70	AVG
11	9.9330	13.66	10.16	23.82	60.00	-36.18	QP
12	9.9330	-1.93	10.16	8.23	50.00	-41.77	AVG

END OF REPORT