



Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community,
Fenghuang Street, Guangming District, Shenzhen, China

FCC PART 15 SUBPART C TEST REPORT
FCC PART 15.247

Report Reference No..... : GRCTR251202032-01

FCC ID..... : 2BLKS-GKD62

Compiled by

(position+printed name+signature)..: Testing Engineer Jimmy Wang

Supervised by

(position+printed name+signature)..: Project Engineer Kelley Zhang

Approved by

(position+printed name+signature)..: Manager Sam Wang

Date of issue..... : Jan. 27, 2026



Testing Laboratory Name..... : **Shenzhen GUOREN Certification Technology Service Co., Ltd.**

Address..... : 101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

Applicant's name..... : **SHENZHEN CHL INDUSTRIES CO.,LTD**

Address..... : ROOM 6F, 6/F, NANYUAN MAPLE BUILDING, NANSHAN AVENUE, NANSHAN DISTRICT, SHENZHEN CITY, GUANGDONG, China

Test specification..... :

Standard..... : **FCC Part 15.247**

Shenzhen GUOREN Certification Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen GUOREN Certification Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen GUOREN Certification Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : **Party Speaker with Flame Light**

Trade Mark..... : /

Manufacturer..... : SHENZHEN CHL INDUSTRIES CO.,LTD

Model/Type reference..... : GKD62

Listed Models : GKD62-A,GKD62-B,GKD62-C,GKD62-D,GKD62-E,GKD62-F,GKS80, GKS80-A,GKS80-B,GKS80-C,GKS80-D,GKS80-E,GKS80-F

Firmware Version..... : V1.0

Hardware Version..... : V1.0

Modulation : GFSK, π /4DQPSK,8DPSK

Frequency..... : From 2402MHz to 2480MHz

Rating..... : DC 5V $\overline{\text{---}}$ 2A Powered by adapter or
7.4V $\overline{\text{---}}$ 5400mAh (By Li-ion rechargeable battery)

Result..... : **PASS**

TEST REPORT

Equipment under Test : Party Speaker with Flame Light

Model /Type : GKD62

Listed Models : GKD62-A,GKD62-B,GKD62-C,GKD62-D,GKD62-E,GKD62-F,GKS80,GKS80-A,GKS80-B,GKS80-C,GKS80-D,GKS80-E,GKS80-F

Applicant : **SHENZHEN CHL INDUSTRIES CO.,LTD**

Address : ROOM 6F, 6/F, NANYUAN MAPLE BUILDING, NANSHAN AVENUE, NANSHAN DISTRICT, SHENZHEN CITY, GUANGDONG, China

Manufacturer : **SHENZHEN CHL INDUSTRIES CO.,LTD**

Address : ROOM 6F, 6/F, NANYUAN MAPLE BUILDING, NANSHAN AVENUE, NANSHAN DISTRICT, SHENZHEN CITY, GUANGDONG, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 TEST STANDARDS	4
2 SUMMARY	5
2.1 General Remarks	5
2.2 Product Description	5
2.3 Equipment Under Test	5
2.4 Short description of the Equipment under Test (EUT)	5
2.5 EUT configuration	6
2.6 EUT operation mode	6
2.7 Block Diagram of Test Setup	6
2.8 Related Submittal(s) / Grant (s)	7
2.9 Modifications	7
3 TEST ENVIRONMENT	8
3.1 Address of the test laboratory	8
3.2 Test Facility	8
3.3 Environmental conditions	8
3.4 Summary of measurement results	8
3.5 Statement of the measurement uncertainty	9
3.6 Equipments Used during the Test	9
4 TEST CONDITIONS AND RESULTS	11
4.1 AC Power Conducted Emission	11
4.2 Radiated Emission	14
4.3 Maximum Peak Output Power	34
4.4 20dB Bandwidth	35
4.5 Frequency Separation	39
4.6 Number of hopping frequency	41
4.7 Time of Occupancy (Dwell Time)	43
4.8 Out-of-band Emissions	47
4.9 Pseudorandom Frequency Hopping Sequence	56
4.10 Antenna Requirement	57
5 TEST SETUP PHOTOS OF THE EUT	58
6 PHOTOS OF THE EUT	60

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024](#): American National Standard for Testing Unlicensed Wireless Devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Dec. 22, 2025
Testing commenced on	:	Dec. 22, 2025
Testing concluded on	:	Jan. 27, 2026

2.2 Product Description

Product Name:	Party Speaker with Flame Light
Model/Type reference:	GKD62
Listed Models:	GKD62-A,GKD62-B,GKD62-C,GKD62-D,GKD62-E,GKD62-F,GKS80,GKS80-A,GKS80-B,GKS80-C,GKS80-D,GKS80-E,GKS80-F (The products are identical in interior structure, electrical circuits and components, just model names and color are different.)
Power supply:	DC 5V $\overline{\text{---}}$ 2A Powered by adapter or 7.4V $\overline{\text{---}}$ 5400mAh (By Li-ion rechargeable battery)
Testing sample ID:	GRCTR251202032-1# (Engineer sample), GRCTR251202032-2# (Normal sample)
Bluetooth	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB antenna
Antenna gain*(Supplied by the customer):	1.70 dBi
Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.	

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 5V Powered by adapter

2.4 Short description of the Equipment under Test (EUT)

This is a Party Speaker with Flame Light.

For more details, refer to the user's manual of the EUT.

2.5 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○ Adapter	M/N:	TPA-83A050200CU01
	Manufacturer:	Tianyin

2.6 EUT operation mode


The Applicant provides communication tools software(SecureCRT Version 7.0.0) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing. There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:


Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
38	2440
39	2441
40	2442
⋮	⋮
77	2479
78	2480

2.7 Block Diagram of Test Setup

AC Power Conducted Emission & Radiated Emissions(below 1GHz&above1GHz)&Band Edge(Radiated)



RF Measurement



2.8 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.9 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 920798 Designation Number: CN1304

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6202.01

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27264 CAB identifier: CN0115

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

CNAS-Lab Code: L15631

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature	15-35 °C
Relative Humidity	30-60 %
Air Pressure	950-1050mbar

3.4 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Test result
§15.247(a)(1)	Carrier Frequency separation	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Number of Hopping channels	GFSK Π/4DQPSK 8DPSK	☒ Full	GFSK Π/4DQPSK 8DPSK	☒ Full	Compliant
§15.247(a)(1)	Time of Occupancy (dwell time)	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Spectrum bandwidth of aFHSS system 20dB bandwidth	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant

§15.247(b)(1)	Maximum output peak power	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	Band edge compliance conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.205	Band edge compliance radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.247(d)	TX spurious emissions conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	TX spurious emissions radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.209(a)	TX spurious Emissions radiated Below 1GHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	Compliant
§15.107(a) §15.207	Conducted Emissions 9KHz-30 MHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	Compliant

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report.
3. N/A means “not applicable”.

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01” Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1” and TR-100028-02 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 “ and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Max output power	30MHz~18GHz	0.54 dB	(1)
Spectrum bandwidth	/	1.2%	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	GRCTEE009	2025/09/11	2026/09/10
LISN	R&S	ENV216	GRCTEE010	2025/09/11	2026/09/10
EMI Test Receiver	R&S	ESPI	GRCTEE017	2025/09/11	2026/09/10
EMI Test Receiver	R&S	ESCI	GRCTEE008	2025/09/11	2026/09/10

Spectrum Analyzer	Agilent	N9020A	GRCTEE002	2025/09/11	2026/09/10
Spectrum Analyzer	R&S	FSP	GRCTEE003	2025/09/12	2026/09/11
Vector Signal generator	Agilent	N5181A	GRCTEE007	2025/09/11	2026/09/10
Analog Signal Generator	R&S	SML03	GRCTEE006	2025/09/11	2026/09/10
Climate Chamber	QIYA	LCD-9530	GRCTES016	2025/09/11	2026/09/10
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	GRCTEE018	2023/09/28	2026/09/27
Horn Antenna	Schwarzbeck	BBHA 9120D	GRCTEE019	2023/09/28	2026/09/27
Loop Antenna	Zhinan	ZN30900C	GRCTEE020	2023/10/15	2026/10/14
Horn Antenna	Beijing Hangwei Dayang	OBH100400	GRCTEE049	2023/09/28	2026/09/27
Amplifier	Schwarzbeck	BBV 9745	GRCTEE021	2025/09/11	2026/09/10
Amplifier	Taiwan chengyi	EMC051845B	GRCTEE022	2025/09/11	2026/09/10
Temperature/Humidity Meter	Huaguan	HG-308	GRCTES037	2025/09/11	2026/09/10
Directional coupler	NARDA	4226-10	GRCTEE004	2025/09/11	2026/09/10
High-Pass Filter	XingBo	XBLBQ-GTA18	GRCTEE053	2025/09/11	2026/09/10
High-Pass Filter	XingBo	XBLBQ-GTA27	GRCTEE054	2025/09/11	2026/09/10
Automated filter bank	Tonscend	JS0806-F	GRCTEE055	2025/09/11	2026/09/10
Power Sensor	Agilent	U2021XA	GRCTEE070	2025/09/11	2026/09/10
Cable	Times	Cable-CE	GRCTEE086	2025/09/11	2026/09/10
Cable	Times	Cable-RE-1	GRCTEE087	2025/09/11	2026/09/10
Cable	Times	Cable-RE-2	GRCTEE088	2025/09/11	2026/09/10
EMI Test Software	ROHDE & SCHWARZ	ESK1-V1.71	GRCTEE060	N/A	N/A
EMI Test Software	Fera	EZ-EMC	GRCTEE061	N/A	N/A

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 Where floor-standing equipment is not typically installed with its base in direct electrical contact with, or connected to, a metal floor or grid, the EUT shall not be placed in direct electrical contact with the test site (or turntable) reference ground plane. If necessary to prevent direct metallic contact of the EUT and the reference ground plane, insulating material (up to 12mm thick) shall be placed under the EUT.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024.
- 4 The EUT received power from variable frequency power supply, the AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. All modes of GFSK, $\pi/4$ DQPSK and 8DPSK were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:



MEASUREMENT RESULT: "GRCT251227004_fin"

12/27/2025 11:26AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.194000	52.40	10.4	64	11.5	QP	L1	GND
0.254000	45.70	10.3	62	15.9	QP	L1	GND
0.262000	45.20	10.2	61	16.2	QP	L1	GND
0.858000	34.30	10.3	56	21.7	QP	L1	GND
12.314000	37.30	10.6	60	22.7	QP	L1	GND
12.782000	37.80	10.6	60	22.2	QP	L1	GND

MEASUREMENT RESULT: "GRCT251227004_fin2"

12/27/2025 11:26AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.186000	33.80	10.3	54	20.4	AV	L1	GND
0.254000	30.30	10.3	52	21.3	AV	L1	GND
0.622000	23.80	10.5	46	22.2	AV	L1	GND
3.714000	23.10	10.5	46	22.9	AV	L1	GND
12.238000	29.80	10.6	50	20.2	AV	L1	GND
12.546000	31.00	10.6	50	19.0	AV	L1	GND

Note:1).Level (dBμV)= Reading (dBμV)+ Transducer (dB)

2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)


3). Margin(dB) = Limit (dBμV) - Level (dBμV)

Power supply:

DC 5V from Adapter
AC 120V/60Hz

Polarization

N

**MEASUREMENT RESULT: "GRCT251227003_fin"**

12/27/2025 11:21AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.190000	53.80	10.3	64	10.2	QP	N	GND
0.198000	52.80	10.4	64	10.9	QP	N	GND
0.334000	39.70	10.3	59	19.7	QP	N	GND
0.342000	39.20	10.4	59	20.0	QP	N	GND
2.986000	29.60	10.5	56	26.4	QP	N	GND
11.810000	36.40	10.7	60	23.6	QP	N	GND

MEASUREMENT RESULT: "GRCT251227003_fin2"

12/27/2025 11:30AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.182000	36.10	10.3	54	17.9	AV	N	GND
0.254000	31.70	10.3	52	19.9	AV	N	GND
0.450000	23.70	10.3	47	23.2	AV	N	GND
3.746000	23.20	10.5	46	22.8	AV	N	GND
12.018000	29.60	10.6	50	20.4	AV	N	GND
12.398000	28.80	10.6	50	21.2	AV	N	GND

Note:1).Level (dBμV)= Reading (dBμV)+ Transducer (dB)


2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBμV) - Level (dBμV)


4.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 12mm above ground plane when testing frequency range 9 KHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-40GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.


The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
3. For below 1GHz testing recorded worst at GFSK DH5 Middle channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz**Horizontal****Radiated Emission Measurement**

Site LAB

Polarization: **Horizontal**

Temperature: 24.5(C)

Limit: FCC Part15 RE-Class B_30-1000MHz

Power: AC120V/60Hz

Humidity: 52 %

EUT:

Distance: 3m

M/N:

Mode:

Note:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	62.6505	42.18	-19.46	22.72	40.00	-17.28	peak	100	147	P	
2	110.9571	44.47	-19.50	24.97	43.50	-18.53	peak	100	243	P	
3	143.3261	44.84	-21.81	23.03	43.50	-20.47	peak	200	297	P	
4	179.3863	46.71	-20.76	25.95	43.50	-17.55	peak	200	225	P	
5	231.7179	42.36	-18.56	23.80	46.00	-22.20	peak	200	234	P	
6	419.1080	37.72	-15.50	22.22	46.00	-23.78	peak	100	208	P	

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBuV/m) - Limit (dBuV/m)

Vertical

Radiated Emission Measurement



Site LAB

Polarization: *Vertical*

Temperature: 24.5(C)

Limit: FCC Part15 RE-Class B_30-1000MHz

Power: AC120V/60Hz

Humidity: 52 %

EUT:

Distance: 3m

M/N:

Mode:

Note:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	48.5015	47.10	-17.49	29.61	40.00	-10.39	peak	100	177	P	
2 *	58.8185	51.51	-18.65	32.86	40.00	-7.14	peak	100	306	P	
3	78.1389	54.43	-22.37	32.06	40.00	-7.94	peak	100	260	P	
4	109.4116	49.74	-19.41	30.33	43.50	-13.17	peak	100	105	P	
5	143.3259	49.49	-21.81	27.68	43.50	-15.82	peak	100	1	P	
6	179.3863	49.27	-20.76	28.51	43.50	-14.99	peak	100	350	P	

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)


2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBuV/m) - Limit (dBuV/m)

For 1GHz to 25GHz

Horizontal

Radiated Emission Measurement



Site LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH00

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4804.000	71.77	-21.16	50.61	74.00	-23.39	peak	100	188	P	
2 *	4804.000	59.77	-21.16	38.61	54.00	-15.39	AVG	100	188	P	
3	7206.000	62.64	-14.42	48.22	74.00	-25.78	peak	100	106	P	
4	7206.000	50.51	-14.42	36.09	54.00	-17.91	AVG	100	106	P	

Note:1).Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier

3). Margin value = Limit value- Emission level

Horizontal

Radiated Emission Measurement



Site LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH00

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	20908.789	45.96	6.28	39.68	74.00	-34.32	peak	100	199	P	
2	21728.062	47.44	6.88	40.56	74.00	-33.44	peak	100	147	P	
3 *	24528.178	50.73	7.83	42.90	74.00	-31.10	peak	100	168	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH00

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4804.000	70.37	-21.16	49.21	74.00	-24.79	peak	200	64	P	
2	4804.000	58.18	-21.16	37.02	54.00	-16.98	AVG	200	64	P	
3	7206.000	62.54	-14.42	48.12	74.00	-25.88	peak	100	99	P	
4 *	7206.000	52.37	-14.42	37.95	54.00	-16.05	AVG	100	99	P	

Note:1).Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier

3). Margin value = Limit value- Emission level

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH00

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	19988.649	44.61	5.90	38.71	74.00	-35.29	peak	100	254	P	
2	21283.004	47.10	6.56	40.54	74.00	-33.46	peak	100	128	P	
3 *	22549.785	49.22	7.30	41.92	74.00	-32.08	peak	100	95	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Horizontal

Radiated Emission Measurement



Site LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH39

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4882.000	71.34	-20.24	51.10	74.00	-22.97	peak	100	335	P	
2 *	4882.000	61.67	-20.24	41.43	54.00	-12.64	AVG	100	335	P	
3	7323.000	64.07	-13.63	50.44	74.00	-23.59	peak	100	276	P	
4	7323.000	52.09	-13.63	38.46	54.00	-15.57	AVG	100	276	P	

Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Horizontal

Radiated Emission Measurement



Site: LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH39

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	18810.050	45.16	5.31	39.85	74.00	-34.15	peak	100	277	P	
2	22182.426	47.49	7.26	40.23	74.00	-33.77	peak	100	160	P	
3 *	23923.384	50.60	7.67	42.93	74.00	-31.08	peak	100	315	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH39

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4882.000	70.45	-20.24	50.21	74.00	-23.86	peak	100	36	P	
2	4882.000	58.67	-20.24	38.43	54.00	-15.64	AVG	100	36	P	
3	7323.000	62.89	-13.63	49.26	74.00	-24.77	peak	200	94	P	
4 *	7323.000	52.69	-13.63	39.06	54.00	-14.97	AVG	200	94	P	

Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Vertical

Radiated Emission Measurement



Site: LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH39

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	19831.676	45.76	5.84	39.92	74.00	-34.08	peak	100	341	P	
2	21171.433	45.85	6.49	39.36	74.00	-34.64	peak	100	209	P	
3 *	24890.625	49.91	7.83	42.08	74.00	-31.92	peak	100	187	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Horizontal

Radiated Emission Measurement



Site LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH78

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4960.000	70.92	-19.53	51.39	74.00	-22.61	peak	200	187	P	
2 *	4960.000	61.56	-19.53	42.03	54.00	-11.97	AVG	200	187	P	
3	7440.000	62.41	-13.20	49.21	74.00	-24.79	peak	200	84	P	
4	7440.000	50.74	-13.20	37.54	54.00	-16.46	AVG	200	84	P	

Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Horizontal

Radiated Emission Measurement



Site LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH78

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	18840.971	44.34	5.33	39.01	74.00	-34.99	peak	100	315	P	
2	20595.208	46.15	6.15	40.00	74.00	-34.00	peak	100	240	P	
3 *	23044.032	48.65	7.36	41.29	74.00	-32.71	peak	100	109	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH78

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4960.000	69.86	-19.53	50.33	74.00	-23.67	peak	100	360	P	
2 *	4960.000	59.55	-19.53	40.02	54.00	-13.98	AVG	100	360	P	
3	7440.000	62.37	-13.20	49.17	74.00	-24.83	peak	200	9	P	
4	7440.000	53.06	-13.20	39.86	54.00	-14.14	AVG	200	9	P	

Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH78


Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	18909.177	45.30	5.38	39.92	74.00	-34.08	peak	100	120	P	
2	21928.841	47.84	7.14	40.74	74.00	-33.26	peak	100	199	P	
3 *	24528.178	48.73	7.83	40.90	74.00	-33.10	peak	100	248	P	

Note:1).Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)


2). Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier

3). Margin value = Limit value- Emission level

Results of Band Edges Test (Radiated)

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH00

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2390.000	76.05	-24.72	51.33	74.00	-22.67	peak	150	311	P	
2	2390.000	61.09	-24.72	36.37	54.00	-17.63	AVG	150	311	P	
3	2400.000	77.35	-24.69	52.66	74.00	-21.34	peak	150	25	P	
4 *	2400.000	62.44	-24.69	37.75	54.00	-16.25	AVG	150	25	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Horizontal

Radiated Emission Measurement



Site LAB

Polarization: **Horizontal**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH78

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	74.43	-24.57	49.86	74.00	-24.14	peak	150	179	P	
2 *	2483.500	57.23	-24.57	32.66	54.00	-21.34	AVG	150	179	P	


Note: 1). Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3). Margin value = Limit value - Emission level

Vertical

Radiated Emission Measurement



Site LAB

Polarization: **Vertical**

Temperature: 21.5(C)

Limit: FCC Part15 RE-Class B_Above 1GHz_PK

Power: Battery

Humidity: 52 %

EUT: Party Speaker with Flame Light

Distance: 3m

M/N: GKD62

Mode: GFSK DH5 CH78

Note: N/A

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	73.39	-24.57	48.82	74.00	-25.18	peak	150	192	P	
2 *	2483.500	60.03	-24.57	35.46	54.00	-18.54	AVG	150	192	P	

Note:1).Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)

2). Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier

3). Margin value = Limit value- Emission level

4.3 Maximum Peak Output Power

Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

Type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	-0.50	20.97	Pass
	39	0.81		
	78	0.42		
$\pi/4$ DQPSK	00	-1.11	20.97	Pass
	39	0.16		
	78	-0.18		
8DPSK	00	-1.35	20.97	Pass
	39	-0.06		
	78	-0.40		

Note: 1.The test results including the cable loss.

4.4 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration




Test Results


Modulation	Channel	20dB bandwidth (MHz)	Result
GFSK	00	0.849	Pass
	39	0.822	
	78	0.843	
$\pi/4$ DQPSK	00	1.260	
	39	1.278	
	78	1.284	
8DPSK	00	1.272	
	39	1.272	
	78	1.290	

Test plot as follows:



$\pi/4$ DQPSK Modulation

CH00




CH39




CH78


8DPSK Modulation



CH00



CH39



CH78

4.5 Frequency Separation

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. CH39 and CH40 was measured by spectrum analyzer with 300 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION




TEST RESULTS

Modulation	Channel	Channel Separation (MHz)	Limit	Result
GFSK	CH39	0.998	0.566 MHz	Pass
	CH40			
$\pi/4$ DQPSK	CH39	1.038	0.856 MHz	Pass
	CH40			
8DPSK	CH39	1.020	0.860 MHz	Pass
	CH40			


Note:

We have tested all mode at high, middle and low channel, and recorded worst case at middle.


Test plot as follows:



GFSK



$\pi/4$ DQPSK



8DPSK

4.6 Number of hopping frequency


Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.


Test Configuration




Test Results

Modulation	Number of Hopping Channel	Limit	Result
GFSK	79	≥15	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		


Test plot as follows:



GFSK Modulation



$\pi/4$ DQPSK Modulation



8DPSK Modulation

4.7 Time of Occupancy (Dwell Time)

Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration



Test Results

Modulation	Packet	Burst time (ms)	Dwell time (s)	Limit (s)	Result
GFSK	DH1	0.374	0.120	0.40	Pass
	DH3	1.629	0.261		
	DH5	2.877	0.307		
π/4DQPSK	2-DH1	0.380	0.122	0.40	Pass
	2-DH3	1.634	0.261		
	2-DH5	2.882	0.307		
8DPSK	3-DH1	0.383	0.123	0.40	Pass
	3-DH3	1.634	0.261		
	3-DH5	2.883	0.308		


Note: We have tested all mode at high, middle and low channel, and recorded worst case at middle channel.


Dwell time = Pulse time (ms) × (1600 ÷ 2 ÷ 79) × 31.6 Second for DH1, 2-DH1, 3-DH1

Dwell time = Pulse time (ms) × (1600 ÷ 4 ÷ 79) × 31.6 Second for DH3, 2-DH3, 3-DH3

Dwell time = Pulse time (ms) × (1600 ÷ 6 ÷ 79) × 31.6 Second for DH5, 2-DH5, 3-DH5

Test plot as follows:




$\pi/4$ DQPSK Modulation

2-DH1 burst time




2-DH3 burst time



2-DH5 burst time


8DPSK Modulation



3-DH1 burst time



3-DH3 burst time



3-DH5 burst time