



FCC CERTIFICATION TEST REPORT

Applicant	:	NSV India Pvt Ltd
Address	:	Khasra No 1173 And 1174 Phase Vii Udyog Vihar Sector-34, Behrampur Road Behind Haryana Roadways Workshop, GURGAON, HARYANA, - 122004
Manufacturer	:	Yulin Tech
Address	:	ROOM 504, 5F, G ZONE HUA'AN ROAD NO.8, ZHONGKAI HIGH-TECH ZONE, HUIZHOU, GUANGDONG PROVINCE, CHINA, 516006.
Equipment under Test	:	Wireless Charger
Model No.	:	B83426VAAB
FCC ID	:	2BLO2PY1B
Report No.	:	DDT-B24071007-2E01
Issue Date	:	Oct. 23, 2024
Issued By	:	Tianjin Dongdian Testing Service Co., Ltd.
Address	:	Building D-1, No. 19 Weisi Road, Microelectronics Industrial Park, Development Area, Tianjin, China. Tel: +86-022-58038033, E-mail: dds@dddt.com, http://www.ddttest.com



REPORT

TABLE OF CONTENTS

	Test report declares.....	3
1	Summary of test results	5
2	General test information	6
2.1.	Description of EUT	6
2.2.	Accessories of EUT	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test.....	7
2.5.	Deviations of test standard.....	7
2.6.	Test environment conditions	7
2.7.	Test laboratory	7
2.8.	Measurement uncertainty.....	8
3	Equipment used during test	9
4	20dB Bandwidth.....	10
4.1.	Block diagram of test setup.....	10
4.2.	Limits	10
4.3.	Test Procedure.....	10
4.4.	Test Result.....	10
4.5.	Original test data.....	11
5	Radiated emission	12
5.1.	Block diagram of test setup.....	12
5.2.	Limit	13
5.3.	Test Procedure.....	13
5.4.	Test result	14
6	Power Line Conducted Emission	17
6.1.	Block diagram of test setup.....	17
6.2.	Power Line Conducted Emission Limits.....	17
6.3.	Test Procedure.....	17
6.4.	Test Result.....	18
7	Antenna Requirements	19
8	Test setup photograph.....	20
9	Photos of the EUT	21

TEST REPORT DECLARE

Applicant	:	NSV India Pvt Ltd
Address	:	Khasra No 1173 And 1174 Phase Vii Udyog Vihar Sector-34, Behrampur Road Behind Haryana Roadways Workshop, GURGAON, HARYANA, - 122004
Equipment under Test	:	Wireless Charger
Model No.	:	B83426VAAB
Trade Mark	:	N/A
Manufacturer	:	Yulin Tech
Address	:	ROOM 504, 5F, G ZONE HUA'AN ROAD NO.8, ZHONGKAI HIGH-TECH ZONE, HUIZHOU, GUANGDONG PROVINCE, CHINA, 516006.

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-Gen Issue 5

Test procedure used:

ANSI C63.10:2020, RSS-Gen Issue 5

We Declare:

The equipment described above is tested by Tianjin Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Tianjin Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-B24071007-2E01		
Date of Receipt:	Oct. 09, 2024	Date of Test:	Oct. 12, 2024 ~ Oct. 23, 2024

Prepared By:

Novak Wei

Novak Wei/Engineer**Approved By:**

Aaron Zhang

Aaron Zhang/Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.
The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Oct. 23, 2024	

1 Summary of test results

Description of Test Item	Standard	Results
20dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.215	PASS
Radiated Emission	FCC Part 15: 15.209	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207	N/A
Antenna requirement	FCC Part 15: 15.203	PASS

2 General test information

2.1. Description of EUT

EUT* Name	:	Wireless Charger
Model Number	:	B83426VAAB
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 12V
Max Output Power	:	15W
Wireless charging Operation frequency	:	130KHz
Number channel	:	1
Antenna Type	:	Inductive loop coil antenna
Sample Number	:	N/A

Note: EUT is the ab. of equipment under test.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number or Type	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test**2.5. Deviations of test standard**

No Deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	20-28℃
Humidity range:	20-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China.

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: ddt@dgddt.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2.8. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	3.12dB (150kHz-30MHz)
	3.51dB (9kHz-150kHz)
Uncertainty for Radiation Emission test (30MHz-1GHz)	2.72 dB (Antenna Polarize: V)
	2.72 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz to 18GHz)	2.74dB(1-6GHz)
	2.72dB (6GHz-18GHz)
Bandwidth	0.14%


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (MW RF test system)					
Microwave Signal Generator	R&S	SMF100A	101396	2024/02/21	1 Year
MXG Vector Signal Generator	Keysight	N5182A	MY50143288	2024/02/21	1 Year
Signal Analyzer	R&S	FSV	101730	2024/02/21	1 Year
Wideband Radio Communication Tester	R&S	CMW500	158800	2024/05/06	1 Year
Power Sensor	KEYSIGHT	U2021XA	MY59150007	2024/02/21	1 Year
DC Power Supply	inSTEK	PSP-2010	EN122317	2024/02/03	1 Year
Test Software	MWRFTesT	MTS8310	V03	N/A	N/A
Radiated Emission -10m EMI Chamber					
Broadband Horn Antenna	TESEQ	BHA 9118	31754	2023/10/11	2 Year
Active Loop Antenna	R&S	HFH2-Z2	100269	2024/08/25	2 Year
Low noise amplifier	MITEQ	TPA0118-36	0914	2024/02/04	1 Year
EMI Test Receiver	R&S	ESCI	101024	2024/02/18	1 Year
EMI Test Receiver	R&S	ESCI	101030	2024/02/18	1 Year
EMI Test Receiver	R&S	ESU26	100244	2024/02/18	1 Year
Bilog Antenna	TESEQ	CBL6112D	29068	2024/10/10	2 Year
Bilog Antenna	TESEQ	CBL6112D	29069	2024/10/10	2 Year
Amplifier	Sonoma	310N	300913	2024/02/18	1 Year
Amplifier	Sonoma	310N	300914	2024/02/18	1 Year
Ant Mast	Innco	MA4000	N/A	N/A	N/A
Ant Mast	Innco	MA4000	N/A	N/A	N/A
Mast Controller	Innco	CO2000	N/A	N/A	N/A
Mast Controller	Innco	CO2000	N/A	N/A	N/A
RF Selector 4CH	TOYO	NS4904N	Selector1	N/A	N/A
RF Selector 4CH	TOYO	NS4904N	Selector2	N/A	N/A
Test software	TOYO	EP5/RSE	Ver 1.9.1	N/A	N/A
Test software	Audix	E3	V 6.11111b	N/A	N/A

4 20dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


4.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 10 kHz RBW and 30 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.4. Test Result

Freq. (kHz)	20dB bandwidth Result (kHz)	99% bandwidth Result (kHz)	Conclusion
130	25.10	22.09	PASS


4.5. Original test data




5 Radiated emission

5.1. Block diagram of test setup

Test Setup Diagram for 9 kHz~30MHz



Test Setup Diagram for 30MHz~1GHz



5.2. Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$	$67.6-20\log(F)$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$	$87.6-20\log(F)$
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{10\text{m}}(\text{dB}\mu\text{V/m}) = \text{Limit}_{300\text{m}}(\text{dB}\mu\text{V/m}) + 40\log(300\text{m}/10\text{m}) = \text{Limit}_{300\text{m}}(\text{dB}\mu\text{V/m}) + 59.08$$

$$\text{Limit}_{10\text{m}}(\text{dB}\mu\text{V/m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V/m}) + 40\log(30\text{m}/10\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V/m}) + 19.08$$

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V/m}) = \text{Limit}_{300\text{m}}(\text{dB}\mu\text{V/m}) + 40\log(300\text{m}/3\text{m}) = \text{Limit}_{300\text{m}}(\text{dB}\mu\text{V/m}) + 80$$

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V/m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V/m}) + 40\log(30\text{m}/3\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V/m}) + 40$$

5.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Test antenna was located 10m or 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	10m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the Trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 1GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT

was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions. Spectrum frequency from 9kHz to 1GHz (tenth harmonic of fundamental frequency) was investigated.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

5.4. Test result

PASS. (See below detailed test result)

Below 30MHz:

Radiated Emission Test Result

Test Site : DDT 10m Chamber

Test Date : 10-22-2024


Tested By : Novak Wei

EUT : Wireless Charger

Model Number : B83426VAAB


Power Supply : DC 12V

Test Mode : Tx mode



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detect or	Polarization
1	0.01	69.84	19.50	0.03	89.37	128.52	-39.15	Peak	parallel
2	0.02	37.97	19.80	0.03	57.80	121.19	-63.39	Peak	parallel
3	0.04	29.72	19.74	0.03	49.49	116.47	-66.98	Peak	parallel
4	0.08	25.85	19.70	0.03	45.58	109.77	-64.19	Peak	parallel
5	0.12	63.61	19.67	0.03	83.31	106.04	-22.73	Peak	parallel
6	0.37	36.77	19.67	0.03	56.47	96.31	-39.84	Peak	parallel
7	0.62	26.86	19.79	0.02	46.67	71.80	-25.13	Peak	parallel
8	0.86	24.27	19.93	0.03	44.23	68.92	-24.69	Peak	parallel
9	1.11	21.15	19.99	0.05	41.19	66.73	-25.54	Peak	parallel
10	1.35	16.95	19.96	0.07	36.98	64.97	-27.99	Peak	parallel
11	1.59	13.44	19.93	0.08	33.45	63.57	-30.12	Peak	parallel
12	2.57	14.49	19.93	0.12	34.54	69.54	-35.00	Peak	parallel
13	2.83	13.82	19.94	0.12	33.88	69.54	-35.66	Peak	parallel
14	8.06	13.43	20.00	0.28	33.71	69.54	-35.83	Peak	parallel
15	12.91	13.70	19.94	0.41	34.05	69.54	-35.49	Peak	parallel
16	21.86	12.91	20.30	0.45	33.66	69.54	-35.88	Peak	parallel

Note: Facing the sample function area, the center point of the sample function area is the center, the right side is the X axis, the upper side is the Z axis, the direction perpendicular to the center point is the Y axis, and the test direction is the Y axis facing the test antenna.

Above 30MHz:**Transmission mode:****Final Result**

No.	Frequency [MHz]	(P)	Reading QP [dB (μV)]	c. f [dB(1/m)]	Result QP [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP [dB]	Height [cm]	Angle [°]	System
1	30.445	H	22.3	-5.3	17.0	29.5	12.5	315.0	13.9	1
2	167.852	H	26.9	-12.3	14.6	33.0	18.4	378.0	331.6	1
3	991.634	H	17.2	6.0	23.2	43.5	20.3	214.0	206.9	1
4	30.680	V	22.9	-5.7	17.2	29.5	12.3	320.0	294.7	2
5	163.265	V	33.3	-12.2	21.1	33.0	11.9	129.0	248.1	2
6	960.041	V	16.3	6.1	22.4	43.5	21.1	386.0	169.2	2

Note) Receiving antenna polarization : Horizontal and/or Vertical


Test Distance : 10 m, Antenna Height : 1 m to 4 m

Level QP (Quasi-Peak) = Reading QP + Factor (Antenna Factor + Cable Loss - Amp. Gain)

Margin QP (Quasi-Peak) = Limit - Level QP

6 Power Line Conducted Emission

6.1. Block diagram of test setup



6.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

6.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

6.4. Test Result

Not Applicable.

7 Antenna Requirements

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8 Test setup photograph

Please refer to the appendix file

9 Photos of the EUT

Please refer to the appendix file

END OF REPORT