
Antenna specification

1、Antenna introduction


The Bluetooth module antenna is directly used on the PCB.

Manufacturer: Shenzhen Yishe Technology Co., Ltd.

Address: Room 601, Building A, Xitou Dongyuan, Longsheng Road, Longhua District, Shenzhen City, Guangdong Province, China

Model/Type reference: J6


2、Antenna shape




Test equipment list

name	Manufacturer	Model
Network analyzer	KEYSIGHT	E5071C
Network analyzer	KEYSIGHT	E5071C
Comprehensive Measuring Instrument	R&S	CWM500
OTA test system	GTS	RayZone-5000

Test setup





3、Antenna parameter

The Bluetooth antenna operates at 2402-2480 MHz and generates resonance in this band. The table below shows the main parameters of the antenna.

Frequency(MHz)	2402 ~ 2480 MHz
VSWR	≤ 1.95
Impedance	50 Ohm Nominal

Return Loss	-15 dB Max
Radiation	Omni-directional
Gain (Peak)	0.64dBi
Polarization	Linear, Vertical
Admitted Power	1MW
Connector	Tin

4、Antenna gain report


Spectrum Detector: PK
 Test By: Mark
 Test Result: PASS
 Modulation: GFSK

Test Date : Feb 18, 2022
 Temperature : 25℃
 Humidity : 52 %


Frequency VNA (MHz)	E Total. dB(dB)
2400MHz	0.0403503
2410MHz	0.0886264
2420MHz	0.267381
2430MHz	0.193012

2440MHz	0.26366
2450MHz	0.0723139
2460MHz	0.36895
2470MHz	0.551525
2480MHz	0.640702
2490MHz	0.05232
2500MHz	0.08443


Direction map:



PHI 0°



PHI 90°



THETA 90°