

**SPECIFICATIONS FOR APPROVAL**

Antenna manufacturer: Shenzhen Lejin radio frequency technology Co., LTD

Company Address: 3rd Floor, Building A4, No. 176 Chongqing Road, Fuhai Street, Bao'an District, Shenzhen, Guangdong Province. (Phone number: 13603098741)

Customer Name:**Product Name:** LTE ANT**Product Model:** LJFD1016**Part Number:****Write By :** Star Li**Issued Date:** 2025/9/9**CUSTOMER**

ENGINEER R&D DEPT	BUSSINESS DEPT	APPROVED BY	DATE	Edition/Part number

LEETN

R&D DEPT	ENGINEER R&D DEPT	APPROVAL	DATE	Edition/Part number
		李明进		数字签名者: 李明进 DN: cn=李明进, o=乐进射频, ou=研发, email=13603098741@163.com, c=CN 日期: 2025.10.28 16:15:45 +0800


ECN/ECR			

Index

- 1、 Cover
- 2、 Index
- 3、 Product Specification
- 4、 est Equipment & Conditions
- 5、 Test Report
- 6、 Antenna Picture
- 7、 Transmission line Specification
- 8、 Product Drawing

Test Equipment & Conditions

1. Network Analyzers :Agilent 8753SE 5071C
2. Communications Test Set:Agilent E5515C/CMW500
3. 3D Chamber Test System(ETS743)/Satimo(433)




LTE ANT

Ant. Type	Frequency (MHz)	VSW R	Efficiency	Impedance (Ohm)	Polarization	Gain (Peak gain with cable loss)(dBi)	Cable Loss(dB)
PIFA	650 ~960	<2.5	>25%	50	Linear	2.3(MAX)	0.85(MAX)
	1710 ~2170	<2.6	>40%				
	2300 ~2700	<2.7	>40%				
Cable Type		Cable Length (mm)	Connector Type		Operation Temperature		Storage Temperature
1.37-50			Cocentra 137-1		- 20 °C ~ + 70 °C		- 30 °C ~ + 80 °C

Antenna Impedance: VSWR


E5071C Network Analyzer

1 Active Ch/Trace 2 Response 3 Stimulus 4 Mkr/Analysis 5 Instr State




Freq(MHz)	650	730	830	960	1710	1930	2170	2300	2500	2700	
Effi(%)	23.37	25.52	36.33	38.58	42.91	45.14	43.94	40.1	43.51	34.88	
Gain((dBi)	-2.72	-2.64	-1.02	1.32	-0.14	-0.71	-0.56	2.37	1.02	2.17	


700.000MHz




830.000MHz




960.000MHz




1710.000MHz




1930.000MHz




2170.000MHz




2300.000MHz




2500.000MHz




2700.000MHz




2300.000MHz H




2500.000MHz H




2700.000MHz H




2300.000MHz E1




2500.000MHz E1




2700.000MHz E1




1710.000MHz H




1930.000MHz H




2170.000MHz H




1710.000MHz E1




1930.000MHz E1




2170.000MHz E1




700.000MHz H




830.000MHz H




960.000MHz H



700.000MHz E1



830.000MHz E1



960.000MHz E1

