



FCC RADIO TEST REPORT

Applicant : EWIC PHILIPPINES INC.
Address : BLDG NOS 7&8 S BLK 2 LOT 2 EZP WAREHOUSE, LAGUNA TECHNOPARK
ANNEX, BARANGAY BO BINAN, BINAN, PHILIPPINES
Equipment : Video Doorbell
Model No. : DW401, W41D2, D-DA
Trade Name : N/A
FCC ID : 2BLTA-DW401

I HEREBY CERTIFY THAT:

The sample was received on Dec. 25, 2025 and the testing was completed on Jan. 11, 2026 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment under Test.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software.....	8
2.4 Description of Test System.....	9
2.5 General Information of Test.....	10
2.6 Measurement Uncertainty	10
3. Test Equipment and Ancillaries Used for Tests.....	11
4. Antenna Requirements.....	12
4.1 Standard Applicable	12
4.2 Antenna Construction and Directional Gain.....	12
5. Test of Conducted Emission.....	13
5.1 Test Limit	13
5.2 Test Procedures	13
5.3 Typical Test Setup	14
5.4 Test Result and Data.....	15
5.5 Test Photographs	17
6. Test of Spurious Emission (Radiated)	18
6.1 Test Limit	18
6.2 Test Procedures	19
6.3 Typical Test Setup	20
6.4 Test Result and Data (9kHz ~ 30MHz)	21
6.5 Test Result and Data (30MHz ~ 1GHz)	21
6.6 Test Result and Data (1GHz ~ 25GHz).....	23
6.7 Restricted Bands of Operation	35
6.8 Test Photographs (30MHz ~ 1GHz).....	36
6.9 Test Photographs (1GHz ~ 25GHz).....	37
7. Test of Spurious Emission (Conducted).....	39
7.1 Test Limit	39
7.2 Test Procedure	39
7.3 Test Setup Layout	39
7.4 Test Result and Data.....	39
8. On Time, Duty Cycle and Measurement methods	42
8.1 Test Limit	42
8.2 Test Procedure	42
8.3 Test Setup Layout	42
8.4 Test Result and Data.....	43
9. 6dB Bandwidth Measurement Data.....	44
9.1 Test Limit	44
9.2 Test Procedures	44



9.3	Test Setup Layout	44
9.4	Test Result and Data	44
10.	Maximum Peak Output Power	46
10.1	Test Limit	46
10.2	Test Procedures	46
10.3	Test Setup Layout	46
10.4	Test Result and Data	46
11.	Power Spectral Density	47
11.1	Test Limit	47
11.2	Test Procedures	47
11.3	Test Setup Layout	47
11.4	Test Result and Data	47



History of this test report

Report No	Issued Date	Description
25120477-TRDFCC01	Jan. 12, 2026	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

**ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
FCC Rules and Regulations Part 15 Subpart C §15.247**

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
Note: Deviations Yes ☐ No ☒ *The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.		



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Equipment	Video Doorbell
Model Name	DW401, W41D2, D-DA
Model Discrepancy	The models are identical to each other except for model name and appearance color.
Frequency Range	BLE/ WIFI 2.4G: 2400MHz-2483.5MHz WIFI 5G: 5150MHz-5250MHz, 5250MHz-5350MHz, 5470MHz -5725MHz, 5725MHz -5850MHz
Modulation Type	BLE: GFSK 2.4GHz 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM 5GHz 802.11a/n: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Data Rate	BLE: GFSK: 1Mbps, 2Mbps, 125kbps, 500kbps WIFI 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0-MCS7, HT20 802.11ax: MCS0-MCS11, HE20 WIFI 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0-MCS7, HT20/HT40 802.11ac: MCS0-MCS9, VHT20/40 802.11ax: MCS0-MCS11, HE20/HE40
Working Temperature	-25°C to 55°C
EUT Power Rating:	5VDC/2A; 10-24VDC/1A; 14-24VAC/1A 50/60Hz

Note:

1. EUT support Client mode without radar detection.
2. The EUT not support TPC
3. 802.11ax only support full RU.
4. For more details, please refer to the User's manual of the EUT.

**2.2 Carrier Frequency of Channels**

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
*00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	*19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	*39	2480
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- b. The complete test system included support units and EUT for RF test.
- c. An executive program, "SecureCRT.exe (Ver.: 6.2.3.313)" under WIN10 system was executed to transmit and receive data via Wireless.
- d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
Mode 1	GFSK (1Mbps) for AC120V
Mode 2	GFSK (2Mbps) for AC120V
Mode 3	GFSK (1Mbps) for AC240V
caused "Test Mode 2 and CH00:2402" generated the worst case, it was reported as the final data.	
Radiation Emissions (Below 1GHz)	
Test Mode	Operating Description
Mode 1	GFSK (1Mbps)
Mode 2	GFSK (2Mbps)
caused "Test Mode 2 and CH00:2402" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
Mode 1	GFSK (1Mbps)
Mode 2	GFSK (2Mbps)
caused "Test Mode 1,2" generated the worst case, it was reported as the final data.	



2.4 Description of Test System

AC Power Line Conducted Emission					
Equipment	Brand	Model	Serial No	Length/Type	Power cord/Length/Type
Notebook	AUAS	P2430U	GBNXC13 M064467	N/A	Adapter / 1.8m / NS
testfixture	YD-TECH	MCS-73 LV	N/A	N/A	N/A
Adapter	Datong	PWC-48028	24120544	N/A	N/A
Type C To C(white)	kolin	KEX-DLCP52	N/A	1M/NS	N/A
Radiated Emissions (Below 1G) / Radiated Emissions (Above 1G) / RF Conducted					
Notebook	AUAS	P2430U	GBNXC13 M064467	N/A	Adapter / 1.8m / NS
testfixture	YD-TECH	MCS-73 LV	N/A	N/A	N/A
USB Cable (A to B)	BENEVO	BUSB0301AMFB	N/A	0.8m / NS	N/A
Adapter	Datong	PWC-48028	24120544	N/A	N/A
Type C To C(white)	kolin	KEX-DLCP52	N/A	1M/NS	N/A



2.5 General Information of Test

Organization	CerpPASS Technology Corp.		
Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881		
	FCC	TW1439, TW1079	
	IC	4934E-1, 4934E-2	
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz		
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.		

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2026/01/05	23.8℃ / 52%	Leon Huang
Radiated Emissions	3M03-NK	2026/01/06~2026/01/11	17.4~24.7℃ / 55~58%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2026/01/08	19.9℃ / 45%	Leon Huang

2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150kHz~30MHz)	±3.2dB
Radiated Spurious Emission(9kHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.2dB
Radiated Spurious Emission(1GHz~25GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±4.4%
20dB Bandwidth	±4.5%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±3.5%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M03-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Sunol	JB1	A020514-1	2025/06/11	2026/06/10
Active Loop Antenna	EMCO	6507	00040855	2025/04/28	2026/04/27
Horn Antenna	EMCO	3116	31974	2025/10/07	2026/10/06
Horn Antenna	Schwarzbeck	BBHA 9120 D	2203	2025/03/07	2026/03/06
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	101329	2025/06/10	2026/06/09
EMI Receiver	ROHDE & SCHWARZ	ESR7	101906	2025/05/19	2026/05/18
Preamplifier	Agilent	8449B	3008A01954	2025/02/12	2026/02/11
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2025/10/13	2026/10/12
Preamplifier	EM Electronics corp.	EM330	60611	2025/03/28	2026/03/27
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2025/07/02	2026/07/01
Cable-8m(10M-26.5G)	HUBER SUHNER	SF126E	587396/126E	2025/10/15	2026/10/14
Cable-3m(10M-26.5G)	HUBER SUHNER	SF126E	587399/126E	2025/10/15	2026/10/14
Cable-1m(10M-40G)	HUBER SUHNER	SF102	804619/2	2025/10/13	2026/10/12
Cable-1m(10M-40G)	HUBER SUHNER	SF102	804398/2	2025/10/13	2026/10/12
Cable-1m(1G-26.5G)	HUBER SUHNER	SF126E	589848/126E	2025/10/15	2026/10/14
Cable-4m(30M-1G)	HUBER SUHNER	RG-214	02953M	2025/07/11	2026/07/10
Cable-1m(30M-1G)	HUBER SUHNER	RG-214	05094M	2025/07/11	2026/07/10
Cable-9m(30M-1G)	HUBER SUHNER	RG-214	00402M	2025/07/11	2026/07/10
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	Warison	WFIL-H3000-18000F-03	WR377WC2B1	2025/10/15	2026/10/14
Highpass Filter	WOKEN	WFIL-H7000-18000F-01	WR377WC2B2	2025/10/15	2026/10/14

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MY54200207	2025/04/23	2026/04/22
Attenuator	KEYSIGHT	8491B	MY39250703	2025/02/12	2026/02/11
Power Meter	Anritsu	ML2495A	1224005	2025/02/12	2026/02/11
Power Sensor	Anritsu	MA2411B	1207295	2025/02/12	2026/02/11

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR7	101906	2025/05/19	2026/05/18
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	1197	2025/02/26	2026/02/25
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	101584	2025/02/26	2026/02/25
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2025/07/02	2026/07/01
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Built-in Antenna
Antenna Gain	3.50dBi



5. Test of Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2020+Cor.1-2023 and ANSI C63.10a-2024. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup





5.4 Test Result and Data

Power	:	From Adapter (AC 120V/60Hz)	Pol/Phase	:	LINE
Test Mode	:	Mode 2		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1752	9.54	26.07	35.61	64.71	-29.10	QP	P
2	0.1752	9.54	10.71	20.25	54.71	-34.46	Average	P
3	0.2249	9.53	22.18	31.71	62.64	-30.93	QP	P
4	0.2249	9.53	7.93	17.46	52.64	-35.18	Average	P
5	0.2526	9.54	21.41	30.95	61.67	-30.72	QP	P
6	0.2526	9.54	8.62	18.16	51.67	-33.51	Average	P
7	0.3371	9.56	19.36	28.92	59.27	-30.35	QP	P
8	0.3371	9.56	9.96	19.52	49.27	-29.75	Average	P
9	0.4107	9.56	15.96	25.52	57.63	-32.11	QP	P
10	0.4107	9.56	6.04	15.60	47.63	-32.03	Average	P
11	0.6700	9.57	16.81	26.38	56.00	-29.62	QP	P
12	0.6700	9.57	7.18	16.75	46.00	-29.25	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	:	From Adapter (AC 120V/60Hz)	Pol/Phase	:	NEUTRAL
Test Mode	:	Mode 2		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1744	9.55	25.28	34.83	64.75	-29.92	QP	P
2	0.1744	9.55	10.38	19.93	54.75	-34.82	Average	P
3	0.2249	9.56	21.31	30.87	62.64	-31.77	QP	P
4	0.2249	9.56	8.09	17.65	52.64	-34.99	Average	P
5	0.2796	9.56	19.71	29.27	60.83	-31.56	QP	P
6	0.2796	9.56	9.54	19.10	50.83	-31.73	Average	P
7	0.3209	9.57	16.72	26.29	59.68	-33.39	QP	P
8	0.3209	9.57	6.34	15.91	49.68	-33.77	Average	P
9	0.4675	9.60	15.68	25.28	56.56	-31.28	QP	P
10	0.4675	9.60	7.45	17.05	46.56	-29.51	Average	P
11	0.6455	9.62	17.94	27.56	56.00	-28.44	QP	P
12	0.6455	9.62	11.74	21.36	46.00	-24.64	Average	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.(X AXIS is the worst.)




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	:	From Adapter(AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	38.73	-8.81	34.94	26.13	40.00	-13.87	Peak	100	33	P
2	127.97	-8.47	35.51	27.04	43.50	-16.46	Peak	200	253	P
3	141.55	-8.92	37.58	28.66	43.50	-14.84	Peak	100	29	P
4	158.04	-10.27	39.86	29.59	43.50	-13.91	Peak	200	230	P
5	387.93	-6.29	36.74	30.45	46.00	-15.55	Peak	200	330	P
6	418.97	-5.16	36.07	30.91	46.00	-15.09	Peak	100	330	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor





Power	:	From Adapter(AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2		:	





No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	30.00	-3.06	26.44	23.38	40.00	-16.62	Peak	100	85	P
2	136.70	-8.78	33.72	24.94	43.50	-18.56	Peak	100	340	P
3	265.71	-8.88	33.68	24.80	46.00	-21.20	Peak	200	20	P
4	319.06	-7.88	34.27	26.39	46.00	-19.61	Peak	200	303	P
5	368.53	-6.77	33.37	26.60	46.00	-19.40	Peak	100	100	P
6	464.56	-3.92	29.84	25.92	46.00	-20.08	Peak	200	201	P


Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor


**6.6 Test Result and Data (1GHz ~ 25GHz)**































6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Spurious Emission (Conducted)

7.1 Test Limit

According to the methods defined in ANSI C63.10-2020 Section 7.8.7


Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

According to the methods defined in ANSI C63.10-2020

- The transmitter output was connected to the spectrum analyzer via a low loss cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

7.3 Test Setup Layout





7.4 Test Result and Data



Note: Test plots refer to the following pages.





Modulation Type: GFSK 1Mbps
CH00



Modulation Type: GFSK 1Mbps
CH19





Modulation Type: GFSK 1Mbps
CH39









Modulation Type: GFSK 2Mbps
CH00



Modulation Type: GFSK 2Mbps
CH19



Modulation Type: GFSK 2Mbps
CH39





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

According to the methods defined in ANSI C63.10-2020 Section 11.6
Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout







8.4 Test Result and Data

Modulation Type	On Time (msec)	Period Time (msec)	Duty Cycle (%)
GFSK(1Mbps)	2.151	2.493	86.28%
GFSK(2Mbps)	1.080	1.875	57.60%

Modulation Type: GFSK 1Mbps



Modulation Type: GFSK 2Mbps





9. 6dB Bandwidth Measurement Data

9.1 Test Limit


The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.8

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and $VBW \geq 3 \times RBW$.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout




9.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
GFSK (1Mbps)	00	2402	662.40	500
	19	2440	666.40	500
	39	2480	678.90	500
GFSK (2Mbps)	00	2402	1275.00	500
	19	2440	1280.00	500
	39	2480	1257.00	500




Modulation Standard: GFSK (1Mbps)
Channel: 00




Modulation Standard: GFSK (2Mbps)
Channel: 00




Modulation Standard: GFSK (1Mbps)
Channel: 19




Modulation Standard: GFSK (2Mbps)
Channel: 19



Modulation Standard: GFSK (1Mbps)
Channel: 39



Modulation Standard: GFSK (2Mbps)
Channel: 39





10. Maximum Peak Output Power

10.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

10.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.9.1.2

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

Power Set	Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
Default	GFSK (1Mbps)	00	2402	3.13	2.056
Default		19	2440	0.65	1.161
Default		39	2480	-1.10	0.776
Default	GFSK (2Mbps)	00	2402	3.24	2.109
Default		19	2440	0.82	1.208
Default		39	2480	-0.97	0.800



11. Power Spectral Density


11.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

11.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.10.1

11.3 Test Setup Layout




11.4 Test Result and Data

Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)	Limit
GFSK (1Mbps)	00	2402	-14.729	8.00
	19	2440	-17.247	8.00
	39	2480	-18.535	8.00
GFSK (2Mbps)	00	2402	-18.15	8.00
	19	2440	-21.529	8.00
	39	2480	-22.017	8.00


Note: Test plots refer to the following pages.




Modulation Standard: GFSK (1Mbps)
Channel: 00




Modulation Standard: GFSK (2Mbps)
Channel: 00




Modulation Standard: GFSK (1Mbps)
Channel: 19




Modulation Standard: GFSK (2Mbps)
Channel: 19



Modulation Standard: GFSK (1Mbps)
Channel: 39



Modulation Standard: GFSK (2Mbps)
Channel: 39



----- THE END OF REPORT -----