



Radio Frequency Exposure

Applicant : EWIC PHILIPPINES INC.

Address : BLDG NOS 7&8 S BLK 2 LOT 2 EZP WAREHOUSE, LAGUNA
TECHNOPARK ANNEX, BARANGAY BO BINAN, BINAN,
PHILIPPINES

Equipment : Access Reader

Model No. : RD1CW, CRD1-CW

Trade Name : N/A

FCC ID : 2BLTA-RD1CW

I HEREBY CERTIFY THAT:

The sample was received on Dec. 22, 2025 and the testing was completed on Dec. 25, 2025 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor



Contents

1. Test Configuration of Equipment under Test.....	3
1.1 Feature of Equipment	3
2. Summary of Test Procedure and Test Results	4
2.1 Applicable Standards	4



1. Test Configuration of Equipment under Test

1.1 Feature of Equipment

Equipment	Access Reader
Model No.	RD1CW, CRD1-CW
Model Discrepancy	Only the appearance color is different.
Frequency Range	13.56MHz
Modulation Type	ASK
Antenna Type	Coil Antenna
Operating Temperature	-30℃~+70℃

Note: For more details, please refer to the User's manual of the EUT.



2. Summary of Test Procedure and Test Results

2.1 Applicable Standards

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

SAR EXCLUSION

Per FCC KDB 447498 D01v06 section 4.3:

- c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):³³
- 1) For *test separation distances* > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f_{\text{(MHz)}})]$
 - 2) For *test separation distances* ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
 - 3) SAR measurement procedures are not established below 100 MHz.

5mm Test Separation

Channel Frequency (MHz)	Fundamental Emission (dBm)	Conducted Power (dBm)	Max. Tune up power (dBm)	Fundamental Emission (mW)	Limit (mW)
13.56	-36.18	-36.18	-35.18	0.000303389	474

power=Transmitter Spurious-95.2= 59.02 -95.2=-36.18dBm

Conclusion

The maximum results have not exceeded the limit, no SAR is required .

----- THE END OF REPORT-----