FCC Test Report

Report No.: AGC02931251205FR06

FCC ID	:	2BLTR-RPT2U
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	DMR Repeater
BRAND NAME	:	TYTECH, ABLEBOW
MODEL NAME	:	MD-7500, AB-ZD7500
APPLICANT	:	Quanzhou RadioBoss Technology Co., Ltd
DATE OF ISSUE	:	May 08, 2026
STANDARD(S)	:	FCC Part 90 Subpart I
REPORT VERSION	:	V1.0

Attestation of ***G***lobal ***C***ompliance (Shenzhen) Co., Ltd

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 08, 2026	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Table of Contents

1. General Information 5
2. Product Information 6
2.1 Product Technical Description 6
2.2 Test Frequency List 7
2.3 Related Submittal(S) / Grant (S) 8
2.4 Test Methodology 8
2.5 Calculation of Emission Indicators 8
2.6 Special Accessories 8
2.7 Equipment Modifications 8
3. Test Environment 9
3.1 Address of The Test Laboratory 9
3.2 Test Facility 9
3.3 Environmental Conditions 10
3.4 Measurement Uncertainty 10
3.5 List of Equipment Used 11
4.System Test Configuration 13
4.1 EUT Configuration 13
4.2 EUT Exercise 13
4.3 Configuration of Tested System 13
4.4 Equipment Used in Tested System 13
4.5 Summary of Test Results 14
5. Description of Test Modes 15
6. Frequency Stability 16
6.1 Provisions Applicable 16
6.2 Measurement Procedure 16
6.3 Measurement Setup 16
6.4 Measurement Result 17
7. 26dB Emission Bandwidth and 99% Occupied Bandwidth 18
7.1 Provisions Applicable 18
7.2 Measurement Procedure 18
7.3 Measurement Setup 18
7.4 Measurement Result 19
8. Spurious Radiated Emission 22
8.1 Provisions Applicable 22
8.2 Measurement Procedure 22
8.3 Measurement Setup 23
8.4 Measurement Result 24
8.5 Emission Mask Measurement Part 41
9. Modulation Characteristics 44
9.1 Provisions Applicable 44

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.2 Measurement Procedure 44
9.3 Measurement Setup 44
9.4 Measurement Result 45
10. Maximum Transmitter Power 47
10.1 Provisions Applicable 47
10.2 Measurement Procedure 47
10.3 Measurement Setup 47
10.4 Measurement Result 49
11. Spurious Emission on Antenna Port 52
11.1 Provisions Applicable 52
11.2 Measurement Procedure 52
11.3 Measurement Setup 52
11.4 Measurement Result 53
12. Transmitter Frequency Behavior 56
12.1 Provisions Applicable 56
12.2 Measurement Setup 56
12.3 Measurement Procedure 57
12.4 Measurement Result 59
13. Audio Low Pass Filter Response 60
13.1 Provisions Applicable 60
13.2 Measurement Procedure 61
13.3 Measurement Setup 61
13.4 Measurement Result 62
Appendix I: Photographs of Test Setup 63
Appendix II: Photographs of Test EUT 63

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

1. General Information

Applicant	Quanzhou RadioBoss Technology Co., Ltd
Address	No.8, Chuangzao Road, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian,China
Manufacturer	Quanzhou RadioBoss Technology Co., Ltd
Address	No.8, Chuangzao Road, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian,China
Factory	Quanzhou RadioBoss Technology Co., Ltd
Address	No.8, Chuangzao Road, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian,China
Product Designation	DMR Repeater
Brand Name	TYTECH, ABLEBOW
Test Model	MD-7500
Series Model(s)	AB-ZD7500
Difference Description	The only difference is the model name
Date of receipt of test item	Dec. 11, 2025
Date of Test	Dec. 11, 2025~Apr. 24, 2026
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC- Repeater-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Zhang (Project Engineer)	May 08, 2026
Reviewed By	Jack Gui (Reviewer)	May 08, 2026
Approved By	Angela Li (Authorized Officer)	May 08, 2026

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2. Product Information

2.1 Product Technical Description

Communication Type	Analog / Digital	
Operation Frequency Range	From 400MHz to 470MHz--UHF	
Hardware Version	V2.0	
Software Version	V1.0.0.56	
Modulation Type	Analog:	FM
	Digital:	4FSK
Digital Type	DMR	
Channel Separation	Analog	12.5 kHz
	Digital	12.5 kHz
Support Data Rate	9600bps	
Emission Designator	Analog:	9K93F3E
	Digital:	7K88F7D/7K88F7W/7K88FXD/7K88FXW
Rated Output Power	50W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Maximum Transmitter Power	UHF Band: 46.20dBm(Analog), 46.11dBm(Digital)	
Antenna Designation	Detachable Antenna	
Antenna Gain	3.0dBi	
Frequency Tolerance	1.019ppm	
Power Supply	AC 120V, 60Hz from AC Main& DC 13.6V 22A from DC Power Supply	

1. **Note:**
   The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
2. This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.
3. The actual working frequency band of the device is UHF: 400-470MHz. According to the frequency division requirements of KDB634817 and the federal frequency allocation requirements, the working frequency band that the device needs to meet is UHF: 406.1-470MHz.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.2 Test Frequency List

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
Analog/ Digital	12.5 kHz	400-470MHz	Bottom	406.125 MHz
	12.5 kHz	400-470MHz	Middle	453.2125 MHz
	12.5 kHz	400-470MHz	Middle	458.025 MHz
	12.5 kHz	400-470MHz	Top	469.975 MHz

Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2BLTR-RPT2U,** filing to comply with Part 2, Part 90 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 90	Private Land Mobile Radio Services
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
3	ANSI TIA-102.CAAA-E	Project 25 Digital C4FM/CQPSK Transceiver Measurement Methods
4	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
5	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
6	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01
7	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01
8	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01

2.5 Calculation of Emission Indicators

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For FM Mode (Channel Spacing: 12.5kHz)
Emission Designator 11K0F3E
In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.
BW = 2(M+D) = 2*(3.0 kHz + 2.5 kHz) = 11 kHz = 11K0
F3E portion of the designator represents an FM voice transmission.
Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)
Emission Designator 7K60FXD and 7K60FXW
The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.
F7D and F7W portion of the designator indicates digital information.
Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F7D and 7K60F7W.
F1D and F1W portion of the designator indicates digital information.
Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.
FXD and FXW portion of the designator indicates digital information.
Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60FXD and 7K60FXW.

2.6 Special Accessories

Not available for this EUT intended for grant.

2.7 Equipment Modifications

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 101 & 201, Building 19(B5), Junfeng Industrial Park, Chongqing Road, P.R.C.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3.3 Environmental Conditions

	Normal Conditions	Extreme Conditions
Temperature range (℃)	15 - 35	-30 - 50
Relative humidty range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC 13.6V	DC 12.24V or DC 17.68V
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.		

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	±0.5%
Transmitter power conducted	±0.8dB
Transmitter power Radiated	±1.3dB
Conducted spurious emission 9kHz-40 GHz	±2.7dB
Conducted Emission	±3.2 dB
Radiated Emission below 1GHz	±3.9 dB
Radiated Emission above 1GHz	±4.8 dB
Occupied Channel Bandwidth	±2 %
FM deviation	±2 %
Audio level	±0.98dB
Low Pass Filter Response	±0.65dB
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3.5 List of Equipment Used

● RF Conducted Test System

Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-ER-E086	Spectrum Analyzer	KEYSIGHT	N9020A	MY53300860	2025-05-08	2026-05-07
☒	AGC-EM-E002	Wireless Connectivity Tester	HP	8920B	US35010161	2025-05-08	2026-05-07
☒	AGC-EM-E001	Digital Connectivity Tester	Aeroflex	3920B	N/A	2023-05-11	2025-05-10
☒	AGC-ER-E059	Signal Generator	Agilent	N5182B	MY53050647	2025-01-14	2026-01-13
☒	AGC-ER-E059	Signal Generator	Agilent	N5182B	MY53050647	2026-01-13	2027-01-12
☒	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2025-05-08	2026-05-07
☒	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2024-07-24	2026-07-23
☒	AGC-EM-A007	30dB Attenuator	Weinachel	58-30-33	ML030	2025-05-31	2027-05-30
☒	AGC-EM-E040	Directional coupler	Werlatone	C5571-10	99463	2024-02-01	2026-01-31
☒	AGC-EM-E040	Directional coupler	Werlatone	C5571-10	99463	2026-01-13	2028-01-12
☒	--	RF Connection Cable	N/A	1#	N/A	Each time	N/A
☒	--	RF Connection Cable	N/A	2#	N/A	Each time	N/A

● Radiated Spurious Emission

Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2025-05-08	2026-05-07
☒	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2025-05-08	2026-05-07
☒	AGC-ER-E032	Universal Radio Communication Tester	R&S	CMW500	120909	2025-05-16	2026-05-15
☒	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
☒	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2026-01-14	2028-01-13
☒	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2025-03-14	2027-03-13
☒	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2023-01-17	2025-01-16
☒	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2025-01-15	2027-01-14
☒	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-07-24	2026-07-23
☒	AGC-EM-E102	Broadband Ridged Horn Antenna	ETS	3117	00154520	2025-05-18	2026-05-17
☐	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2025-09-10	2027-09-09
☒	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23
☐	AGC-EM-E021	Pre-amplifier	MITEQ	AM-4A-000115	1465421	2024-05-28	2026-05-27
☒	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2025-05-08	2026-05-07

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

☐	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-2W	N/A	2023-06-09	2025-06-08
☒	AGC-EM-A088	UHF Filter	N/A	N/A	N/A	2025-05-16	2026-05-15

● Test Software

Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
☒	AGC-EM-S004	RE Test System	Tonscend	TS+ Ver2.1(JS32-RE)	4.0.0.0

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Fig. 2-1 Configuration of Tested System

Table 2-1 Equipment Used in Tested System

4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:
☒ Test Accessories Come From The Laboratory
☐ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Load Antenna	Amphenol	HG-E10	Terminator DC -3G 50W	--
2	Hand microphone	N/A	N/A	N/A	--

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.5 Summary of Test Results

Item	FCC Rules	Description Of Test	Result
1	47 CFR FCC PART 90	Antenna Equipment	Pass
2	§90.205& 2.1046	Maximum Transmitter Power	Pass
3	§90.207& 2.1047	Modulation Characteristic	Pass
4	§2.1047	Audio Low Pass Filter Response	Pass
5	§90.209& 2.1049	26dB Emission Bandwidth and 99% Occupied Bandwidth	Pass
6	§90.210& 2.1049	Emission Mask	Pass
7	§90.213& 2.1055	Frequency Tolerance	Pass
8	§90.214	Transmitter Frequency Behavior	Pass
9	§90.210& 2.1051	Spurious Emission on Antenna Port	Pass
10	§90.210& 2.1053	Spurious Radiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5. Description of Test Modes

The EUT (**DMR Repeater**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

No.	Test Mode Description	Channel Separation
1	TX Bottom channel-VHF_	12.5 kHz
2	TX Middle channel-VHF	12.5 kHz
3	TX Top channel-VHF	12.5 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
4. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6. Frequency Stability

6.1 Provisions Applicable

a) According to FCC §2.1055, §90.213, the frequency stability shall be measured with variation of ambient temperature from –30℃ to +50℃ centigrade.
b) According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
c) According to FCC Part 90 Section 90.213, the 421-512 MHz band, fixed and base stations with a 12.5kHz channel bandwidth must have a frequency stability of 1.5 ppm..

6.2 Measurement Procedure

6.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz.Record this frequency as reference frequency.
3. Set the temperature of chamber to 50℃. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10℃ decreased per stage until the lowest temperature -30℃ is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15℃ to 25℃. Otherwise, an environment chamber set for a temperature of 20℃ shall be used. The EUT shall be powered by DC 13.6V
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6.4 Measurement Result

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (℃)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
13.6	-30	0.711	0.945	0.938	0.501	1.5	Pass
	-20	1.007	0.631	0.916	0.501		
	-10	0.927	1.008	0.700	0.307		
	0	0.632	1.000	0.521	0.965		
	10	0.879	0.817	0.941	0.414		
	20	0.662	0.685	0.788	0.572		
	30	0.621	0.510	0.648	0.941		
	40	0.562	1.019	0.853	0.982		
	50	0.833	0.994	0.854	0.336		
12.24	20	0.899	0.767	0.573	0.890		
17.68	20	0.987	0.762	0.956	0.507		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7. 26dB Emission Bandwidth and 99% Occupied Bandwidth

7.1 Provisions Applicable

FCC Part 90.209 & FCC Part 2.1049:
The authorized bandwidth shall be 11.25 kHz for 12.5 kHz channel separation and 6 kHz for 6.25 kHz channel separation.

7.2 Measurement Procedure

1. The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.
2. Rated system deviation is 2.5 kHz for 12.5kHz channel spacing.
3. Spectrum set as follow:
4. Centre frequency = fundamental frequency.
5. Span=50kHz for 12.5kHz channel spacing.
6. RBW=100Hz, VBW=300Hz, Sweep = auto.
7. Detector function = peak, Trace = max hold.
8. Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
9. Measure and record the results in the test report.

7.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7.4 Measurement Result

Measurement Result of Analog Modulation				
Operating Frequency (MHz)	12.5 kHz Channel Separation			
	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Limits (kHz)	Result
406.125	9.926	10.16	11.25 kHz	Pass
453.2125	9.932	10.16	11.25 kHz	Pass
458.2125	9.925	10.16	11.25 kHz	Pass
469.975	9.920	10.15	11.25 kHz	Pass

Measurement Result of Digital Modulation				
Operating Frequency (MHz)	12.5 kHz Channel Separation			
	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Limits (kHz)	Result
406.125	7.756	9.849	11.25 kHz	Pass
453.2125	7.880	9.534	11.25 kHz	Pass
458.2125	7.802	9.650	11.25 kHz	Pass
469.975	7.663	9.499	11.25 kHz	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:

12.5kHz, FM Modulation:406.125MHz



12.5kHz, FM Modulation:453.2125MHz



12.5kHz, FM Modulation:458.2125MHz



12.5kHz, FM Modulation:469.975MHz



12.5kHz, 4FSK Modulation:406.125MHz-50W



12.5kHz, 4FSK Modulation:453.2125MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5kHz, 4FSK Modulation:458.2125MHz	12.5kHz, 4FSK Modulation:469.975MHz
	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8. Spurious Radiated Emission

8.1 Provisions Applicable

According to FCC §2.1053 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.
Emission Mask D -for 12.5 kHz Channel Separation:

(1) On any frequency removed from the center of the authorized bandwidth fo to 5.625 kHz removed from fo: Zero dB.
(2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (fd in kHz) fo of more than 5.625 kHz but no more than 12.5 kHz: At least 7.27(fd-2.88 kHz) dB
(3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (fd in kHz)fo of more than 12.5 kHz: At least 50+10 log(P) dB or 70 dB, whichever is lesser attenuation.

8.2 Measurement Procedure

1. On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
2. The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
3. The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
4. The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
6. The transmitter shall than be rotated through 360°in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The measurement shall be repeated with the test antenna set to horizontal polarization.
10. (Replace the antenna with a proper Antenna (substitution antenna).
11. The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
12. The substitution antenna shall be connected to a calibrated signal generator.
13. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
14. The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
15. The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
16. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
17. The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.3 Measurement Setup

Radiated Emissions 30MHz to 1GHz Test setup





Radiated Emissions Above 1GHz Test setup





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.4 Measurement Result

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The “Read Value” is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.

EIRP = “Read Value” + Measured substitution value + 2.15.

Test limit calculation:

Preliminary calculation	Final Result
At least 50+10 log (P) =50+10log (50) =66.99 (dB)	Limit=P- Preliminary calculation=46.99-66.99=-20dBm

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:406.125MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	34.85	-100.29	-70.78	-20.00	50.78	29.51	360	Horizontal
2	55.22	-101.25	-74.40	-20.00	54.40	26.85	177	Horizontal
3	139.61	-101.42	-74.45	-20.00	54.45	26.97	360	Horizontal
4	257.95	-100.97	-73.56	-20.00	53.56	27.41	243	Horizontal
5	831.22	-100.47	-63.88	-20.00	43.88	36.59	313	Horizontal
6	955.38	-100.34	-62.23	-20.00	42.23	38.11	225	Horizontal

Test Mode:	TX:406.125MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	30.97	-100.39	-70.83	-20.00	50.83	29.56	193	Vertical
2	58.13	-100.39	-74.01	-20.00	54.01	26.38	0	Vertical
3	138.64	-101.07	-74.30	-20.00	54.30	26.77	325	Vertical
4	306.45	-100.90	-73.62	-20.00	53.62	27.28	351	Vertical
5	624.61	-98.40	-64.13	-20.00	44.13	34.27	60	Vertical
6	938.89	-99.65	-61.77	-20.00	41.77	37.88	0	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:406.125MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1195.0695	-54.56	-58.64	-20.00	38.64	-4.08	170	Horizontal
2	2577.0077	-53.92	-51.55	-20.00	31.55	2.37	220	Horizontal
3	3753.3003	-56.19	-53.79	-20.00	33.79	2.40	60	Horizontal
4	5412.5663	-57.24	-51.60	-20.00	31.60	5.64	200	Horizontal
5	8056.5807	-54.75	-47.08	-20.00	27.08	7.67	30	Horizontal
6	11901.5652	-56.38	-43.19	-20.00	23.19	13.19	320	Horizontal

Test Mode:	TX:406.125MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1526.4526	-55.03	-58.84	-20.00	38.84	-3.81	60	Vertical
2	2215.0715	-53.33	-51.09	-20.00	31.09	2.24	40	Vertical
3	3260.9261	-54.56	-52.64	-20.00	32.64	1.92	330	Vertical
4	4423.1173	-54.77	-50.64	-20.00	30.64	4.13	230	Vertical
5	6931.9932	-55.98	-47.76	-20.00	27.76	8.22	180	Vertical
6	12305.8056	-57.26	-44.02	-20.00	24.02	13.24	0	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:453.2125MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	35.82	-100.27	-70.68	-20.00	50.68	29.59	1	Horizontal
2	49.4	-100.57	-72.78	-20.00	52.78	27.79	53	Horizontal
3	139.61	-101.22	-74.25	-20.00	54.25	26.97	258	Horizontal
4	265.71	-100.72	-73.30	-20.00	53.30	27.42	142	Horizontal
5	768.17	-99.42	-63.72	-20.00	43.72	35.70	10	Horizontal
6	906.88	-97.19	-60.31	-20.00	40.31	36.88	158	Horizontal

Test Mode:	TX:453.2125MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	40.67	-100.86	-71.31	-20.00	51.31	29.55	78	Vertical
2	55.22	-100.84	-73.99	-20.00	53.99	26.85	350	Vertical
3	137.67	-101.69	-75.13	-20.00	55.13	26.56	192	Vertical
4	249.22	-99.87	-72.47	-20.00	52.47	27.40	52	Vertical
5	796.3	-101.05	-64.11	-20.00	44.11	36.94	292	Vertical
6	906.88	-93.82	-56.94	-20.00	36.94	36.88	192	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:453.2125MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1518.2268	-55.28	-59.18	-20.00	39.18	-3.90	290	Horizontal
2	2246.7997	-54.77	-52.50	-20.00	32.50	2.27	230	Horizontal
3	3137.5388	-55.54	-53.81	-20.00	33.81	1.73	290	Horizontal
4	5404.3404	-57.26	-51.63	-20.00	31.63	5.63	130	Horizontal
5	7842.7093	-55.37	-47.83	-20.00	27.83	7.54	240	Horizontal
6	10970.8721	-56.75	-43.03	-20.00	23.03	13.72	290	Horizontal

Test Mode:	TX:453.2125MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1408.9409	-55.06	-59.18	-20.00	39.18	-4.12	200	Vertical
2	2267.9518	-54.29	-52.00	-20.00	32.00	2.29	220	Vertical
3	3259.751	-55.65	-53.73	-20.00	33.73	1.92	40	Vertical
4	5249.2249	-56.70	-51.32	-20.00	31.32	5.38	30	Vertical
5	7195.2195	-54.89	-46.92	-20.00	26.92	7.97	200	Vertical
6	12364.5615	-56.66	-43.40	-20.00	23.40	13.26	100	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:458.2125MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	30	-92.30	-62.85	-20.00	42.85	29.45	308	Horizontal
2	32.91	-92.57	-62.98	-20.00	42.98	29.59	142	Horizontal
3	39.7	-94.77	-65.11	-20.00	45.11	29.66	106	Horizontal
4	136.7	-94.27	-67.88	-20.00	47.88	26.39	220	Horizontal
5	476.2	-95.73	-65.32	-20.00	45.32	30.41	97	Horizontal
6	916.58	-93.17	-55.97	-20.00	35.97	37.20	212	Horizontal

Test Mode:	TX:458.2125MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	36.79	-84.35	-54.73	-20.00	34.73	29.62	350	Vertical
2	58.13	-93.61	-67.23	-20.00	47.23	26.38	359	Vertical
3	141.55	-101.86	-75.04	-20.00	55.04	26.82	47	Vertical
4	260.86	-101.22	-73.78	-20.00	53.78	27.44	359	Vertical
5	794.36	-100.00	-63.15	-20.00	43.15	36.85	38	Vertical
6	916.58	-91.31	-54.11	-20.00	34.11	37.20	234	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:458.2125MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1117.5118	-55.20	-59.27	-20.00	39.27	-4.07	20	Horizontal
2	2298.5048	-54.91	-52.58	-20.00	32.58	2.33	50	Horizontal
3	3334.9585	-55.27	-53.24	-20.00	33.24	2.03	190	Horizontal
4	5221.0221	-57.15	-51.81	-20.00	31.81	5.34	360	Horizontal
5	6883.8134	-54.82	-46.66	-20.00	26.66	8.16	100	Horizontal
6	12042.5793	-56.53	-43.37	-20.00	23.37	13.16	210	Horizontal

Test Mode:	TX:458.2125MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1237.3737	-54.66	-58.74	-20.00	38.74	-4.08	170	Vertical
2	2186.8687	-55.13	-52.91	-20.00	32.91	2.22	270	Vertical
3	3477.1477	-55.61	-53.35	-20.00	33.35	2.26	270	Vertical
4	5013.0263	-56.70	-51.70	-20.00	31.70	5.00	70	Vertical
5	6832.1082	-55.07	-46.98	-20.00	26.98	8.09	90	Vertical
6	10983.7984	-57.65	-43.89	-20.00	23.89	13.76	60	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:469.975MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	37.76	-100.01	-70.38	-20.00	50.38	29.63	55	Horizontal
2	53.28	-92.11	-64.93	-20.00	44.93	27.18	9	Horizontal
3	109.54	-93.81	-73.83	-20.00	53.83	19.98	82	Horizontal
4	255.04	-100.17	-72.81	-20.00	52.81	27.36	360	Horizontal
5	679.9	-91.53	-57.34	-20.00	37.34	34.19	65	Horizontal
6	940.83	-94.29	-56.37	-20.00	36.37	37.92	204	Horizontal

Test Mode:	TX:469.975MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	35.82	-99.24	-69.65	-20.00	49.65	29.59	0	Vertical
2	62.01	-99.03	-73.51	-20.00	53.51	25.52	15	Vertical
3	139.61	-101.63	-74.66	-20.00	54.66	26.97	85	Vertical
4	253.1	-100.65	-73.25	-20.00	53.25	27.40	315	Vertical
5	639.16	-100.16	-65.70	-20.00	45.70	34.46	342	Vertical
6	940.83	-88.10	-50.18	-20.00	30.18	37.92	191	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:469.975MHz-FM	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1185.6686	-55.23	-59.31	-20.00	39.31	-4.08	350	Horizontal
2	2233.8734	-53.00	-50.74	-20.00	30.74	2.26	280	Horizontal
3	3498.2998	-55.61	-53.32	-20.00	33.32	2.29	200	Horizontal
4	5404.3404	-57.81	-52.18	-20.00	32.18	5.63	250	Horizontal
5	6841.5092	-55.38	-47.27	-20.00	27.27	8.11	160	Horizontal
6	10942.6693	-57.22	-43.59	-20.00	23.59	13.63	150	Horizontal

Test Mode:	TX:469.975MHz-FM	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1185.6686	-54.06	-58.14	-20.00	38.14	-4.08	250	Vertical
2	2332.5833	-55.63	-53.27	-20.00	33.27	2.36	220	Vertical
3	3172.7923	-55.64	-53.86	-20.00	33.86	1.78	170	Vertical
4	5179.893	-56.94	-51.67	-20.00	31.67	5.27	310	Vertical
5	6997.7998	-55.00	-46.69	-20.00	26.69	8.31	270	Vertical
6	12035.5286	-56.46	-43.31	-20.00	23.31	13.15	140	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:406.125MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	30	-100.44	-70.99	-20.00	50.99	29.45	193	Horizontal
2	54.25	-100.58	-73.53	-20.00	53.53	27.05	86	Horizontal
3	148.34	-100.31	-74.48	-20.00	54.48	25.83	260	Horizontal
4	291.9	-100.70	-73.48	-20.00	53.48	27.22	203	Horizontal
5	544.1	-100.73	-68.69	-20.00	48.69	32.04	9	Horizontal
6	986.42	-100.63	-62.70	-20.00	42.70	37.93	106	Horizontal

Test Mode:	TX:406.125MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	31.94	-100.84	-71.27	-20.00	51.27	29.57	290	Vertical
2	39.7	-100.48	-70.82	-20.00	50.82	29.66	5	Vertical
3	140.58	-101.23	-74.26	-20.00	54.26	26.97	219	Vertical
4	272.5	-100.61	-73.26	-20.00	53.26	27.35	290	Vertical
5	799.21	-101.31	-64.22	-20.00	44.22	37.09	0	Vertical
6	952.47	-99.87	-61.70	-20.00	41.70	38.17	351	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:406.125MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1195.0695	-54.56	-58.64	-20.00	38.64	-4.08	170	Horizontal
2	2577.0077	-53.92	-51.55	-20.00	31.55	2.37	220	Horizontal
3	3753.3003	-56.19	-53.79	-20.00	33.79	2.40	60	Horizontal
4	5412.5663	-57.24	-51.60	-20.00	31.60	5.64	200	Horizontal
5	8056.5807	-54.75	-47.08	-20.00	27.08	7.67	30	Horizontal
6	11901.5652	-56.38	-43.19	-20.00	23.19	13.19	320	Horizontal

Test Mode:	TX:406.125MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1526.4526	-55.03	-58.84	-20.00	38.84	-3.81	60	Vertical
2	2215.0715	-53.33	-51.09	-20.00	31.09	2.24	40	Vertical
3	3260.9261	-54.56	-52.64	-20.00	32.64	1.92	330	Vertical
4	4423.1173	-54.77	-50.64	-20.00	30.64	4.13	230	Vertical
5	6931.9932	-55.98	-47.76	-20.00	27.76	8.22	180	Vertical
6	12305.8056	-57.26	-44.02	-20.00	24.02	13.24	0	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:453.2125MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	41.64	-99.20	-69.82	-20.00	49.82	29.38	338	Horizontal
2	60.07	-100.33	-74.48	-20.00	54.48	25.85	1	Horizontal
3	139.61	-101.03	-74.06	-20.00	54.06	26.97	83	Horizontal
4	283.17	-101.00	-73.75	-20.00	53.75	27.25	145	Horizontal
5	824.43	-100.58	-63.85	-20.00	43.85	36.73	242	Horizontal
6	906.88	-97.29	-60.41	-20.00	40.41	36.88	215	Horizontal

Test Mode:	TX:453.2125MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	48.43	-93.10	-65.09	-20.00	45.09	28.01	3	Vertical
2	67.83	-88.32	-63.70	-20.00	43.70	24.62	270	Vertical
3	130.88	-84.38	-59.11	-20.00	39.11	25.27	234	Vertical
4	288.99	-98.48	-71.24	-20.00	51.24	27.24	252	Vertical
5	807.94	-101.28	-64.19	-20.00	44.19	37.09	161	Vertical
6	906.88	-93.21	-56.33	-20.00	36.33	36.88	198	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:453.2125MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1518.2268	-55.28	-59.18	-20.00	39.18	-3.90	290	Horizontal
2	2246.7997	-54.77	-52.50	-20.00	32.50	2.27	230	Horizontal
3	3137.5388	-55.54	-53.81	-20.00	33.81	1.73	290	Horizontal
4	5404.3404	-57.26	-51.63	-20.00	31.63	5.63	130	Horizontal
5	7842.7093	-55.37	-47.83	-20.00	27.83	7.54	240	Horizontal
6	10970.8721	-56.75	-43.03	-20.00	23.03	13.72	290	Horizontal

Test Mode:	TX:453.2125MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1408.9409	-55.06	-59.18	-20.00	39.18	-4.12	200	Vertical
2	2267.9518	-54.29	-52.00	-20.00	32.00	2.29	220	Vertical
3	3259.751	-55.65	-53.73	-20.00	33.73	1.92	40	Vertical
4	5249.2249	-56.70	-51.32	-20.00	31.32	5.38	30	Vertical
5	7195.2195	-54.89	-46.92	-20.00	26.92	7.97	200	Vertical
6	12364.5615	-56.66	-43.40	-20.00	23.40	13.26	100	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:458.2125MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	37.76	-100.02	-70.39	-20.00	50.39	29.63	72	Horizontal
2	59.1	-100.08	-73.93	-20.00	53.93	26.15	196	Horizontal
3	144.46	-100.82	-74.41	-20.00	54.41	26.41	178	Horizontal
4	248.25	-100.87	-73.59	-20.00	53.59	27.28	301	Horizontal
5	813.76	-100.98	-63.98	-20.00	43.98	37.00	19	Horizontal
6	916.58	-91.78	-54.58	-20.00	34.58	37.20	214	Horizontal

Test Mode:	TX:458.2125MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	32.91	-101.40	-71.81	-20.00	51.81	29.59	359	Vertical
2	54.25	-101.28	-74.23	-20.00	54.23	27.05	219	Vertical
3	147.37	-100.73	-74.80	-20.00	54.80	25.93	201	Vertical
4	254.07	-100.91	-73.53	-20.00	53.53	27.38	0	Vertical
5	807.94	-100.73	-63.64	-20.00	43.64	37.09	0	Vertical
6	916.58	-90.88	-53.68	-20.00	33.68	37.20	236	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:458.2125MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1117.5118	-55.20	-59.27	-20.00	39.27	-4.07	20	Horizontal
2	2298.5048	-54.91	-52.58	-20.00	32.58	2.33	50	Horizontal
3	3334.9585	-55.27	-53.24	-20.00	33.24	2.03	190	Horizontal
4	5221.0221	-57.15	-51.81	-20.00	31.81	5.34	360	Horizontal
5	6883.8134	-54.82	-46.66	-20.00	26.66	8.16	100	Horizontal
6	12042.5793	-56.53	-43.37	-20.00	23.37	13.16	210	Horizontal

Test Mode:	TX:458.2125MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1237.3737	-54.66	-58.74	-20.00	38.74	-4.08	170	Vertical
2	2186.8687	-55.13	-52.91	-20.00	32.91	2.22	270	Vertical
3	3477.1477	-55.61	-53.35	-20.00	33.35	2.26	270	Vertical
4	5013.0263	-56.70	-51.70	-20.00	31.70	5.00	70	Vertical
5	6832.1082	-55.07	-46.98	-20.00	26.98	8.09	90	Vertical
6	10983.7984	-57.65	-43.89	-20.00	23.89	13.76	60	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions 30MHz to 1GHz			
Test Mode:	TX:469.975MHz-4FSK	Polarity:	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	30.97	-101.00	-71.44	-20.00	51.44	29.56	106	Horizontal
2	54.25	-101.41	-74.36	-20.00	54.36	27.05	334	Horizontal
3	138.64	-101.32	-74.55	-20.00	54.55	26.77	36	Horizontal
4	259.89	-100.69	-73.25	-20.00	53.25	27.44	10	Horizontal
5	808.91	-100.36	-63.29	-20.00	43.29	37.07	10	Horizontal
6	940.83	-94.48	-56.56	-20.00	36.56	37.92	202	Horizontal

Test Mode:	TX:469.975MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	30	-100.09	-70.64	-20.00	50.64	29.45	0	Vertical
2	56.19	-101.02	-74.32	-20.00	54.32	26.70	104	Vertical
3	140.58	-101.62	-74.65	-20.00	54.65	26.97	0	Vertical
4	255.04	-100.11	-72.75	-20.00	52.75	27.36	289	Vertical
5	819.58	-99.66	-62.85	-20.00	42.85	36.81	183	Vertical
6	940.83	-88.98	-51.06	-20.00	31.06	37.92	183	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Emissions Above 1GHz			
Test Mode:	TX:469.975MHz-4FSK	Polarity:	Horizontal



2

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1185.6686	-55.23	-59.31	-20.00	39.31	-4.08	350	Horizontal
2	2233.8734	-53.00	-50.74	-20.00	30.74	2.26	280	Horizontal
3	3498.2998	-55.61	-53.32	-20.00	33.32	2.29	200	Horizontal
4	5404.3404	-57.81	-52.18	-20.00	32.18	5.63	250	Horizontal
5	6841.5092	-55.38	-47.27	-20.00	27.27	8.11	160	Horizontal
6	10942.6693	-57.22	-43.59	-20.00	23.59	13.63	150	Horizontal

Test Mode:	TX:469.975MHz-4FSK	Polarity:	Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1185.6686	-54.06	-58.14	-20.00	38.14	-4.08	250	Vertical
2	2332.5833	-55.63	-53.27	-20.00	33.27	2.36	220	Vertical
3	3172.7923	-55.64	-53.86	-20.00	33.86	1.78	170	Vertical
4	5179.893	-56.94	-51.67	-20.00	31.67	5.27	310	Vertical
5	6997.7998	-55.00	-46.69	-20.00	26.69	8.31	270	Vertical
6	12035.5286	-56.46	-43.31	-20.00	23.31	13.15	140	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.5 Emission Mask Measurement Part

The detailed procedure employed for Emission Mask measurements are specified as following:

-Connect the equipment as illustrated.

-Spectrum set as follow:

1. Centre frequency = fundamental frequency, Span=50kHz for 12.5kHz channel spacing, RBW=100Hz, VBW=300Hz for 12.5kHz, Sweep = auto, Detector function = peak, Trace = max hold
2. Key the transmitter, and set the level of the unmodulated carrier to a fullscale reference line. This is the 0dB reference for the measurement.
3. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing). The input level shall be established at the frequency of maximum response of the audio modulating circuit.
4. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
5. Measure and record the results in the test report.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:

Emission Mask D@406.125MHz-FM



Emission Mask D@453.2125MHz-FM



Emission Mask D@458.2125MHz-FM



Emission Mask D@469.975MHz-FM



Emission Mask D@406.125MHz-4FSK



Emission Mask D@453.2125MHz-4FSK



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Emission Mask D@458.2125MHz-4FSK	Emission Mask D@469.975MHz-4FSK
	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9. Modulation Characteristics

9.1 Provisions Applicable

According to FCC§2.1047 and §90.207, for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

9.2 Measurement Procedure

- **Modulation Limit**

1. Test layout and build equipment as shown below.
2. adjust the audio input for 60% of rated system deviation at 1kHz using this level as a reference (0dB).
3. Vary the input level from –20 to +20dB.
4. Record the frequency deviation obtained as a function of the input level.
5. Repeat step 2 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

- **Audio Frequency Response**

1. Test layout and build equipment as shown below.
2. Adjust the audio input for 20% of rated system deviation at 1 kHz using this level as a reference (0 dB).
3. Vary the Audio frequency from 100 Hz to 10 kHz and record the frequency deviation.
4. Audio Frequency Response = 20log10 (Deviation of test frequency/Deviation of 1 kHz reference).

9.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.4 Measurement Result

A. Modulation Limit:

12.5kHz, Analog modulation, Assigned Frequency:406.125MHz				
Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (kHz)	Peak Freq. Deviation At 1000 Hz (kHz)	Peak Freq. Deviation At 1500 Hz (kHz)	Peak Freq. Deviation At 3000 Hz (kHz)
-20	0.25	0.52	0.82	1.06
-15	0.37	0.66	0.99	1.21
-10	0.41	0.74	1.05	1.32
-5	0.52	0.96	1.12	1.45
0	0.63	1.05	1.23	1.53
+5	0.82	1.12	1.45	1.61
+10	0.99	1.23	1.53	1.78
+15	1.05	1.35	1.61	1.82
+20	1.04	1.31	1.59	1.74



Note: All the modes had been tested, but only the worst data recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

B. Audio Frequency Response:

12.5kHz, Analog modulation, Assigned Frequency:406.125MHz		
Frequency (Hz)	Deviation (kHz)	Audio Frequency Response(dB)
100	--	--
200	--	--
300	0.16	-14.51
400	0.28	-9.65
500	0.39	-6.77
600	0.45	-5.52
700	0.53	-4.10
800	0.66	-2.20
900	0.74	-1.20
1000	**0.85**	0.00
1200	0.99	1.32
1400	1.12	2.40
1600	1.29	3.62
1800	1.37	4.15
2000	1.55	5.22
2400	1.71	6.07
2500	1.92	7.08
2800	2.05	7.65
3000	2.22	8.34



Note: All the modes had been tested, but only the worst data recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10. Maximum Transmitter Power

10.1 Provisions Applicable

Per FCC §2.1046 and §90.205: Maximum ERP is dependent upon the station's antenna HAAT and required service area.

10.2 Measurement Procedure

The RF output of Two-way Radio was conducted to a spectrum analyzer through an appropriate attenuator.
In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.
The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum.
So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.
EIRP = "Read Value" + Measured substitution value + 2.15.

10.3 Measurement Setup

☒Conducted Output Power:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

☒Effective Radiated Power:

Radiated Below 1GHz





Radiated Above 1 GHz





Any report havin ng/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10.4 Measurement Result

Conducted Power Measurement Results			
Mode	Channel Separation	Test Channel	Measurement Result (dBm)
			For 46.99dBm(50W)
Analog	12.5 kHz	Bottom(406.125MHz)	46.11
		Middle(453.2125MHz)	46.12
		Middle(458.2125MHz)	**46.20**
		Top (469.975MHz)	46.17
Digital	12.5 kHz	Bottom(406.125MHz)	**46.11**
		Middle(453.2125MHz)	46.03
		Middle(458.2125MHz)	46.09
		Top (469.975MHz)	46.07

Radiated Power Measurement Results								
Test Mode	Frequency (MHz)	Reading Level (dBuv/m)	Antenna Polarization	S.G. (dBm)	Cable Loss (dB)	Ant.Gain (dBi)	ERP Results (dBm)	Limit (dBm)
Analog + Voice	406.1250	114.97	V	39.74	0.85	6.9	45.79	46.99
	406.1250	114.89	H	39.66	0.85	6.9	45.71	46.99
	453.2125	114.98	V	39.75	0.85	6.9	45.80	46.99
	453.2125	114.95	H	39.72	0.85	6.9	45.77	46.99
	458.2125	115.07	V	39.84	0.85	6.9	45.89	46.99
	458.2125	114.99	H	39.76	0.85	6.9	45.81	46.99
	469.975	115.03	V	39.80	0.85	6.9	45.85	46.99
	469.975	114.91	H	39.68	0.85	6.9	45.73	46.99
Digital (Voice +Data)	406.1250	114.99	V	39.76	0.85	6.9	45.81	46.99
	406.1250	114.90	H	39.67	0.85	6.9	45.72	46.99
	453.2125	114.88	V	39.65	0.85	6.9	45.70	46.99
	453.2125	114.84	H	39.61	0.85	6.9	45.66	46.99
	458.2125	114.91	V	39.68	0.85	6.9	45.73	46.99
	458.2125	114.81	H	39.58	0.85	6.9	45.63	46.99
	469.975	114.89	V	39.66	0.85	6.9	45.71	46.99
	469.975	114.84	H	39.61	0.85	6.9	45.66	46.99

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Note:

Calculation Formula: CP = R + A + L

- CP: The final Conducted Power
- R: The reading value from spectrum analyzer
- A: The attenuation value of the used attenuator
- L: The loss of all connection cables
- Measurement Result=Peak Power (Max)

Test plot as follows:

12.5kHz, FM Modulation:406.125MHz	12.5kHz, FM Modulation:453.2125MHz
	
12.5kHz, FM Modulation:458.2125MHz	12.5kHz, FM Modulation:469.975MHz
	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.