

FCC RADIO TEST REPORT

FCC ID: 2BLU9-LD5093

Product: Q-Book+, Notebook

Trade Mark: Compaq

Model No.: QL15R3HE8256

Family Model: H15W1P-3200U

Report No.: N26042904605E

Issue Date: Aug. 07, 2025

Prepared for

M&M Electronics, S.A.

Cocosolito, Colon Free Zone, Main Entrance Warehouse 10D and 11D,
Colon, Panama

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : M&M Electronics, S.A.
Address : Cocosolito, Colon Free Zone, Main Entrance Warehouse 10D and 11D, Colon, Panama
Manufacturer's Name : Hena Digital Technology (Shenzhen) Co., Ltd.
Address : 13F, Block B, Tairan Building Tairan 8th Road, Futian District, Shenzhen, China

Product description

Product name : Q-Book+, Notebook
Trademark : Compaq
Model and/or type reference : QL15R3HE8256
Family Model : H15W1P-3200U
Test Sample Number : S2605070340-1#

Standards : FCC Part15.407

Test procedure ANSI C63.10-2020+Cor 1-2023
 KDB 789033 D02 General UNII Test Procedures New Rules v02r01
 KDB 905462 D03 Client Without DFS New Rules v01r02
 KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Apr. 29, 2026 ~ Jun. 02, 2026

Date of Issue Jun. 02, 2026

Test Result **Pass**

Prepared By : Allen Liu
 Allen Liu
 (Project Engineer)

Reviewed By : Aaron Cheng
 Aaron Cheng
 (Supervisor)

Approved By : Alex Li
 Alex Li
 (Manager)

Table of Contents

	Page
1. SUMMARY OF TEST RESULTS	7
1.1 FACILITIES AND ACCREDITATIONS	8
1.2 MEASUREMENT UNCERTAINTY	8
2. GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	13
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	14
3. EMC EMISSION TEST	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.1.1 APPLICABLE STANDARD	16
3.1.2 CONFORMANCE LIMIT	16
3.1.3 TEST CONFIGURATION	16
3.1.4 TEST PROCEDURE	17
3.2 RADIATED EMISSION MEASUREMENT	26
3.2.1 APPLICABLE STANDARD	26
3.2.2 CONFORMANCE LIMIT	26
3.2.3 MEASURING INSTRUMENTS	26
3.2.4 TEST CONFIGURATION	27
3.2.5 TEST PROCEDURE	28
3.2.6 TEST RESULTS (9KHZ – 30 MHZ)	29
3.2.7 TEST RESULTS (30MHZ – 1GHZ)	30
3.2.9 TEST RESULTS (18GHZ-40GHZ)	42
4 POWER SPECTRAL DENSITY TEST	53
4.1 APPLIED PROCEDURES / LIMIT	53
4.2 TEST PROCEDURE	54
4.3 DEVIATION FROM STANDARD	54
4.4 TEST SETUP	54
4.5 EUT OPERATION CONDITIONS	54
4.6 TEST RESULTS	55
5. 26DB & 99% EMISSION BANDWIDTH	56
5.1 APPLIED PROCEDURES / LIMIT	56
5.2 TEST PROCEDURE	56
5.3 EUT OPERATION CONDITIONS	57
5.4 TEST RESULTS	57

Table of Contents

	Page
6. MINIMUM 6 DB BANDWIDTH	58
6.1 APPLIED PROCEDURES / LIMIT	58
6.2 EST PROCEDURE	58
6.3 DEVIATION FROM STANDARD	58
6.4 TEST SETUP	58
6.5 EUT OPERATION CONDITIONS	58
6.6 TEST RESULTS	59
7. MAXIMUM CONDUCTED OUTPUT POWER	60
7.1 PPLIED PROCEDURES / LIMIT	60
7.6 TEST RESULTS	62
8. OUT OF BAND EMISSIONS	63
8.1 APPLICABLE STANDARD	63
8.2 TEST PROCEDURE	63
8.3 DEVIATION FROM STANDARD	63
8.4 TEST SETUP	63
8.5 EUT OPERATION CONDITIONS	64
8.6 TEST RESULTS	65
9. FREQUENCY STABILITY MEASUREMENT	66
9.1 LIMIT	66
9.2 TEST PROCEDURES	66
9.3 TEST SETUP LAYOUT	66
9.4 EUT OPERATION DURING TEST	66
9.5 TEST RESULTS	67
10. DYNAMIC FREQUENCY SELECTION(DFS)	79
10.1 APPLICABILITY OF DFS REQUIREMENTS	79
10.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE Q-BOOK+, NOTEBOOKING	79
10.3 DFS RESPONSE REQUIREMENT VALUES	80
10.4 SHORT PULSE RADAR TEST WAVEFORMS	80
10.5 CALIBRATION SETUP AND DFS TEST RESULTS	81
10.6 CONDUCTED CALIBRATION SETUP	81
10.7 RADAR WAVEFORM CALIBRATION RESULT	81
10.8 IN-SERVICE Q-BOOK+, NOTEBOOKING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD	82
10.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME	

Table of Contents

	Page
AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST	83
11. ANTENNA REQUIREMENT	84
11.1 STANDARD REQUIREMENT	84
11.2 EUT ANTENNA	84

Revision History

Report No.	Version	Description	Issued Date
N26042904605E	Rev.01	Initial issue of report	Jun. 02, 2026

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4) 15.407(b)(8)(9)	Spurious Radiated Emissions	PASS	
15.407 (a)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)	Maximum Conducted Output Power	PASS	
15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4)	Band Edge	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.407(g)	Frequency Stability Measurement	PASS	
15.407(h)	Dynamic Frequency Selection(DFS)	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	(Note 3)

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) This device operates with a duty cycle greater than 99%
- (3) The product is a client device, and the data transmission is limited by the AP.
When the information to be sent is missing or the operation fails,
the device will automatically stop sending and directly connect to the AP correctly again.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong,
People's Republic of China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and
CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District,
Shenzhen, Guangdong, People's Republic of China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a
standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of
approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
5	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
6	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
7	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
8	Temperature	$\pm 0.5^{\circ}\text{C}$
9	Humidity	$\pm 2\%$
10	Radio Frequency	$\pm 0.2\text{ppm}$
11	Occupied bandwidth	$\pm 3.7\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Q-Book+, Notebook	
Trade Mark	Compaq	
Model Name	QL15R3HE8256	
Family Model	H15W1P-3200U	
Model Difference	All models have the same circuit and RF module, except for model names.	
FCC ID	2BLU9-LD5093	
Product Description	Mode Supported	☒ 802.11a ☒ 802.11n(HT20) ☒ 802.11n(HT40) ☒ 802.11ac(HT20) ☒ 802.11ac(HT40) ☒ 802.11ac(HT80)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT20): NSS1, MCS0-MCS8 802.11ac(VHT40/VHT80):NSS1, MCS0-MCS9
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM
	Operating Frequency Range	☒ U-NII-1: 5150 MHz ~5250MHz ☒ U-NII-2A: 5250MHz~5350MHz ☒ U-NII-2C: 5470MHz~5725MHz ☒ U-NII-3: 5725 MHz ~5850 MHz
	Function:	☐ Outdoor AP ☐ Indoor AP ☐ Fixed P2P ☒ Client
	DFS type:	☐ master devices ☐ Slave devices with radar detection ☒ Slave devices without radar detection
	Support TPC	☐ YES ☒ NO
	Antenna Type	Antenna 1: FPC antenna Antenna 2: FPC antenna
	Antenna Gain	Antenna 1: 2.75 dBi Antenna 2: 2.59 dBi
	Smart system	☒ SISO for 802.11a/n/ac ☐ MIMO
Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.		
Adapter	Model: BSY065A190342U W Input: 100-240V~50/60Hz 1.5A Output: 19.0V---3.42A, 64.98W	
Battery	DC 11.4V, 5100mAh, 58.14Wh	
Rating	DC 11.4V from battery or DC 19V from adapter	
Connecting I/O Port(s)	Please refer to the User's Manual	
HW Version	A140P REV3.1	
FW version:	N/A	
SW Version	Windows 11	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Frequency and Channel list:

Band	20MHz		40MHz		80MHz	
	Channel	Frequency	Channel	Frequency	Channel	Frequency
U-NII-1	36	5180 MHz	38	5190 MHz	42	5210 MHz
	40	5200 MHz	46	5230 MHz	-	-
	44	5220 MHz				
	48	5240 MHz				
U-NII-2A	52	5260 MHz	54	5270 MHz	58	5290 MHz
	56	5280 MHz	62	5310 MHz		
	60	5300 MHz				
	64	5320 MHz				
U-NII-2C	100	5500 MHz	102	5510 MHz	106	5530 MHz
	104	5520 MHz	110	5550 MHz	122	5610 MHz
	108	5540 MHz	118	5590 MHz		
	112	5560 MHz	126	5630 MHz		
	116	5580 MHz	134	5670 MHz		
	120	5600 MHz				
	124	5620 MHz				
	128	5640 MHz				
	132	5660 MHz				
	136	5680 MHz				
	140	5700 MHz				
U-NII-3	149	5745 MHz	151	5755 MHz	155	5775 MHz
	153	5765 MHz	159	5795 MHz		
	157	5785 MHz				
	161	5805 MHz				
	165	5825 MHz				

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n/ ac 20 CH36/ CH40/ CH48/CH52/CH56/CH64/CH100/CH120/CH140/CH149/ CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46/CH54/CH62/CH102/CH118/CH134/CH151/ CH159
Mode 4	802.11ac80 CH42/CH58/CH106/CH122/CH155


For Conducted Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n/ ac 20 CH36/ CH40/ CH48/CH52/CH56/CH64/CH100/CH120/CH140/CH149/ CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46/CH54/CH62/CH102/CH118/CH134/CH151/ CH159
Mode 4	802.11ac80 CH42/CH58/CH106/CH122/CH155

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Q-Book+, Notebook	QL15R3HE8256	N/A	EUT
AE-2	Adapter	BSY065A190342U W	N/A	Peripherals
AE-3	Monitor	N/A	N/A	Peripherals
AE-4	U disk*3	N/A	N/A	Peripherals
AE-5	Earphone	N/A	N/A	Peripherals
AE-6	Mouse	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.4m
C-2	HDMI Cable	YES	NO	1.5m
C-3	Earphone Cable	NO	NO	1.2m
C-4	USB Cable	NO	NO	1.2m
C-5	RF Cable	YES	NO	0.1m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2026.04.15	2027.04.14	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2026.04.08	2027.04.07	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2026.04.08	2027.04.07	1 year
4	Test Receiver	R&S	ESPI7	101318	N/A	N/A	N/A
5	Bilog Antenna	TESEQ	CBL6111D	31216	N/A	N/A	N/A
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2026.04.08	2027.04.07	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2026.04.08	2027.04.07	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2024.05.06	2027.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2024.05.06	2027.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2024.05.06	2027.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2026.04.08	2027.04.07	1 year
2	LISN	R&S	ENV216	101313	2026.04.08	2027.04.07	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2026.04.08	2027.04.07	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2024.05.06	2027.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2024.05.06	2027.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2024.05.06	2027.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5°C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1780	36.89	20.40	57.29	64.58	-7.29	QP
0.1780	23.55	20.40	43.95	54.58	-10.63	AVG
0.5340	23.18	20.47	43.65	56.00	-12.35	QP
0.5340	14.22	20.47	34.69	46.00	-11.31	AVG
1.1019	23.21	20.29	43.50	56.00	-12.50	QP
1.1019	10.51	20.29	30.80	46.00	-15.20	AVG
1.6660	24.36	20.28	44.64	56.00	-11.36	QP
1.6660	11.72	20.28	32.00	46.00	-14.00	AVG
3.2260	27.43	20.28	47.71	56.00	-8.29	QP
3.2260	11.69	20.28	31.97	46.00	-14.03	AVG
10.4180	28.60	20.34	48.94	60.00	-11.06	QP
10.4180	17.21	20.34	37.55	50.00	-12.45	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5°C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1780	37.93	20.38	58.31	64.58	-6.27	QP
0.1780	20.18	20.38	40.56	54.58	-14.02	AVG
0.5299	25.10	20.42	45.52	56.00	-10.48	QP
0.5299	14.15	20.42	34.57	46.00	-11.43	AVG
0.9820	24.48	20.27	44.75	56.00	-11.25	QP
0.9820	17.38	20.27	37.65	46.00	-8.35	AVG
3.4100	28.61	20.19	48.80	56.00	-7.20	QP
3.4100	13.79	20.19	33.98	46.00	-12.02	AVG
5.8340	22.00	20.26	42.26	60.00	-17.74	QP
5.8340	12.44	20.26	32.70	50.00	-17.30	AVG
10.6500	27.51	20.26	47.77	60.00	-12.23	QP
10.6500	16.41	20.26	36.67	50.00	-13.33	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5°C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.3G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	38.17	20.38	58.55	64.96	-6.41	QP
0.1700	22.52	20.38	42.90	54.96	-12.06	AVG
0.2380	30.53	20.47	51.00	62.17	-11.17	QP
0.2380	15.38	20.47	35.85	52.17	-16.32	AVG
0.5299	24.37	20.47	44.84	56.00	-11.16	QP
0.5299	11.17	20.47	31.64	46.00	-14.36	AVG
3.3940	26.31	20.28	46.59	56.00	-9.41	QP
3.3940	12.75	20.28	33.03	46.00	-12.97	AVG
5.8060	21.99	20.31	42.30	60.00	-17.70	QP
5.8060	10.68	20.31	30.99	50.00	-19.01	AVG
10.7460	27.27	20.36	47.63	60.00	-12.37	QP
10.7460	17.32	20.36	37.68	50.00	-12.32	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5°C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.3G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1819	36.48	20.38	56.86	64.40	-7.54	QP
0.1819	21.30	20.38	41.68	54.40	-12.72	AVG
0.5980	24.06	20.46	44.52	56.00	-11.48	QP
0.5980	11.84	20.46	32.30	46.00	-13.70	AVG
0.9780	25.55	20.27	45.82	56.00	-10.18	QP
0.9780	17.92	20.27	38.19	46.00	-7.81	AVG
3.4140	28.54	20.19	48.73	56.00	-7.27	QP
3.4140	13.63	20.19	33.82	46.00	-12.18	AVG
5.9380	22.44	20.25	42.69	60.00	-17.31	QP
5.9380	10.12	20.25	30.37	50.00	-19.63	AVG
10.7260	26.63	20.26	46.89	60.00	-13.11	QP
10.7260	15.52	20.26	35.78	50.00	-14.22	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5°C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	38.75	20.35	59.10	65.79	-6.69	QP
0.1539	14.22	20.35	34.57	55.79	-21.22	AVG
0.3300	25.68	20.50	46.18	59.45	-13.27	QP
0.3300	12.99	20.50	33.49	49.45	-15.96	AVG
1.0580	23.53	20.29	43.82	56.00	-12.18	QP
1.0580	11.51	20.29	31.80	46.00	-14.20	AVG
3.2260	27.43	20.28	47.71	56.00	-8.29	QP
3.2260	11.69	20.28	31.97	46.00	-14.03	AVG
5.5900	21.41	20.31	41.72	60.00	-18.28	QP
5.5900	11.45	20.31	31.76	50.00	-18.24	AVG
10.4180	28.10	20.34	48.44	60.00	-11.56	QP
10.4180	16.71	20.34	37.05	50.00	-12.95	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5°C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1780	35.93	20.38	56.31	64.58	-8.27	QP
0.1780	21.01	20.38	41.39	54.58	-13.19	AVG
0.5299	22.60	20.42	43.02	56.00	-12.98	QP
0.5299	11.65	20.42	32.07	46.00	-13.93	AVG
0.9820	23.48	20.27	43.75	56.00	-12.25	QP
0.9820	15.88	20.27	36.15	46.00	-9.85	AVG
1.5780	23.69	20.26	43.95	56.00	-12.05	QP
1.5780	11.81	20.26	32.07	46.00	-13.93	AVG
3.4100	27.11	20.19	47.30	56.00	-8.70	QP
3.4100	12.29	20.19	32.48	46.00	-13.52	AVG
10.6500	27.01	20.26	47.27	60.00	-12.73	QP
10.6500	15.91	20.26	36.17	50.00	-13.83	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5℃	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	38.17	20.38	58.55	64.96	-6.41	QP
0.1700	22.52	20.38	42.90	54.96	-12.06	AVG
0.2660	29.69	20.50	50.19	61.24	-11.05	QP
0.2660	18.06	20.50	38.56	51.24	-12.68	AVG
0.5299	24.87	20.47	45.34	56.00	-10.66	QP
0.5299	11.67	20.47	32.14	46.00	-13.86	AVG
3.1300	25.78	20.27	46.05	56.00	-9.95	QP
3.1300	10.65	20.27	30.92	46.00	-15.08	AVG
5.8060	21.99	20.31	42.30	60.00	-17.70	QP
5.8060	10.68	20.31	30.99	50.00	-19.01	AVG
10.7460	27.27	20.36	47.63	60.00	-12.37	QP
10.7460	17.32	20.36	37.68	50.00	-12.32	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	25.5 °C	Relative Humidity :	56.5%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1819	36.48	20.38	56.86	64.40	-7.54	QP
0.1819	21.43	20.38	41.81	54.40	-12.59	AVG
0.3020	27.13	20.56	47.69	60.19	-12.50	QP
0.3020	14.39	20.56	34.95	50.19	-15.24	AVG
0.9780	25.55	20.27	45.82	56.00	-10.18	QP
0.9780	17.92	20.27	38.19	46.00	-7.81	AVG
3.4140	26.04	20.19	46.23	56.00	-9.77	QP
3.4140	10.80	20.19	30.99	46.00	-15.01	AVG
5.9380	22.94	20.25	43.19	60.00	-16.81	QP
5.9380	10.62	20.25	30.87	50.00	-19.13	AVG
10.7260	26.13	20.26	46.39	60.00	-13.61	QP
10.7260	14.65	20.26	34.91	50.00	-15.09	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407 and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407: radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHZ – 30 MHZ)

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	26 °C	Relative Humidity :	54%
Pressure:	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHZ – 1GHZ)

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	23.1℃	Relative Humidity :	56.5%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.2G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	46.9947	14.33	19.97	34.30	40.00	-5.70	QP
V	108.6470	22.19	17.95	40.14	43.50	-3.36	QP
V	133.1510	23.22	14.95	38.17	43.50	-5.33	QP
V	170.1947	24.88	15.53	40.41	43.50	-3.09	QP
V	235.8163	18.80	19.08	37.88	46.00	-8.12	QP
V	457.5072	11.44	23.61	35.05	46.00	-10.95	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBUV)	(dB)	(dBUV/m)	(dBUV/m)	(dB)	
H	47.4917	8.09	20.08	28.17	40.00	-11.83	QP
H	137.4200	22.16	14.85	37.01	43.50	-6.49	QP
H	157.5586	25.38	14.96	40.34	43.50	-3.16	QP
H	178.1325	22.96	16.15	39.11	43.50	-4.39	QP
H	234.1682	24.06	19.03	43.09	46.00	-2.91	QP
H	470.5230	13.11	24.01	37.12	46.00	-8.88	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11a” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	23.1℃	Relative Humidity :	56.6%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.3G)- 802.11n20 (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	38.6160	12.75	18.54	31.29	40.00	-8.71	QP
V	63.3132	10.99	18.08	29.07	40.00	-10.93	QP
V	109.0284	20.67	17.91	38.58	43.50	-4.92	QP
V	181.9200	23.76	16.54	40.30	43.50	-3.20	QP
V	234.9910	19.74	19.11	38.85	46.00	-7.15	QP
V	463.9696	11.05	23.90	34.95	46.00	-11.05	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	38.3462	8.67	18.40	27.07	40.00	-12.93	QP
H	109.7960	15.70	17.83	33.53	43.50	-9.97	QP
H	182.5592	25.62	16.53	42.15	43.50	-1.35	QP
H	252.0627	19.66	19.35	39.01	46.00	-6.99	QP
H	400.4318	13.73	22.78	36.51	46.00	-9.49	QP
H	470.5230	13.60	24.01	37.61	46.00	-8.39	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11n20” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	23.1℃	Relative Humidity :	56.6%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.6G)- 802.11ac20 (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	46.9947	14.83	19.97	34.80	40.00	-5.20	QP
V	108.6470	20.65	17.95	38.60	43.50	-4.90	QP
V	133.1510	24.22	14.95	39.17	43.50	-4.33	QP
V	170.1947	24.38	15.53	39.91	43.50	-3.59	QP
V	234.1682	19.25	19.03	38.28	46.00	-7.72	QP
V	457.5072	10.44	23.61	34.05	46.00	-11.95	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	42.7494	8.05	19.52	27.57	40.00	-12.43	QP
H	137.4200	22.16	14.85	37.01	43.50	-6.49	QP
H	157.5586	25.38	14.96	40.34	43.50	-3.16	QP
H	162.0413	24.82	15.52	40.34	43.50	-3.16	QP
H	234.1682	24.06	19.03	43.09	46.00	-2.91	QP
H	468.8761	12.35	24.01	36.36	46.00	-9.64	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11ac20” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	23.1℃	Relative Humidity :	56.6%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.8G)- 802.11ac20 (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	61.7780	8.46	18.70	27.16	40.00	-12.84	QP
V	109.0284	21.67	17.91	39.58	43.50	-3.92	QP
V	181.9200	22.82	16.54	39.36	43.50	-4.14	QP
V	234.9910	20.24	19.11	39.35	46.00	-6.65	QP
V	457.5072	10.91	23.61	34.52	46.00	-11.48	QP
V	766.0570	10.52	28.69	39.21	46.00	-6.79	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	109.7960	17.70	17.83	35.53	43.50	-7.97	QP
H	182.5592	25.49	16.53	42.02	43.50	-1.48	QP
H	233.3486	19.98	18.97	38.95	46.00	-7.05	QP
H	252.0627	20.66	19.35	40.01	46.00	-5.99	QP
H	331.3546	15.30	21.06	36.36	46.00	-9.64	QP
H	470.5230	14.10	24.01	38.11	46.00	-7.89	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1) "802.11ac20" mode is the worst mode.

(2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25.3 °C	Relative Humidity :	46.9%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.2G) - 802.11a mode		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	3694.10	50.34	-9.41	40.93	74.00	-33.07	Pk
Vertical	3694.10	40.01	-9.41	30.60	54.00	-23.40	AV
Vertical	10360.15	50.25	1.27	51.52	68.20	-16.68	Pk
Vertical	15540.22	50.01	5.01	55.02	74.00	-18.98	Pk
Vertical	15540.22	40.57	5.01	45.58	54.00	-8.42	AV
Horizontal	3713.00	49.91	-9.17	40.74	74.00	-33.26	Pk
Horizontal	3713.00	40.45	-9.17	31.28	54.00	-22.72	AV
Horizontal	10360.47	49.92	1.27	51.19	68.20	-17.01	Pk
Horizontal	15540.38	50.02	5.01	55.03	74.00	-18.97	Pk
Horizontal	15540.38	40.21	5.01	45.22	54.00	-8.78	AV
middle Channel (5200 MHz)-Above 1G							
Vertical	3624.13	49.93	-9.60	40.33	74.00	-33.67	Pk
Vertical	3624.13	39.13	-9.60	29.53	54.00	-24.47	AV
Vertical	10400.09	50.63	1.16	51.79	68.20	-16.41	Pk
Vertical	15600.15	50.54	5.21	55.75	74.00	-18.25	Pk
Vertical	15600.15	39.15	5.21	44.36	54.00	-9.64	AV
Horizontal	4202.14	50.83	-7.92	42.91	74.00	-31.09	Pk
Horizontal	4202.14	40.74	-7.92	32.82	54.00	-21.18	AV
Horizontal	10400.14	50.09	1.16	51.25	68.20	-16.95	Pk
Horizontal	15600.51	50.10	5.21	55.31	74.00	-18.69	Pk
Horizontal	15600.51	40.91	5.21	46.12	54.00	-7.88	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4597.70	49.83	-8.05	41.78	74.00	-32.22	Pk
Vertical	4597.70	40.59	-8.05	32.54	54.00	-21.46	AV
Vertical	10480.23	50.64	1.66	52.30	68.20	-15.90	Pk
Vertical	15720.15	49.61	4.47	54.08	74.00	-19.92	Pk
Vertical	15720.15	39.56	4.47	44.03	54.00	-9.97	AV
Horizontal	4589.26	50.49	-7.98	42.51	74.00	-31.49	Pk
Horizontal	4589.26	39.51	-7.98	31.53	54.00	-22.47	AV
Horizontal	10480.59	50.91	1.66	52.57	68.20	-15.63	Pk
Horizontal	15720.18	50.92	4.47	55.39	74.00	-18.61	Pk
Horizontal	15720.18	40.07	4.47	44.54	54.00	-9.46	AV

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level=Read Level+ Factor

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25.3 °C	Relative Humidity :	46.9%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.3G) - 802.11n20 mode		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4633.25	48.44	-7.81	40.63	74.00	-33.37	Pk
Vertical	4633.25	38.43	-7.81	30.62	54.00	-23.38	AV
Vertical	10520.12	49.29	1.99	51.28	68.20	-16.92	Pk
Vertical	15780.34	50.34	4.6	54.94	74.00	-19.06	Pk
Vertical	15780.34	39.62	4.6	44.22	54.00	-9.78	AV
Horizontal	4366.15	50.15	-7.45	42.70	74.00	-31.30	Pk
Horizontal	4366.15	40.81	-7.45	33.36	54.00	-20.64	AV
Horizontal	10520.26	50.53	1.99	52.52	68.20	-15.68	Pk
Horizontal	15780.34	49.29	4.6	53.89	74.00	-20.11	Pk
Horizontal	15780.34	39.64	4.6	44.24	54.00	-9.76	AV
middle Channel (5280 MHz)-Above 1G							
Vertical	4122.34	50.77	-8.6	42.17	74.00	-31.83	Pk
Vertical	4122.34	40.98	-8.6	32.38	54.00	-21.62	AV
Vertical	10560.19	49.09	2.4	51.49	68.20	-16.71	Pk
Vertical	15840.36	50.65	4.65	55.30	74.00	-18.70	Pk
Vertical	15840.36	40.97	4.65	45.62	54.00	-8.38	AV
Horizontal	3869.48	49.39	-8.54	40.85	74.00	-33.15	Pk
Horizontal	3869.48	40.00	-8.54	31.46	54.00	-22.54	AV
Horizontal	10560.74	49.69	2.4	52.09	68.20	-16.11	Pk
Horizontal	15840.37	50.63	4.65	55.28	74.00	-18.72	Pk
Horizontal	15840.37	40.05	4.65	44.70	54.00	-9.30	AV
High Channel (5320 MHz)-Above 1G							
Vertical	5366.52	49.15	-6.73	42.42	74.00	-31.58	Pk
Vertical	5366.52	39.84	-6.73	33.11	54.00	-20.89	AV
Vertical	10640.58	49.46	2.54	52.00	74.00	-22.00	Pk
Vertical	10640.58	39.88	2.54	42.42	54.00	-11.58	Pk
Vertical	15960.41	49.15	5.1	54.25	74.00	-19.75	AV
Horizontal	15960.41	39.79	5.1	44.89	54.00	-9.11	Pk
Horizontal	5436.59	50.48	-6.22	44.26	74.00	-29.74	AV
Horizontal	5436.59	39.63	-6.22	33.41	54.00	-20.59	Pk
Horizontal	10640.24	49.96	2.54	52.50	74.00	-21.50	Pk
Horizontal	10640.24	40.91	2.54	43.45	54.00	-10.55	AV

Note:"802.11n20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level=Read Level+ Factor

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25.3 °C	Relative Humidity :	46.9%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX(5.6G) - 802.11ac20 mode		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	5433.02	50.61	-6.26	44.35	74.00	-29.65	Pk
Vertical	5433.02	39.29	-6.26	33.03	54.00	-20.97	AV
Vertical	11000.25	49.43	3.63	53.06	74.00	-20.94	Pk
Vertical	11000.25	39.57	3.63	43.20	54.00	-10.80	AV
Vertical	16500.41	49.42	6.24	55.66	68.20	-12.54	Pk
Horizontal	5126.47	50.27	-6.32	43.95	74.00	-30.05	Pk
Horizontal	5126.47	39.29	-6.32	32.97	54.00	-21.03	AV
Horizontal	11000.32	50.60	3.63	54.23	74.00	-19.77	Pk
Horizontal	11000.32	39.11	3.63	42.74	54.00	-11.26	AV
Horizontal	16500.47	46.78	6.24	53.02	68.20	-15.18	Pk
middle Channel (5600 MHz)-Above 1G							
Vertical	4933.25	49.08	-6.48	42.60	74.00	-31.40	Pk
Vertical	4933.25	39.45	-6.48	32.97	54.00	-21.03	AV
Vertical	11200.58	49.56	2.58	52.14	74.00	-21.86	Pk
Vertical	11200.58	40.03	2.58	42.61	54.00	-11.39	AV
Vertical	16800.45	49.39	6.18	55.57	68.20	-12.63	Pk
Horizontal	4766.32	49.23	-7.30	41.93	74.00	-32.07	Pk
Horizontal	4766.32	39.69	-7.30	32.39	54.00	-21.61	AV
Horizontal	11200.45	50.63	2.58	53.21	74.00	-20.79	Pk
Horizontal	11200.45	39.24	2.58	41.82	54.00	-12.18	AV
Horizontal	16800.33	49.91	6.18	56.09	68.20	-12.11	Pk
High Channel (5700 MHz)-Above 1G							
Vertical	5647.33	49.05	-5.69	43.36	68.20	-24.84	Pk
Vertical	11400.29	50.42	3.53	53.95	74.00	-20.05	Pk
Vertical	11400.29	39.66	3.53	43.19	54.00	-10.81	AV
Vertical	17100.54	50.30	6.27	56.57	68.20	-11.63	Pk
Vertical	5433.26	50.86	-6.26	44.60	74.00	-29.40	Pk
Horizontal	5433.26	39.99	-6.26	33.73	54.00	-20.27	AV
Horizontal	11400.43	50.39	3.53	53.92	74.00	-20.08	Pk
Horizontal	11400.43	39.42	3.53	42.95	54.00	-11.05	AV
Horizontal	17100.58	50.84	6.27	57.11	68.20	-11.09	Pk

Note:"802.11ac20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level=Read Level+ Factor

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25.3 °C	Relative Humidity :	46.9%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5.8G) -- 802.11ac20 mode		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	5122.51	50.87	-6.4	44.47	74.00	-29.53	Pk
Vertical	5122.51	40.83	-6.4	34.43	54.00	-19.57	AV
Vertical	11490.60	50.60	3.19	53.79	74.00	-20.21	Pk
Vertical	11490.60	40.07	3.19	43.26	54.00	-10.74	AV
Vertical	17235.65	49.17	6.48	55.65	68.20	-12.55	Pk
Horizontal	5166.60	50.09	-6.08	44.01	68.20	-24.19	Pk
Horizontal	11490.47	49.41	3.19	52.60	74.00	-21.40	Pk
Horizontal	11490.47	38.47	3.19	41.66	54.00	-12.34	AV
Horizontal	17235.47	49.80	6.48	56.28	68.20	-11.92	Pk
middle Channel (5785 MHz)-Above 1G							
Vertical	5433.40	49.51	-6.26	43.25	74.00	-30.75	Pk
Vertical	5433.40	39.15	-6.26	32.89	54.00	-21.11	AV
Vertical	11570.41	50.00	2.75	52.75	74.00	-21.25	Pk
Vertical	11570.41	40.38	2.75	43.13	54.00	-10.87	AV
Vertical	17355.84	48.58	7.23	55.81	68.20	-12.39	Pk
Horizontal	4866.60	50.03	-7.06	42.97	74.00	-31.03	Pk
Horizontal	4866.60	40.79	-7.06	33.73	54.00	-20.27	AV
Horizontal	11570.28	49.71	2.75	52.46	74.00	-21.54	Pk
Horizontal	11570.28	39.94	2.75	42.69	54.00	-11.31	AV
Horizontal	17355.49	49.40	7.23	56.63	68.20	-11.57	Pk
High Channel (5825 MHz)-Above 1G							
Vertical	5244.48	50.12	-6.26	43.86	68.20	-24.34	Pk
Vertical	11652.42	49.41	2.75	52.16	74.00	-21.84	Pk
Vertical	11652.42	40.21	2.75	42.96	54.00	-11.04	AV
Vertical	17473.74	47.46	8.49	55.95	68.20	-12.25	Pk
Horizontal	5285.29	50.77	-6.61	44.16	68.20	-24.04	Pk
Horizontal	11652.67	49.50	2.75	52.25	74.00	-21.75	Pk
Horizontal	11652.67	40.29	2.75	43.04	54.00	-10.96	AV
Horizontal	17474.68	49.63	8.49	58.12	68.20	-10.08	Pk

Note:"802.11ac20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level=Read Level+ Factor

3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25.3 °C	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5.2G)-802.11a ;TX (5.3G)-802.11n20 TX (5.6G)-802.11ac20;TX (5.8G)-802.11ac20		

WIFI 5.2G

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	35081.533	53.48	3.49	56.97	68.20	-11.23	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5180MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	33946.333	53.75	0.56	54.31	68.20	-13.89	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5180MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



WIFI 5.3G

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39635.533	56.59	2.86	59.45	68.20	-8.75	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11n20 5260MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	38786.333	58.93	1.82	60.75	68.20	-7.45	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11n20 5260MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



WIFI 5.6G

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	38782.666	60.74	1.82	62.56	68.20	-5.64	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11ac20 5500MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	39801.267	59.09	3.12	62.21	68.20	-5.99	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11 ac20 5500MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



WIFI 5.8G

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39194.800	58.49	2.18	60.67	68.20	-7.53	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11ac20 5745MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	39813.733	58.62	3.14	61.76	68.20	-6.44	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11 ac20 5745MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



3.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	26.4 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5.2G)-802.11a		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency	Meter Reading	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (5180 MHz)							
4500	49.91	-7.74	42.17	74	-31.83	Pk	Horizontal
4500	37.23	-7.74	29.49	54	-24.51	AV	Horizontal
4500	49.56	-7.74	41.82	74	-32.18	Pk	Vertical
4500	32.98	-7.74	25.24	54	-28.76	AV	Vertical
5150	57.11	0.1	57.21	74	-16.79	Pk	Horizontal
5150	44.38	0.1	44.48	54	-9.52	AV	Horizontal
5150	58.37	0.1	58.47	74	-15.53	Pk	Vertical
5150	43.24	0.1	43.34	54	-10.66	AV	Vertical
High Channel (5240 MHz)							
5350	52.62	-0.79	51.83	74	-22.17	Pk	Vertical
5350	42.98	-0.79	42.19	54	-11.81	AV	Vertical
5350	53.78	-0.79	52.99	74	-21.01	Pk	Horizontal
5350	41.51	-0.79	40.72	54	-13.28	AV	Horizontal

Note: (1) Emission Level= Read Level+ Factor

(2) "802.11a" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	24.5 °C	Relative Humidity :	47.5%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5.3G)-802.11n20		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency	Meter Reading	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (5320 MHz) -Above 1G							
5350	52.45	-0.79	51.66	74	-22.34	Pk	Horizontal
5350	42.33	-0.79	41.54	54	-12.46	AV	Horizontal
5350	53.07	-0.79	52.28	74	-21.72	Pk	Vertical
5350	41.23	-0.79	40.44	54	-13.56	AV	Vertical

Note: (1) Emission Level= Read Level+ Factor

(2) "802.11n20 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	26.4 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5.6G)-802.11ac20		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency	Meter Reading	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (5500 MHz) -Above 1G							
5460	53.14	0.06	53.20	74	-20.80	Pk	Horizontal
5460	42.33	0.06	42.39	54	-11.61	AV	Horizontal
5460	52.45	0.06	52.51	74	-21.49	Pk	Vertical
5460	42.51	0.06	42.57	54	-11.43	AV	Vertical

Note: (1) Emission Level= Read Level+ Factor

(2) "802.11ac20 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

4 POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

For the band 5.15-5.25 GHz,

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

- (3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz), Band 2C (5470-5725MHz), Band 3 (5745-5825MHz)		

Test data reference attachment.

5. 26DB & 99% EMISSION BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

5.2 TEST PROCEDURE

- a) Set RBW= shall be in the range of 1% to 5% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz), Band 2C(5470-5725MHz), Band 3(5725-5850MHz)		

Test data reference attachment.

6. MINIMUM 6 DB BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

6.2 EST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5G) Mode Frequency Band 3 (5725-5850MHz)		

Test data reference attachment.

7. MAXIMUM CONDUCTED OUTPUT POWER

7.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5250~5350	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5470~5725	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5725~5850	1W


7.2 TEST PROCEDURE

- Method PM-G is measurement using a gated RF average power meter. Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX (5G) Mode Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz) Band 2C, (5470-5725MHz), Band 3 (5725-5850MHz)		

Test data reference attachment.

8. OUT OF BAND EMISSIONS

8.1 APPLICABLE STANDARD

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(10) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.


8.2 TEST PROCEDURE

The testing per ANSI C63.10 Section 12.7.4.2

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

EUT :	Q-Book+, Notebook	Model Name :	QL15R3HE8256
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V

Test data reference attachment.

9. Frequency Stability Measurement


9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm
- t6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is -20°C~70°C.

9.3 TEST SETUP LAYOUT



9.4 EUT OPERATION DURING TEST

1. The EUT was programmed to be in continuously un-modulation transmitting mode.

9.5 TEST RESULTS

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5180.0036	5180	0.0036	0.6863
		V max (V)	13.11	5180.0002	5180	0.0002	0.0430
		V min (V)	9.69	5180.0090	5180	0.0090	1.7450
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5180.0094	5180	0.0094	1.8058
		T (°C)	-10	5180.0092	5180	0.0092	1.7680
		T (°C)	0	5180.0075	5180	0.0075	1.4410
		T (°C)	10	5180.0002	5180	0.0002	0.0390
		T (°C)	20	5180.0025	5180	0.0025	0.4897
		T (°C)	30	5180.0049	5180	0.0049	0.9394
		T (°C)	40	5180.0046	5180	0.0046	0.8803
		T (°C)	50	5180.0044	5180	0.0044	0.8581
		T (°C)	60	5180.0076	5180	0.0076	1.4631
		T (°C)	70	5180.0090	5180	0.0090	1.7340
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5200.0054	5200	0.0054	1.0316
		V max (V)	13.11	5200.0000	5200	0.0000	0.0086
		V min (V)	9.69	5200.0023	5200	0.0023	0.4476
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5200.0088	5200	0.0088	1.6894
		T (°C)	-10	5200.0053	5200	0.0053	1.0270
		T (°C)	0	5200.0067	5200	0.0067	1.2968
		T (°C)	10	5200.0036	5200	0.0036	0.6968
		T (°C)	20	5200.0068	5200	0.0068	1.3093
		T (°C)	30	5200.0007	5200	0.0007	0.1434
		T (°C)	40	5200.0058	5200	0.0058	1.1217
		T (°C)	50	5200.0007	5200	0.0007	0.1406
		T (°C)	60	5200.0082	5200	0.0082	1.5828
		T (°C)	70	5200.0036	5200	0.0036	0.6870
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5240.0010	5240	0.0010	0.1826
		V max (V)	13.11	5240.0070	5240	0.0070	1.3291
		V min (V)	9.69	5240.0034	5240	0.0034	0.6522
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5240.0010	5240	0.0010	0.1964
		T (°C)	-10	5240.0003	5240	0.0003	0.0487
		T (°C)	0	5240.0058	5240	0.0058	1.0998
		T (°C)	10	5240.0058	5240	0.0058	1.1033
		T (°C)	20	5240.0092	5240	0.0092	1.7564
		T (°C)	30	5240.0056	5240	0.0056	1.0695
		T (°C)	40	5240.0092	5240	0.0092	1.7577
		T (°C)	50	5240.0016	5240	0.0016	0.3063
		T (°C)	60	5240.0060	5240	0.0060	1.1365
		T (°C)	70	5240.0040	5240	0.0040	0.7656
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX Frequency Band 2A (5250-5350MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5260MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5260.0047	5260	0.00474	0.9006
		V max (V)	13.11	5260.0005	5260	0.00049	0.0939
		V min (V)	9.69	5260.0063	5260	0.00630	1.1980
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5260MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5260.0085	5260	0.00846	1.6092
		T (°C)	-10	5260.0081	5260	0.00813	1.5457
		T (°C)	0	5260.0028	5260	0.00280	0.5317
		T (°C)	10	5260.0070	5260	0.00699	1.3285
		T (°C)	20	5260.0087	5260	0.00871	1.6568
		T (°C)	30	5260.0047	5260	0.00472	0.8968
		T (°C)	40	5260.0067	5260	0.00668	1.2706
		T (°C)	50	5260.0002	5260	0.00025	0.0471
		T (°C)	60	5260.0043	5260	0.00430	0.8179
		T (°C)	70	5260.0036	5260	0.00357	0.6781
Limits				Within 5250-5350MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5280MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5280.0082	5280	0.00825	1.5619
		V max (V)	13.11	5280.0023	5280	0.00234	0.4424
		V min (V)	9.69	5280.0036	5280	0.00358	0.6776
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5280MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5280.0077	5280	0.00769	1.4564
		T (°C)	-10	5280.0004	5280	0.00045	0.0843
		T (°C)	0	5280.0020	5280	0.00202	0.3822
		T (°C)	10	5280.0058	5280	0.00580	1.0977
		T (°C)	20	5280.0002	5280	0.00019	0.0363
		T (°C)	30	5280.0065	5280	0.00645	1.2221
		T (°C)	40	5280.0001	5280	0.00014	0.0258
		T (°C)	50	5280.0002	5280	0.00018	0.0343
		T (°C)	60	5280.0100	5280	0.00998	1.8892
		T (°C)	70	5280.0054	5280	0.00537	1.0175
Limits				Within 5250-5350MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5320MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5320.0058	5320	0.00585	1.0994
		V max (V)	13.11	5320.0006	5320	0.00060	0.1134
		V min (V)	9.69	5320.0095	5320	0.00952	1.7888
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5320MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5320.0032	5320	0.00316	0.5947
		T (°C)	-10	5320.0038	5320	0.00383	0.7202
		T (°C)	0	5320.0013	5320	0.00134	0.2513
		T (°C)	10	5320.0045	5320	0.00453	0.8521
		T (°C)	20	5320.0031	5320	0.00305	0.5737
		T (°C)	30	5320.0028	5320	0.00284	0.5333
		T (°C)	40	5320.0055	5320	0.00554	1.0421
		T (°C)	50	5320.0091	5320	0.00914	1.7181
		T (°C)	60	5320.0018	5320	0.00181	0.3398
		T (°C)	70	5320.0017	5320	0.00171	0.3214
Limits				Within 5250-5350MHz			
Result				Complies			

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX Frequency Band 2C (5470-5725MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5500.0003	5500	0.00033	0.0602
		V max (V)	13.11	5500.0052	5500	0.00521	0.9470
		V min (V)	9.69	5500.0008	5500	0.00075	0.1371
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5500.0049	5500	0.00491	0.8919
		T (°C)	-10	5500.0084	5500	0.00843	1.5332
		T (°C)	0	5500.0094	5500	0.00942	1.7124
		T (°C)	10	5500.0052	5500	0.00521	0.9468
		T (°C)	20	5500.0093	5500	0.00934	1.6984
		T (°C)	30	5500.0072	5500	0.00718	1.3047
		T (°C)	40	5500.0065	5500	0.00654	1.1890
		T (°C)	50	5500.0086	5500	0.00861	1.5651
		T (°C)	60	5500.0015	5500	0.00148	0.2682
		T (°C)	70	5500.0095	5500	0.00949	1.7259
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5600.0036	5600	0.00364	0.6507
		V max (V)	13.11	5600.0081	5600	0.00810	1.4465
		V min (V)	9.69	5600.0050	5600	0.00497	0.8881
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5600.0081	5600	0.00809	1.4443
		T (°C)	-10	5600.0099	5600	0.00992	1.7708
		T (°C)	0	5600.0043	5600	0.00435	0.7766
		T (°C)	10	5600.0062	5600	0.00620	1.1069
		T (°C)	20	5600.0035	5600	0.00351	0.6273
		T (°C)	30	5600.0094	5600	0.00943	1.6842
		T (°C)	40	5600.0059	5600	0.00587	1.0474
		T (°C)	50	5600.0057	5600	0.00575	1.0259
		T (°C)	60	5600.0082	5600	0.00821	1.4653
		T (°C)	70	5600.0088	5600	0.00878	1.5682
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5700.0038	5700	0.00375	0.6585
		V max (V)	13.11	5700.0060	5700	0.00597	1.0475
		V min (V)	9.69	5700.0099	5700	0.00991	1.7389
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5700.0017	5700	0.00174	0.3046
		T (°C)	-10	5700.0023	5700	0.00233	0.4092
		T (°C)	0	5700.0092	5700	0.00922	1.6169
		T (°C)	10	5700.0059	5700	0.00589	1.0332
		T (°C)	20	5700.0038	5700	0.00385	0.6750
		T (°C)	30	5700.0051	5700	0.00509	0.8930
		T (°C)	40	5700.0077	5700	0.00766	1.3432
		T (°C)	50	5700.0018	5700	0.00179	0.3132
		T (°C)	60	5700.0084	5700	0.00835	1.4650
		T (°C)	70	5700.0033	5700	0.00333	0.5849
Limits				Within 5470-5725MHz			
Result				Complies			

EUT :	Q-Book+, Notebook	Model Name. :	QL15R3HE8256
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 11.4V
Test Mode :	TX Frequency(5745-5850MHz)		

Voltage vs. Frequency Stability

Page 107 Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5745.0043	5745	0.00431	0.7506
		V max (V)	13.11	5745.0027	5745	0.00267	0.4648
		V min (V)	9.69	5745.0022	5745	0.00219	0.3820
Limits				Within 5725-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5745.0014	5745	0.00137	0.2382
		T (°C)	-10	5745.0097	5745	0.00971	1.6901
		T (°C)	0	5745.0004	5745	0.00038	0.0657
		T (°C)	10	5745.0092	5745	0.00916	1.5939
		T (°C)	20	5745.0064	5745	0.00636	1.1066
		T (°C)	30	5745.0097	5745	0.00974	1.6950
		T (°C)	40	5745.0067	5745	0.00665	1.1577
		T (°C)	50	5745.0034	5745	0.00336	0.5855
		T (°C)	60	5745.0098	5745	0.00983	1.7113
		T (°C)	70	5745.0068	5745	0.00683	1.1884
Limits				Within 5725-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5785.0081	5785	0.00812	1.4037
		V max (V)	13.11	5785.0059	5785	0.00590	1.0197
		V min (V)	9.69	5785.0016	5785	0.00164	0.2829
Limits				Within 5725-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5785.0037	5785	0.00369	0.6380
		T (°C)	-10	5785.0045	5785	0.00452	0.7818
		T (°C)	0	5785.0092	5785	0.00922	1.5933
		T (°C)	10	5785.0071	5785	0.00708	1.2230
		T (°C)	20	5785.0092	5785	0.00916	1.5832
		T (°C)	30	5785.0016	5785	0.00161	0.2779
		T (°C)	40	5785.0004	5785	0.00044	0.0765
		T (°C)	50	5785.0050	5785	0.00499	0.8634
		T (°C)	60	5785.0012	5785	0.00124	0.2149
		T (°C)	70	5785.0046	5785	0.00464	0.8025
Limits				Within 5725-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	11.4	5825.0040	5825	0.00399	0.6856
		V max (V)	13.11	5825.0085	5825	0.00848	1.4562
		V min (V)	9.69	5825.0067	5825	0.00673	1.1552
Limits				Within 5725-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	11.4	T (°C)	-20	5825.0074	5825	0.00737	1.2659
		T (°C)	-10	5825.0029	5825	0.00290	0.4976
		T (°C)	0	5825.0094	5825	0.00942	1.6168
		T (°C)	10	5825.0092	5825	0.00922	1.5823
		T (°C)	20	5825.0005	5825	0.00048	0.0828
		T (°C)	30	5825.0085	5825	0.00855	1.4670
		T (°C)	40	5825.0072	5825	0.00715	1.2277
		T (°C)	50	5825.0025	5825	0.00247	0.4236
		T (°C)	60	5825.0003	5825	0.00033	0.0574
		T (°C)	70	5825.0099	5825	0.00990	1.6994
Limits				Within 5725-5850MHz			
Result				Complies			

10. DYNAMIC FREQUENCY SELECTION(DFS)

10.1 APPLICABILITY OF DFS REQUIREMENTS

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes
Client Beacon Test	N/A	Yes	Yes

Additional requirements for devices with multiple bandwidth modes	Operational Mode	
	Master or Client With Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

10.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE Q-BOOK+, NOTEBOOKING

Maximum Transmit Power	Value (see notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: EIRP is based on the highest antenna gain.	

10.3 DFS RESPONSE REQUIREMENT VALUES

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth See Note 3.

Note 1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

10.4 SHORT PULSE RADAR TEST WAVEFORMS

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B	$\text{Roundup}\left(\frac{1}{360} \cdot \frac{19 \cdot 10^6}{\text{PRI}_{\text{min}}}\right)$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.


If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

10.5 CALIBRATION SETUP AND DFS TEST RESULTS

Radar Waveform Calibration Procedure

- 1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master
- 2) The interference Radar Detection Threshold Level is $-62\text{dBm} + 3.69\text{dB} = -58.31\text{dBm}$ that had been taken into account the output power range and antenna gain.
- 3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz. The spectrum analyzer had offset -1.0dB to compensate RF cable loss 1.0dB.
- 4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} + 3.69\text{dB} + 1\text{dB} = -57.31\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.

10.6 CONDUCTED CALIBRATION SETUP



Wireless AP	Manufacturer	ASUSTek Computer Inc
	Model NO.	AX5400
	FCC ID	MSQ-RTAXJ300

Note:1. The Slave device associated with the EUT during these tests does not have radar detection capability.

2. WLAN traffic is generated by using the iperf software to send packets from the Master IP address to the Slave IP address.

3. The time required for the master and slave devices to fully start up is 120s.

4. EUT does not support TPC.


10.7 RADAR WAVEFORM CALIBRATION RESULT

Test data reference attachment.

10.8 IN-SERVICE Q-BOOK+, NOTEBOOKING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD

TEST CONFIGURATION:

Setup for Client with injection at the Master



TEST PROCEDURE:

1. The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device
3. A trigger is provided from the pulse generator to the DFS Q-Book+, Notebooking system in order to capture the traffic and the occurrence of the radar pulse.
4. EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is Streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom In 600ms plot of the Short Pulse Radar Type
7. Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
8. Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

TEST MODE:

Mode	Frequency (MHz)
ac80	5290
ac80	5530
n40	5310
n40	5510
a	5320
a	5500

10.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST

Test data reference attachment.

11. ANTENNA REQUIREMENT

11.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

11.2 EUT ANTENNA

The EUT antenna is FPC Antenna. It comply with the standard requirement.

END OF REPORT