TEST REPORT

Product	:	Industrial Wireless Routers
Trade mark	:	N/A
Model/Type reference	:	See section 4.2
Serial Number	:	N/A
Report Number	:	EED32Q81626902
FCC ID	:	2BLUFEDGE-RX8XX-SFX
Date of Issue	:	Nov. 20, 2024
Test Standards	:	47 CFR Part 15 Subpart E
Test result	:	PASS

Prepared for:

Tianjin Elco Automation Co., Ltd
No.12, 4th XEDA Branch Rd, Xiqing Economic-Technological Development Area, Tianjin

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:	Zhenxia Wen	Reviewed by:	Frazer Li
	Zhenxia Wen		Frazer Li
Approved by:	Aaron Ma	Date:	Nov. 20, 2024
	Aaron Ma		

Check No.: 3726141024

1 Content

1 CONTENT 2
2 VERSION 3
3 TEST SUMMARY 4
4 GENERAL INFORMATION 5
4.1 CLIENT INFORMATION 5
4.2 GENERAL DESCRIPTION OF EUT 5
4.3 TEST CONFIGURATION 7
4.4 TEST ENVIRONMENT 7
4.5 DESCRIPTION OF SUPPORT UNITS 8
4.6 TEST LOCATION 8
4.7 DEVIATION FROM STANDARDS 8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS 8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 8
4.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) 9
5 EQUIPMENT LIST 10
6 RADIO TECHNICAL REQUIREMENTS SPECIFICATION 13
6.1 ANTENNA REQUIREMENT 13
6.2 MAXIMUM CONDUCTED OUTPUT POWER 14
6.3 6DB EMISSON BANDWIDTH 15
6.4 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH 16
6.5 MAXIMUM POWER SPECTRAL DENSITY 17
6.6 FREQUENCY STABILITY 18
6.7 RADIATED EMISSION 19
6.8 RADIATED EMISSION WHICH FALL IN THE RESTRICTED BANDS 30
7 APPENDIX 5G WI-FI 128
PHOTOGRAPHS OF TEST SETUP 129
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS 131

2 Version

Version No.	Date	Description
00	Nov. 20, 2024	Original

3 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	N/A
Duty Cycle	47 CFR Part 15 Subpart E Section 15.407	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
26dB emission bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
99% Occupied bandwidth	\	PASS
6dB emission bandwidth	47 CFR Part 15 Subpart E Section 15.407 (e)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	PASS
Radiated Emissions	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS
Radiated Emissions which fall in the restricted bands	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS

Remark:

N/A: The product is DC power supply.

Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.: EDGE-R0831-SF2-01A, EDGE-R series, Model EDGE-R, followed by 0 to 9, followed by 8, followed by 0 to 9, followed by 0 to 9, followed by AL,U,R or vacant , followed by –SF, followed by 0 to 9,followed by –01A to -09A or vacant.

Only the model EDGE-R0831-SF2-01A was tested, Their have same electrical, PCB and BOM, only the model's names definition are different for marketing requirements.

4 General Information

4.1 Client Information

Applicant:	Tianjin Elco Automation Co., Ltd
Address of Applicant:	No.12, 4th XEDA Branch Rd, Xiqing Economic-Technological Development Area, Tianjin
Manufacturer:	Tianjin Elco Automation Co., Ltd
Address of Manufacturer:	No.12, 4th XEDA Branch Rd, Xiqing Economic-Technological Development Area, Tianjin
Factory :	Tianjin Elco Automation Co., Ltd
Address of Factory :	No.12, 4th XEDA Branch Rd, Xiqing Economic-Technological Development Area, Tianjin

4.2 General Description of EUT

Product Name:	Industrial Wireless Routers
Model No.:	EDGE-R0831-SF2-01A, EDGE-R series, Model EDGE-R, followed by 0 to 9, followed by 8, followed by 0 to 9, followed by 0 to 9, followed by AL,U,R or vacant , followed by –SF, followed by 0 to 9,followed by –01A to -09A or vacant.
Test Model No.:	EDGE-R0831-SF2-01A
Trade mark:	N/A
Product Type:	☐ Mobile ☐ Portable ☒ Fixed Location
Type of Modulation:	IEEE 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11n(HT20/HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac(VHT20/VHT40/VHT80): OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) IEEE 802.11ax(HE20/HE40/HE80): OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM,1024QAM)
Operating Frequency	U-NII-1: 5150-5250MHz U-NII-3:5745-5825MHz
Antenna Type:	External Antenna
Antenna Gain:	U-NII-1: 5150-5250MHz 2.57 dBi U-NII-3:5745-5825MHz 3.12 dBi
Power Supply:	DC 30V
Test voltage:	DC 30V
Sample Received Date:	Oct. 23, 2024
Sample tested Date:	Oct. 23, 2024 to Nov. 05, 2024

Operation Frequency each of channel

802.11a/802.11n/802.11ac/802.11ax (20MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	149	5745
40	5200	153	5765
44	5220	157	5785
48	5240	161	5805
-	-	165	5825

802.11n/802.11ac/802.11ax (40MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
38	5190	151	5755
46	5230	159	5795

802.11ac/802.11ax (80MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
42	5210	155	5775

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

4.3 Test Configuration

EUT Test Software Settings:	
Software:	MobaXterm_Personal_22.1
EUT Power Grade:	Default
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ac(VHT20)	MCS0
802.11ac(VHT40)	MCS0
802.11ac(VHT80)	MCS0
802.11ax(VHT20)	MCS0
802.11ax(VHT40)	MCS0
802.11ax(VHT80)	MCS0

4.4 Test Environment

Operating Environment:		
Radiated Spurious Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Conducted Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
RF Conducted:		
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Temperature:	NT (Normal Temperature)	22~25.0 °C
	LT (Low Temperature)	0 °C
	HT (High Temperature)	55.0 °C
Working Voltage of the EUT:	NV (Normal Voltage)	30V
	LV (Low Voltage)	27V
	HV (High Voltage)	33V

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Netbook	Asus	FL8700JP1065-0D8GXYQ2X10	FCC&CE	CTI

4.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385
No tests were sub-contracted.
FCC Designation No.: CN1164

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

5 Equipment List

RF test system					
Equipment	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. Date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
Communication test set	R&S	CMW500	107929	06-26-2024	06-25-2025
Signal Generator	R&S	SMBV100A	1407.6004K02-262149-CV	09-05-2023 09-02-2024	09-04-2024 09-01-2025
Spectrum Analyzer	R&S	FSV40	101200	07-18-2024	07-17-2025
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI-42	06-25-2024	06-24-2025
High-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-12-2023	12-10-2024
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-29-2024	05-28-2025
BT&WI-FI Automatic test software	MWRF-test	MTS 8310	V2.0.0.0	---	---
Spectrum Analyzer	R&S	FSV3044	101509	01-17-2024	01-16-2025

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05/22/2022	05/21/2025
Receiver	R&S	ESCI7	100938-003	09/07/2024	09/06/2025
Spectrum Analyzer	R&S	FSV40	101200	07/18/2024	07/17/2025
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/22/2022	05/21/2025
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04/16/2024	04/15/2025
Microwave Preamplifier	Tonscend	EMC051845SE	980380	12/14/2023	12/13/2024
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023	07/01/2026
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/16/2024	04/15/2025
Preamplifier	Agilent	11909A	12-1	03/22/2024	03/21/2025
Preamplifier	CD	PAP-1840-60	6041.6042	06/19/2024	06/18/2025
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---

3M full-anechoic Chamber					
Equipment	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. Date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-09-2024	01-08-2025
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-29-2024	01-28-2025
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-23-2024	01-22-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2024	04-27-2025
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-16-2024	04-15-2025
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024	07-02-2025
Preamplifier	EMCI	EMC001330	980563	03-08-2024	03-07-2025
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-18-2024	07-17-2025
Preamplifier	Tonscend	EMC051845SE	980380	12-14-2023	12-13-2024
Communication test set	R&S	CMW500	102898	12-14-2023	12-13-2024
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	04-07-2024	04-06-2025
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001		---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

6 Radio Technical Requirements Specification

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	Please see Internal photos
The antenna is external antenna. The best case gain of the antenna are U-NII-1: 5150-5250MHz 2.57 dBi U-NII-3:5745-5825MHz 3.12 dBi	

6.2 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E
Test Setup:	
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report.
Limit:	

Frequency band (MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*
5725-5850	≤1W(30dBm)
Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.3 6dB Emisson Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (e)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Limit:	≥ 500 kHz
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.4 26dB Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Limit:	No restriction limits
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.5 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level.
Limit:	

Frequency band (MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500kHz
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.6 Frequency Stability

Test Requirement:	47 CFR Part 15C Section 15.407 (g)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1.The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. 2. Turn the EUT on and couple its output to a spectrum analyzer. 3. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. 4. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. 5. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix 5G Wi-Fi

6.7 Radiated Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.407 (b)
Test Method:	ANSI C63.10 2013
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10kHz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(4) For transmitters operating in the 5.725-5.85 GHz band:
(i) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing

	an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. Note: (i) EIRP = ((E*d)^2) / 30 where: • E is the field strength in V/m; • d is the measurement distance in meters; • EIRP is the equivalent isotropically radiated power in watts. (ii) Working in dB units, the above equation is equivalent to: EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77 (iii) Or, if d is 3 meters: EIRP[dBm] = E[dBμV/m] - 95.2
Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz:

	Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel and the highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting mode with modulation
Test Results:	Pass

Radiated Spurious Emissions test Data:
Radiated Emission below 1GHz

Remark: During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case lowest channel of 6Mbps for 802.11 a was recorded in the report.

Horizontal:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		97.4047	22.42	12.78	35.20	43.50	-8.30	QP	199	352	
2		165.3127	21.68	10.63	32.31	43.50	-11.19	QP	199	168	
3	*	357.3017	21.39	17.23	38.62	46.00	-7.38	QP	100	318	
4		600.0571	12.87	22.26	35.13	46.00	-10.87	QP	199	352	
5		840.0650	12.34	25.07	37.41	46.00	-8.59	QP	199	72	
6		906.3235	9.13	25.96	35.09	46.00	-10.91	QP	100	318	

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		65.1145	22.57	10.97	33.54	40.00	-6.46	QP	100	352	
2		75.3538	24.14	8.95	33.09	40.00	-6.91	QP	100	213	
3	*	96.5715	27.94	11.62	39.56	43.50	-3.94	QP	100	0	
4		161.6158	23.93	8.81	32.74	43.50	-10.76	QP	100	74	
5		353.9969	19.84	15.12	34.96	46.00	-11.04	QP	100	53	
6		507.0122	18.16	17.55	35.71	46.00	-10.29	QP	100	43	

Transmitter Emission above 1GHz

Remark: During the test, the Radiates Emission above 1G was performed in all modes, only the worst case ant1 and ant2 transmit simultaneously was recorded in the report.

MIMO:

Mode:		802.11 n(HT20) Transmitting				Channel:		5180MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1071.5072	9.38	40.64	50.02	68.20	18.18	PASS	Horizontal	PK
2	1941.1441	16.91	36.14	53.05	68.20	15.15	PASS	Horizontal	PK
3	3444.4444	19.47	35.33	54.80	68.20	13.40	PASS	Horizontal	PK
4	4500	23.87	32.62	56.49	68.20	11.71	PASS	Horizontal	PK
5	7344.7172	-4.29	48.48	44.19	68.20	24.01	PASS	Horizontal	PK
6	11224.4362	4.70	46.05	50.75	68.20	17.45	PASS	Horizontal	PK
7	1070.9571	9.39	41.92	51.31	68.20	16.89	PASS	Vertical	PK
8	1948.2948	17.09	35.57	52.66	68.20	15.54	PASS	Vertical	PK
9	2938.9439	17.44	36.29	53.73	68.20	14.47	PASS	Vertical	PK
10	4494.4994	23.33	33.63	56.96	68.20	11.24	PASS	Vertical	PK
11	9133.6317	0.02	46.85	46.87	68.20	21.33	PASS	Vertical	PK
12	11798.3149	3.24	47.59	50.83	68.20	17.37	PASS	Vertical	PK

Mode:		802.11 n(HT20) Transmitting				Channel:		5200MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1167.7668	9.83	37.57	47.40	68.20	20.80	PASS	Horizontal	PK
2	2421.8922	16.13	37.39	53.52	68.20	14.68	PASS	Horizontal	PK
3	3426.2926	19.22	34.76	53.98	68.20	14.22	PASS	Horizontal	PK
4	4499.4499	23.82	32.94	56.76	68.20	11.44	PASS	Horizontal	PK
5	7590.2545	-3.47	48.06	44.59	68.20	23.61	PASS	Horizontal	PK
6	11967.9484	5.31	45.35	50.66	68.20	17.54	PASS	Horizontal	PK
7	1070.9571	9.39	41.54	50.93	68.20	17.27	PASS	Vertical	PK
8	1947.7448	17.08	35.06	52.14	68.20	16.06	PASS	Vertical	PK
9	3078.6579	17.70	36.63	54.33	68.20	13.87	PASS	Vertical	PK
10	4509.901	23.52	32.70	56.22	68.20	11.98	PASS	Vertical	PK
11	7390.7195	-4.60	49.25	44.65	68.20	23.55	PASS	Vertical	PK
12	11238.2369	4.86	45.98	50.84	68.20	17.36	PASS	Vertical	PK

Mode:			802.11 n(HT20) Transmitting			Channel:		5240MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1071.5072	9.38	38.87	48.25	68.20	19.95	PASS	Horizontal	PK
2	1950.495	17.10	36.26	53.36	68.20	14.84	PASS	Horizontal	PK
3	3050.055	17.26	36.32	53.58	68.20	14.62	PASS	Horizontal	PK
4	3952.1452	20.94	34.58	55.52	68.20	12.68	PASS	Horizontal	PK
5	7888.6944	-3.08	48.11	45.03	68.20	23.17	PASS	Horizontal	PK
6	11245.1373	4.94	46.50	51.44	68.20	16.76	PASS	Horizontal	PK
7	1070.9571	9.39	41.56	50.95	68.20	17.25	PASS	Vertical	PK
8	1947.1947	17.06	35.60	52.66	68.20	15.54	PASS	Vertical	PK
9	2935.0935	17.38	35.82	53.20	68.20	15.00	PASS	Vertical	PK
10	3956.5457	20.83	34.17	55.00	68.20	13.20	PASS	Vertical	PK
11	7866.8433	-3.10	47.16	44.06	68.20	24.14	PASS	Vertical	PK
12	11993.8247	5.86	45.44	51.30	68.20	16.90	PASS	Vertical	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		5190MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1070.9571	9.39	40.73	50.12	68.20	18.08	PASS	Horizontal	PK
2	1949.3949	17.12	35.28	52.40	68.20	15.80	PASS	Horizontal	PK
3	2419.692	16.15	35.98	52.13	68.20	16.07	PASS	Horizontal	PK
4	3455.4455	19.30	35.38	54.68	68.20	13.52	PASS	Horizontal	PK
5	9660.358	1.53	46.63	48.16	68.20	20.04	PASS	Horizontal	PK
6	12997.2499	8.03	43.29	51.32	68.20	16.88	PASS	Horizontal	PK
7	1145.2145	10.19	37.84	48.03	68.20	20.17	PASS	Vertical	PK
8	1968.0968	16.07	36.66	52.73	68.20	15.47	PASS	Vertical	PK
9	3381.7382	18.76	34.79	53.55	68.20	14.65	PASS	Vertical	PK
10	4514.3014	23.36	33.54	56.90	68.20	11.30	PASS	Vertical	PK
11	7612.1056	-3.56	48.04	44.48	68.20	23.72	PASS	Vertical	PK
12	11248.0124	4.97	45.47	50.44	68.20	17.76	PASS	Vertical	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		5230MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1138.6139	9.97	37.26	47.23	68.20	20.97	PASS	Horizontal	PK
2	1925.1925	16.51	37.27	53.78	68.20	14.42	PASS	Horizontal	PK
3	2848.1848	17.02	37.12	54.14	68.20	14.06	PASS	Horizontal	PK
4	4518.7019	23.20	34.21	57.41	68.20	10.79	PASS	Horizontal	PK
5	7895.0198	-3.07	47.97	44.90	68.20	23.30	PASS	Horizontal	PK
6	11245.7123	4.95	45.36	50.31	68.20	17.89	PASS	Horizontal	PK
7	1070.407	9.41	38.90	48.31	68.20	19.89	PASS	Vertical	PK
8	1951.0451	17.07	35.42	52.49	68.20	15.71	PASS	Vertical	PK
9	3205.7206	17.37	36.67	54.04	68.20	14.16	PASS	Vertical	PK
10	3953.2453	20.91	33.84	54.75	68.20	13.45	PASS	Vertical	PK
11	7626.4813	-4.11	48.45	44.34	68.20	23.86	PASS	Vertical	PK
12	11213.5107	4.59	45.74	50.33	68.20	17.87	PASS	Vertical	PK

Mode:			802.11 ac(VHT80) Transmitting			Channel:		5210MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1070.407	9.41	41.18	50.59	68.20	17.61	PASS	Horizontal	PK
2	1942.7943	16.95	35.82	52.77	68.20	15.43	PASS	Horizontal	PK
3	3076.4576	17.67	37.10	54.77	68.20	13.43	PASS	Horizontal	PK
4	4517.0517	23.26	33.85	57.11	68.20	11.09	PASS	Horizontal	PK
5	7587.9544	-3.56	48.03	44.47	68.20	23.73	PASS	Horizontal	PK
6	11260.088	4.49	46.25	50.74	68.20	17.46	PASS	Horizontal	PK
7	1070.9571	9.39	38.94	48.33	68.20	19.87	PASS	Vertical	PK
8	1925.7426	16.52	36.03	52.55	68.20	15.65	PASS	Vertical	PK
9	3095.7096	17.97	36.21	54.18	68.20	14.02	PASS	Vertical	PK
10	4508.8009	23.56	33.36	56.92	68.20	11.28	PASS	Vertical	PK
11	7759.888	-3.55	48.03	44.48	68.20	23.72	PASS	Vertical	PK
12	11238.8119	4.86	46.10	50.96	68.20	17.24	PASS	Vertical	PK

Mode:			802.11 n(HT20) Transmitting			Channel:		5745MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1281.6282	9.47	38.84	48.31	68.20	19.89	PASS	Horizontal	PK
2	1954.8955	16.81	35.65	52.46	68.20	15.74	PASS	Horizontal	PK
3	2938.3938	17.52	35.39	52.91	68.20	15.29	PASS	Horizontal	PK
4	3904.8405	20.23	34.16	54.39	68.20	13.81	PASS	Horizontal	PK
5	7762.7842	-3.58	48.49	44.91	68.20	23.29	PASS	Horizontal	PK
6	11235.249	4.83	46.04	50.87	68.20	17.33	PASS	Horizontal	PK
7	1070.9571	9.23	39.03	48.26	68.20	19.94	PASS	Vertical	PK
8	1606.1606	11.85	38.08	49.93	68.20	18.27	PASS	Vertical	PK
9	1937.8438	16.74	35.77	52.51	68.20	15.69	PASS	Vertical	PK
10	3304.7305	18.09	35.65	53.74	68.20	14.46	PASS	Vertical	PK
11	7846.3564	-3.16	48.24	45.08	68.20	23.12	PASS	Vertical	PK
12	9791.5194	2.73	46.50	49.23	68.20	18.97	PASS	Vertical	PK

Mode:			802.11 n(HT20) Transmitting			Channel:		5785MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1070.9571	9.23	40.10	49.33	68.20	18.87	PASS	Horizontal	PK
2	1955.9956	16.75	35.93	52.68	68.20	15.52	PASS	Horizontal	PK
3	2912.5413	17.16	36.55	53.71	68.20	14.49	PASS	Horizontal	PK
4	4512.1012	23.69	33.86	57.55	68.20	10.65	PASS	Horizontal	PK
5	7609.4406	-3.46	47.72	44.26	68.20	23.94	PASS	Horizontal	PK
6	11241.3828	4.89	45.59	50.48	68.20	17.72	PASS	Horizontal	PK
7	1070.407	9.24	39.49	48.73	68.20	19.47	PASS	Vertical	PK
8	1947.1947	17.00	35.39	52.39	68.20	15.81	PASS	Vertical	PK
9	2958.7459	17.54	36.10	53.64	68.20	14.56	PASS	Vertical	PK
10	3940.044	20.55	34.21	54.76	68.20	13.44	PASS	Vertical	PK
11	7585.6724	-3.63	48.11	44.48	68.20	23.72	PASS	Vertical	PK
12	12408.3272	6.02	45.62	51.64	68.20	16.56	PASS	Vertical	PK

Mode:			802.11 n(HT20) Transmitting			Channel:		5825MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1167.2167	9.85	37.43	47.28	68.20	20.92	PASS	Horizontal	PK
2	1928.4928	16.48	36.36	52.84	68.20	15.36	PASS	Horizontal	PK
3	2944.9945	17.62	35.96	53.58	68.20	14.62	PASS	Horizontal	PK
4	4515.4015	23.56	32.83	56.39	68.20	11.81	PASS	Horizontal	PK
5	7160.9107	-4.95	50.27	45.32	68.20	22.88	PASS	Horizontal	PK
6	11974.365	5.45	46.18	51.63	68.20	16.57	PASS	Horizontal	PK
7	1070.9571	9.23	40.79	50.02	68.20	18.18	PASS	Vertical	PK
8	1949.945	17.08	35.89	52.97	68.20	15.23	PASS	Vertical	PK
9	2946.6447	17.64	36.27	53.91	68.20	14.29	PASS	Vertical	PK
10	4509.3509	23.80	33.51	57.31	68.20	10.89	PASS	Vertical	PK
11	9784.619	2.43	46.52	48.95	68.20	19.25	PASS	Vertical	PK
12	11959.7973	5.14	46.04	51.18	68.20	17.02	PASS	Vertical	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		5755MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1139.1639	9.95	38.51	48.46	68.20	19.74	PASS	Horizontal	PK
2	1922.4422	16.30	36.65	52.95	68.20	15.25	PASS	Horizontal	PK
3	2929.0429	17.40	35.63	53.03	68.20	15.17	PASS	Horizontal	PK
4	4283.2783	21.77	32.98	54.75	68.20	13.45	PASS	Horizontal	PK
5	7841.7561	-3.23	47.74	44.51	68.20	23.69	PASS	Horizontal	PK
6	11962.0975	5.19	47.09	52.28	68.20	15.92	PASS	Horizontal	PK
7	1070.9571	9.23	40.81	50.04	68.20	18.16	PASS	Vertical	PK
8	1957.0957	16.69	36.07	52.76	68.20	15.44	PASS	Vertical	PK
9	3053.9054	17.09	36.39	53.48	68.20	14.72	PASS	Vertical	PK
10	4104.5105	21.26	33.66	54.92	68.20	13.28	PASS	Vertical	PK
11	7864.7577	-3.10	47.78	44.68	68.20	23.52	PASS	Vertical	PK
12	12282.5855	5.42	46.21	51.63	68.20	16.57	PASS	Vertical	PK

Mode:			802.11 n(HT40) Transmitting			Channel:		5795MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1070.9571	9.23	42.56	51.79	68.20	16.41	PASS	Horizontal	PK
2	1947.1947	17.00	35.51	52.51	68.20	15.69	PASS	Horizontal	PK
3	3347.0847	18.73	36.06	54.79	68.20	13.41	PASS	Horizontal	PK
4	4511.0011	23.74	33.70	57.44	68.20	10.76	PASS	Horizontal	PK
5	7851.7234	-3.11	47.43	44.32	68.20	23.88	PASS	Horizontal	PK
6	11034.369	4.18	46.54	50.72	68.20	17.48	PASS	Horizontal	PK
7	1138.6139	9.93	37.85	47.78	68.20	20.42	PASS	Vertical	PK
8	1948.8449	17.05	35.97	53.02	68.20	15.18	PASS	Vertical	PK
9	2880.6381	16.98	36.20	53.18	68.20	15.02	PASS	Vertical	PK
10	4508.8009	23.83	33.37	57.20	68.20	11.00	PASS	Vertical	PK
11	7584.1389	-3.69	48.93	45.24	68.20	22.96	PASS	Vertical	PK
12	11350.2567	5.05	45.87	50.92	68.20	17.28	PASS	Vertical	PK

Mode:			802.11 ac(VHT80) Transmitting			Channel:		5775MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1057.5705	6.92	47.37	54.29	68.20	13.91	PASS	Horizontal	PK
2	1994.0996	9.84	38.85	48.69	68.20	19.51	PASS	Horizontal	PK
3	3801.5201	16.50	33.83	50.33	68.20	17.87	PASS	Horizontal	PK
4	7613.2742	-2.75	45.54	42.79	68.20	25.41	PASS	Horizontal	PK
5	11999.6666	6.28	43.56	49.84	68.20	18.36	PASS	Horizontal	PK
6	15892.2928	10.40	41.22	51.62	68.20	16.58	PASS	Horizontal	PK
7	1053.1702	7.02	41.75	48.77	68.20	19.43	PASS	Vertical	PK
8	1929.1953	11.84	35.80	47.64	68.20	20.56	PASS	Vertical	PK
9	4278.5852	18.66	32.57	51.23	68.20	16.97	PASS	Vertical	PK
10	6910.9607	-4.55	47.48	42.93	68.20	25.27	PASS	Vertical	PK
11	10447.0631	4.98	43.40	48.38	68.20	19.82	PASS	Vertical	PK
12	15899.1933	10.75	41.93	52.68	68.20	15.52	PASS	Vertical	PK

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor– Antenna Factor–Cable Factor

2) Scan from 9kHz to 40GHz, the disturbance above 18GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

6.8 Radiated Emission which fall in the restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.407 (b)
Test Method:	ANSI C63.10 2013
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10kHz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(4) For transmitters operating in the 5.725-5.85 GHz band:
(i) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated

	emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. Note: (i) EIRP = ((E*d)^2) / 30 where: • E is the field strength in V/m; • d is the measurement distance in meters; • EIRP is the equivalent isotropically radiated power in watts. (ii) Working in dB units, the above equation is equivalent to: EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77 (iii) Or, if d is 3 meters: EIRP[dBm] = E[dBμV/m] - 95.2
Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	j. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

	Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. k. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. l. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. m. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. n. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. o. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. p. Test the EUT in the lowest channel, the Highest channel q. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. r. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting mode with modulation
Test Results:	Pass

Test Data:

EUT_Name		Test_Model	
Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.72	56.70	68.38	11.68	PASS	Horizontal	PK
2	5150	21.98	22.09	44.07	54.00	9.93	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.49	56.47	68.38	11.91	PASS	Vertical	PK
2	5150	21.98	22.41	44.39	54.00	9.61	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.57	56.55	68.38	11.83	PASS	Horizontal	PK
2	5150	21.98	21.79	43.77	54.00	10.23	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	33.69	55.67	68.38	12.71	PASS	Vertical	PK
2	5150	21.98	22.15	44.13	54.00	9.87	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	30.02	51.75	68.20	16.45	PASS	Horizontal	PK
2	5150	21.73	17.63	39.36	54.00	14.64	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	32.52	54.25	68.20	13.95	PASS	Vertical	PK
2	5150	21.73	17.49	39.22	54.00	14.78	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	32.83	54.81	68.38	13.57	PASS	Horizontal	PK
2	5150	21.98	21.46	43.44	54.00	10.56	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.89	56.87	68.38	11.51	PASS	Vertical	PK
2	5150	21.98	21.76	43.74	54.00	10.26	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	30.38	52.11	68.20	16.09	PASS	Horizontal	PK
2	5150	21.73	16.87	38.60	54.00	15.40	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	31.74	53.47	68.20	14.73	PASS	Vertical	PK
2	5150	21.73	17.19	38.92	54.00	15.08	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	34.74	56.47	68.20	11.73	PASS	Horizontal	PK
2	5150	21.73	22.00	43.73	54.00	10.27	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	34.03	55.76	68.20	12.44	PASS	Vertical	PK
2	5150	21.73	21.92	43.65	54.00	10.35	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	33.20	55.18	68.38	13.20	PASS	Horizontal	PK
2	5150	21.98	22.42	44.40	54.00	9.60	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.43	56.41	68.38	11.97	PASS	Vertical	PK
2	5150	21.98	21.95	43.93	54.00	10.07	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	30.42	52.15	68.20	16.05	PASS	Horizontal	PK
2	5150	21.73	15.79	37.52	54.00	16.48	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	30.37	52.10	68.20	16.10	PASS	Vertical	PK
2	5150	21.73	16.12	37.85	54.00	16.15	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	34.86	56.59	68.20	11.61	PASS	Horizontal	PK
2	5150	21.73	21.71	43.44	54.00	10.56	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/29
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	35.42	57.15	68.20	11.05	PASS	Vertical	PK
2	5150	21.73	22.16	43.89	54.00	10.11	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 a Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5748.3867	-7.54	98.22	90.68	122.20	31.52	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 a Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5748.9495	-7.52	98.58	91.06	122.20	31.14	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 a Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5830.2901	-7.59	99.02	91.43	122.20	30.77	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 a Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5826.9885	-7.62	98.30	90.68	122.20	31.52	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5746.9235	-7.60	97.96	90.36	122.20	31.84	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5751.0505	-7.49	97.06	89.57	122.20	32.63	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5822.8614	-7.63	98.15	90.52	122.20	31.68	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5826.9885	-7.62	97.75	90.13	122.20	32.07	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5753.5268	-7.50	94.88	87.38	122.20	34.82	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5759.3047	-7.54	94.55	87.01	122.20	35.19	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5789.8449	-7.72	95.69	87.97	122.20	34.23	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5804.7024	-7.75	95.39	87.64	122.20	34.56	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5746.9235	-7.60	97.00	89.40	122.20	32.80	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5747.7489	-7.57	96.66	89.09	122.20	33.11	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5826.1631	-7.62	96.76	89.14	122.20	33.06	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5828.6393	-7.60	97.82	90.22	122.20	31.98	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5763.4317	-7.56	94.66	87.10	122.20	35.10	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5748.5743	-7.53	94.38	86.85	122.20	35.35	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5797.2736	-7.76	94.25	86.49	122.20	35.71	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5787.3687	-7.70	93.59	85.89	122.20	36.31	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5754.3522	-7.50	91.60	84.10	122.20	38.10	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5785.7179	-7.69	91.25	83.56	122.20	38.64	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5747.7489	-7.57	96.98	89.41	122.20	32.79	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5749.3997	-7.50	95.97	88.47	122.20	33.73	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5824.5123	-7.63	97.13	89.50	122.20	32.70	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5828.6393	-7.60	96.48	88.88	122.20	33.32	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5765.908	-7.57	93.55	85.98	122.20	36.22	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5758.4792	-7.53	94.03	86.50	122.20	35.70	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5801.4007	-7.77	94.39	86.62	122.20	35.58	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5790.6703	-7.72	95.22	87.50	122.20	34.70	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5784.067	-7.69	90.78	83.09	122.20	39.11	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5773.3367	-7.62	92.74	85.12	122.20	37.08	PASS	Vertical	PK

MIMO:

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.99	56.97	68.38	11.41	PASS	Horizontal	PK
2	5150	21.98	21.11	43.09	54.00	10.91	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	35.05	57.03	68.38	11.35	PASS	Vertical	PK
2	5150	21.98	21.46	43.44	54.00	10.56	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	28.88	50.61	68.20	17.59	PASS	Horizontal	PK
2	5150	21.73	15.64	37.37	54.00	16.63	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	28.86	50.59	68.20	17.61	PASS	Vertical	PK
2	5150	21.73	15.32	37.05	54.00	16.95	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.23	56.21	68.38	12.17	PASS	Horizontal	PK
2	5150	21.98	21.52	43.50	54.00	10.50	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	33.73	55.71	68.38	12.67	PASS	Vertical	PK
2	5150	21.98	21.90	43.88	54.00	10.12	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	28.60	50.33	68.20	17.87	PASS	Horizontal	PK
2	5150	21.73	15.17	36.90	54.00	17.10	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	29.55	51.28	68.20	16.92	PASS	Vertical	PK
2	5150	21.73	15.22	36.95	54.00	17.05	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	33.44	55.17	68.20	13.03	PASS	Horizontal	PK
2	5150	21.73	21.82	43.55	54.00	10.45	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	34.22	55.95	68.20	12.25	PASS	Vertical	PK
2	5150	21.73	21.48	43.21	54.00	10.79	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	33.64	55.62	68.38	12.76	PASS	Horizontal	PK
2	5150	21.98	21.28	43.26	54.00	10.74	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5180MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.98	34.53	56.51	68.38	11.87	PASS	Vertical	PK
2	5150	21.98	21.52	43.50	54.00	10.50	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	29.16	50.89	68.20	17.31	PASS	Horizontal	PK
2	5150	21.73	16.22	37.95	54.00	16.05	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5190MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	28.19	49.92	68.20	18.28	PASS	Vertical	PK
2	5150	21.73	15.44	37.17	54.00	16.83	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	34.48	56.21	68.20	11.99	PASS	Horizontal	PK
2	5150	21.73	21.82	43.55	54.00	10.45	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5210MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5150	21.73	33.78	55.51	68.20	12.69	PASS	Vertical	PK
2	5150	21.73	21.24	42.97	54.00	11.03	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5746.9235	-7.60	95.62	88.02	122.20	34.18	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5751.8759	-7.49	95.34	87.85	122.20	34.35	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5822.8614	-7.63	95.95	88.32	122.20	33.88	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5827.8139	-7.61	96.92	89.31	122.20	32.89	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5763.4317	-7.56	93.72	86.16	122.20	36.04	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5757.6538	-7.53	92.75	85.22	122.20	36.98	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5790.6703	-7.72	92.96	85.24	122.20	36.96	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5806.3532	-7.74	92.76	85.02	122.20	37.18	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5750.2251	-7.48	94.34	86.86	122.20	35.34	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5744.4472	-7.70	95.44	87.74	122.20	34.46	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5819.5598	-7.66	95.49	87.83	122.20	34.37	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5828.6393	-7.60	94.68	87.08	122.20	35.12	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5765.908	-7.57	91.69	84.12	122.20	38.08	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5748.5743	-7.53	91.14	83.61	122.20	38.59	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5787.3687	-7.70	92.91	85.21	122.20	36.99	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5785.7179	-7.69	91.81	84.12	122.20	38.08	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5786.5433	-7.70	88.79	81.09	122.20	41.11	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5793.1466	-7.74	89.97	82.23	122.20	39.97	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5749.3997	-7.50	93.35	85.85	122.20	36.35	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5745MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5751.0505	-7.49	93.41	85.92	122.20	36.28	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5824.5123	-7.63	95.49	87.86	122.20	34.34	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE20)Transmitting	Test_Frequency	5825MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5817.0835	-7.67	95.46	87.79	122.20	34.41	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5763.4317	-7.56	90.85	83.29	122.20	38.91	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5755MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5760.1301	-7.54	90.92	83.38	122.20	38.82	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5786.5433	-7.70	91.87	84.17	122.20	38.03	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE40)Transmitting	Test_Frequency	5795MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5802.2261	-7.77	91.90	84.13	122.20	38.07	PASS	Vertical	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5775.8129	-7.64	88.98	81.34	122.20	40.86	PASS	Horizontal	PK

EUT_Name		Test_Model	
Test_Mode	802.11 ax(HE80)Transmitting	Test_Frequency	5775MHz
Tset_Engineer	chenjun	Test_Date	2024/10/30
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	5765.908	-7.57	88.48	80.91	122.20	41.29	PASS	Vertical	PK

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor– Antenna Factor–Cable Factor

2) Scan from 1GHz to 25GHz, the disturbance above 13GHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

7 Appendix 5G Wi-Fi

Refer to Appendix: 5G Wi-Fi of EED32Q81626902

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No.EED32Q81626901 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***