



## FCC RF Exposure

EUT Description: Parking heater

Model No.: KF620025US-01HDR-001

FCC ID: 2BM49-KF620025US

Equipment type: mobile equipment

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

| Frequency range<br>(MHz)                                | Electric field<br>strength<br>(V/m) | Magnetic field strength<br>(A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|---------------------------------------------------------|-------------------------------------|----------------------------------|----------------------------------------|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                                     |                                  |                                        |                             |
| 0.3–3.0                                                 | 614                                 | 1.63                             | *(100)                                 | 6                           |
| 3.0–30                                                  | 1842/f                              | 4.89/f                           | *(900/f <sup>2</sup> )                 | 6                           |
| 30–300                                                  | 61.4                                | 0.163                            | 1.0                                    | 6                           |
| 300–1500                                                |                                     |                                  | f/300                                  | 6                           |
| 1500–100,000                                            |                                     |                                  | 5                                      | 6                           |
| (B) Limits for General Population/Uncontrolled Exposure |                                     |                                  |                                        |                             |
| 0.3–1.34                                                | 614                                 | 1.63                             | *(100)                                 | 30                          |
| 1.34–30                                                 | 824/f                               | 2.19/f                           | *(180/f <sup>2</sup> )                 | 30                          |
| 30–300                                                  | 27.5                                | 0.073                            | 0.2                                    | 30                          |
| 300–1500                                                |                                     |                                  | f/1500                                 | 30                          |
| 1500–100,000                                            |                                     |                                  | 1.0                                    | 30                          |

F = frequency in MHz

Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where :

$P_d$  = power density in mW/cm<sup>2</sup>,

$P_{out}$  = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi$  = 3.14;

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



### 3. Test Result of RF Exposure Evaluation

BLE

| Frequency(MHz) | Output power(dBm) | Max tune-up(mW) | Antenna Gain(dBi) | Power Density at R=20cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|----------------|-------------------|-----------------|-------------------|-----------------------------------------------|-----------------------------|--------|
| 2402           | 3.26              | 2.1184          | 5.3               | 0.0014                                        | 1.0                         | Pass   |
| 2440           | 2.30              | 1.6982          | 5.3               | 0.0011                                        | 1.0                         | Pass   |
| 2480           | 2.40              | 1.7378          | 5.3               | 0.0012                                        | 1.0                         | Pass   |

Conclusion: No SAR is required