TEST REPORT

Product Name:	camera
FCC ID:	2BMBD-C1S1A
Trademark:	Tails & Frames
Model Number:	C1S1A, C1S2A, C1S3A
Prepared For:	VERITI PTE. LTD.
Address:	15 SCOTTS ROAD#03-1215 SCOTTSSINGAPORE (228218)
Manufacturer:	VERITI PTE. LTD.
Address:	15 SCOTTS ROAD#03-1215 SCOTTSSINGAPORE (228218)
Prepared By:	Shenzhen CTB Testing Technology Co., Ltd.
Address:	1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date:	Nov. 14, 2024
Sample tested Date:	Nov. 14, 2024 to Jan. 16, 2025
Issue Date:	Jan. 16, 2025
Report No.:	CTB24111407001RF02
Test Standards	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 789033 V02r01
Test Results	PASS
Remark:	This is WIFI-5GHz band radio test report.

Compiled by:	Reviewed by:	Approved by:
Zhou Kui	Arron Liu	Bin Mei
Zhou Kui	Arron Liu	Bin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration Page

1. VERSION 3
2. TEST SUMMARY 4
3. MEASUREMENT UNCERTAINTY 5
4. PRODUCT INFORMATION AND TEST SETUP 6
4.1 Product Information 6
4.2 Test Setup Configuration 6
4.3 Support Equipment 6
4.5 Test Mode 8
4.6 Test Environment 8
5. TEST FACILITY AND TEST INSTRUMENT USED 9
5.1 Test Facility 9
5.2 Test Instrument Used 9
6. AC POWER LINE CONDUCTED EMISSION 12
6.1 Block Diagram Of Test Setup 12
6.2 Limit 12
6.3 Test procedure 12
6.4 Test Result 14
7. RADIATED SPURIOUS EMISSIONS 16
7.1 Block Diagram Of Test Setup 16
7.2 Limit 16
7.3 Test procedure 17
7.4 Test Result 18
8. BAND EDGE 24
8.1 Block Diagram Of Test Setup 24
8.2 Limit 24
8.3 Test procedure 24
8.4 Test Result 25
9. CONDUCTED OUTPUT POWER 35
9.1 Block Diagram Of Test Setup 35
9.2 Limit 35
9.3 Test procedure 36
9.4 Test Result 37
10. EMISSION BANDWIDTH& OCCUPIED BANDWIDTH 51
10.1 Block Diagram Of Test Setup 51
10.2 Limits 51
10.3 Test Procedure 51
10.4 Test Results 53
11. POWER SPECTRAL DENSITY 67
11.1 Block Diagram Of Test Setup 67
11.2 Limit 67
11.3 Test procedure 67
11.4 Test Result 69
12. FREQUENCY STABILITY 83
12.1 Block Diagram Of Test Setup 83
12.2 Limit 83
12.3 Test procedure 83
12.4 Test Result 84
13. OPERATION IN THE ABSENCE OF INFORMATION TO THE TRANSMIT 96
13.1 Requirement 96
13.2 Test Results 96
14. ANTENNA REQUIREMENT 97
15. EUT TEST SETUP PHOTOGRAPHS 98

(NOTE: N/A MEANS NOT APPLICABLE)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB24111407001RF02	Jan. 16, 2025	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(9)	ANSI C63.10-2013	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033v02r01	PASS
Band edge	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033v02r01	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033v02r01	PASS
Emission Bandwidth & Occupied Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)(e)	KDB789033v02r01	PASS
Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033v02r01	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	KDB789033v02r01	PASS
Operation in the absence of information to the transmit	47 CFR Part 15 Subpart E Section 15.407 (c)	47 CFR Part 15 Subpart E	PASS
Antenna Requirement	47 CFR Part 15 Subpart E Section 15.203	ANSI C63.10-2013	PASS

Remark:
Test according to ANSI C63.10-2013.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	Occupancy bandwidth	U=±54.3Hz
2	Adjacent channel power	U=±1.3dB
3	Conducted Adjacent channel power	U=±1.38dB
4	Conducted output power Above 1G	U=±1.0dB
5	Conducted output power below 1G	U=±0.9dB
6	Power Spectral Density , Conduction	U=±1.0dB
7	Conduction spurious emissions	U=±2.8dB
8	Out of band emission	U=±54Hz
9	3m camber Radiated spurious emission(30MHz-1GHz)	U=±4.3dB
10	3m chamber Radiated spurious emission(1GHz-18GHz)	U=±4.5dB
11	humidity uncertainty	U=±5.3%
12	Temperature uncertainty	U=±0.59℃
13	Supply volyages	U=±3%
14	Time	U=±5%
15	Conducted Emission (150KHz-30MHz)	3.2 dB
16	3m camber Radiated spurious emission(9KHz-30MHz)	4.8dB
17	3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	C1S1A, C1S2A, C1S3A
Model Description:	All the model are the same circuit and RF module, only the model names are different. Test sample model: C1S1A
Wi-Fi Specification:	IEEE 802.11a/n/ac/ax
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11a/n/ac/ax(20M): 5250MHz ~5350 MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5250MHz ~5350 MHz/ 2 channel IEEE 802.11a/n/ac/ax(20M): 5470MHz ~5725 MHz/ 11 channel IEEE 802.11n/ac/ax(40M): 5470MHz ~5725 MHz/ 5 channel IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac/ax(40M): 5725MHz ~5850MHz/ 2 channel
Max. RF output power:	WiFi (5G): 18.772dBm
Type of Modulation:	WiFi (5G): OFDM, OFDMA
Antenna installation:	WiFi (5G): FPC antenna
Antenna Gain:	WiFi (5.2G): 4.15dBi WiFi (5.3G): 4.29dBi WiFi (5.6G): 4.10dBi WiFi (5.8G): 4.56dBi
Ratings:	Input: 100-240V~50/60Hz 0.35A Max Output: 5.0V⎓2.0A 10W

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1.	Adapter	Shenzhen Flypower Technology Co, Ltd.	PS1OUAO50K2000EU	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

For 802.11a/n/ac/ax(20M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz
For 802.11a/n/ac/ax(20M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
52	5260MHz	60	5300MHz
56	5280MHz	64	5320MHz
For 802.11a/n/ac/ax(20M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
100	5500MHz	124	5620 MHz
104	5520MHz	128	5640 MHz
108	5540MHz	132	5660 MHz
112	5560MHz	136	5680MHz
116	5580MHz	140	5700MHz
120	5600 MHz		
For 802.11a/n/ac/ax(20M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz	NA	NA

For 802.11n/ac/ax(40M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz
For 802.11n/ac/ax(40M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
54	5270MHz	62	5310MHz
For 802.11n/ac/ax(40M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
102	5510MHz	126	5630MHz
110	5550MHz	134	5670MHz
118	5590MHz		
For 802.11n/ac/ax(40M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

NOTE: Dutycycle>98%.

Test mode	Rate
802.11a	54M
802.11n	500M
802.11/ac/ax	500M

4.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11a/n/ac/ax(20M)	5150MHz ~5250 MHz	Channel 36	Channel 40	Channel 48
		5180MHz	5200MHz	5240MHz
802.11n/ac/ax(40M)		Channel 38	N/A	Channel 46
		5190MHz	N/A	5230MHz
802.11a/n/ac/ax(20M)	5250MHz ~5350 MHz	Channel 52	Channel 56	Channel 64
		5260MHz	5280MHz	5320MHz
802.11n/ac/ax(40M)		Channel 54	N/A	Channel 62
		5270MHz	N/A	5310MHz
802.11a/n/ac/ax(20M)	5470MHz ~5725 MHz	Channel 100	Channel 116	Channel 140
		5500MHz	5580MHz	5700MHz
802.11n/ac/ax(40M)		Channel 102	N/A	Channel 134
		5510MHz	N/A	5670MHz
802.11a/n/ac/ax(20M)	5725MHz ~5850 MHz	Channel 149	Channel 157	Channel 165
		5745MHz	5785MHz	5825MHz
802.11n/ac/ax(40M)		Channel 151	N/A	Channel 159
		5755MHz	N/A	5795MHz

4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(AC):NV	120V
Normal Temperature(℃):NT	23
Low Temperature(℃):LT	0
High Temperature(℃):HT	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2025/6/28
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2025/6/28
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2025/6/28
4	Communication test set	R&S	CMW500	108058	V3.5.80	2025/6/28
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2025/6/28
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2025/6/28
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2025/6/28
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	/	2025/6/30
10	5 GHz Filter	Shenxiang	MSF5150-5850MS-1155	20181015001	/	2025/6/30
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	/	2025/6/30
12	BT&WI-FI Automatic test software	Micowave	MTS8310	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2025/6/28
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2025/6/28
15	234G Automatic test software	Micowave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2027/6/21
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/6/28
18	Amplifier	HP	8447E	2945A02747	/	2025/6/28
19	Amplifier	Agilent	8449B	3008A01838	/	2025/6/28
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/28
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2025/6/28

22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/28
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2025/6/28
26	Amplifier	AEROFLEX	Aeroflex	097	/	2025/6/28
27	Power Metter	KEYSIGHT	N1912AP	N/A	A.05.00	2025/6/28

Continuous disturbance						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2027/6/21
2	AMN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/6/30
3	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	/	2025/6/28
4	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/6/30
5	Coaxial cable	ZDECL	Z302S	18091904	/	2025/6/30
6	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/30
7	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/10/25
8	EZ-EMC	Frad	EMC-con3A1.1	/	/	/
9	Current Probe	FCC	F-52B	199453	/	2025/5/27
10	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
11	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

Radiated emission(No.2 Chamber)						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2026/11/14
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/7/07
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/7/06
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/23
6	EMI TEST RECEIVER	R&S	ESCI7	100861	/	2025/10/25
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/
9	Coaxial cable	Rosenberg	8m	/	/	2025/10/25
10	Coaxial cable	Times	2m	/	/	2025/10/25

11	Coaxial cable	Times	2m	/	/	2025/10/25
12	Coaxial cable	Times	1m	/	/	2025/10/25
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56[Note 1]	56 to 46[Note 1]
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

* Decreasing linearly with the logarithm of the frequency

6.3 Test procedure

1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under

test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

6.4 Test Result

Test Specification: Neutral



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1539	32.03	10.88	42.91	65.79	-22.88	QP
2		0.1539	19.53	10.88	30.41	55.79	-25.38	AVG
3		0.5420	36.73	10.55	47.28	56.00	-8.72	QP
4	*	0.5420	28.03	10.55	38.58	46.00	-7.42	AVG
5		1.6180	25.68	11.34	37.02	56.00	-18.98	QP
6		1.6180	14.30	11.34	25.64	46.00	-20.36	AVG
7		3.7020	23.33	11.95	35.28	56.00	-20.72	QP
8		3.7020	12.59	11.95	24.54	46.00	-21.46	AVG
9		7.7180	20.42	13.01	33.43	60.00	-26.57	QP
10		7.7180	7.95	13.01	20.96	50.00	-29.04	AVG
11		26.9980	27.37	14.21	41.58	60.00	-18.42	QP
12		26.9980	17.02	14.21	31.23	50.00	-18.77	AVG

Test Specification: Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1539	32.27	10.88	43.15	65.79	-22.64	QP
2		0.1539	18.22	10.88	29.10	55.79	-26.69	AVG
3		0.5580	33.73	10.56	44.29	56.00	-11.71	QP
4	*	0.5580	25.01	10.56	35.57	46.00	-10.43	AVG
5		1.6980	20.14	11.39	31.53	56.00	-24.47	QP
6		1.6980	7.63	11.39	19.02	46.00	-26.98	AVG
7		4.6940	18.36	12.17	30.53	56.00	-25.47	QP
8		4.6940	8.87	12.17	21.04	46.00	-24.96	AVG
9		8.9780	17.68	13.14	30.82	60.00	-29.18	QP
10		8.9780	5.58	13.14	18.72	50.00	-31.28	AVG
11		26.9980	27.44	14.21	41.65	60.00	-18.35	QP
12		26.9980	17.27	14.21	31.48	50.00	-18.52	AVG

Remark:
1. Factor = Cable loss + LISN factor, Margin = Limit – Level
2. All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
3. All the test modes completed for test. Only the worst result of was reported.

7. RADIATED SPURIOUS EMISSIONS

7.1 Block Diagram Of Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	20log 2400/F (kHz) + 80	Quasi-peak	3
0.490MHz-1.705MHz	20log 24000/F (kHz) + 40	Quasi-peak	3
1.705MHz-30MHz	20log 30 + 40	Quasi-peak	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

If radiated measurements are performed, field strength is then converted to EIRP as follows:
(i) EIRP = ((E*d)^2) / 30
where:
• E is the field strength in V/m;
• d is the measurement distance in meters;
• EIRP is the equivalent isotropically radiated power in watts.
(ii) Working in dB units, the above equation is equivalent to:
EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
(iii) Or, if d is 3 meters:
EIRP[dBm] = E[dBμV/m] - 95.2

7.3 Test procedure

Below 1GHz test procedure as below:
a.The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b.The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d.For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
e.The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f.If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Above 1GHz test procedure as below:
g.Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
h.Test the EUT in the lowest channel ,the middle channel ,the Highest channel
j.Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

7.4 Test Result

30MHz-1GHzTest Results:
Modulation : 802.11a (the worst data)
Test Channel : 5180MHz
Antenna polarity: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.0000	38.79	-12.93	25.86	40.00	-14.14	QP
2	84.9993	31.51	-18.42	13.09	40.00	-26.91	QP
3	148.4410	39.28	-13.32	25.96	43.50	-17.54	QP
4	215.2678	38.31	-16.86	21.45	43.50	-22.05	QP
5	351.7080	43.78	-13.07	30.71	46.00	-15.29	QP
6 *	793.3960	36.95	-2.90	34.05	46.00	-11.95	QP

Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	35.8746	43.59	-13.10	30.49	40.00	-9.51	QP
2	102.0013	48.93	-17.85	31.08	43.50	-12.42	QP
3	189.0743	44.05	-16.87	27.18	43.50	-16.32	QP
4	300.3672	41.72	-13.78	27.94	46.00	-18.06	QP
5	675.2080	36.43	-5.67	30.76	46.00	-15.24	QP
6	793.3960	33.10	-2.90	30.20	46.00	-15.80	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

1. The margin of 9K-30MH measurement exceeds 20dB, so the test chart is not included. Test Mode: 802.11a20 (the worst)

Radiated Spurious Emission (Above 1GHz):
Modulation : 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	39.31	16.39	55.70	74	-18.30	PK	1.18	13	H
10360	25.86	16.39	42.25	54	-11.75	AV	1.09	122	H
10360	40.09	16.39	56.48	74	-17.52	PK	1.17	357	V
10360	26.57	16.39	42.96	54	-11.04	AV	1.36	111	V
Channel:5240MHz									
10480	39.31	16.11	55.42	74	-18.58	PK	1.36	208	H
10480	27.83	16.11	43.94	54	-10.06	AV	1.08	123	H
10480	39.99	16.11	56.10	74	-17.90	PK	1.53	68	V
10480	27.98	16.11	44.09	54	-9.91	AV	1.29	130	V
Channel:5260MHz									
10520	39.31	16.39	55.70	74	-18.30	PK	1.18	13	H
10520	25.86	16.39	42.25	54	-11.75	AV	1.09	122	H
10520	40.09	16.39	56.48	74	-17.52	PK	1.17	357	V
10520	26.57	16.39	42.96	54	-11.04	AV	1.36	111	V
Channel:5320MHz									
10640	41.81	16.39	58.20	74	-15.80	PK	1.48	171	H
10640	25.06	16.39	41.45	54	-12.55	AV	1.18	33	H
10640	41.05	16.39	57.44	74	-16.56	PK	1.25	81	V
10640	27.66	16.39	44.05	54	-9.95	AV	1.19	221	V
Channel:5500MHz									
11000	39.67	16.39	56.06	74	-17.94	PK	1.57	311	H
11000	25.31	16.39	41.70	54	-12.30	AV	1.33	354	H
11000	39.69	16.39	56.08	74	-17.92	PK	1.13	282	V
11000	26.90	16.39	43.29	54	-10.71	AV	1.50	183	V

Channel:5700MHz									
11400	41.07	16.39	57.46	74	-16.54	PK	1.49	276	H
11400	26.80	16.39	43.19	54	-10.81	AV	1.43	324	H
11400	39.90	16.39	56.29	74	-17.71	PK	1.08	253	V
11400	25.10	16.39	41.49	54	-12.51	AV	1.56	221	V
Channel:5745MHz									
11490	41.76	17.46	59.22	74	-14.78	PK	1.14	205	H
11490	27.82	17.46	45.28	54	-8.72	AV	1.11	86	H
11490	41.77	17.46	59.23	74	-14.77	PK	1.16	202	V
11490	26.05	17.46	43.51	54	-10.49	AV	1.40	11	V
Channel:5825MHz									
11650	40.93	17.57	58.50	74	-15.50	PK	1.56	132	H
11650	25.27	17.57	42.84	54	-11.16	AV	1.26	132	H
11650	39.07	17.57	56.64	74	-17.36	PK	1.17	343	V
11650	27.21	17.57	44.78	54	-9.22	AV	1.45	119	V

Modulation : 802.11(n40) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	41.03	16.34	57.37	74	-16.63	PK	1.60	190	H
10380	26.31	16.34	42.65	54	-11.35	AV	1.30	253	H
10380	39.09	16.34	55.43	74	-18.57	PK	1.27	222	V
10380	27.33	16.34	43.67	54	-10.33	AV	1.47	151	V
Channel:5230MHz									
10460	41.34	16.15	57.49	74	-16.51	PK	1.32	184	H
10460	26.07	16.15	42.22	54	-11.78	AV	1.49	158	H
10460	39.42	16.15	55.57	74	-18.43	PK	1.80	322	V
10460	26.67	16.15	42.82	54	-11.18	AV	1.81	281	V
Channel:5270MHz									
10540	40.75	16.34	57.09	74	-16.91	PK	1.25	108	H
10540	25.22	16.34	41.56	54	-12.44	AV	1.42	78	H
10540	40.67	16.34	57.01	74	-16.99	PK	1.23	95	V
10540	27.02	16.34	43.36	54	-10.64	AV	1.48	85	V
Channel:5310MHz									
10620	40.80	16.34	57.14	74	-16.86	PK	1.88	259	H
10620	25.31	16.34	41.65	54	-12.35	AV	1.26	183	H
10620	41.70	16.34	58.04	74	-15.96	PK	1.28	162	V
10620	25.93	16.34	42.27	54	-11.73	AV	1.05	343	V
Channel:5510MHz									
11020	41.48	16.34	57.82	74	-16.18	PK	1.64	59	H
11020	26.33	16.34	42.67	54	-11.33	AV	1.12	126	H
11020	41.36	16.34	57.70	74	-16.30	PK	1.11	171	V
11020	25.03	16.34	41.37	54	-12.63	AV	1.33	143	V

Channel:5670MHz									
11340	40.10	16.34	56.44	74	-17.56	PK	1.76	0	H
11340	27.33	16.34	43.67	54	-10.33	AV	1.22	314	H
11340	40.48	16.34	56.82	74	-17.18	PK	1.37	65	V
11340	25.75	16.34	42.09	54	-11.91	AV	1.41	56	V

Channel:5755MHz									
11510	39.73	17.49	57.22	74	-16.78	PK	1.30	131	H
11510	25.98	17.49	43.47	54	-10.53	AV	1.28	306	H
11510	40.23	17.49	57.72	74	-16.28	PK	1.89	91	V
11510	25.87	17.49	43.36	54	-10.64	AV	1.84	302	V
Channel:5795MHz									
11590	41.91	17.52	59.43	74	-16.57	PK	1.02	4	H
11590	25.18	17.52	42.70	54	-14.57	AV	1.54	6	H
11590	41.98	17.52	59.50	74	-14.50	PK	1.21	48	V
11590	26.07	17.52	43.59	54	-10.41	AV	1.83	314	V

Remark:
1.Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits
2.The EUT was tested in the low, high channel and the worst case position data was reported.
3.Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. BAND EDGE

8.1 Block Diagram Of Test Setup



8.2 Limit

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of −17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of −27 dBm/MHz.
(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

8.3 Test procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.4 Test Result

Test Graph

5150-5250MHz

802.11a-5180



802.11a-5240



802.11ac(VH20)-5180



802.11ac(VH20)-5240



802.11ac(VH40)-5190



802.11ac(VH40)-5230



802.11n(HT20)-5180

802.11n(HT20)-5240



802.11n(HT40)-5190



802.11n(HT40)-5230

802.11ax(VH20)-5180



802.11ax(VH20)-5240



802.11ax(VH40)-5190



802.11ax(VH40)-5230





5250-5350MHz:

802.11a-5260



802.11a-5320



802.11ac(VH20)-5260



802.11ac(VH20)-5320



802.11ac(VH40)-5270

802.11ac(VH40)-5310



802.11n(HT20)-5260



802.11n(HT20)-5320



802.11n(HT40)-5270



802.11n(HT40)-5310



802.11ax(VH20)-5260



802.11ax(VH20)-5320

802.11ax(VH40)-5270

802.11ax(VH40)-5310



5470-5725MHz:

802.11a-5500



802.11ac(VH20)-5500

802.11a-5700



802.11ac(VH20)-5700



802.11ac(VH40)-5510



802.11ac(VH40)-5670



802.11n(HT20)-5500



802.11n(HT20)-5700



802.11n(HT40)-5510



802.11n(HT40)-5670

802.11ax(VH20)-5500



802.11ax(VH20)-5700



802.11ax(VH40)-5510



802.11ax(VH40)-5670





5725-5850MHz

802.11a-5745	802.11a-5825

802.11ac(VH20)-5745

802.11ac(VH20)-5825



802.11ac(VH40)-5755

802.11ac(VH40)-5795



802.11(n20)-5745

802.11(n20)-5825



802.11(n40)-5755



802.11(n40)-5795



802.11ax(VH20)-5745



802.11ax(VH20)-5825



802.11ax(VH40)-5755

802.11ax(VH40)-5795


Agilent Spectrum Analyzer - Swept SA
Center Freq 5.695000000 GHz
PASS
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
Ref Offset 9.74 dB
10 dB/div Ref 20.00 dBm
Mkr1 5.761 84 GHz
1.766 dBm
Trace 1 Pass
Start 5.5950 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz
Stop 5.7950 GHz
Sweep 1.333 ms (10001 pts)

Agilent Spectrum Analyzer - Swept SA
Center Freq 5.855000000 GHz
PASS
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
Ref Offset 9.52 dB
10 dB/div Ref 20.00 dBm
Mkr1 5.780 60 GHz
1.034 dBm
Trace 1 Pass
Start 5.7550 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz
Stop 5.9550 GHz
Sweep 1.333 ms (10001 pts)

9. CONDUCTED OUTPUT POWER

9.1 Block Diagram Of Test Setup



9.2 Limit

(1) For the band 5.15-5.25 GHz.
(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p.
at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition,the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.
(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a

bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

(h) Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).
(1) Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW.

9.3 Test procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 × span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98%, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”

(viii) Trace average at least 100 traces in power averaging (rms) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

9.4 Test Result

5150-5250MHz:

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5180	17.584	23.98
	5200	15.44	23.98
	5240	15.31	23.98
802.11ac20	5180	16.925	23.98
	5200	17.171	23.98
	5240	18.168	23.98
802.11ac40	5190	13.182	23.98
	5230	13.485	23.98
802.11ax(HT20)	5180	14.994	23.98
	5200	15.202	23.98
	5240	16.26	23.98
802.11ax(HT40)	5190	7.491	23.98
	5230	8.818	23.98
802.11n20	5180	18.161	23.98
	5200	18.552	23.98
	5240	18.74	23.98
802.11n40	5190	17.777	23.98
	5230	18.712	23.98

5250-5350MHz:

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5260	13.68	23.98
	5280	13.13	23.98
	5320	13.071	23.98
802.11ac20	5260	12.436	23.98
	5280	13.744	23.98
	5320	11.013	23.98
802.11ac40	5270	12.178	23.98
	5310	13.68	23.98
802.11ax(HT20)	5270	10.77	23.98
	5310	11.093	23.98
	5260	11.327	23.98
802.11ax(HT40)	5280	12.708	23.98
	5320	12.901	23.98
802.11n20	5270	13.003	23.98
	5310	12.708	23.98
	5260	12.901	23.98
802.11n40	5280	17.065	23.98
	5320	12.57	23.98

5470-5725MHz:

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5500	12.651	23.98
	5580	15.704	23.98
	5700	12.813	23.98
802.11ac20	5500	12.054	23.98
	5580	13.167	23.98
	5700	14.761	23.98
802.11ac40	5510	12.78	23.98
	5670	13.677	23.98
802.11ax(HT20)	5500	13.475	23.98
	5580	13.65	23.98
	5700	13.869	23.98
802.11ax(HT40)	5510	12.919	23.98
	5670	13.463	23.98
802.11n20	5500	13.416	23.98
	5580	15.448	23.98
	5700	14.351	23.98
802.11n40	5510	14.918	23.98
	5670	14.897	23.98

5725-5850MHz:

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5745	16.912	30
	5785	16.809	30
	5825	15.852	30
802.11ac20	5745	16.419	30
	5785	16.413	30
	5825	15.87	30
802.11ac40	5755	12.892	30
	5795	12.5	30
802.11ax(HT20)	5745	14.677	30
	5785	14.618	30
	5825	14.119	30
802.11ax(HT40)	5755	11.972	30
	5795	11.453	30
802.11n20	5745	16.74	30
	5785	16.759	30
	5825	15.718	30
802.11n40	5755	16.797	30
	5795	16.316	30

5150-5250MHz

802.11a-5180



802.11a-5200



802.11a-5240



802.11ac(VH20)-5180



802.11ac(VH20)-5200



802.11ac(VH20)-5240



802.11ac(VH40)-5190

802.11ac(VH40)-5230



802.11ax(HT20)-5180



802.11ax(HT20)-5200



802.11ax(HT20)-5240



802.11ax(HT40)-5190



802.11ax(HT40)-5230



802.11n(VH20)-5180



802.11n(VH20)-5200



802.11n(VH20)-5240



802.11n(VH40)-5190



802.11n(VH40)-5230





5250-5350MHz

802.11a-5260



802.11a-5280



802.11a-5320



802.11ac(VH20)-5260



802.11ac(VH20)-5280



802.11ac(VH20)-5320



802.11ac(VH40)-5270

802.11ac(VH40)-5310



802.11ax(HT20)-5260



802.11ax(HT20)-5280

802.11ax(HT20)-5320



802.11ax(HT40)-5270



802.11ax(HT40)-5310



802.11n(VH20)-5260



802.11n(VH20)-5280



8802.11n(VH20)-5320

802.11n(VH40)-5270



802.11n(VH40)-5310





5470-5725MHz

802.11a-5500



802.11a-5580



802.11a-5700



802.11ac(VH20)-5500



802.11ac(VH20)-5580



802.11ac(VH20)-5700



802.11ac(VH40)-5510

802.11ac(VH40)-5670



802.11ax(HT20)-5500



802.11ax(HT20)-5580



802.11ax(HT20)-5700



802.11ax(HT40)-5510



802.11ax(HT40)-5670



802.11n(VH20)-5500



802.11n(VH20)-5580



802.11n(VH20)-5700



802.11n(VH40)-5510



802.11n(VH40)-5670



5725-5850MHz

802.11a-5745	802.11a-5785



802.11a-5825



802.11ac(VH20)-5745



802.11ac(VH20)-5785



802.11ac(VH20)-5825



802.11ac(VH40)-5755



802.11ac(VH40)-5795



802.11ax(HT20)-5745



802.11ax(HT20)-5785



802.11ax(HT20)-5825



5802.11ax(HT40)-5755



802.11ax(HT40)-5795



802.11n(VH20)-5745



802.11n(VH20)-5785



802.11n(VH20)-5825



802.11n(VH40)-5755



802.11n(VH40)-5795





10. EMISSION BANDWIDTH& OCCUPIED BANDWIDTH

10.1 Block Diagram Of Test Setup



10.2 Limits

(1) For the band 5.15-5.25 GHz.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

10.3 Test Procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

1. Emission Bandwidth (EBW)
a) Set RBW = approximately 1% of the emission bandwidth.
b) Set the VBW > RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
2. Minimum Emission Bandwidth for the band 5.725−5.85 GHz
Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 kHz for the band 5.725−5.85 GHz. The following procedure shall be used for measuring this bandwidth:
a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 * RBW.

c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

D. 99% Occupied Bandwidth

The 99% occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Measurement of the 99% occupied bandwidth is *required* only as a condition for using the optional band-edge measurement techniques described in II.G.3.d). Measurements of 99% occupied bandwidth may also optionally be used in lieu of the EBW to define the minimum frequency range over which the 789033 D02 General UNII Test Procedures New Rules v02r01 Page 4 spectrum is integrated when measuring maximum conducted output power as described in II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with Section 15.407(a).
The following procedure shall be used for measuring (99%) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.

2. Set span = 1.5 times to 5.0 times the OBW.

3. Set RBW = 1% to 5% of the OBW

4. Set VBW ≥ 3 * RBW

5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.

6. Use the 99% power bandwidth function of the instrument (if available).

7. If the instrument does not have a 99% power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

10.4 Test Results

5150-5250MHz:

Test mode	Test Channel (MHz)	26dB Bandwidth (MHz)
802.11a	5180	23.112
	5200	24.201
	5240	23.739
802.11ac20	5180	26.308
	5200	25.532
	5240	25.683
802.11ac40	5190	43.679
	5230	42.183
802.11ax(HT20)	5180	24.037
	5200	26.367
	5240	24.184
802.11ax(HT40)	5190	43.289
	5230	42.499
802.11n20	5180	24.473
	5200	25.808
	5240	25.567
802.11n40	5190	43.034
	5230	44.069

5250-5350 MHz:

Test mode	Test Channel (MHz)	26dB Bandwidth (MHz)
802.11a	5260	25.278
	5280	24.033
	5320	22.328
802.11ac20	5260	25.983
	5280	25.8
	5320	25.315
802.11ac40	5270	43.466
	5310	42.954
802.11ax20	5260	29.316
	5280	29.258
	5320	29.296
802.11ax40	5270	50.74
	5310	56.35
802.11n(HT20)	5260	24.358
	5280	24.21
	5320	25.613
802.11n(HT40)	5270	42.814
	5310	42.36