FCC TEST REPORT
FCC ID:2BMCB-WUDUNGW01

Report Number.....:	**ZKT-241030L14170**
Date of Test.....	October 28 to November 11, 2024
Date of issue.....:	November 11, 2024
Total number of pages.....	62
Test Result..... :	PASS
Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address .....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	**Shenzhen Wudong Technology Co.,Ltd**
Address .....:	Room 205, Building 28, Country Garden, Yintian Industrial Zone, Xixiang Street, Bao'an District, Shenzhen
Manufacturer's name .....:	**Shenzhen Wudong Technology Co.,Ltd**
Address .....:	Room 205, Building 28, Country Garden, Yintian Industrial Zone, Xixiang Street, Bao'an District, Shenzhen
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10:2013
Test procedure..... :	/
Non-standard test method .....:	N/A
Test Report Form No.....:	TRF-EL-110_V0
Test Report Form(s) Originator..... :	ZKT Testing
Master TRF .....:	Dated: 2022-02-17

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....:	**TV BOX**
Trademark .....:	N/A
Model/Type reference..... :	WUDUNG W01,Tanix TX1,WUDUNG W02,WUDUNG W03, WUDUNG W04,WUDUNG W05,WUDUNG W06,WUDUNG W07, WUDUNG W08,WUDUNG W09,WUDUNG W10,WUDUNGW11, WUDUNG W12,WUDUNG W13,WUDUNG W14,WUDUNG W15, WUDUNG W16,WUDUNG W17,WUDUNG W18,WUDUNG W19, WUDUNG W20,WUDUNG TX1

Ratings..... : DC5V 2A from adapter AC120V/60Hz

Testing procedure and testing location:

Testing Laboratory..... :	Shenzhen ZKT Technology Co., Ltd.
Address..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature)..... :	Alen He
Reviewer (name + signature)..... :	Joe Liu
Approved (name + signature)..... :	Lake Xie

Table of Contents

Page

1. VERSION 5
2. SUMMARY OF TEST RESULTS 6
2.1 TEST FACILITY 7
2.2 MEASUREMENT UNCERTAINTY 7
3. GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.2 DESCRIPTION OF TEST MODES 9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 9
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 13
4.1 CONDUCTED EMISSION MEASUREMENT 13
4.1.1 POWER LINE CONDUCTED EMISSION Limits 13
4.1.2 TEST PROCEDURE 13
4.1.3 DEVIATION FROM TEST STANDARD 13
4.1.4 TEST SETUP 14
4.1.5 EUT OPERATING CONDITIONS 14
4.1.6 TEST RESULT 15
4.2 RADIATED EMISSION MEASUREMENT 17
4.2.1 RADIATED EMISSION LIMITS 17
4.2.2 TEST PROCEDURE 17
4.2.3 DEVIATION FROM TEST STANDARD 18
4.2.4 TEST SETUP 18
4.2.5 EUT OPERATING CONDITIONS 19
4.2.6 TEST RESULTS 20
5.RADIATED BAND EMISSIONMEASUREMENT 31
5.1 TEST REQUIREMENT: 31
5.2 TEST PROCEDURE 31
5.3 DEVIATION FROM TEST STANDARD 31
5.4 TEST SETUP 32
5.5 EUT OPERATING CONDITIONS 32
5.6 TEST RESULT 33
6.POWER SPECTRAL DENSITY TEST 35
6.1 APPLIED PROCEDURES / LIMIT 35
6.2 TEST PROCEDURE 35
6.3 DEVIATION FROM STANDARD 35
6.4 TEST SETUP 35
6.5 EUT OPERATION CONDITIONS 35

6.6 TEST RESULT 36
7. CHANNEL BANDWIDTH 44
7.1 APPLIED PROCEDURES / LIMIT 44
7.2 TEST PROCEDURE 44
7.3 DEVIATION FROM STANDARD 44
7.4 TEST SETUP 44
7.5 EUT OPERATION CONDITIONS 44
7.6 TEST RESULT 45
8.PEAK OUTPUT POWER TEST 48
8.1 APPLIED PROCEDURES/LIMIT 48
8.2 TEST PROCEDURE 48
8.3 DEVIATION FROM STANDARD 48
8.4 TEST SETUP 48
8.5 EUT OPERATION CONDITIONS 48
8.6 TEST RESULT 49
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 52
9.1 APPLICABLE STANDARD 52
9.2 TEST PROCEDURE 52
9.3 DEVIATION FROM STANDARD 52
9.4 TEST SETUP 52
9.5 EUT OPERATION CONDITIONS 52
9.6 TEST RESULTS 52
10.ANTENNA REQUIREMENT 61
11. TEST SETUP PHOTO 62
12. EUT CONSTRUCTIONAL DETAILS 62

1. VERSION

Report No.	Version	Description	Approved
ZKT-241030L14170	Rev.01	Initial issue of report	November 11, 2024

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Spurious Emission (Conducted) / Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U,where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2,providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power conducted	±0.16dB
3	Spurious emissions conducted	±0.21dB
4	All emissions radiated(<1G)	±4.68dB
5	All emissions radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	TV BOX
Model No.:	WUDUNG W01,Tanix TX1,WUDUNG W02,WUDUNG W03, WUDUNG W04,WUDUNG W05,WUDUNG W06,WUDUNG W07, WUDUNG W08,WUDUNG W09,WUDUNG W10,WUDUNGW11, WUDUNG W12,WUDUNG W13,WUDUNG W14,WUDUNG W15, WUDUNG W16,WUDUNG W17,WUDUNG W18,WUDUNG W19, WUDUNG W20,WUDUNG TX1
Model Different.:	All models covered in this report are the same with each other, except for different model No. and appearance (for color, silk-screen only) for trading purpose.
Serial No.:	N/A
Hardware Version:	H1.0
Software Version:	S1.0
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/802.11n(HT20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing(OFDM)
Antenna Type:	PIFA Antenna
Antenna gain:	3.4945dBi
Power supply:	DC5V 2A from adapter AC120V/60Hz
SWITCHING POWER ADAPTER:	N/A
Battery:	N/A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

Test Software	Realtek Test Tool
Power level setup	<8dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious

3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	TV BOX	N/A	WUDUNG W01	N/A	EUT
E-2	Adapter	N/A	Adapter1		Supply by Lab

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8M	DC Line

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Sep. 29, 2024	Sep. 28, 2025
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	00877	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Sep. 30, 2024	Sep. 29, 2025
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Sep. 30, 2024	Sep. 29, 2025
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Oct. 11, 2024	Oct. 10, 2025
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Sep. 29, 2024	Sep. 28, 2025
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Sep. 30, 2024	Sep. 29, 2025
11	Test Cable	N/A	R-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
12	Test Cable	N/A	R-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
13	Test Cable	N/A	R-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
14	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Sep. 30, 2024	Sep. 29, 2025
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Sep. 30, 2024	Sep. 29, 2025
3	Test Cable	N/A	C-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
4	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Sep. 29, 2024	Sep. 28, 2025
5	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

RF Conducted Test

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	Test Cable	N/A	RF-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
4	Test Cable	N/A	RF-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Test Cable	N/A	RF-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
6	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Sep. 29, 2024	Sep. 28, 2025
7	Signal Generator	Agilent	N5182A	N/A	A.01.87	Sep. 29, 2024	Sep. 28, 2025
8	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Nov. 16, 2023	Nov. 15, 2024
9	Van der Hoofden measuring head	Schwarzbeck Mess-elektronik	VDHH 9502	9502-039	N/A	Sep. 30, 2024	Sep. 29, 2025
10	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Sep. 30, 2024	Sep. 29, 2025
11	MWRF Power Meter Test system	MW	MW100-RFCB	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
12	D.C. Power Supply	LongWei	TPR-6405 D	N/A	N/A	\	\
13	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

Temperature :	26℃	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	TX 802.11b-2402MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1 *	0.154	48.60	10.15	58.75	65.79	-7.04	QP	P
2	0.154	19.99	10.15	30.14	55.79	-25.65	AVG	P
3	0.274	35.69	10.16	45.85	61.00	-15.15	QP	P
4	0.274	14.50	10.16	24.66	51.00	-26.34	AVG	P
5	0.570	28.22	10.16	38.38	56.00	-17.62	QP	P
6	0.570	17.15	10.16	27.31	46.00	-18.69	AVG	P
7	1.366	21.14	10.17	31.31	56.00	-24.69	QP	P
8	1.366	9.00	10.17	19.17	46.00	-26.83	AVG	P
9	6.422	16.38	10.26	26.64	60.00	-33.36	QP	P
10	6.422	0.00	10.26	10.26	50.00	-39.74	AVG	P
11	29.922	15.07	10.84	25.91	60.00	-34.09	QP	P
12	29.922	5.36	10.84	16.20	50.00	-33.80	AVG	P

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature :	26℃	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	TX 802.11b-2402MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1 *	0.158	45.80	10.15	55.95	65.57	-9.62	QP	P
2	0.158	19.78	10.15	29.93	55.57	-25.64	AVG	P
3	0.198	41.78	10.15	51.93	63.69	-11.76	QP	P
4	0.198	17.51	10.15	27.66	53.69	-26.03	AVG	P
5	0.574	31.84	10.16	42.00	56.00	-14.00	QP	P
6	0.574	18.48	10.16	28.64	46.00	-17.36	AVG	P
7	2.290	18.79	10.18	28.97	56.00	-27.03	QP	P
8	2.290	6.94	10.18	17.12	46.00	-28.88	AVG	P
9	6.554	20.16	10.26	30.42	60.00	-29.58	QP	P
10	6.554	2.57	10.26	12.83	50.00	-37.17	AVG	P
11	29.910	13.43	10.85	24.28	60.00	-35.72	QP	P
12	29.910	3.68	10.85	14.53	50.00	-35.47	AVG	P

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of avariable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum valueof the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned toheights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber andchange form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11b-2412MHz

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.6340	39.11	-12.27	26.84	40.00	-13.16	QP
2	128.1130	48.90	-18.32	30.58	43.50	-12.92	QP
3	304.6100	50.49	-18.49	32.00	46.00	-14.00	QP
4	455.9057	50.88	-15.26	35.62	46.00	-10.38	QP
5	558.7300	49.30	-10.82	38.48	46.00	-7.52	QP
6	665.8034	58.12	-13.59	44.53	46.00	-1.47	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11b-2412MHz

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33.0950	49.78	-12.54	37.24	40.00	-2.76	QP
2	75.7112	54.67	-25.06	29.61	40.00	-10.39	QP
3	144.8418	49.73	-17.43	32.30	43.50	-11.20	QP
4	455.9057	51.13	-15.26	35.87	46.00	-10.13	QP
5	668.1422	50.99	-13.63	37.36	46.00	-8.64	QP
6	935.5461	46.09	-7.40	38.69	46.00	-7.31	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case 802.11b mode

1GHz~25GHz

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	51.40	30.55	5.77	31.12	57.74	74.00	-16.26	PK
V	4824.00	31.26	30.55	5.77	31.12	37.60	54.00	-16.40	AV
V	7236.00	49.49	30.33	6.32	36.00	61.48	74.00	-12.52	PK
V	7236.00	31.97	30.33	6.32	36.00	43.96	54.00	-10.04	AV
V	9648.00	49.99	30.85	7.45	37.14	63.73	74.00	-10.27	PK
V	9648.00	31.87	30.85	7.45	37.14	45.61	54.00	-8.39	AV
V	12060.00	45.09	31.02	8.99	39.10	62.16	74.00	-11.84	PK
V	12060.00	27.87	31.02	8.99	39.10	44.94	54.00	-9.06	AV
H	4824.00	51.74	30.55	5.77	31.12	58.08	74.00	-15.92	PK
H	4824.00	31.59	30.55	5.77	31.12	37.93	54.00	-16.07	AV
H	7236.00	50.38	30.33	6.32	36.00	62.37	74.00	-11.63	PK
H	7236.00	31.64	30.33	6.32	36.00	43.63	54.00	-10.37	AV
H	9648.00	50.38	30.85	7.45	37.14	64.12	74.00	-9.88	PK
H	9648.00	31.64	30.85	7.45	37.14	45.38	54.00	-8.62	AV
H	12060.00	45.38	31.02	8.99	39.10	62.45	74.00	-11.55	PK
H	12060.00	26.64	31.02	8.99	39.10	43.71	54.00	-10.29	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	49.45	30.55	5.77	31.45	56.12	74.00	-17.88	PK
V	4874.00	30.34	30.55	5.77	31.45	37.01	54.00	-16.99	AV
V	7311.00	47.98	30.33	6.32	36.10	60.07	74.00	-13.93	PK
V	7311.00	30.02	30.33	6.32	36.10	42.11	54.00	-11.89	AV
V	9748.00	48.05	30.85	7.45	36.50	61.15	74.00	-12.85	PK
V	9748.00	30.02	30.85	7.45	36.50	43.12	54.00	-10.88	AV
V	12185.00	42.95	31.02	8.99	39.11	60.03	74.00	-13.97	PK
V	12185.00	23.59	31.02	8.99	39.11	40.67	54.00	-13.33	AV
H	4874.00	50.81	30.55	5.77	31.45	57.48	74.00	-16.52	PK
H	4874.00	30.37	30.55	5.77	31.45	37.04	54.00	-16.96	AV
H	7311.00	51.52	30.33	6.32	36.10	63.61	74.00	-10.39	PK
H	7311.00	30.15	30.33	6.32	36.10	42.24	54.00	-11.76	AV
H	9748.00	51.52	30.85	7.45	36.50	64.62	74.00	-9.38	PK
H	9748.00	30.15	30.85	7.45	36.50	43.25	54.00	-10.75	AV
H	12185.00	45.00	31.02	8.99	39.11	62.08	74.00	-11.92	PK
H	12185.00	24.15	31.02	8.99	39.11	41.23	54.00	-12.77	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	52.25	30.55	5.77	31.79	59.26	74.00	-14.74	PK
V	4924.00	33.79	30.55	5.77	31.79	40.80	54.00	-13.20	AV
V	7386.00	54.76	30.33	6.32	36.21	66.96	74.00	-7.04	PK
V	7386.00	34.11	30.33	6.32	36.21	46.31	54.00	-7.69	AV
V	9848.00	54.76	30.85	7.45	36.50	67.86	74.00	-6.14	PK
V	9848.00	34.60	30.85	7.45	36.50	47.70	54.00	-6.30	AV
V	12310.00	46.76	31.02	8.99	39.15	63.88	74.00	-10.12	PK
V	12310.00	29.00	31.02	8.99	39.15	46.12	54.00	-7.88	AV
H	4924.00	52.31	30.55	5.77	31.79	59.32	74.00	-14.68	PK
H	4924.00	33.95	30.55	5.77	31.79	40.96	54.00	-13.04	AV
H	7386.00	53.93	30.33	6.32	36.21	66.13	74.00	-7.87	PK
H	7386.00	34.27	30.33	6.32	36.21	46.47	54.00	-7.53	AV
H	9848.00	54.53	30.85	7.45	36.50	67.63	74.00	-6.37	PK
H	9848.00	33.97	30.85	7.45	36.50	47.07	54.00	-6.93	AV
H	12310.00	48.43	31.02	8.99	39.15	65.55	74.00	-8.45	PK
H	12310.00	27.36	31.02	8.99	39.15	44.48	54.00	-9.52	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	51.03	30.55	5.77	31.12	57.37	74.00	-16.63	PK
V	4824.00	30.79	30.55	5.77	31.12	37.13	54.00	-16.87	AV
V	7236.00	48.82	30.33	6.32	36.00	60.81	74.00	-13.19	PK
V	7236.00	31.74	30.33	6.32	36.00	43.73	54.00	-10.27	AV
V	9648.00	48.82	30.85	7.45	37.14	62.56	74.00	-11.44	PK
V	9648.00	31.30	30.85	7.45	37.14	45.04	54.00	-8.96	AV
V	12060.00	45.92	31.02	8.99	39.10	62.99	74.00	-11.01	PK
V	12060.00	27.20	31.02	8.99	39.10	44.27	54.00	-9.73	AV
H	4824.00	51.37	30.55	5.77	31.12	57.71	74.00	-16.29	PK
H	4824.00	31.22	30.55	5.77	31.12	37.56	54.00	-16.44	AV
H	7236.00	50.12	30.33	6.32	36.00	62.11	74.00	-11.89	PK
H	7236.00	31.43	30.33	6.32	36.00	43.42	54.00	-10.58	AV
H	9648.00	50.14	30.85	7.45	37.14	63.88	74.00	-10.12	PK
H	9648.00	31.45	30.85	7.45	37.14	45.19	54.00	-8.81	AV
H	12060.00	45.17	31.02	8.99	39.10	62.24	74.00	-11.76	PK
H	12060.00	24.46	31.02	8.99	39.10	41.53	54.00	-12.47	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	49.37	30.55	5.77	31.45	56.04	74.00	-17.96	PK
V	4874.00	30.22	30.55	5.77	31.45	36.89	54.00	-17.11	AV
V	7311.00	47.97	30.33	6.32	36.10	60.06	74.00	-13.94	PK
V	7311.00	30.08	30.33	6.32	36.10	42.17	54.00	-11.83	AV
V	9748.00	48.05	30.85	7.45	36.50	61.15	74.00	-12.85	PK
V	9748.00	29.31	30.85	7.45	36.50	42.41	54.00	-11.59	AV
V	12185.00	45.08	31.02	8.99	39.11	62.16	74.00	-11.84	PK
V	12185.00	23.42	31.02	8.99	39.11	40.50	54.00	-13.50	AV
H	4874.00	50.64	30.55	5.77	31.45	57.31	74.00	-16.69	PK
H	4874.00	30.59	30.55	5.77	31.45	37.26	54.00	-16.74	AV
H	7311.00	51.34	30.33	6.32	36.10	63.43	74.00	-10.57	PK
H	7311.00	30.16	30.33	6.32	36.10	42.25	54.00	-11.75	AV
H	9748.00	51.54	30.85	7.45	36.50	64.64	74.00	-9.36	PK
H	9748.00	29.97	30.85	7.45	36.50	43.07	54.00	-10.93	AV
H	12185.00	45.79	31.02	8.99	39.11	62.87	74.00	-11.13	PK
H	12185.00	25.10	31.02	8.99	39.11	42.18	54.00	-11.82	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	49.55	30.55	5.77	31.79	56.56	74.00	-17.44	PK
V	4924.00	31.05	30.55	5.77	31.79	38.06	54.00	-15.94	AV
V	7386.00	51.89	30.33	6.32	36.21	64.09	74.00	-9.91	PK
V	7386.00	31.39	30.33	6.32	36.21	43.59	54.00	-10.41	AV
V	9848.00	51.89	30.85	7.45	36.50	64.99	74.00	-9.01	PK
V	9848.00	31.83	30.85	7.45	36.50	44.93	54.00	-9.07	AV
V	12310.00	44.99	31.02	8.99	39.15	62.11	74.00	-11.89	PK
V	12310.00	27.03	31.02	8.99	39.15	44.15	54.00	-9.85	AV
H	4924.00	49.57	30.55	5.77	31.79	56.58	74.00	-17.42	PK
H	4924.00	31.24	30.55	5.77	31.79	38.25	54.00	-15.75	AV
H	7386.00	51.06	30.33	6.32	36.21	63.26	74.00	-10.74	PK
H	7386.00	31.56	30.33	6.32	36.21	43.76	54.00	-10.24	AV
H	9848.00	51.76	30.85	7.45	36.50	64.86	74.00	-9.14	PK
H	9848.00	31.60	30.85	7.45	36.50	44.70	54.00	-9.30	AV
H	12310.00	45.66	31.02	8.99	39.15	62.78	74.00	-11.22	PK
H	12310.00	24.60	31.02	8.99	39.15	41.72	54.00	-12.28	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	51.55	30.55	5.77	31.12	57.89	74.00	-16.11	PK
V	4824.00	31.35	30.55	5.77	31.12	37.69	54.00	-16.31	AV
V	7236.00	48.44	30.33	6.32	36.00	60.43	74.00	-13.57	PK
V	7236.00	32.35	30.33	6.32	36.00	44.34	54.00	-9.66	AV
V	9648.00	49.64	30.85	7.45	37.14	63.38	74.00	-10.62	PK
V	9648.00	31.72	30.85	7.45	37.14	45.46	54.00	-8.54	AV
V	12060.00	45.44	31.02	8.99	39.10	62.51	74.00	-11.49	PK
V	12060.00	26.79	31.02	8.99	39.10	43.86	54.00	-10.14	AV
H	4824.00	51.69	30.55	5.77	31.12	58.03	74.00	-15.97	PK
H	4824.00	31.54	30.55	5.77	31.12	37.88	54.00	-16.12	AV
H	7236.00	50.64	30.33	6.32	36.00	62.63	74.00	-11.37	PK
H	7236.00	31.85	30.33	6.32	36.00	43.84	54.00	-10.16	AV
H	9648.00	50.56	30.85	7.45	37.14	64.30	74.00	-9.70	PK
H	9648.00	31.77	30.85	7.45	37.14	45.51	54.00	-8.49	AV
H	12060.00	44.69	31.02	8.99	39.10	61.76	74.00	-12.24	PK
H	12060.00	25.88	31.02	8.99	39.10	42.95	54.00	-11.05	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	49.81	30.55	5.77	31.45	56.48	74.00	-17.52	PK
V	4874.00	30.70	30.55	5.77	31.45	37.37	54.00	-16.63	AV
V	7311.00	47.67	30.33	6.32	36.10	59.76	74.00	-14.24	PK
V	7311.00	30.53	30.33	6.32	36.10	42.62	54.00	-11.38	AV
V	9748.00	48.72	30.85	7.45	36.50	61.82	74.00	-12.18	PK
V	9748.00	30.70	30.85	7.45	36.50	43.80	54.00	-10.20	AV
V	12185.00	45.62	31.02	8.99	39.11	62.70	74.00	-11.30	PK
V	12185.00	24.63	31.02	8.99	39.11	41.71	54.00	-12.29	AV
H	4874.00	51.10	30.55	5.77	31.45	57.77	74.00	-16.23	PK
H	4874.00	30.83	30.55	5.77	31.45	37.50	54.00	-16.50	AV
H	7311.00	51.83	30.33	6.32	36.10	63.92	74.00	-10.08	PK
H	7311.00	30.61	30.33	6.32	36.10	42.70	54.00	-11.30	AV
H	9748.00	51.98	30.85	7.45	36.50	65.08	74.00	-8.92	PK
H	9748.00	30.61	30.85	7.45	36.50	43.71	54.00	-10.29	AV
H	12185.00	44.61	31.02	8.99	39.11	61.69	74.00	-12.31	PK
H	12185.00	25.69	31.02	8.99	39.11	42.77	54.00	-11.23	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	51.08	30.55	5.77	31.79	58.09	74.00	-15.91	PK
V	4924.00	32.28	30.55	5.77	31.79	39.29	54.00	-14.71	AV
V	7386.00	53.32	30.33	6.32	36.21	65.52	74.00	-8.48	PK
V	7386.00	33.00	30.33	6.32	36.21	45.20	54.00	-8.80	AV
V	9848.00	53.42	30.85	7.45	36.50	66.52	74.00	-7.48	PK
V	9848.00	33.42	30.85	7.45	36.50	46.52	54.00	-7.48	AV
V	12310.00	46.32	31.02	8.99	39.15	63.44	74.00	-10.56	PK
V	12310.00	25.56	31.02	8.99	39.15	42.68	54.00	-11.32	AV
H	4924.00	51.10	30.55	5.77	31.79	58.11	74.00	-15.89	PK
H	4924.00	32.77	30.55	5.77	31.79	39.78	54.00	-14.22	AV
H	7386.00	52.59	30.33	6.32	36.21	64.79	74.00	-9.21	PK
H	7386.00	33.23	30.33	6.32	36.21	45.43	54.00	-8.57	AV
H	9848.00	53.29	30.85	7.45	36.50	66.39	74.00	-7.61	PK
H	9848.00	33.22	30.85	7.45	36.50	46.32	54.00	-7.68	AV
H	12310.00	47.19	31.02	8.99	39.15	64.31	74.00	-9.69	PK
H	12310.00	26.13	31.02	8.99	39.15	43.25	54.00	-10.75	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2422MHz									
V	4844.00	51.00	30.55	5.77	31.14	57.36	74.00	-16.64	PK
V	4844.00	32.19	30.55	5.77	31.14	38.55	54.00	-15.45	AV
V	7266.00	53.24	30.33	6.32	36.09	65.32	74.00	-8.68	PK
V	7266.00	33.05	30.33	6.32	36.09	45.13	54.00	-8.87	AV
V	9688.00	53.32	30.85	7.45	37.16	67.08	74.00	-6.92	PK
V	9688.00	33.30	30.85	7.45	37.16	47.06	54.00	-6.94	AV
V	12110.00	45.87	31.02	8.99	39.15	62.99	74.00	-11.01	PK
V	12110.00	26.56	31.02	8.99	39.15	43.68	54.00	-10.32	AV
H	4844.00	51.25	30.55	5.77	31.14	57.61	74.00	-16.39	PK
H	4844.00	32.72	30.55	5.77	31.14	39.08	54.00	-14.92	AV
H	7266.00	52.52	30.33	6.32	36.09	64.60	74.00	-9.40	PK
H	7266.00	33.20	30.33	6.32	36.09	45.28	54.00	-8.72	AV
H	9688.00	53.19	30.85	7.45	37.16	66.95	74.00	-7.05	PK
H	9688.00	32.77	30.85	7.45	37.16	46.53	54.00	-7.47	AV
H	12110.00	45.24	31.02	8.99	39.15	62.36	74.00	-11.64	PK
H	12110.00	26.08	31.02	8.99	39.15	43.20	54.00	-10.80	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	49.81	30.55	5.77	31.45	56.48	74.00	-17.52	PK
V	4874.00	31.01	30.55	5.77	31.45	37.68	54.00	-16.32	AV
V	7311.00	52.05	30.33	6.32	36.10	64.14	74.00	-9.86	PK
V	7311.00	31.73	30.33	6.32	36.10	43.82	54.00	-10.18	AV
V	9748.00	52.15	30.85	7.45	36.50	65.25	74.00	-8.75	PK
V	9748.00	32.15	30.85	7.45	36.50	45.25	54.00	-8.75	AV
V	12185.00	45.05	31.02	8.99	39.11	62.13	74.00	-11.87	PK
V	12185.00	25.29	31.02	8.99	39.11	42.37	54.00	-11.63	AV
H	4874.00	49.83	30.55	5.77	31.45	56.50	74.00	-17.50	PK
H	4874.00	31.50	30.55	5.77	31.45	38.17	54.00	-15.83	AV
H	7311.00	51.32	30.33	6.32	36.10	63.41	74.00	-10.59	PK
H	7311.00	31.96	30.33	6.32	36.10	44.05	54.00	-9.95	AV
H	9748.00	52.02	30.85	7.45	36.50	65.12	74.00	-8.88	PK
H	9748.00	31.95	30.85	7.45	36.50	45.05	54.00	-8.95	AV
H	12185.00	46.92	31.02	8.99	39.11	64.00	74.00	-10.00	PK
H	12185.00	25.86	31.02	8.99	39.11	42.94	54.00	-11.06	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2452MHz									
V	4904.00	49.85	30.55	5.77	31.69	56.76	74.00	-17.24	PK
V	4904.00	30.79	30.55	5.77	31.69	37.70	54.00	-16.30	AV
V	7356.00	51.48	30.33	6.32	36.15	63.62	74.00	-10.38	PK
V	7356.00	31.42	30.33	6.32	36.15	43.56	54.00	-10.44	AV
V	9808.00	52.18	30.85	7.45	37.32	66.10	74.00	-7.90	PK
V	9808.00	31.84	30.85	7.45	37.32	45.76	54.00	-8.24	AV
V	12260.00	45.69	31.02	8.99	39.13	62.79	74.00	-11.21	PK
V	12260.00	24.77	31.02	8.99	39.13	41.87	54.00	-12.13	AV
H	4904.00	49.53	30.55	5.77	31.69	56.44	74.00	-17.56	PK
H	4904.00	31.93	30.55	5.77	31.69	38.84	54.00	-15.16	AV
H	7356.00	51.11	30.33	6.32	36.15	63.25	74.00	-10.75	PK
H	7356.00	32.19	30.33	6.32	36.15	44.33	54.00	-9.67	AV
H	9808.00	51.74	30.85	7.45	37.32	65.66	74.00	-8.34	PK
H	9808.00	31.58	30.85	7.45	37.32	45.50	54.00	-8.50	AV
H	12260.00	44.73	31.02	8.99	39.13	61.83	74.00	-12.17	PK
H	12260.00	26.59	31.02	8.99	39.13	43.69	54.00	-10.31	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	60.54	30.22	4.85	27.59	62.76	74.00	PK	PASS
	H	2390.00	41.32	30.22	4.85	27.59	43.54	54.00	AV	PASS
	H	2400.00	62.27	30.22	4.85	27.58	64.48	74.00	PK	PASS
	H	2400.00	40.98	30.22	4.85	27.58	43.19	54.00	AV	PASS
	V	2390.00	60.36	30.22	4.85	27.59	62.58	74.00	PK	PASS
	V	2390.00	42.23	30.22	4.85	27.59	44.45	54.00	AV	PASS
	V	2400.00	62.12	30.22	4.85	27.58	64.33	74.00	PK	PASS
	V	2400.00	41.05	30.22	4.85	27.58	43.26	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	58.87	30.22	4.85	27.40	60.90	74.00	PK	PASS
	H	2483.50	39.91	30.22	4.85	27.40	41.94	54.00	AV	PASS
	H	2485.50	60.38	30.22	4.85	27.40	62.41	74.00	PK	PASS
	H	2485.50	40.49	30.22	4.85	27.40	42.52	54.00	AV	PASS
	V	2483.50	59.68	30.22	4.85	27.40	61.71	74.00	PK	PASS
	V	2483.50	41.30	30.22	4.85	27.40	43.33	54.00	AV	PASS
	V	2485.50	60.07	30.22	4.85	27.40	62.10	74.00	PK	PASS
	V	2485.50	40.76	30.22	4.85	27.40	42.79	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	57.79	30.22	4.85	27.59	60.01	74.00	PK	PASS
	H	2390.00	40.02	30.22	4.85	27.59	42.24	54.00	AV	PASS
	H	2400.00	59.82	30.22	4.85	27.58	62.03	74.00	PK	PASS
	H	2400.00	39.92	30.22	4.85	27.58	42.13	54.00	AV	PASS
	V	2390.00	58.04	30.22	4.85	27.59	60.26	74.00	PK	PASS
	V	2390.00	39.82	30.22	4.85	27.59	42.04	54.00	AV	PASS
	V	2400.00	56.78	30.22	4.85	27.58	58.99	74.00	PK	PASS
	V	2400.00	39.60	30.22	4.85	27.58	41.81	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	59.40	30.22	4.85	27.40	61.43	74.00	PK	PASS
	H	2483.50	41.13	30.22	4.85	27.40	43.16	54.00	AV	PASS
	H	2485.50	61.23	30.22	4.85	27.40	63.26	74.00	PK	PASS
	H	2485.50	41.33	30.22	4.85	27.40	43.36	54.00	AV	PASS
	V	2483.50	59.30	30.22	4.85	27.40	61.33	74.00	PK	PASS
	V	2483.50	41.23	30.22	4.85	27.40	43.26	54.00	AV	PASS
	V	2485.50	61.28	30.22	4.85	27.40	63.31	74.00	PK	PASS
	V	2485.50	41.40	30.22	4.85	27.40	43.43	54.00	AV	PASS
802.11n20	Low Channel 2412MHz									
	H	2390.00	58.42	30.22	4.85	27.59	60.64	74.00	PK	PASS
	H	2390.00	40.28	30.22	4.85	27.59	42.50	54.00	AV	PASS
	H	2400.00	60.82	30.22	4.85	27.58	63.03	74.00	PK	PASS
	H	2400.00	40.23	30.22	4.85	27.58	42.44	54.00	AV	PASS
	V	2390.00	58.29	30.22	4.85	27.59	60.51	74.00	PK	PASS
	V	2390.00	40.24	30.22	4.85	27.59	42.46	54.00	AV	PASS
	V	2400.00	60.66	30.22	4.85	27.58	62.87	74.00	PK	PASS
	V	2400.00	48.42	30.22	4.85	27.58	50.63	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	58.03	30.22	4.85	27.40	60.06	74.00	PK	PASS
	H	2483.50	39.96	30.22	4.85	27.40	41.99	54.00	AV	PASS
	H	2485.50	59.77	30.22	4.85	27.40	61.80	74.00	PK	PASS
	H	2485.50	39.84	30.22	4.85	27.40	41.87	54.00	AV	PASS
	V	2483.50	58.06	30.22	4.85	27.40	60.09	74.00	PK	PASS
	V	2483.50	39.81	30.22	4.85	27.40	41.84	54.00	AV	PASS
	V	2485.50	60.29	30.22	4.85	27.40	62.32	74.00	PK	PASS

	V	2485.50	39.64	30.22	4.85	27.40	41.67	54.00	AV	PASS
802.11n40	LowChannel 2422MHz									
	H	2390.00	58.84	30.22	4.85	27.59	61.06	74.00	PK	PASS
	H	2390.00	40.72	30.22	4.85	27.59	42.94	54.00	AV	PASS
	H	2400.00	61.04	30.22	4.85	27.58	63.25	74.00	PK	PASS
	H	2400.00	40.68	30.22	4.85	27.58	42.89	54.00	AV	PASS
	V	2390.00	58.65	30.22	4.85	27.59	60.87	74.00	PK	PASS
	V	2390.00	40.74	30.22	4.85	27.59	42.96	54.00	AV	PASS
	V	2400.00	60.80	30.22	4.85	27.58	63.01	74.00	PK	PASS
	V	2400.00	40.66	30.22	4.85	27.58	42.87	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	58.29	30.22	4.85	27.40	60.32	74.00	PK	PASS
	H	2483.50	40.22	30.22	4.85	27.40	42.25	54.00	AV	PASS
	H	2485.50	59.79	30.22	4.85	27.40	61.82	74.00	PK	PASS
	H	2485.50	40.10	30.22	4.85	27.40	42.13	54.00	AV	PASS
	V	2483.50	58.22	30.22	4.85	27.40	60.25	74.00	PK	PASS
	V	2483.50	40.00	30.22	4.85	27.40	42.03	54.00	AV	PASS
	V	2485.50	60.57	30.22	4.85	27.40	62.60	74.00	PK	PASS
	V	2485.50	47.63	30.22	4.85	27.40	49.66	74.00	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6.POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidance v 05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX b Mode		

Frequency	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-10.51	8	PASS
2437 MHz	-11.16	8	PASS
2462 MHz	-10.45	8	PASS

TX CH01



TX CH06



TX CH11

Temperature：	26℃	Relative Humidity：	54%
Pressure：	101kPa	Test Voltage：	AC 120V/60Hz
Test Mode ：	TX g Mode		

Frequency	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-16.75	8	PASS
2437 MHz	-17.86	8	PASS
2462 MHz	-17.95	8	PASS

TX CH01



TX CH06



TX CH11



Temperature：	26℃	Relative Humidity：	54%
Pressure：	101kPa	Test Voltage：	AC 120V/60Hz
Test Mode ：	TX n Mode(20M)		

Frequency	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-16.93	8	PASS
2437 MHz	-18.00	8	PASS
2462 MHz	-19.05	8	PASS

TX CH01



TX CH06

TX CH11



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX n Mode(40M)		

Frequency	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2422 MHz	-19.22	8	PASS
2437 MHz	-19.76	8	PASS
2452 MHz	-20.36	8	PASS

TX CH03



TX CH06



TX CH09



7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode		

	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
802.11b	2412	9.120	>500	Pass
	2437	9.520	>500	Pass
	2462	9.080	>500	Pass
802.11g	2412	15.680	>500	Pass
	2437	15.720	>500	Pass
	2462	16.040	>500	Pass
802.11n20	2412	16.120	>500	Pass
	2437	16.120	>500	Pass
	2462	16.480	>500	Pass
802.11n40	2422	35.040	>500	Pass
	2437	35.120	>500	Pass
	2452	35.520	>500	Pass

Test plot as follows:

802.11b

802.11g

Lowest channel

Middle channel

Highest channel



802.11n20 801.11n40

Lowest channel



Middle channel



Highest channel