



Certificate #2343.01

TEST REPORT N°: DOE-ESH-P25111761B-2

FCC Test Report

Applicant:	Pro Design, LLC
Address:	1151 Campus Dr.Stow, 0H 44224
Manufacturer:	Pro Design, LLC
Address:	1151 Campus Dr.Stow, 0H 44224
Factory:	Ningbo Dooya Mechanic & Electronic Technology Co., Ltd
Address:	No. 168 Shengguang Road, Luotuo, Zhenhai, Ningbo, China
This document includes 35 pages	

Product Name:	Tubular motor	
Test Model:	DM25LEU/S-0.2/16	
Serial Models:	N/A	
Brand Name:	Motoshade	
FCC ID:	2BMF4DM25LEUS0216	
Rated Voltage/Power:	DC 5V	
Received Date:	Nov. 24, 2025	
Test Date:	Dec. 01, 2025 to Dec. 31, 2025	
Applicable Standards:	47 CFR Part 15 Subpart C, § 15.231 ANSI C63.10-2020	
Clause Examined:	All Clauses Relevant	

CONCLUSION : The submitted sample was found to COMPLY with the test requirement.**Test done by:***Ghost Li*Name: Ghost Li
Title: Project Engineer
Date: Jan. 05, 2026**Approved by:***Sean Yu*Name: Sean YU
Title: RF Supervisor
Date: Jan. 05, 2026

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TEST REPORT N°: DOE-ESH-P25111761B-2

Table of Contents

Release Control Record	4
1 Summary of Test Results	5
1.1 Test Instruments	6
1.2 Measurement Uncertainty	7
1.3 Modification Record	7
2 General Information	8
2.1 General Description of EUT	8
2.2 Description of Test Modes	9
2.2.1 Test Mode Applicability:	10
2.2.2 Test Condition:	11
2.3 Description of Support Units	11
2.4 General Description of Applied Standards	12
3 Test Procedure and Results	13
3.1 AC Power Conducted Emission	13
3.1.1 Limits	13
3.1.2 Test Procedures	13
3.1.3 Deviation from Test Standard	13
3.1.4 Test Setup	14
3.1.5 EUT Operating Conditions	14
3.1.6 Test Results	15
3.2 20dB Spectrum Bandwidth Measurement	17
3.2.1 Limit	17
3.2.2 Test Setup	17
3.2.3 Test Procedures	17
3.2.4 Deviation of Test Standard	17
3.2.5 Test Results	18
3.3 Dwell Time Measurement	19
3.3.1 Limit	19
3.3.2 Test Setup	19
3.3.3 Test Procedures	19
3.3.4 Deviation of Test Standard	19
3.3.5 Test Results	20



TEST REPORT N°: DOE-ESH-P25111761B-2

3.4 Field Strength of Fundamental Emissions and Mask Measurement	22
3.4.1 Test Limit	22
3.4.2 Test Setup	22
3.4.3 Test Results	23
3.5 Radiated Emissions Measurement	24
3.5.1 Test Procedure Reference	25
3.5.2 Test Procedures	25
3.5.3 Deviation from Test Standard	26
3.5.4 Test Setup	27
3.5.5 Test Results	28
4 Pictures of Test Arrangements	33



TEST REPORT N°: DOE-ESH-P25111761B-2

Release Control Record

Issue No.	Description	Date Issued
DOE-ESH-P25111761B-2	Original release	Jan. 05, 2026



TEST REPORT N°: DOE-ESH-P25111761B-2

1 Summary of Test Results

The EUT has been tested according to the following specifications:

47 CFR FCC Part 15, Subpart C			
FCC Clause	Test Item	Result	Remarks
15.203	Antenna Requirement	PASS	No antenna connector is used.
15.207	AC Power Conducted Emission	NA	The EUT is powered by battery.
15.231(c)	20dB Spectrum Bandwidth	PASS	Meet the requirement of limit.
15.231(a)	Dwell Time	PASS	Meet the requirement of limit.
15.231(e)	Field Strength of Fundamental Emissions	PASS	Meet the requirement of limit.
15.225 / 15.209 /	Radiated Emissions Measurement	PASS	Meet the requirement of limit.



TEST REPORT N°: DOE-ESH-P25111761B-2

1.1 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Loop Antenna	ETS-LINDGRE N	6502	SN0021581 7	Jul.30, 25	Jul.29, 26
Hybrid Antenna(25MHz-1.5GHz)	Schwarzbeck	VULB9168	E1A1012	Jul.29, 25	Jul.28, 26
Horn Antenna(1GHz -18GHz)	Schwarzbeck	BBHA9120D	E1A1017	Aug.25, 25	Aug.24, 26
Double Ridge Horn Antenna(18G-40G)	COM-POWER	AH-840	E1A1040	Jul.15, 25	Jul.14, 26
Pre-Amplifier(100kHz-1.3GHz)	Agilent	8447D	E1A2001	Apr.19, 25	Apr.18, 26
Pre-Amplifier(0.5GHz-18GHz)	EMCI	EMC184045SE	E1A2009	Jul.05, 25	Jul.04, 26
Pre-Amplifier(18GHz-40GHz)	EMCI	EMC051845SE	E1A2008	Jul.05, 25	Jul.04, 26
EMI test receiver	R&S	ESR7	E1R1005	Apr.19, 25	Apr.18, 26
Spectrum Analyzer	Keysight	N9030B	E1S1003	Jul.22, 25	Jul.21, 26
Spectrum Analyzer	Keysight	N9020A	E1S1004	Mar.02, 25	Mar.01, 26
EMI test receiver	R&S	ESCS30	E1R1001	May.11, 25	May.10, 26
LISN	R&S	ENV216	E1L1011	May.11, 25	May.10, 26
Humidity&Temp Tester	Baolima	WS508	E1H1011	Apr. 02, 25	Apr. 01, 26
RF Control Unit	Toscend	JS0806-2	E1C5003	N/A	N/A
Test Software	ADT	ADT_COND_V7 .3.1	N/A	N/A	N/A
Test Software	Toscend	JS32-RE	N/A	N/A	N/A
Test Software	Toscend	JS1120	N/A	N/A	N/A
Test Software	Toscend	JS1120-3	N/A	N/A	N/A



TEST REPORT N°: DOE-ESH-P25111761B-2

1.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Expanded Uncertainty ($k=2$) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.36 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.47 dB
	6GHz ~ 18GHz	3.75 dB
	18GHz ~ 40GHz	3.30 dB

1.3 Modification Record

There were no modifications required for compliance.



TEST REPORT N°: DOE-ESH-P25111761B-2

2 General Information

2.1 General Description of EUT

Product	Tubular motor
Brand	Motoshade
Test Model	DM25LEU/S-0.2/16
Power Rating	DC 5V
Modulation Type	ASK
Operating Frequency	433.92MHz
Number of Channel	1
Antenna Type	External Antenna
Antenna Connector	--

Note:

1. For more details, please refer to the User's manual of the EUT.



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

2.2 Description of Test Modes

CHANNEL	FREQUENCY	MODULATION TYPE
1	433.92 MHz	ASK



TEST REPORT N°: DOE-ESH-P25111761B-2

2.2.1 Test Mode Applicability:

EUT Configure Mode	Applicable to					Description
	RE (9 kHz~30MHz)	RE (30MHz~1GHz)	PLC	BW	DW	
-	√	√	-	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz **RE< 1G**: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission **BW**: 20dB Spectrum Bandwidth

DW: Dwell Time

NOTE:

Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

Radiated Emission Test RE (9 kHz~30MHz):

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	TX	433.92 MHz	433.92 MHz	ASK

Radiated Emission Test RE (30MHz~1GHz):

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	TX	433.92 MHz	433.92 MHz	ASK

Power Line Conducted Emission Test:

☐ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	TX	433.92 MHz	433.92 MHz	ASK



TEST REPORT N°: DOE-ESH-P25111761B-2

20dB Spectrum Bandwidth

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	TX	433.92 MHz	433.92 MHz	ASK

Dwell Time

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	TX	433.92 MHz	433.92 MHz	ASK

2.2.2 Test Condition:

Applicable to	Normal Environmental Conditions	Normal Input Power
RE (9 kHz~30MHz)	23deg. C, 58%RH	Battery
RE (30MHz~1GHz)	23deg. C, 58%RH	Battery
PLC	--	Battery
BW	25deg. C, 60%RH	Battery
DW	25deg. C, 60%RH	Battery

2.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.



TEST REPORT N°: DOE-ESH-P25111761B-2

2.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

47 CFR Part 15 Subpart C, § 15.231

ANSI C63.10-2020

All relaxed test items have been performed and recorded as per the above standard.



TEST REPORT N°: DOE-ESH-P25111761B-2

3 Test Procedure and Results

3.1 AC Power Conducted Emission

3.1.1 Limits

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.2 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

3.1.3 Deviation from Test Standard

No deviation.

3.1.4 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.5 EUT Operating Conditions

Same as 3.1.6.




LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

3.1.6 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Power supply	AC 120V, 60Hz		
Test Mode	Charging and Working		



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]
1	0.17	19.77	16.89	36.66	64.84	28.18	3.88	23.65	54.84	31.19
2	0.54	19.58	24.58	44.16	56.00	11.84	11.58	31.16	46.00	14.84
3	1.50	19.58	17.92	37.50	56.00	18.50	4.74	24.32	46.00	21.68
4	2.87	19.73	15.45	35.18	56.00	20.82	2.42	22.15	46.00	23.85
5	4.55	19.70	14.70	34.40	56.00	21.60	1.64	21.34	46.00	24.66
6	5.89	19.72	14.85	34.57	60.00	25.43	1.97	21.69	50.00	28.31

REMARKS:


1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Power supply	AC 120V, 60Hz		
Test Mode	Charging and Working		



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading [dBuV]	QP Value [dBuV]	QP Limit [dBuV]	QP Margin [dB]	AV Reading [dBuV]	AV Value [dBuV]	AV Limit [dBuV]	AV Margin [dB]
1	0.18	19.74	18.73	38.47	64.63	26.16	8.50	28.24	54.63	26.39
2	0.54	19.54	28.03	47.57	56.00	8.43	17.50	37.04	46.00	8.96
3	1.14	19.53	20.12	39.65	56.00	16.35	8.53	28.06	46.00	17.94
4	2.75	19.76	17.08	36.84	56.00	19.16	6.50	26.26	46.00	19.74
5	4.64	19.72	16.35	36.07	56.00	19.93	5.74	25.46	46.00	20.54
6	10.09	19.96	16.80	36.76	60.00	23.24	6.53	26.49	50.00	23.51

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss




TEST REPORT N°: DOE-ESH-P25111761B-2

3.2 20dB Spectrum Bandwidth Measurement

3.2.1 Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

3.2.2 Test Setup



3.2.3 Test Procedures

1. The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were used.
2. EUT in peak Max hold mode.
3. Measured the spectrum width with power higher than 20dB below carrier.

3.2.4 Deviation of Test Standard

No deviation.



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

3.2.5 Test Results

Center Frequency (MHz)	20dB bandwidth (kHz)	Limit(MHz)	Result
433.92	82.2	1084.80	Pass




TEST REPORT N°: DOE-ESH-P25111761B-2

3.3 Dwell Time Measurement

3.3.1 Limit

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

3.3.2 Test Setup



3.3.3 Test Procedures

1. The resolution bandwidth of 1 MHz and the video bandwidth of 1 MHz were used.
2. EUT in peak Max hold mode.
3. Measured the spectrum width with power higher than 20dB below carrier.

3.3.4 Deviation of Test Standard

No deviation.




LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

3.3.5 Test Results

Frequency(MHz)	Transmission Time(s)	Limit(s)	Results
433.92	0.006	≤5	Pass





Transmission Time(ms)	Total Time(ms)	Duty Cycle(%)	Duty Cycle Factory(dB)
5.60	100	5.60	-25.04

[illegible]

TEST REPORT N°: DOE-ESH-P25111761B-2

3.4 Field Strength of Fundamental Emissions and Mask Measurement


3.4.1 Test Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.231	
Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

¹ Linear interpolations.

3.4.2 Test Setup

For Radiated emission 30MHz to 1GHz




TEST REPORT N°: DOE-ESH-P25111761B-2

3.4.3 Test Results

Position: Horizontal


Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Duty Cycle Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
433.92	98.68	-5.47	-	93.21	100.82	7.61	H	PK
433.92	-	-	-25.04	68.17	80.82	18.93	H	AV



◆ QP Detector

Position: Vertical

Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Duty Cycle Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
433.92	89.61	-5.47	-	84.14	100.82	16.68	V	PK
433.92	-	-	-25.04	59.10	80.82	28.00	V	AV



◆ QP Detector

Margin [dB] = Limit [dBμV/m] – Level [dBμV/m]



TEST REPORT N°: DOE-ESH-P25111761B-2

3.5 Radiated Emissions Measurement

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
1 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(2)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.



TEST REPORT N°: DOE-ESH-P25111761B-2

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.1 Test Procedure Reference

ANSI C63.10 Section 6.3 (General Requirements)

3.5.2 Test Procedures

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

Receiver Parameter	Setting
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

For Radiated emission below 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degree to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotate table was turned from 0 degree to 360 degree to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



TEST REPORT N°: DOE-ESH-P25111761B-2

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

3.5.3 Deviation from Test Standard

No deviation.




LCIE


TEST REPORT N°: DOE-ESH-P25111761B-2

3.5.4 Test Setup

For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).



TEST REPORT N°: DOE-ESH-P25111761B-2

3.5.5 Test Results

Radiated Emissions Range 9kHz~30MHz


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

Radiated Emissions Range 30MHz~1GHz



Suspected Data List

NO.	Freq. [MHz]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detector	Height [cm]	Angle[°]	Polarity
1	52.31	-10.35	38.26	40.00	1.74	PK	200	131	Horizontal
2	62.20	-10.87	31.12	40.00	8.88	PK	200	29	Horizontal
3	65.50	-11.35	25.14	40.00	14.86	PK	200	40	Horizontal
4	90.53	-15.46	38.04	43.50	5.46	PK	200	36	Horizontal
5	158.62	-9.70	29.43	43.50	14.07	PK	200	163	Horizontal
6	198.00	-12.58	28.67	43.50	14.83	PK	200	40	Horizontal

Final Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Value [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detector	Height [cm]	Angle[°]	Polarity
1	52.64	22.71	-10.35	12.36	40.00	27.64	QP	121.1	174.6	Horizontal
2	90.41	22.40	-15.46	6.94	43.50	36.56	QP	178.3	128.5	Horizontal


REMARKS:

1. Emission Level(dBuV/m) = Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2



Suspected Data List

NO.	Freq. [MHz]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detector	Height [cm]	Angle[°]	Polarity
1	46.88	-10.60	33.48	40.00	6.52	PK	100	163	Vertical
2	62.20	-10.87	29.62	40.00	10.38	PK	200	35	Vertical
3	67.83	-11.75	28.61	40.00	11.39	PK	100	128	Vertical
4	98.68	-15.17	27.17	43.50	16.33	PK	200	35	Vertical
5	149.89	-9.59	31.31	43.50	12.19	PK	200	142	Vertical
6	250.00	-10.13	23.65	46.00	22.35	PK	100	128	Vertical

REMARKS:


1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

Radiated Emission Range above 1GHz



Suspected List										
NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detector	Height [cm]	Angle [°]	Polarity
1	1334.90	48.03	-14.04	33.99	74.00	40.01	PK	100	354	Horizontal
2	2118.60	46.33	-11.54	34.79	74.00	39.21	PK	200	180	Horizontal
3	3578.90	43.57	-6.90	36.67	74.00	37.33	PK	200	359	Horizontal
4	6977.20	39.74	2.33	42.07	74.00	31.93	PK	200	301	Horizontal
5	10758.00	36.87	10.54	47.41	74.00	26.59	PK	200	20	Horizontal
6	14620.40	35.35	14.75	50.10	74.00	23.90	PK	200	262	Horizontal
7	1348.50	40.22	-13.96	26.26	54.00	27.74	AV	200	70	Horizontal
8	2166.20	38.20	-10.82	27.38	54.00	26.62	AV	200	341	Horizontal
9	3733.60	35.75	-6.05	29.70	54.00	24.30	AV	100	76	Horizontal
10	7181.20	32.31	3.91	36.22	54.00	17.78	AV	100	332	Horizontal
11	10914.40	28.87	10.88	39.75	54.00	14.25	AV	100	317	Horizontal
12	14589.80	27.31	14.41	41.72	54.00	12.28	AV	100	229	Horizontal


REMARKS:

- Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Factor(dB/m)
- Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Limit value – Emission Level



LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2



Suspected List										
NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detector	Height [cm]	Angle [°]	Polarity
1	2178.10	46.07	-10.61	35.46	74.00	38.54	PK	200	354	Vertical
2	2783.30	45.02	-9.40	35.62	74.00	38.38	PK	100	35	Vertical
3	5018.80	42.20	-2.17	40.03	74.00	33.97	PK	100	1	Vertical
4	7172.70	40.86	3.82	44.68	74.00	29.32	PK	100	57	Vertical
5	9595.20	36.72	9.99	46.71	74.00	27.29	PK	200	347	Vertical
6	14367.10	35.86	14.16	50.02	74.00	23.98	PK	200	340	Vertical
7	2166.20	38.33	-10.82	27.51	54.00	26.49	AV	100	262	Vertical
8	2873.40	37.47	-8.85	28.62	54.00	25.38	AV	100	35	Vertical
9	5020.50	33.94	-2.17	31.77	54.00	22.23	AV	100	79	Vertical
10	7194.80	31.66	4.06	35.72	54.00	18.28	AV	200	119	Vertical
11	10263.30	28.64	10.68	39.32	54.00	14.68	AV	100	29	Vertical
12	14593.20	27.41	14.48	41.89	54.00	12.11	AV	200	61	Vertical


REMARKS:

- Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Factor(dB/m)
- Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Limit value – Emission Level

TEST REPORT N°: DOE-ESH-P25111761B-2

4 Pictures of Test Arrangements

AC Power Line Conducted Emission






LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

Radiated Spurious Emission Below 1 GHz






LCIE

TEST REPORT N°: DOE-ESH-P25111761B-2

Radiated Spurious Emission Above 1 GHz



--- END ---