

RF EXPOSURE EVALUATION

According to FCC 1.1310 and KDB 447498 D01 V06, The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

2.4G WIFI

Operation Frequency:

WIFI 802.11b/g/n HT20: 2412-2462MHz,

WIFI 802.11n HT40:2422-2452MHz

Power density limited: 1mW/ cm²

Antenna Type: FPC antenna

Antenna1 gain/Antenna2 gain: 1.95 dBi;

R=20cm

mW=10^{^(dBm/10)}

Antenna gain Numeric=10^{^(dBi/10)}

Antenna	Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
			(dBm)		tune-up power		Gain			
					(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
Ant 2	2412	802.11b	15.69	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 2	2437		14.83	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 2	2462		14.73	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 1	2412	802.11g	14.51	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 1	2437		15.25	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 1	2462		14.89	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 1&2	2412	802.11n H20	16.21	16±1	17	50.119	1.95	1.57	0.0156	1
Ant 1&2	2437		14.8	14±1	15	31.623	1.95	1.57	0.0099	1
Ant 1&2	2462		14.43	14±1	15	31.623	1.95	1.57	0.0099	1
Ant 1&2	2422	802.11n H40	15.91	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 1&2	2437		15.31	15±1	16	39.811	1.95	1.57	0.0124	1
Ant 1&2	2452		15.15	15±1	16	39.811	1.95	1.57	0.0124	1

Signature:

Date: 2025-11-13



NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China