Radio Test Report

Report No.:STS2412005W01

Issued for

Genea Biomedx Pty Ltd

Level 2, 321 Kent Street, Sydney, New South Wales, 2000, Australia

Product Name:	Gelida 47
Brand Name:	N/A
Model Name:	GELI-01-US
Series Model(s):	GELI-02-US, GELI-01-CE, GELI-02-CE, GELI-01-RUO, GELI-02-RUO, GELI-01-DEMO, GELI-02-DEMO
FCC ID:	2BMMAGELI-01-US
Test Standards:	FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

TEST REPORT

Applicant's Name .....: Genea Biomedx Pty Ltd

Address .....: Level 2, 321 Kent Street, Sydney, New South Wales, 2000, Australia

Manufacturer's Name.....: Genea Biomedx Pty Ltd

Address .....: Level 2, 321 Kent Street, Sydney, New South Wales, 2000, Australia

Product Description

Product Name.....: Gelida 47

Brand Name.....: N/A

Model Name .....: .. GELI-01-US

Series Model(s) .....: GELI-02-US, GELI-01-CE, GELI-02-CE, GELI-01-RUO, GELI-02-RUO, GELI-01-DEMO, GELI-02-DEMO

Test Standards .....: FCC Part 15.247

Test Procedure.....: ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test .....:

Date of receipt of test item.....: 02 Dec. 2024

Date (s) of performance of tests .....: 02 Dec. 2024 ~ 20 Dec. 2024

Date of Issue .....: 20 Dec. 2024

Test Result.....: **Pass**

Testing Engineer : Aaron Bu

(Aaron Bu)

Technical Manager : Tony Liu

(Tony Liu)

Authorized Signatory : Bovey Yang

(Bovey Yang)

SHENZHEN STS TEST SERVICES CO., LTD. TESTING APPROVAL

Table of Contents Page

1. SUMMARY OF TEST RESULTS 6
1.1 TEST FACTORY 7
1.2 MEASUREMENT UNCERTAINTY 7
2. GENERAL INFORMATION 8
2.1 GENERAL DESCRIPTION OF THE EUT 8
2.2 DESCRIPTION OF THE TEST MODES 10
2.3 TEST SOFTWARE AND POWER LEVEL 10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS 11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS 12
3. EMC EMISSION TEST 13
3.1 CONDUCTED EMISSION MEASUREMENT 13
3.2 RADIATED EMISSION MEASUREMENT 17
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION 30
4.1 LIMIT 30
4.2 TEST PROCEDURE 30
4.3 DEVIATION FROM STANDARD 30
4.4 TEST SETUP 30
4.5 EUT OPERATION CONDITIONS 30
4.6 TEST RESULTS 30
5. POWER SPECTRAL DENSITY TEST 31
5.1 LIMIT 31
5.2 TEST PROCEDURE 31
5.3 DEVIATION FROM STANDARD 31
5.4 TEST SETUP 31
5.5 EUT OPERATION CONDITIONS 31
5.6 TEST RESULTS 31
6. BANDWIDTH TEST 32
6.1 LIMIT 32
6.2 TEST PROCEDURE 32
6.3 DEVIATION FROM STANDARD 32
6.4 TEST SETUP 32
6.5 EUT OPERATION CONDITIONS 32

Table of Contents Page

6.6 TEST RESULTS 32
7. PEAK OUTPUT POWER TEST 33
7.1 LIMIT 33
7.2 TEST PROCEDURE 33
7.3 DEVIATION FROM STANDARD 33
7.4 TEST SETUP 34
7.5 EUT OPERATION CONDITIONS 34
7.6 TEST RESULTS 34
8. ANTENNA REQUIREMENT 35
8.1 STANDARD REQUIREMENT 35
8.2 EUT ANTENNA 35
APPENDIX 1-TEST DATA 36
1. DUTY CYCLE 36
2. MAXIMUM AVERAGE CONDUCTED OUTPUT POWER 42
3. MAXIMUM PEAK CONDUCTED OUTPUT POWER 48
4. -6DB BANDWIDTH 49
5. MAXIMUM POWER SPECTRAL DENSITY LEVEL 55
6. BAND EDGE 61
7. CONDUCTED RF SPURIOUS EMISSION 68
8. OCCUPIED CHANNEL BANDWIDTH 78
APPENDIX 2-PHOTOS OF TEST SETUP 80

Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	20 Dec. 2024	STS2412005W01	ALL	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) ‘N/A’ denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2020.

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD
Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	±0.755dB
2	Unwanted Emissions, conducted	±2.874dB
3	All emissions, radiated 9K-30MHz	±3.80dB
4	All emissions, radiated 30M-1GHz	±4.18dB
5	All emissions, radiated 1G-6GHz	±4.90dB
6	All emissions, radiated>6G	±5.24dB
7	Conducted Emission (9KHz-150KHz)	±2.19dB
8	Conducted Emission (150KHz-30MHz)	±2.53dB
9	Occupied Channel Bandwidth	±3.5%
10	Power Spectral Density, conducted	±1.245dB
11	Duty Cycle	±3.2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

<table>
<tr><td>Product Name</td><td>Gelida 47</td></tr>
<tr><td>Brand Name</td><td>N/A</td></tr>
<tr><td>Model Name</td><td>GELI-01-US</td></tr>
<tr><td>Series Model(s)</td><td>GELI-02-US, GELI-01-CE, GELI-02-CE, GELI-01-RUO, GELI-02-RUO, GELI-01-DEMO, GELI-02-DEMO</td></tr>
<tr><td>Model Difference</td><td>Except for the differences in the labels, bucket/basket styles, and quantities, the other parts of the 8 models are the same.</td></tr>
<tr><td>Product Description</td><td>The EUT is a Gelida 47
<table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n 20: 2412~2462 MHz</td></tr>
<tr><td>Modulation Type:</td><td>802.11b(DSSS):CCK,DQPSK,DBPSK
802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM
802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM</td></tr>
<tr><td>Bit Rate of Transmitter:</td><td>802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n(20MHz):
65/58.5/52/39/26/19.5/13/6.5Mbps</td></tr>
<tr><td>Number of Channel:</td><td>802.11b/g/n20: 11CH</td></tr>
<tr><td>Antenna Type:</td><td>PCB</td></tr>
<tr><td>Antenna Gain:</td><td>2dBi</td></tr>
</table></td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 3.</td></tr>
<tr><td>Power Rating</td><td>N/A</td></tr>
<tr><td>Adapter</td><td>Input: 100-240V~50/60Hz,0.5A
Output:5.0V⎓3.0A.15.0W</td></tr>
<tr><td>Battery</td><td>Rated Voltage:3.7V
Charge Limit Voltage:5V
Capacity: 9.5Ah/35.15Wh</td></tr>
<tr><td>Hardware version number</td><td>004-YDG-MB01-V1.0</td></tr>
<tr><td>Software version number</td><td>V1.0.0.0</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the Note 1.</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.

3.

Operation Frequency of channel	
802.11b/g/n(20MHz)	
Channel	Frequency
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, themiddle frequency, and the highest frequency of channel were selected to perform the test, and the selectedchannel see below:
Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n (HT20)	
Channel	Freq.(MHz)
01	2412
06	2437
11	2462

2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0

Note:
(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V /60Hz is shown in the report.
(3) The battery is fully-charged during the radited and RF conducted test.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode10: Keeping WIFI TX

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(2.4G)	2.4G WIFI	802.11b	2	0	EspRFTestTool_v3.6_Manual
		802.11g		4	
		802.11n(HT20)		4	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiation Test Set



Conduction Test Set



2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Personal computer	DELL	Inspiron 3501	N/A
E-2	Adapter	ZTC	NB-A515A	N/A
C-1	Serial port board	XES	WTYZK	N/A
C-2	USB Cable	ZTC	NB-A515A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-2	Shielded	NO	150cm	N/A

Note:

(1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(2) “YES” is means “with core”; “NO” is means “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2024.03.15	2025.03.14
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2024.02.23	2025.02.22
Pre-Amplifier(1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2024.09.23	2025.09.22
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2024.02.23	2025.02.22
Active loop Antenna	ZHINAN	ZN30900C	16035	2023.02.28	2025.02.27
Bilog Antenna	TESEQ	CBL6111D	34678	2024.09.30	2025.09.29
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2023.09.24	2025.09.23
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2023.10.10	2025.10.09
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2024.09.23	2025.09.22
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENGFENG	DPS-305AF	17064939	2024.09.23	2025.09.22
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2024.09.24	2025.09.23
Limtter	CYBERTEK	EM5010	N/A	2024.09.24	2025.09.23
LISN	R&S	ENV216	101242	2024.09.24	2025.09.23
LISN	EMCO	3810/2NM	23625	2024.09.24	2025.09.23
Temperature & Humidity	SW-108	SuWei	N/A	2024.03.15	2025.03.14
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2024.02.23	2025.02.22
Power Sensor	Keysight	U2021XA	MY56120038	2024.09.23	2025.09.22
Temperature & Humidity	SW-108	SuWei	N/A	2024.03.15	2025.03.14
Test SW	MW	MTS 8310_2.0.0.0			

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	**Setting**
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed Less than or equal to 0.15m from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang Less than or equal to 0.15m to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



3.1.4EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.5 TEST RESULT

Temperature:	25.1℃	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 10		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	30.95	19.78	50.73	66.00	-15.27	QP
2	0.1500	15.25	19.78	35.03	56.00	-20.97	AVG
3	0.2140	21.15	19.83	40.98	63.05	-22.07	QP
4	0.2140	7.64	19.83	27.47	53.05	-25.58	AVG
5	0.3820	11.71	20.05	31.76	58.24	-26.48	QP
6	0.3820	2.74	20.05	22.79	48.24	-25.45	AVG
7	0.7860	7.63	19.81	27.44	56.00	-28.56	QP
8	0.7860	-2.94	19.81	16.87	46.00	-29.13	AVG
9	1.7180	9.00	19.79	28.79	56.00	-27.21	QP
10	1.7180	-2.40	19.79	17.39	46.00	-28.61	AVG
11	3.1580	7.16	19.83	26.99	56.00	-29.01	QP
12	3.1580	-3.04	19.83	16.79	46.00	-29.21	AVG

Remark:
1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)



Temperature:	25.1℃	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	33.60	19.78	53.38	66.00	-12.62	QP
2	0.1500	15.22	19.78	35.00	56.00	-21.00	AVG
3	0.2220	22.79	19.87	42.66	62.74	-20.08	QP
4	0.2220	7.68	19.87	27.55	52.74	-25.19	AVG
5	0.3140	17.65	20.19	37.84	59.86	-22.02	QP
6	0.3140	5.22	20.19	25.41	49.86	-24.45	AVG
7	0.4900	8.22	20.01	28.23	56.17	-27.94	QP
8	0.4900	-2.59	20.01	17.42	46.17	-28.75	AVG
9	0.9700	7.77	19.78	27.55	56.00	-28.45	QP
10	0.9700	-3.38	19.78	16.40	46.00	-29.60	AVG
11	2.9020	8.58	19.83	28.41	56.00	-27.59	QP
12	2.9020	-2.05	19.83	17.78	46.00	-28.22	AVG

Remark:
1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)



3.2 RADIATED EMISSION MEASUREMENT

3.2.1RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2430 MHz Upper Band Edge: 2445 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
b. The EUT was placed on the top of a rotating table Less than or equal to 0.15 meter above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting theAmplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

Factor=AF+CL-AG

3.2.6 TEST RESULT

9KHz-30MHz

Temperature:	23.4℃	Relative Humidtity:	60%
Test Voltage:	DC 3.7V From Battery	Polarization:	--
Test Mode:	TX Mode		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F	Test Result
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

(30MHz - 1000MHz)

Temperature:	23.4℃	Relative Humidtity:	60%
Test Voltage:	DC 3.7V From Battery	Phase:	Horizontal
Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 6 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	79.4700	51.27	-23.11	28.16	40.00	-11.84	peak
2	119.2400	52.33	-18.38	33.95	43.50	-9.55	peak
3	159.9800	54.76	-18.81	35.95	43.50	-7.55	peak
4	198.7800	57.53	-21.12	36.41	43.50	-7.09	peak
5	320.0300	51.40	-14.00	37.40	46.00	-8.60	peak
6	480.0800	48.30	-8.65	39.65	46.00	-6.35	peak

Remark:
1. Margin = Result (Result =Reading + Factor)–Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.



Temperature:	23.4℃	Relative Humidtity:	60%
Test Voltage:	DC 3.7V From Battery	Phase:	Vertical
Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 6 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	47.30	-15.91	31.39	40.00	-8.61	peak
2	79.4700	52.36	-23.11	29.25	40.00	-10.75	peak
3	119.2400	54.80	-18.38	36.42	43.50	-7.08	peak
4	159.9800	56.44	-18.81	37.63	43.50	-5.87	peak
5	198.7800	54.43	-21.12	33.31	43.50	-10.19	peak
6	480.0800	46.42	-8.65	37.77	46.00	-8.23	peak

Remark:.
1. Margin = Result (Result =Reading + Factor)–Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.



(1000MHz-25GHz) Spurious emission Requirements

Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (802.11g/2412 MHz)										
3264.82	62.20	44.70	6.70	28.20	-9.80	52.40	74.00	-21.60	PK	Vertical
3264.82	49.90	44.70	6.70	28.20	-9.80	40.10	54.00	-13.90	AV	Vertical
3264.79	60.93	44.70	6.70	28.20	-9.80	51.13	74.00	-22.87	PK	Horizontal
3264.79	50.04	44.70	6.70	28.20	-9.80	40.24	54.00	-13.76	AV	Horizontal
4824.36	58.88	44.20	9.04	31.60	-3.56	55.32	74.00	-18.68	PK	Vertical
4824.36	49.22	44.20	9.04	31.60	-3.56	45.66	54.00	-8.34	AV	Vertical
4824.59	58.40	44.20	9.04	31.60	-3.56	54.84	74.00	-19.16	PK	Horizontal
4824.59	49.27	44.20	9.04	31.60	-3.56	45.71	54.00	-8.29	AV	Horizontal
5359.70	48.09	44.20	9.86	32.00	-2.34	45.74	74.00	-28.26	PK	Vertical
5359.70	40.17	44.20	9.86	32.00	-2.34	37.83	54.00	-16.17	AV	Vertical
5359.85	47.74	44.20	9.86	32.00	-2.34	45.39	74.00	-28.61	PK	Horizontal
5359.85	39.53	44.20	9.86	32.00	-2.34	37.18	54.00	-16.82	AV	Horizontal
7235.74	54.20	43.50	11.40	35.50	3.40	57.60	74.00	-16.40	PK	Vertical
7235.74	44.43	43.50	11.40	35.50	3.40	47.83	54.00	-6.17	AV	Vertical
7235.71	54.35	43.50	11.40	35.50	3.40	57.75	74.00	-16.25	PK	Horizontal
7235.71	44.04	43.50	11.40	35.50	3.40	47.44	54.00	-6.56	AV	Horizontal
Middle Channel (802.11g/2437 MHz)										
3264.72	61.86	44.70	6.70	28.20	-9.80	52.06	74.00	-21.94	PK	Vertical
3264.72	49.87	44.70	6.70	28.20	-9.80	40.07	54.00	-13.93	AV	Vertical
3264.60	61.92	44.70	6.70	28.20	-9.80	52.12	74.00	-21.88	PK	Horizontal
3264.60	49.97	44.70	6.70	28.20	-9.80	40.17	54.00	-13.83	AV	Horizontal
4874.54	58.60	44.20	9.04	31.60	-3.56	55.04	74.00	-18.96	PK	Vertical
4874.54	50.08	44.20	9.04	31.60	-3.56	46.52	54.00	-7.48	AV	Vertical
4874.42	58.84	44.20	9.04	31.60	-3.56	55.28	74.00	-18.72	PK	Horizontal
4874.42	49.15	44.20	9.04	31.60	-3.56	45.59	54.00	-8.41	AV	Horizontal
5359.77	49.14	44.20	9.86	32.00	-2.34	46.80	74.00	-27.20	PK	Vertical
5359.77	39.97	44.20	9.86	32.00	-2.34	37.63	54.00	-16.37	AV	Vertical
5359.61	47.78	44.20	9.86	32.00	-2.34	45.43	74.00	-28.57	PK	Horizontal
5359.61	39.41	44.20	9.86	32.00	-2.34	37.06	54.00	-16.94	AV	Horizontal
7310.83	54.33	43.50	11.40	35.50	3.40	57.73	74.00	-16.27	PK	Vertical
7310.83	44.84	43.50	11.40	35.50	3.40	48.24	54.00	-5.76	AV	Vertical
7310.66	53.66	43.50	11.40	35.50	3.40	57.06	74.00	-16.94	PK	Horizontal
7310.66	44.45	43.50	11.40	35.50	3.40	47.85	54.00	-6.15	AV	Horizontal

High Channel (802.11g/2462 MHz)										
3264.74	61.83	44.70	6.70	28.20	-9.80	52.03	74.00	-21.97	PK	Vertical
3264.74	51.50	44.70	6.70	28.20	-9.80	41.70	54.00	-12.30	AV	Vertical
3264.73	61.12	44.70	6.70	28.20	-9.80	51.32	74.00	-22.68	PK	Horizontal
3264.73	51.06	44.70	6.70	28.20	-9.80	41.26	54.00	-12.74	AV	Horizontal
4924.42	59.49	44.20	9.04	31.60	-3.56	55.93	74.00	-18.07	PK	Vertical
4924.42	49.61	44.20	9.04	31.60	-3.56	46.05	54.00	-7.95	AV	Vertical
4924.45	58.54	44.20	9.04	31.60	-3.56	54.98	74.00	-19.02	PK	Horizontal
4924.45	49.91	44.20	9.04	31.60	-3.56	46.35	54.00	-7.65	AV	Horizontal
5359.79	48.56	44.20	9.86	32.00	-2.34	46.21	74.00	-27.79	PK	Vertical
5359.79	39.62	44.20	9.86	32.00	-2.34	37.27	54.00	-16.73	AV	Vertical
5359.83	48.39	44.20	9.86	32.00	-2.34	46.04	74.00	-27.96	PK	Horizontal
5359.83	38.93	44.20	9.86	32.00	-2.34	36.59	54.00	-17.41	AV	Horizontal
7385.80	54.45	43.50	11.40	35.50	3.40	57.85	74.00	-16.15	PK	Vertical
7385.80	44.86	43.50	11.40	35.50	3.40	48.26	54.00	-5.74	AV	Vertical
7385.72	53.99	43.50	11.40	35.50	3.40	57.39	74.00	-16.61	PK	Horizontal
7385.72	44.79	43.50	11.40	35.50	3.40	48.19	54.00	-5.81	AV	Horizontal

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. All modes have been measurement, only worst mode was reported.
   Emission Level = Reading + Factor
   Margin = Emission Level-Limit
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.

3.2.6 TEST RESULTS(Band edge Requirements)

802.11 g-Low

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2382.960	47.04	4.23	51.27	74.00	-22.73	peak
2	2390.000	45.11	4.34	49.45	74.00	-24.55	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2358.840	42.18	3.87	46.05	74.00	-27.95	peak
2	2390.000	40.30	4.34	44.64	74.00	-29.36	peak

802.11 g-High

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	42.79	4.60	47.39	74.00	-26.61	peak
2	2488.130	42.74	4.62	47.36	74.00	-26.64	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	38.95	4.60	43.55	74.00	-30.45	peak
2	2491.740	43.65	4.63	48.28	74.00	-25.72	peak

Note: All modes have been measurement, only worst mode was reported.

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2432 MHz Upper Band Edge: 2442 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP

The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.
Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

4.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

5. POWER SPECTRAL DENSITY TEST

5.1 LIMIT

FCC Part15.247 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤8 dBm (RBW ≥3KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the 100 kHz ≥ RBW ≥3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP

5.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

5.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

6. BANDWIDTH TEST

6.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	≥500KHz (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW≥3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be≥6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP

6.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

6.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

7. PEAK OUTPUT POWER TEST

7.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

One of the following procedures may be used to determine the averaging conducted output powe r of a DTS EUT.
Method AVGSA-2 uses trace averaging across ON and OFF times of the EUT transmissions, foll owed by duty cycle correction. The procedure for this method is as follows:
a) Measure the duty cycle D of the transmitter output signal as described in 11.6.
b) Set span to at least 1.5 times the OBW.
c) Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
d) Set VBW ≥ [3 × RBW].
e) Number of points in sweep ≥ [2 × span / RBW]. (This gives bin-to-bin spacing ≤ RBW / 2, so th at narrowband signals are not lost between frequency bins.)
f) Sweep time = auto.
g) Detector = RMS (i.e., power averaging), if available. Otherwise, use the sample detector mode . h) Do not use sweep triggering. Allow the sweep to “free run.”
i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of trac es to be averaged shall be increased above 100 as needed such that the average accurately re presents the true average over the ON and OFF periods of the transmitter.
j) Compute power by integrating the spectrum across the OBW of the signal using the instrument ’s band power measurement function with band limits set equal to the OBW band edges. If the in strument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
k) Add [10 log (1 / D)], where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average o ver both the ON and OFF times of the transmission). For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is 25%.
Integrated band power method:
The following procedure can be used when the maximum available RBW of the instrument is less than the
DTS bandwidth:
a) Set the RBW = 1 MHz.
b) Set the VBW ≥ [3 × RBW].
c) Set the span ≥ [1.5 × DTS bandwidth].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the instrument’s band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.
PKPM1 Peak power meter method:
The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP

7.5 EUT OPERATION CONDITIONS
Please refer to section 3.1.4 of this report.

7.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible partyshall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PCB Antenna. It comply with the standard requirement.

APPENDIX 1-TEST DATA

1. Duty Cycle

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	92.15	0.36	0.99
NVNT	b	2437	91.98	0.36	0.99
NVNT	b	2462	91.97	0.36	0.99
NVNT	g	2412	94.49	0.25	1.62
NVNT	g	2437	93.63	0.29	1.62
NVNT	g	2462	93.47	0.29	1.62
NVNT	n20	2412	93.29	0.3	1.63
NVNT	n20	2437	93.45	0.29	1.63
NVNT	n20	2462	93.6	0.29	1.63

Test Graphs

Duty Cycle NVNT b 2412MHz



Duty Cycle NVNT b 2437MHz



Duty Cycle NVNT b 2462MHz



Duty Cycle NVNT g 2412MHz



Duty Cycle NVNT g 2437MHz



Duty Cycle NVNT g 2462MHz



Duty Cycle NVNT n20 2412MHz



Duty Cycle NVNT n20 2437MHz



Duty Cycle NVNT n20 2462MHz



2. Maximum Average Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	11.28	0.36	11.64	<=30	Pass
NVNT	b	2437	11.33	0.36	11.69	<=30	Pass
NVNT	b	2462	11.47	0.36	11.83	<=30	Pass
NVNT	g	2412	10.11	0.25	10.36	<=30	Pass
NVNT	g	2437	10.36	0.29	10.65	<=30	Pass
NVNT	g	2462	10.42	0.29	10.71	<=30	Pass
NVNT	n20	2412	9.77	0.3	10.07	<=30	Pass
NVNT	n20	2437	10.15	0.29	10.44	<=30	Pass
NVNT	n20	2462	10.31	0.29	10.6	<=30	Pass

Test Graphs

Average Power NVNT b 2412MHz



Average Power NVNT b 2437MHz



Average Power NVNT b 2462MHz



Average Power NVNT g 2412MHz



Average Power NVNT g 2437MHz



Average Power NVNT g 2462MHz



Average Power NVNT n20 2412MHz



Average Power NVNT n20 2437MHz



Average Power NVNT n20 2462MHz



3. Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	14.92	<=30	Pass
NVNT	b	2437	14.96	<=30	Pass
NVNT	b	2462	15.02	<=30	Pass
NVNT	g	2412	18.22	<=30	Pass
NVNT	g	2437	18.52	<=30	Pass
NVNT	g	2462	18.55	<=30	Pass
NVNT	n20	2412	17.94	<=30	Pass
NVNT	n20	2437	18.34	<=30	Pass
NVNT	n20	2462	18.49	<=30	Pass

4. -6dB Bandwidth

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	10.0689	>=0.5	Pass
NVNT	b	2437	10.0625	>=0.5	Pass
NVNT	b	2462	10.079	>=0.5	Pass
NVNT	g	2412	16.4051	>=0.5	Pass
NVNT	g	2437	16.4023	>=0.5	Pass
NVNT	g	2462	16.3821	>=0.5	Pass
NVNT	n20	2412	17.6528	>=0.5	Pass
NVNT	n20	2437	17.6362	>=0.5	Pass
NVNT	n20	2462	17.6499	>=0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz



-6dB Bandwidth NVNT b 2437MHz



-6dB Bandwidth NVNT b 2462MHz



-6dB Bandwidth NVNT g 2412MHz



-6dB Bandwidth NVNT g 2437MHz



-6dB Bandwidth NVNT g 2462MHz



-6dB Bandwidth NVNT n20 2412MHz



-6dB Bandwidth NVNT n20 2437MHz



-6dB Bandwidth NVNT n20 2462MHz



5. Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	-12.89	<=8	Pass
NVNT	b	2437	-12.54	<=8	Pass
NVNT	b	2462	-12.69	<=8	Pass
NVNT	g	2412	-14.53	<=8	Pass
NVNT	g	2437	-14.09	<=8	Pass
NVNT	g	2462	-14.02	<=8	Pass
NVNT	n20	2412	-16.13	<=8	Pass
NVNT	n20	2437	-16.02	<=8	Pass
NVNT	n20	2462	-15.6	<=8	Pass

Test Graphs

PSD NVNT b 2412MHz



PSD NVNT b 2437MHz



PSD NVNT b 2462MHz



PSD NVNT g 2412MHz



PSD NVNT g 2437MHz



PSD NVNT g 2462MHz



PSD NVNT n20 2412MHz



PSD NVNT n20 2437MHz



PSD NVNT n20 2462MHz



6. Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-38.58	<=-20	Pass
NVNT	b	2462	-42.99	<=-20	Pass
NVNT	g	2412	-26.41	<=-20	Pass
NVNT	g	2462	-43.58	<=-20	Pass
NVNT	n20	2412	-27.4	<=-20	Pass
NVNT	n20	2462	-42.86	<=-20	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ref



Band Edge NVNT b 2412MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.411 0 GHz	(Δ) 2.818 dBm			
2	N	1	f	2.400 0 GHz	-38.048 dBm			
3	N	1	f	2.400 0 GHz	-38.048 dBm			
4	N	1	f	2.398 5 GHz	-36.166 dBm			
5								
6								
7								
8								
9								
10								
11								
12								

Band Edge NVNT b 2462MHz Ref



Band Edge NVNT b 2462MHz Emission



Band Edge NVNT g 2412MHz Ref



Band Edge NVNT g 2412MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.413 2 GHz	(Δ) -0.862 dBm			
2	N	1	f	2.400 0 GHz	-27.314 dBm			
3	N	1	f	2.400 0 GHz	-27.314 dBm			
4	N	1	f	2.400 0 GHz	-27.314 dBm			
5								
6								
7								
8								
9								
10								
11								
12								

Band Edge NVNT g 2462MHz Ref



Band Edge NVNT g 2462MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.463 3 GHz	(Δ) -0.416 dBm			
2	N	1	f	2.483 5 GHz	-44.170 dBm			
3	N	1	f	2.500 0 GHz	-47.432 dBm			
4	N	1	f	2.483 5 GHz	-44.170 dBm			
5								
6								
7								
8								
9								
10								
11								
12								

Band Edge NVNT n20 2412MHz Ref



Band Edge NVNT n20 2412MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.413 3 GHz	(Δ) -0.996 dBm			
2	N	1	f	2.400 0 GHz	-29.166 dBm			
3	N	1	f	2.400 0 GHz	-29.166 dBm			
4	N	1	f	2.399 9 GHz	-28.618 dBm			
5								
6								
7								
8								
9								
10								
11								
12								

Band Edge NVNT n20 2462MHz Ref



Band Edge NVNT n20 2462MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.463 3 GHz	(Δ) -0.443 dBm			
2	N	1	f	2.483 5 GHz	-44.094 dBm			
3	N	1	f	2.500 0 GHz	-46.513 dBm			
4	N	1	f	2.483 8 GHz	-43.863 dBm			
5								
6								
7								
8								
9								
10								
11								
12								

7. Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-48.51	<=-20	Pass
NVNT	b	2437	-47.3	<=-20	Pass
NVNT	b	2462	-47.04	<=-20	Pass
NVNT	g	2412	-46.86	<=-20	Pass
NVNT	g	2437	-46.08	<=-20	Pass
NVNT	g	2462	-46.06	<=-20	Pass
NVNT	n20	2412	-46.1	<=-20	Pass
NVNT	n20	2437	-44.94	<=-20	Pass
NVNT	n20	2462	-46.38	<=-20	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ref



Tx. Spurious NVNT b 2412MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.413 2 GHz	(Δ) 1.159 dBm			
2	N	1	f	9.648 3 GHz	-45.807 dBm			
3	N	1	f	4.823 7 GHz	-49.974 dBm			
4	N	1	f	7.235 1 GHz	-46.675 dBm			
5	N	1	f	9.648 3 GHz	-45.807 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT b 2437MHz Ref



Tx. Spurious NVNT b 2437MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.436 1 GHz	(Δ) 1.982 dBm			
2	N	1	f	7.310 1 GHz	-44.378 dBm			
3	N	1	f	4.874 0 GHz	-47.266 dBm			
4	N	1	f	7.310 1 GHz	-44.378 dBm			
5	N	1	f	9.748 0 GHz	-44.876 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT b 2462MHz Ref



Tx. Spurious NVNT b 2462MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.460 8 GHz	(Δ) 1.953 dBm			
2	N	1	f	4.924 3 GHz	-44.177 dBm			
3	N	1	f	4.924 3 GHz	-44.177 dBm			
4	N	1	f	7.387 8 GHz	-45.531 dBm			
5	N	1	f	9.847 7 GHz	-46.959 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT g 2412MHz Ref



Tx. Spurious NVNT g 2412MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.419 4 GHz	(Δ) -4.415 dBm			
2	N	1	f	24.772 4 GHz	-47.662 dBm			
3	N	1	f	5.016 9 GHz	-56.699 dBm			
4	N	1	f	7.236 0 GHz	-49.694 dBm			
5	N	1	f	9.648 3 GHz	-54.029 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT g 2437MHz Ref



Tx. Spurious NVNT g 2437MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.442 3 GHz	(Δ) -1.362 dBm			
2	N	1	f	25.295 6 GHz	-47.158 dBm			
3	N	1	f	4.875 8 GHz	-56.912 dBm			
4	N	1	f	7.311 9 GHz	-48.100 dBm			
5	N	1	f	9.749 8 GHz	-54.947 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT g 2462MHz Ref



Tx. Spurious NVNT g 2462MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.466 1 GHz	(Δ) -1.334 dBm			
2	N	1	f	25.771 2 GHz	-46.716 dBm			
3	N	1	f	4.925 2 GHz	-52.846 dBm			
4	N	1	f	7.388 7 GHz	-47.582 dBm			
5	N	1	f	9.849 5 GHz	-55.552 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT n20 2412MHz Ref



Tx. Spurious NVNT n20 2412MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.416 7 GHz	(Δ) -2.962 dBm			
2	N	1	f	24.660 3 GHz	-47.739 dBm			
3	N	1	f	5.004 6 GHz	-57.466 dBm			
4	N	1	f	7.233 4 GHz	-48.093 dBm			
5	N	1	f	9.646 6 GHz	-55.386 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT n20 2437MHz Ref



Tx. Spurious NVNT n20 2437MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.439 7 GHz	(Δ) -1.264 dBm			
2	N	1	f	7.311 0 GHz	-46.086 dBm			
3	N	1	f	4.875 8 GHz	-54.411 dBm			
4	N	1	f	7.311 0 GHz	-46.086 dBm			
5	N	1	f	9.749 8 GHz	-54.884 dBm			
6								
7								
8								
9								
10								
11								
12								

Tx. Spurious NVNT n20 2462MHz Ref



Tx. Spurious NVNT n20 2462MHz Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ) 2.455 5 GHz	(Δ) -1.208 dBm			
2	N	1	f	7.393 1 GHz	-47.497 dBm			
3	N	1	f	4.921 7 GHz	-53.937 dBm			
4	N	1	f	7.393 1 GHz	-47.497 dBm			
5	N	1	f	9.847 7 GHz	-53.817 dBm			
6								
7								
8								
9								
10								
11								
12								

8. Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	b	2462	13.1053

Test Graphs

OBW NVNT b 2462MHz



APPENDIX 2-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※