FCC TEST REPORT
FCC ID: 2BMND-ALS-24V

Report Number.....:	ZKT-241128L16950
Date of Test.....:	Nov. 19, 2024 -- Nov. 29, 2024
Date of issue.....:	Nov. 29, 2024
Total number of pages..... :	48
Test Result..... :	PASS
Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address ..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	Shenzhenshijinghuangkeji Co.,Ltd.
Address ..... :	Room 205, Building B, No. 310, Anlan Road, Luhu Community, Guanhu Street, Longhua District, Shenzhen, Guangdong Province, 518000,China
Manufacturer's name .....:	Shenzhenshijinghuangkeji Co.,Ltd.
Address ..... :	Room 205, Building B, No. 310, Anlan Road, Luhu Community, Guanhu Street, Longhua District, Shenzhen, Guangdong Province, 518000,China
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10:2013
Test procedure..... :	/
Non-standard test method .....:	N/A
Test Report Form No..... :	TRF-EL-110_V0
Test Report Form(s) Originator..... :	ZKT Testing
Master TRF .....:	Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... :	LED Strip Lights
Trademark .....:	N/A
Model/Type reference..... :	ALS-24V01, ALS-612RGB
Ratings..... :	DC24V 0.5A from adapter

Testing procedure and testing location:

Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address.....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Alen He
Reviewer (name + signature).....:	Joe Liu
Approved (name + signature).....:	Lake Xie

Table of Contents

Page

1. VERSION 5
2. SUMMARY OF TEST RESULTS 6
3. GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.2 DESCRIPTION OF TEST MODES 9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 12
4.1 CONDUCTED EMISSION MEASUREMENT 12
4.1.1 POWER LINE CONDUCTED EMISSION Limits 12
4.1.2 TEST PROCEDURE 12
4.1.3 DEVIATION FROM TEST STANDARD 12
4.1.4 TEST SETUP 13
4.1.5 EUT OPERATING CONDITIONS 13
4.1.6 TEST RESULT 14
4.2 RADIATED EMISSION MEASUREMENT 16
4.2.1 RADIATED EMISSION LIMITS 16
4.2.2 TEST PROCEDURE 16
4.2.3 DEVIATION FROM TEST STANDARD 17
4.2.4 TEST SETUP 17
4.2.5 EUT OPERATING CONDITIONS 18
4.2.6 TEST RESULTS 19
5.RADIATED BAND EMISSIONMEASUREMENT 22
5.1 TEST REQUIREMENT: 22
5.2 TEST PROCEDURE 22
5.3 DEVIATION FROM TEST STANDARD 22
5.4 TEST SETUP 23
5.5 EUT OPERATING CONDITIONS 23
6.POWER SPECTRAL DENSITY TEST 24
6.1 APPLIED PROCEDURES / LIMIT 24
6.2 TEST PROCEDURE 24
6.3 DEVIATION FROM STANDARD 24
6.4 TEST SETUP 24
6.5 EUT OPERATION CONDITIONS 24
6.6 TEST RESULT 24
7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH 25

7.1 APPLIED PROCEDURES / LIMIT 25
7.2 TEST PROCEDURE 25
7.3 DEVIATION FROM STANDARD 25
7.4 TEST SETUP 25
7.5 EUT OPERATION CONDITIONS 25
7.6 TEST RESULT 25
8.PEAK OUTPUT POWER TEST 26
8.1 APPLIED PROCEDURES/LIMIT 26
8.2 TEST PROCEDURE 26
8.3 DEVIATION FROM STANDARD 26
8.4 TEST SETUP 26
8.5 EUT OPERATION CONDITIONS 26
8.6 TEST RESULT 26
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 27
9.1 APPLICABLE STANDARD 27
9.2 TEST PROCEDURE 27
9.3 DEVIATION FROM STANDARD 27
9.4 TEST SETUP 27
9.5 EUT OPERATION CONDITIONS 27
9.6 TEST RESULTS 27
10. ANTENNA REQUIREMENT 28
11. TEST SETUP PHOTO 29
12. EUT CONSTRUCTIONAL DETAILS 31
APPENDIX 38
1. -6DB BANDWIDTH 38
2. PEAK OUTPUT POWER 40
3. POWER SPECTRAL DENSITY 42
4. BANDEDGE 44
5. SPURIOUS EMISSION 46

1. VERSION

Report No.	Version	Description	Approved
ZKT-241128L16950	Rev.01	Initial issue of report	Nov. 30, 2024

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

Item	Method	Requirement	Result
Antenna requirement	/	47 CFR 15.203	Pass
Conducted Emission at AC power line	ANSI C63.10-2013 section 6.2	47 CFR 15.207(a)	Pass
Occupied Bandwidth	ANSI C63.10-2013, section 11.8 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	ANSI C63.10-2013, section 11.10 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	ANSI C63.10-2013 section 11.11 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Band edge emissions (Radiated)	ANSI C63.10-2013 section 6.10 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass

Note:1.N/A -this device(EUT) is not applicable to this testing item

2. RF-conducted test results including cable loss.

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power conducted	±0.16dB
3	Spurious emissions conducted	±0.21dB
4	All emissions radiated(<1G)	±4.68dB
5	All emissions radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	LED Strip Light
Model No.:	ALS-24V01
Sseries Model:	ALS-612RGB
Model difference:	There are two models of the product, with the difference being the appearance of the light strip (one is waterproof and the other is non waterproof). The Bluetooth controller part is the same(PCB & Bom), and the model used for testing is: ALS-24V01
Hardware Version:	V10
Software Version:	BT_TOOL_V1.0.8
Sample(s) Status:	Engineer sample
Channel numbers:	40
Channel separation:	2402MHz~2480MHz
Date rate:	1Mbps
Modulation technology:	GFSK
Antenna Type:	PCB antenna
Antenna gain:	0.0dBi
Power supply:	DC24V 0.5A from adapter

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402	11	2422	21	2442	31	2462
2	2404	12	2424	22	2444	32	2464
3	2406	13	2426	23	2446	33	2466
4	2408	14	2428	24	2448	34	2468
5	2410	15	2430	25	2450	35	2470
6	2412	16	2432	26	2452	36	2472
7	2414	17	2434	27	2454	37	2474
8	2416	18	2436	28	2456	38	2476
9	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency**
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

No	Title	Description
TM1	TX mode	Keep the EUT connect to AC power line and works in continuously transmitting mode with GFSK modulation at lowest, middle and highest channel.

☒ Special software is used.

☐ Through engineering command into the engineering mode.

engineering command: *#*#3646633#*#*

☐ Other method:

Special software:



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission

AC POWER | EUT

Radiated Emission

AC POWER | EUT

Conducted Spurious

AC POWER | EUT

3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1					
2					
3					
4					

Item	Shielded Type	Ferrite Core	Length	Note

Note:
(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	Oct. 18, 2024	Oct. 17, 2025
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 18, 2024	Oct. 17, 2025
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2024	Oct. 17, 2025
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 18, 2024	Oct. 17, 2025
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 18, 2024	Oct. 17, 2025
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 18, 2024	Oct. 17, 2025
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 18, 2024	Oct. 17, 2025
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2024	Oct. 17, 2025
9	RF cables1	N/A	9kHz-30MHz	N/A	Oct. 18, 2024	Oct. 17, 2025
10	RF cables2	N/A	30MHz-1GHz	N/A	Oct. 18, 2024	Oct. 17, 2025
11	RF cables3	N/A	1GHz-40GHz	N/A	Oct. 18, 2024	Oct. 17, 2025
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 18, 2024	Oct. 17, 2025
13	Signal Generator	Agilent	N5182A	N/A	Oct. 18, 2024	Oct. 17, 2025
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 18, 2024	Oct. 17, 2025
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 18, 2024	Oct. 17, 2025
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 18, 2024	Oct. 17, 2025
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 18, 2024	Oct. 17, 2025
3	Test Cable	N/A	C01	N/A	Oct. 18, 2024	Oct. 17, 2025
4	Test Cable	N/A	C02	N/A	Oct. 18, 2024	Oct. 17, 2025
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 18, 2024	Oct. 17, 2025
6	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V , the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1620	28.57	10.12	38.69	55.36	-16.67	AVG	
2	*	0.1819	48.42	10.12	58.54	64.39	-5.85	peak	
3		0.2420	41.56	10.10	51.66	62.02	-10.36	peak	
4		0.3020	27.40	10.10	37.50	50.19	-12.69	AVG	
5		0.6460	34.72	10.09	44.81	56.00	-11.19	peak	
6		0.6540	27.52	10.09	37.61	46.00	-8.39	AVG	
7		1.6620	23.97	10.03	34.00	56.00	-22.00	peak	
8		1.8020	18.61	10.01	28.62	46.00	-17.38	AVG	
9		6.2299	10.69	10.21	20.90	50.00	-29.10	AVG	
10		7.1939	25.57	10.22	35.79	60.00	-24.21	peak	
11		22.4060	37.90	10.65	48.55	60.00	-11.45	peak	
12		28.0020	16.13	10.96	27.09	50.00	-22.91	AVG	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1620	32.16	10.12	42.28	55.36	-13.08	AVG	
2	*	0.1819	47.63	10.12	57.75	64.39	-6.64	peak	
3		0.6419	34.41	10.09	44.50	56.00	-11.50	peak	
4		0.6540	28.99	10.09	39.08	46.00	-6.92	AVG	
5		1.2300	20.47	10.09	30.56	56.00	-25.44	peak	
6		1.2820	16.80	10.09	26.89	46.00	-19.11	AVG	
7		2.4020	27.11	10.02	37.13	56.00	-18.87	peak	
8		2.8699	15.43	10.05	25.48	46.00	-20.52	AVG	
9		16.0219	29.94	10.50	40.44	60.00	-19.56	peak	
10		16.0219	8.92	10.50	19.42	50.00	-30.58	AVG	
11		24.7820	36.93	10.73	47.66	60.00	-12.34	peak	
12		24.7820	15.37	10.73	26.10	50.00	-23.90	AVG	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of avariable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum valueof the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned toheights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber andchange form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC120V 60Hz		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	116.5401	33.72	-5.67	28.05	43.50	-15.45	QP	100		P	
2	178.7584	42.02	-8.18	33.84	43.50	-9.66	QP	100		P	
3 *	192.4186	44.35	-8.66	35.69	43.50	-7.81	QP	100		P	
4	213.0151	40.19	-8.39	31.80	43.50	-11.70	QP	100		P	
5	297.2241	34.61	-5.71	28.90	46.00	-17.10	QP	100		P	
6	366.8231	34.21	-4.37	29.84	46.00	-16.16	QP	100		P	

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC120V 60Hz		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	55.2207	50.30	-12.83	37.47	40.00	-2.53	QP	100		P	
2	69.3568	41.22	-11.57	29.65	40.00	-10.35	QP	100		P	
3	90.5374	42.00	-10.91	31.09	43.50	-12.41	QP	100		P	
4	104.1701	36.41	-7.10	29.31	43.50	-14.19	QP	100		P	
5	109.0286	34.33	-6.19	28.14	43.50	-15.36	QP	100		P	
6 !	184.4898	42.96	-8.53	34.43	43.50	-9.07	QP	100		P	

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.

1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	43.81	32.4	3.22	19.26	33.89	74.00	-40.11	PK
V	4804.00	44.14	32.4	3.22	19.26	34.22	54.00	-19.78	AV
V	7206.00	46.76	32.4	3.22	19.26	36.84	74.00	-37.16	PK
V	7206.00	44.51	32.4	3.22	19.26	34.59	54.00	-19.41	AV
V	9608.00	50.92	30.85	7.45	24.69	52.21	74.00	-21.79	PK
V	9608.00	38.14	30.85	7.45	24.69	39.43	54.00	-14.57	AV
H	4804.00	54.06	30.55	5.77	24.66	53.94	74.00	-20.06	PK
H	4804.00	39.91	30.55	5.77	24.66	39.79	54.00	-14.21	AV
H	7206.00	52.90	30.33	6.32	24.55	53.44	74.00	-20.56	PK
H	7206.00	40.24	30.33	6.32	24.55	40.78	54.00	-13.22	AV
H	9608.00	50.94	30.85	7.45	24.69	52.23	74.00	-21.77	PK
H	9608.00	36.30	30.85	7.45	24.69	37.59	54.00	-16.41	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2440MHz									
V	4880.00	46.62	32.4	3.22	19.26	36.70	74.00	-37.30	PK
V	4880.00	44.96	32.4	3.22	19.26	35.04	54.00	-18.96	AV
V	7320.00	47.22	32.4	3.22	19.26	37.30	74.00	-36.70	PK
V	7320.00	44.53	32.4	3.22	19.26	34.61	54.00	-19.39	AV
V	9760.00	49.83	30.85	7.45	24.69	51.12	74.00	-22.88	PK
V	9760.00	37.64	30.85	7.45	24.69	38.93	54.00	-15.07	AV
H	4880.00	55.93	30.55	5.77	24.66	55.81	74.00	-18.19	PK
H	4880.00	39.29	30.55	5.77	24.66	39.17	54.00	-14.83	AV
H	7320.00	54.73	30.33	6.32	24.55	55.27	74.00	-18.73	PK
H	7320.00	40.67	30.33	6.32	24.55	41.21	54.00	-12.79	AV
H	9760.00	49.88	30.85	7.45	24.69	51.17	74.00	-22.83	PK
H	9760.00	36.72	30.85	7.45	24.69	38.01	54.00	-15.99	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	44.68	32.4	3.22	19.26	34.76	74.00	-39.24	PK
V	4960.00	44.74	32.4	3.22	19.26	34.82	54.00	-19.18	AV
V	7440.00	45.94	32.4	3.22	19.26	36.02	74.00	-37.98	PK
V	7440.00	45.02	32.4	3.22	19.26	35.10	54.00	-18.90	AV
V	9920.00	52.54	30.85	7.45	24.69	53.83	74.00	-20.17	PK
V	9920.00	38.20	30.85	7.45	24.69	39.49	54.00	-14.51	AV
H	4960.00	55.55	30.55	5.77	24.66	55.43	74.00	-18.57	PK
H	4960.00	42.11	30.55	5.77	24.66	41.99	54.00	-12.01	AV
H	7440.00	54.32	30.33	6.32	24.55	54.86	74.00	-19.14	PK
H	7440.00	40.52	30.33	6.32	24.55	41.06	54.00	-12.94	AV
H	9920.00	51.56	30.85	7.45	24.69	52.85	74.00	-21.15	PK
H	9920.00	36.32	30.85	7.45	24.69	37.61	54.00	-16.39	AV

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
Low Channel 2402MHz										
H	2310.00	51.88	30.22	4.7	23.98	50.34	74.00	-23.66	PK	PASS
H	2310.00	39.33	30.22	4.7	23.98	37.79	54.00	-16.21	AV	PASS
H	2390.00	53.49	30.22	4.85	23.98	52.10	74.00	-21.90	PK	PASS
H	2390.00	36.60	30.22	4.85	23.98	35.21	54.00	-18.79	AV	PASS
V	2310.00	53.44	30.22	4.7	23.98	51.90	74.00	-22.10	PK	PASS
V	2310.00	38.53	30.22	4.7	23.98	36.99	54.00	-17.01	AV	PASS
V	2390.00	52.38	30.22	4.85	23.98	50.99	74.00	-23.01	PK	PASS
V	2390.00	36.46	30.22	4.85	23.98	35.07	54.00	-18.93	AV	PASS
High Channel: 2480MHz										
H	2483.50	53.65	30.22	4.85	23.98	52.26	74.00	-21.74	PK	PASS
H	2483.50	38.49	30.22	4.85	23.98	37.10	54.00	-16.90	AV	PASS
H	2500.00	54.42	30.22	4.85	23.98	53.03	74.00	-20.97	PK	PASS
H	2500.00	36.81	30.22	4.85	23.98	35.42	54.00	-18.58	AV	PASS
V	2483.50	51.15	30.22	4.85	23.98	49.76	74.00	-24.24	PK	PASS
V	2483.50	37.99	30.22	4.85	23.98	36.60	54.00	-17.40	AV	PASS
V	2500.00	53.18	30.22	4.85	23.98	51.79	74.00	-22.21	PK	PASS
V	2500.00	37.28	30.22	4.85	23.98	35.89	54.00	-18.11	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6.POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidance v 05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

PLEASE REFER TO APPENDIX FOR DETAILS.

7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

PLEASE REFER TO APPENDIX FOR DETAILS.

8.PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

PLEASE REFER TO APPENDIX FOR DETAILS.

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP

9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

PLEASE REFER TO APPENDIX FOR DETAILS.

10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

EUT Antenna:

The antenna is PCB antenna, the best case gain of the antennas are 0dBi, reference to the below photo for details



11. TEST SETUP PHOTO

Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)

Conducted Emission at AC power line

12. EUT CONSTRUCTIONAL DETAILS

External







LED CONTROLLER
UK
CA
IR RECEIVER




LED CONTROLLER
UK
CA
IR RECEIVER


LED CONTROLLER
UK
CA
IR RECEIVER



Internal







ANT
ELK-1027RXX-20-V10
SN30332233
C07EBA
UNM839

APPENDIX

1. -6DB BANDWIDTH

Condition	Antenna	Rate	Frequency (MHz)	-6dB BW(kHz)	limit(kHz)	Result
NVNT	ANT1	1Mbps	2402.00	515.73	500	Pass
NVNT	ANT1	1Mbps	2440.00	517.87	500	Pass
NVNT	ANT1	1Mbps	2480.00	521.15	500	Pass

-6dB_Bandwidth_NVNT_ANT1_1Mbps_2402

-6dB_Bandwidth_NVNT_ANT1_1Mbps_2440

-6dB_Bandwidth_NVNT_ANT1_1Mbps_2480

2. PEAK OUTPUT POWER

Condition	Antenna	Rate	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1Mbps	2402.00	-1.49	0.71	1000	Pass
NVNT	ANT1	1Mbps	2440.00	-3.12	0.49	1000	Pass
NVNT	ANT1	1Mbps	2480.00	-3.33	0.46	1000	Pass

Peak_Output_Power_NVNT_ANT1_1Mbps_2402



Peak_Output_Power_NVNT_ANT1_1Mbps_2440



Peak_Output_Power_NVNT_ANT1_1Mbps_2480



3. POWER SPECTRAL DENSITY

Condition	Antenna	Rate	Frequency (MHz)	Power Spectral Density(dBm/3kHz)	Limit(dBm/3kHz)	Result
NVNT	ANT1	1Mbps	2402.00	-14.18	8	Pass
NVNT	ANT1	1Mbps	2440.00	-15.74	8	Pass
NVNT	ANT1	1Mbps	2480.00	-15.93	8	Pass

Power_Spectral_Density_NVNT_ANT1_1Mbps_2402



Power_Spectral_Density_NVNT_ANT1_1Mbps_2440

Power_Spectral_Density_NVNT_ANT1_1Mbps_2480

4. BANDEDGE

Condition	Antenna	Rate	TX_Frequency (MHz)	Max. Mark Frequency (MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402.00	2377.830	-35.631	-21.958	Pass
NVNT	ANT1	1Mbps	2480.00	2483.575	-59.839	-23.775	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402

2_Bandedge_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2480

2_Bandedge_NVNT_ANT1_1Mbps_2480



5. SPURIOUS EMISSION

Condition	Antenna	Rate	TX_Frequency(MHz)	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1Mbps	2402.00	-42.980	-21.958	Pass
NVNT	ANT1	1Mbps	2440.00	-39.690	-23.723	Pass
NVNT	ANT1	1Mbps	2480.00	-36.278	-23.775	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402

2_Spurious_Emission_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2440

2_Spurious_Emission_NVNT_ANT1_1Mbps_2440



1_Reference_Level_NVNT_ANT1_1Mbps_2480

2_Spurious_Emission_NVNT_ANT1_1Mbps_2480



※※※※※ **END OF REPORT** ※※※※※