



TEST REPORT

Applicant Name : Zhuhai Glory Technology Co., Ltd
Address : 8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town,
Zhuhai,Guangdong, 519000 China
Report Number : 2604P16309E-RF
FCC ID: 2BMPT-N18

Test Standard (s)

47 CFR §2.1091

Sample Description

Product Type: Wi-Fi Halow Video Recorder
Model No.: N1, GLH-1908AY, H3
Trade Mark: N/A
Date Received: 2026-01-26
Report Date: 2026-04-14

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Jason Fan

Jason Fan
EMC Engineer

Approved By:

Bob. Liao

Bob.Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY..... 3

GENERAL INFORMATION..... 4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

 OBJECTIVE 4

 TEST FACILITY 4

RF EXPOSURE 5

 APPLICABLE STANDARD..... 5

 RESULT 5

EXHIBIT A-EUT PHOTOGRAPHS 7

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2604P16309E-RF	Original Report	2026-04-14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Wi-Fi Halow Video Recorder
Tested Model	N1
Multiple Model	GLH-1908AY, H3
Model Difference [#]	Only the model names are different. Please refer to DOS letter for details. The applicant provided model "N1" for testing.
Frequency Range	2.4G Wi-Fi: 802.11b/g/n20/ax20: 2412-2462MHz 802.11n40/ax40: 2422-2452MHz 5G Wi-Fi: 5150-5250MHz; 5250-5350MHz 5470-5725MHz; 5725-5850MHz WIFI Halow 1M: 903.5-926.5MHz WIFI Halow 2M: 905-925MHz WIFI Halow 4M: 906-926MHz WIFI Halow 8M: 908-924MHz
Maximum Conducted Output Power	2.4G Wi-Fi: 23.6 dBm 5G Wi-Fi: 5150-5250MHz:15.05dBm 5250-5350MHz:13.94dBm 5470-5725MHz:10.89dBm 5725-5850MHz:14.09dBm WIFI Halow : 24.87 dBm
Antenna Specification [#]	Internal Antenna: 2.4G Wi-Fi: 2.01 dBi 5G Wi-Fi: 4.9 dBi External Antenna: WIFI Halow : 2.45 dBi (It is provided by the manufacturer.)
Voltage Range [#]	DC 12V from power port
Sample Serial Number	3GNR-2 (RF Conducted Test) (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts C and Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC §2.1091 rules.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01.

RF EXPOSURE

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Mode	Frequency (MHz)	Antenna Gain [#]		Tune up conducted power [#]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G Wi-Fi	2412-2462	2.01	1.59	24	251.19	20	0.0794	1.00
5G Wi-Fi	5150-5250	4.9	3.09	15.5	35.48	20	0.022	1.00
	5250-5350	4.9	3.09	14	25.12	20	0.0154	1.00
	5470-5725	4.9	3.09	11	12.59	20	0.00774	1.00
	5725-5850	4.9	3.09	14.5	28.18	20	0.0173	1.00
WIFI Halow	903.5-926.5	2.45	1.76	25	316.23	20	0.1106	0.6

Note 1: The tune-up power and antenna gain are declared by the applicant.

Note 2: The 2.4G Wi-Fi and 5G Wi-Fi can't transmission simultaneously.

Note 3: The WIFI and WIFI Halow can transmission simultaneously.

Simultaneous transmitting consideration (worst case):

The ratio=2.4G Wi-Fi /Limit + WIFI Halow WIFI/Limit

$$= 0.0794/1 + 0.1106/0.6$$

$$= 0.2637 < 1.0$$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2604P16309E-RF EUT External Photos and Attachment No.2 2604P16309E-RF EUT Internal Photos

***** END OF REPORT *****