

TEST REPORT

FCC ID.	2BMPT-N28	
Test Report No.	TCT250827E008	
Date of issue	Oct. 14, 2025	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name	Zhuhai Glory Technology Co., Ltd	
Address	8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, 519000 China	
Manufacturer's name ...	Zhuhai Glory Technology Co., Ltd	
Address	8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, 519000 China	
Standard(s)	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name	8 CH Network Video Recorder	
Trade Mark	N/A	
Model/Type reference	N28 Lite, N28	
Rating(s)	DC 48V	
Date of receipt of test item	Aug. 27, 2025	
Date (s) of performance of test	Aug. 27, 2025 ~ Oct. 14, 2025	
Tested by (+signature) ...	Rleo LIU	
Check by (+signature)	Beryl ZHAO	
Approved by (+signature):	Tomsin	

**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Test Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units	9
4. Facilities and Accreditations	10
4.1. Facilities	10
4.2. Location	10
5. Measurement Uncertainty	10
6. Test Results and Measurement Data	11
6.1. Antenna requirement	11
6.2. Conducted Emission.....	12
6.3. Maximum Conducted Output Power	16
6.4. 6dB Emission Bandwidth.....	18
6.5. 26dB Bandwidth and 99% Occupied Bandwidth	19
6.6. Power Spectral Density.....	20
6.7. Band edge	21
6.8. Unwanted Emissions	32
6.9. Frequency Stability Measurement	81

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name.....:	8 CH Network Video Recorder
Model/Type reference.....:	N28 Lite, N28
Sample Number.....:	TCT250827E007-0101
Operation Frequency	Band 1: 5180MHz~5240MHz Band 2A: 5260MHz~5320MHz Band 2C: 5500MHz~5700MHz Band 3: 5745MHz~5825MHz
Channel Bandwidth.....:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz 802.11ax: 20MHz, 40MHz
Modulation Technology	Orthogonal Frequency Division Multiplexing (OFDM)
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type.....:	PCB Antenna
Antenna Gain.....:	Band 1: 3.3dBi Band 2A: 3.8dBi Band 2C: 4.7dBi Band 3: 4.3dBi
Rating(s).....:	DC 48V

Note: 1. The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

2. 802.11ax not support partial RU mode.

1.2. Model(s) list

No.	Model No.	Tested with
1	N28 Lite	☒
Other models	N28	☒

Note: The difference between the N28 series model and the main test model N28 Lite is that: the N28 series model removes the SD card function, the HDMI socket becomes horizontal, the reset button is placed next to the HDMI socket, and the PoE network interface changes from 1 * 8 RJ45 network port to 2 * 4 RJ45 network port.

1.3. Test Frequency

Band 1

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
36	5180	38	5190
40	5200	46	5230
48	5240		

Band 2A

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
52	5260	54	5270
60	5300	62	5310
64	5320		

Band 2C

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
100	5500	102	5510
120	5600	118	5590
140	5700	134	5670

Band 3

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
149	5745	151	5755
157	5785	159	5795
165	5825		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. For the band 5.15-5.25GHz, EUT meet the requirements of 15.407(a)(ii).

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	SecureCRT_6.70
Power Level:	Band 1: 802.11a: L/M/H: 16/16/16 802.11n(HT20): L/M/H: 16/16/16 802.11n(HT40): L/H: 14/14 802.11ac(VHT20): L/M/H: 16/16/16 802.11ac(VHT40): L/H: 14/14 802.11ax(HE20): L/M/H: 16/16/16 802.11ax(HE40): L/H: 14/14 Band 2A: 802.11a: L/M/H: 16/16/16 802.11n(HT20): L/M/H: 16/16/16 802.11n(HT40): L/H: 16/14 802.11ac(VHT20): L/M/H: 16/16/16 802.11ac(VHT40): L/H: 16/14 802.11ax(HE20): L/M/H: 16/16/16 802.11ax(HE40): L/H: 16/14 Band 2C: 802.11a: L/M/H: 16/16/16 802.11n(HT20): L/M/H: 16/16/16 802.11n(HT40): L/M/H: 14/14/14 802.11ac(VHT20): L/M/H: 16/16/16 802.11ac(VHT40): L/M/H: 14/14/14 802.11ax(HE20): L/M/H: 16/16/16 802.11ax(HE40): L/M/H: 14/14/14 Band 3: 802.11a: L/M/H: 16/16/16 802.11n(HT20): L/M/H: 16/16/16 802.11n(HT40): L/H: 16/16

	802.11ac(VHT20): L/M/H: 16/16/16 802.11ac(VHT40): L/H: 16/16 802.11ax(HE20): L/M/H: 16/16/16 802.11ax(HE40): L/H: 16/16
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.
The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps
802.11ac(VHT20)	6.5 Mbps
802.11ac(VHT40)	13.5 Mbps
802.11ax(HE20)	6.5 Mbps
802.11ax(HE40)	13.5 Mbps

Final Test Mode:

Operation mode:	Keep the EUT in continuous transmitting with modulation
-----------------	---

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
LCD Monitor	272P7V	272P7VPTKE B/93	/	PHILIPS
Mouse	N1050	18802NX1723 440	/	RAPOO
Adapter	CS-4801500	/	/	C.SA Electronics (DongGuan) Co., Ltd
Camera	GL-338KUI-N1 E3BY	/	/	Glory
HDD	MQ04ABF100	/	/	TOSHIBA

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339


5. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT antenna is PCB antenna which permanently attached, and the best case gain of the antenna is 4.7dBi of UNII-2C	
	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2020														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane 40cm E.U.T AC power 80cm LISN Filter AC power EMI Receiver Test table/Insulation plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Transmitting Mode														
Test Procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2020 on conducted measurement.														
Test Result:	PASS														


6.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025	Jun. 25, 2026
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 21, 2025	Jan. 20, 2026
Attenuator	N/A	10dB	164080	Jun. 26, 2025	Jun. 25, 2026
Line-5	TCT	CE-05	/	Jun. 26, 2025	Jun. 25, 2026
EMI Test Software	EZ EMC	EMEC-3A1	1.1.4.2	/	/

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **L1**

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 48 V(Adapter Input AC 120 V/60 Hz)

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1740	50.59	8.53	59.12	64.77	-5.65	QP	
2		0.1740	37.29	8.53	45.82	54.77	-8.95	AVG	
3		0.2060	46.89	8.51	55.40	63.37	-7.97	QP	
4		0.2060	32.68	8.51	41.19	53.37	-12.18	AVG	
5	*	0.4580	43.85	8.51	52.36	56.73	-4.37	QP	
6		0.4580	30.66	8.51	39.17	46.73	-7.56	AVG	
7		4.3100	27.99	8.71	36.70	56.00	-19.30	QP	
8		4.3100	10.65	8.71	19.36	46.00	-26.64	AVG	
9		16.4740	27.83	9.05	36.88	60.00	-23.12	QP	
10		16.4740	19.84	9.05	28.89	50.00	-21.11	AVG	
11		29.7860	36.76	9.49	46.25	60.00	-13.75	QP	
12		29.7860	14.94	9.49	24.43	50.00	-25.57	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **N**

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 48 V(Adapter Input AC 120 V/60 Hz)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	53.86	8.53	62.39	66.00	-3.61	QP	
2		0.1500	38.16	8.53	46.69	56.00	-9.31	AVG	
3		0.1940	49.71	8.52	58.23	63.86	-5.63	QP	
4		0.1940	34.81	8.52	43.33	53.86	-10.53	AVG	
5	*	0.4700	44.44	8.53	52.97	56.51	-3.54	QP	
6		0.4700	32.63	8.53	41.16	46.51	-5.35	AVG	
7		4.2538	25.55	8.71	34.26	56.00	-21.74	QP	
8		4.2538	12.59	8.71	21.30	46.00	-24.70	AVG	
9		16.4819	25.02	9.09	34.11	60.00	-25.89	QP	
10		16.4819	15.32	9.09	24.41	50.00	-25.59	AVG	
11		29.7860	35.91	9.74	45.65	60.00	-14.35	QP	
12		29.7860	15.62	9.74	25.36	50.00	-24.64	AVG	

Note: 1. Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ax(HE20), 802.11ax(HE40) and the worst case Mode (Highest channel and 802.11ax(HE20)) was submitted only.

3. The both models were tested, and the worst result (model: N28 Lite) is recorded.

6.3. Maximum Conducted Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046	
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E	
Limit:	Frequency Band (MHz)	Limit
	5180 - 5240	24dBm(250mW) for client device
	5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz
	5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz
	5745 - 5825	30dBm(1W)
Test Setup:	 Spectrum AnalyzerEUT	
Test Mode:	Transmitting mode with modulation	
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 2, b 2. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report.	
Test Result:	PASS	
Remark1:	Conducted output power= measurement power +10log(1/x), X is duty cycle=1, so 10log(1/1)=0 Conducted output power= measurement power	
Remark2:	The test data can be found on page 130-169	

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

6.4. 6dB Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS
Remark:	The test data can be found on page 201-210

6.4.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

6.5. 26dB Bandwidth and 99% Occupied Bandwidth

6.5.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS
Remark:	The test data can be found on page 170-200 and 211-250

6.5.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFtest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

6.6. Power Spectral Density

6.6.1. Test Specification


Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz The e.i.r.p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS
Remark:	The test data can be found on page 251-290

6.6.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

6.7. Band edge

6.7.1. Test Specification

Test Requirement:	FCC CFR47 Part 15E Section 15.407																										
Test Method:	ANSI C63.10 2020																										
Limit:	In un-restricted band: For Band 1&2A&2C: -27dBm/MHz For Band 3: <table><tr><th>Frequency (MHz)</th><th>Limit (dBm/MHz)</th><th>Frequency (MHz)</th><th>Limit (dBm/MHz)</th></tr><tr><td>< 650</td><td>-27</td><td>5850~5855</td><td>27~15.6</td></tr><tr><td>5650~5700</td><td>-27~10</td><td>5855~5875</td><td>15.6~10</td></tr><tr><td>5700~5720</td><td>10~15.6</td><td>5875~5925</td><td>10~-27</td></tr><tr><td>5720~5725</td><td>15.6~27</td><td>> 5925</td><td>-27</td></tr></table> E[dBμV/m] = EIRP[dBm] + 95.2 @3m In restricted band: <table><tr><th>Detector</th><th>Limit@3m</th></tr><tr><td>Peak</td><td>74dBμV/m</td></tr><tr><td>AVG</td><td>54dBμV/m</td></tr></table>	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)	< 650	-27	5850~5855	27~15.6	5650~5700	-27~10	5855~5875	15.6~10	5700~5720	10~15.6	5875~5925	10~-27	5720~5725	15.6~27	> 5925	-27	Detector	Limit@3m	Peak	74dBμV/m	AVG	54dBμV/m
Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)																								
< 650	-27	5850~5855	27~15.6																								
5650~5700	-27~10	5855~5875	15.6~10																								
5700~5720	10~15.6	5875~5925	10~-27																								
5720~5725	15.6~27	> 5925	-27																								
Detector	Limit@3m																										
Peak	74dBμV/m																										
AVG	54dBμV/m																										
Test Setup:																											
Test Mode:	Transmitting mode with modulation																										
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect																										


	Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi peak or average method as specified and then reported in a data sheet.
Test Result:	PASS

6.7.2. Test Instruments

Radiated Emission Test Site (966)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI7	100529	Jan. 21, 2025	Jan. 20, 2026
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025	Jun. 25, 2026
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 21, 2025	Jan. 20, 2026
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Apr. 11, 2025	Apr. 10, 2026
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025	Jun. 25, 2026
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 30, 2025	Jun. 29, 2026
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 29, 2025	Jun. 28, 2026
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 29, 2025	Jun. 28, 2026
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jan. 24, 2025	Jan. 23, 2026
Coaxial cable	SKET	RE-03-D	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-03-M	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-03-L	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-D	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-M	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-L	/	Jun. 27, 2025	Jun. 26, 2026
Antenna Mast	Keleto	RE-AM	/	/	/
EMI Test Software	EZ_EMCC	FA-03A2 RE+	1.1.4.2	/	/

6.7.3. Test Data


802.11ax(HE20)-5180



Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 22.9(°C) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	53.09	-8.94	44.15	74.00	-29.85	peak	P	
2 *	5150.000	41.95	-8.94	33.01	54.00	-20.99	AVG	P	




Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 22.9(°C) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	54.50	-8.94	45.56	74.00	-28.44	peak	P	
2 *	5150.000	43.58	-8.94	34.64	54.00	-19.36	AVG	P	

802.11ax(HE40)-5190



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 22.9(°C)

Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	55.79	-8.94	46.85	74.00	-27.15	peak	P	
2 *	5150.000	44.72	-8.94	35.78	54.00	-18.22	AVG	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 22.9(°C)


Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	59.50	-8.94	50.56	74.00	-23.44	peak	P	
2 *	5150.000	45.94	-8.94	37.00	54.00	-17.00	AVG	P	

802.11ax(HE20)-5320



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 22.9(°C)

Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	54.38	-8.45	45.93	74.00	-28.07	peak	P	
2 *	5350.000	43.24	-8.45	34.79	54.00	-19.21	AVG	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 22.9(°C)


Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	53.34	-8.45	44.89	74.00	-29.11	peak	P	
2 *	5350.000	42.00	-8.45	33.55	54.00	-20.45	AVG	P	

802.11ax(HE40)-5310



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 22.9(°C)

Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	59.20	-8.45	50.75	74.00	-23.25	peak	P	
2 *	5350.000	43.82	-8.45	35.37	54.00	-18.63	AVG	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 22.9(°C)


Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	58.50	-8.45	50.05	74.00	-23.95	peak	P	
2 *	5350.000	48.26	-8.45	39.81	54.00	-14.19	AVG	P	

802.11ax(HE20)-5500



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 22.9(°C)

Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5470.000	52.00	-8.02	43.98	68.20	-24.22	peak	P	
2	5470.000	41.20	-8.02	33.18	68.20	-35.02	AVG	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 22.9(°C)


Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5470.000	53.54	-8.02	45.52	68.20	-22.68	peak	P	
2	5470.000	42.84	-8.02	34.82	68.20	-33.38	AVG	P	

802.11ax(HE40)-5510



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 22.9(°C)

Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5470.000	53.98	-8.02	45.96	68.20	-22.24	peak	P	
2	5470.000	44.09	-8.02	36.07	68.20	-32.13	AVG	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 22.9(°C)


Humidity: 63 %

Limit: FCC part 15.407 band edge (PK)

Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5470.000	58.93	-8.02	50.91	68.20	-17.29	peak	P	
2	5470.000	46.94	-8.02	38.92	68.20	-29.28	AVG	P	

802.11ax(HE20)-5825



Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 22.9(°C) Humidity: 63 %
 Limit: FCC part 15.407 band edge B3 (PK) Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5940.200	51.48	-6.54	44.94	68.20	-23.26	peak	P	



Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 22.9(°C) Humidity: 63 %
 Limit: FCC part 15.407 band edge B3 (PK) Power:DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5938.800	52.68	-6.54	46.14	68.20	-22.06	peak	P	

802.11ax(HE40)-5795



Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 22.9(°C) Humidity: 63 %
 Limit: FCC part 15.407 band edge B3 (PK) Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5950.090	51.59	-6.49	45.10	68.20	-23.10	peak	P	




Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 22.9(°C) Humidity: 63 %
 Limit: FCC part 15.407 band edge B3 (PK) Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5969.870	52.10	-6.42	45.68	68.20	-22.52	peak	P	

Note: 1. All modulation (802.11a, 802.11n, 802.11ac, 802.11ax) have been tested, only the worst case in 802.11ax be reported.
 2. The both models were tested, and the worst result (model: N28 Lite) is recorded.


6.8. Unwanted Emissions

6.8.1. Test Specification


Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205				
Test Method:	KDB 789033 D02 v02r01				
Frequency Range:	9kHz to 40GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Transmitting mode with modulation				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table, In restricted bands:				
	Frequency		Detector		Limit@3m
	Above 1G		Peak		74dBµV/m
			AVG		54dBµV/m
	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)
	0.009-0.490		2400/F(KHz)		300
	0.490-1.705		24000/F(KHz)		3
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 960		500		3
Test setup:	In un-restricted bands: 68.2dBuV/m				
	For radiated emissions below 30MHz				
					



30MHz to 1GHz



Above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test results:

PASS

6.8.2. Test Instruments


Radiated Emission Test Site (966)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI7	100529	Jan. 21, 2025	Jan. 20, 2026
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025	Jun. 25, 2026
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 21, 2025	Jan. 20, 2026
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Apr. 11, 2025	Apr. 10, 2026
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025	Jun. 25, 2026
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 30, 2025	Jun. 29, 2026
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 29, 2025	Jun. 28, 2026
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 29, 2025	Jun. 28, 2026
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jan. 24, 2025	Jan. 23, 2026
Coaxial cable	SKET	RE-03-D	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-03-M	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-03-L	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-D	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-M	/	Jun. 27, 2025	Jun. 26, 2026
Coaxial cable	SKET	RE-04-L	/	Jun. 27, 2025	Jun. 26, 2026
Antenna Mast	Keleto	RE-AM	/	/	/
EMI Test Software	EZ_EMCC	FA-03A2 RE+	1.1.4.2	/	/

6.8.3. Test Data

Please refer to following diagram for individual
Below 1GHz

Model: N28 Lite

Horizontal:



Site 3m Anechoic Chamber2

Polarization: **Horizontal**


Temperature: 22.8(C) Humidity: 51 %

Limit: FCC Part 15C RE_3m

Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	69.1140	56.27	-20.27	36.00	40.00	-4.00	QP	P	
2	102.0013	55.34	-21.09	34.25	43.50	-9.25	QP	P	
3	155.3642	49.16	-16.86	32.30	43.50	-11.20	QP	P	
4	372.0045	54.53	-15.84	38.69	46.00	-7.31	QP	P	
5 !	480.5276	53.56	-12.77	40.79	46.00	-5.21	QP	P	
6	996.4995	48.09	-4.88	43.21	54.00	-10.79	QP	P	

Vertical:



Site 3m Anechoic Chamber2

Polarization: **Vertical**

Temperature: 22.8(C) Humidity: 51 %


Limit: FCC Part 15C RE_3m

Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 !	47.4917	53.83	-18.69	35.14	40.00	-4.86	QP	P	
2 !	69.3568	57.40	-20.30	37.10	40.00	-2.90	QP	P	
3 *	84.1100	59.93	-22.63	37.30	40.00	-2.70	QP	P	
4 !	104.5360	60.02	-20.92	39.10	43.50	-4.40	QP	P	
5 !	147.9214	56.53	-17.40	39.13	43.50	-4.37	QP	P	
6 !	601.4265	50.35	-10.11	40.24	46.00	-5.76	QP	P	

Model: N28

Horizontal:



Site 3m Anechoic Chamber2

Polarization: **Horizontal**


Temperature: 23.6(C) Humidity: 47 %

Limit: FCC Part 15C RE_3m

Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	74.3953	50.88	-20.86	30.02	40.00	-9.98	QP	P	
2 *	106.7587	59.30	-20.68	38.62	43.50	-4.88	QP	P	
3	150.0107	53.52	-17.28	36.24	43.50	-7.26	QP	P	
4	250.3009	56.84	-19.44	37.40	46.00	-8.60	QP	P	
5	350.4766	54.28	-16.76	37.52	46.00	-8.48	QP	P	
6	480.5276	51.56	-12.77	38.79	46.00	-7.21	QP	P	

Vertical:



Site 3m Anechoic Chamber2

Polarization: **Vertical**

Temperature: 23.6(C) Humidity: 47 %

Limit: FCC Part 15C RE_3m

Power: DC 48 V(Adapter Input AC 120 V/ 60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	38.8877	53.69	-18.60	35.09	40.00	-4.91	QP	P	
2 !	108.6470	58.36	-20.56	37.80	43.50	-5.70	QP	P	
3	150.0107	53.94	-17.28	36.66	43.50	-6.84	QP	P	
4	250.3009	54.64	-19.44	35.20	46.00	-10.80	QP	P	
5	572.6144	49.22	-11.05	38.17	46.00	-7.83	QP	P	
6	1000.0000	45.11	-4.80	40.31	54.00	-13.69	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ax(HE20), 802.11ax(HE40)) and the worst case Mode (Highest Channel and 802.11ax(HE20)) was submitted only.

3.Measurement (dBuV) = Reading level + Correction Factor, correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Model: N28 Lite

Modulation Type: Band 1

11a CH36: 5180MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.22	---	1.78	40.00	---	68.2	---	-28.20
15540	H	39.73	---	5.21	44.94	---	74	54	-9.06
---	H	---	---	---	---	---	---	---	---

10360	V	38.32	---	1.78	40.10	---	68.2	---	-28.10
15540	V	40.53	---	5.21	45.74	---	74	54	-8.26
---	V	---	---	---	---	---	---	---	---

11a CH40: 5200MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.63	---	1.83	41.46	---	68.2	---	-26.74
15600	H	40.01	---	5.23	45.24	---	74	54	-8.76
---	H	---	---	---	---	---	---	---	---

10400	V	40.17	---	1.83	42.00	---	68.2	---	-26.20
15600	V	40.89	---	5.23	46.12	---	74	54	-7.88
---	V	---	---	---	---	---	---	---	---

11a CH48: 5240MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.98	---	1.85	39.83	---	68.2	---	-28.37
15720	H	39.43	---	5.25	44.68	---	74	54	-9.32
---	H	---	---	---	---	---	---	---	---

10480	V	38.21	---	1.85	40.06	---	68.2	---	-28.14
15720	V	40.37	---	5.25	45.62	---	74	54	-8.38
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH36: 5180MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.45	---	1.78	43.23	---	68.2	---	-24.97
15540	H	40.64	---	5.21	45.85	---	74	54	-8.15
---	H	---	---	---	---	---	---	---	---

10360	V	41.85	---	1.78	43.63	---	68.2	---	-24.57
15540	V	41.26	---	5.21	46.47	---	74	54	-7.53
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.41	---	1.83	42.24	---	68.2	---	-25.96
15600	H	41.02	---	5.23	46.25	---	74	54	-7.75
---	H	---	---	---	---	---	---	---	---
10400	V	40.04	---	1.83	41.87	---	68.2	---	-26.33
15600	V	39.66	---	5.23	44.89	---	74	54	-9.11
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.33	---	1.85	43.18	---	68.2	---	-25.02
15720	H	41.47	---	5.25	46.72	---	74	54	-7.28
---	H	---	---	---	---	---	---	---	---
10480	V	40.01	---	1.85	41.86	---	68.2	---	-26.34
15720	V	39.76	---	5.25	45.01	---	74	54	-8.99
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.62	---	1.80	41.42	---	68.2	---	-26.78
15570	H	41.35	---	5.22	46.57	---	74	54	-7.43
---	H	---	---	---	---	---	---	---	---
10380	V	40.72	---	1.80	42.52	---	68.2	---	-25.68
15570	V	39.03	---	5.22	44.25	---	74	54	-9.75
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.42	---	1.85	43.27	---	68.2	---	-24.93
15690	H	38.78	---	5.08	43.86	---	74	54	-10.14
---	H	---	---	---	---	---	---	---	---
10460	V	41.27	---	1.85	43.12	---	68.2	---	-25.08
15690	V	40.14	---	5.08	45.22	---	74	54	-8.78
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.17	---	1.78	41.95	---	68.2	---	-26.25
15540	H	39.62	---	5.21	44.83	---	74	54	-9.17
---	H	---	---	---	---	---	---	---	---
10360	V	38.38	---	1.78	40.16	---	68.2	---	-28.04
15540	V	38.89	---	5.21	44.10	---	74	54	-9.90
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.43	---	1.83	41.26	---	68.2	---	-26.94
15600	H	39.91	---	5.23	45.14	---	74	54	-8.86
---	H	---	---	---	---	---	---	---	---
10400	V	39.55	---	1.83	41.38	---	68.2	---	-26.82
15600	V	39.22	---	5.23	44.45	---	74	54	-9.55
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.53	---	1.85	39.38	---	68.2	---	-28.82
15720	H	38.72	---	5.25	43.97	---	74	54	-10.03
---	H	---	---	---	---	---	---	---	---
10480	V	38.01	---	1.85	39.86	---	68.2	---	-28.34
15720	V	39.25	---	5.25	44.50	---	74	54	-9.50
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.66	---	1.80	42.46	---	68.2	---	-25.74
15570	H	39.57	---	5.22	44.79	---	74	54	-9.21
---	H	---	---	---	---	---	---	---	---
10380	V	38.18	---	1.80	39.98	---	68.2	---	-28.22
15570	V	39.36	---	5.22	44.58	---	74	54	-9.42
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.21	---	1.85	40.06	---	68.2	---	-28.14
15690	H	39.68	---	5.08	44.76	---	74	54	-9.24
---	H	---	---	---	---	---	---	---	---
10460	V	39.25	---	1.85	41.10	---	68.2	---	-27.10
15690	V	40.13	---	5.08	45.21	---	74	54	-8.79
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.76	---	1.78	40.54	---	68.2	---	-27.66
15540	H	40.22	---	5.21	45.43	---	74	54	-8.57
---	H	---	---	---	---	---	---	---	---
10360	V	37.96	---	1.78	39.74	---	68.2	---	-28.46
15540	V	40.34	---	5.21	45.55	---	74	54	-8.45
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.43	---	1.83	41.26	---	68.2	---	-26.94
15600	H	40.21	---	5.23	45.44	---	74	54	-8.56
---	H	---	---	---	---	---	---	---	---
10400	V	39.55	---	1.83	41.38	---	68.2	---	-26.82
15600	V	38.86	---	5.23	44.09	---	74	54	-9.91
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.78	---	1.85	39.63	---	68.2	---	-28.57
15720	H	39.35	---	5.25	44.60	---	74	54	-9.40
---	H	---	---	---	---	---	---	---	---
10480	V	38.24	---	1.85	40.09	---	68.2	---	-28.11
15720	V	39.17	---	5.25	44.42	---	74	54	-9.58
---	V	---	---	---	---	---	---	---	---

11ax(HE40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.12	---	1.80	41.92	---	68.2	---	-26.28
15570	H	39.34	---	5.22	44.56	---	74	54	-9.44
---	H	---	---	---	---	---	---	---	---
10380	V	37.86	---	1.80	39.66	---	68.2	---	-28.54
15570	V	38.72	---	5.22	43.94	---	74	54	-10.06
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.52	---	1.85	40.37	---	68.2	---	-27.83
15690	H	39.13	---	5.08	44.21	---	74	54	-9.79
---	H	---	---	---	---	---	---	---	---
10460	V	38.73	---	1.85	40.58	---	68.2	---	-27.62
15690	V	40.24	---	5.08	45.32	---	74	54	-8.68
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: Band 2A									
11a CH52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	37.91	---	1.87	39.78	---	68.2	---	-28.42
15780	H	39.22	---	5.01	44.23	---	74	54	-9.77
---	H	---	---	---	---	---	---	---	---
10520	V	41.55	---	1.87	43.42	---	68.2	---	-24.78
15780	V	40.37	---	5.01	45.38	---	74	54	-8.62
---	V	---	---	---	---	---	---	---	---
11a CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	44.62	---	1.89	46.51	---	74	54	-7.49
15900	H	40.25	---	4.93	45.18	---	74	54	-8.82
---	H	---	---	---	---	---	---	---	---
10600	V	44.96	---	1.89	46.85	---	74	54	-7.15
15900	V	41.47	---	4.93	46.40	---	74	54	-7.60
---	V	---	---	---	---	---	---	---	---
11a CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	44.33	---	1.94	46.27	---	74	54	-7.73
15960	H	39.56	---	4.83	44.39	---	74	54	-9.61
---	H	---	---	---	---	---	---	---	---
10640	V	44.86	---	1.94	46.80	---	74	54	-7.20
15960	V	41.01	---	4.83	45.84	---	74	54	-8.16
---	V	---	---	---	---	---	---	---	---
11n(HT20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	41.56	---	1.87	43.43	---	68.2	---	-24.77
15780	H	40.13	---	5.01	45.14	---	74	54	-8.86
---	H	---	---	---	---	---	---	---	---
10520	V	38.32	---	1.87	40.19	---	68.2	---	-28.01
15780	V	39.43	---	5.01	44.44	---	74	54	-9.56
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	44.77	---	1.89	46.66	---	74	54	-7.34
15900	H	39.28	---	4.93	44.21	---	74	54	-9.79
---	H	---	---	---	---	---	---	---	---
10600	V	45.62	---	1.89	47.51	---	74	54	-6.49
15900	V	41.19	---	4.93	46.12	---	74	54	-7.88
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	45.94	---	1.94	47.88	---	74	54	-6.12
15960	H	42.42	---	4.83	47.25	---	74	54	-6.75
---	H	---	---	---	---	---	---	---	---
10640	V	44.26	---	1.94	46.20	---	74	54	-7.80
15960	V	40.77	---	4.83	45.60	---	74	54	-8.40
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	41.27	---	1.87	43.14	---	68.2	---	-25.06
15810	H	39.32	---	4.99	44.31	---	74	54	-9.69
---	H	---	---	---	---	---	---	---	---
10540	V	37.47	---	1.87	39.34	---	68.2	---	-28.86
15810	V	40.73	---	4.99	45.72	---	74	54	-8.28
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	45.45	---	1.92	47.37	---	74	54	-6.63
15930	H	40.53	---	4.88	45.41	---	74	54	-8.59
---	H	---	---	---	---	---	---	---	---
10620	V	43.97	---	1.92	45.89	---	74	54	-8.11
15930	V	39.16	---	4.88	44.04	---	74	54	-9.96
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	40.27	---	1.87	42.14	---	68.2	---	-26.06
15780	H	39.23	---	5.01	44.24	---	74	54	-9.76
---	H	---	---	---	---	---	---	---	---
10520	V	40.53	---	1.87	42.40	---	68.2	---	-25.80
15780	V	40.06	---	5.01	45.07	---	74	54	-8.93
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	43.27	---	1.89	45.16	---	74	54	-8.84
15900	H	40.14	---	4.93	45.07	---	74	54	-8.93
---	H	---	---	---	---	---	---	---	---
10600	V	43.89	---	1.89	45.78	---	74	54	-8.22
15900	V	40.62	---	4.93	45.55	---	74	54	-8.45
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	43.23	---	1.94	45.17	---	74	54	-8.83
15960	H	39.46	---	4.83	44.29	---	74	54	-9.71
---	H	---	---	---	---	---	---	---	---
10640	V	44.53	---	1.94	46.47	---	74	54	-7.53
15960	V	39.02	---	4.83	43.85	---	74	54	-10.15
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	40.56	---	1.87	42.43	---	68.2	---	-25.77
15810	H	39.02	---	4.99	44.01	---	74	54	-9.99
---	H	---	---	---	---	---	---	---	---
10540	V	39.37	---	1.87	41.24	---	68.2	---	-26.96
15810	V	39.59	---	4.99	44.58	---	74	54	-9.42
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	44.26	---	1.92	46.18	---	74	54	-7.82
15930	H	39.54	---	4.88	44.42	---	74	54	-9.58
---	H	---	---	---	---	---	---	---	---
10620	V	43.63	---	1.92	45.55	---	74	54	-8.45
15930	V	39.87	---	4.88	44.75	---	74	54	-9.25
---	V	---	---	---	---	---	---	---	---
11ax(HE20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	40.25	---	1.87	42.12	---	68.2	---	-26.08
15780	H	39.64	---	5.01	44.65	---	74	54	-9.35
---	H	---	---	---	---	---	---	---	---
10520	V	40.53	---	1.87	42.4	---	68.2	---	-25.8
15780	V	39.45	---	5.01	44.46	---	74	54	-9.54
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	44.15	---	1.89	46.04	---	74	54	-7.96
15900	H	40.47	---	4.93	45.40	---	74	54	-8.60
---	H	---	---	---	---	---	---	---	---
10600	V	44.34	---	1.89	46.23	---	74	54	-7.77
15900	V	41.14	---	4.93	46.07	---	74	54	-7.93
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	45.27	---	1.94	47.21	---	74	54	-6.79
15960	H	41.55	---	4.83	46.38	---	74	54	-7.62
---	H	---	---	---	---	---	---	---	---
10640	V	45.94	---	1.94	47.88	---	74	54	-6.12
15960	V	41.02	---	4.83	45.85	---	74	54	-8.15
---	V	---	---	---	---	---	---	---	---

11ax(HE40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	40.68	---	1.87	42.55	---	68.2	---	-25.65
15810	H	38.95	---	4.99	43.94	---	74	54	-10.06
---	H	---	---	---	---	---	---	---	---
10540	V	39.66	---	1.87	41.53	---	68.2	---	-26.67
15810	V	39.78	---	4.99	44.77	---	74	54	-9.23
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	44.25	---	1.92	46.17	---	74	54	-7.83
15930	H	39.49	---	4.88	44.37	---	74	54	-9.63
---	H	---	---	---	---	---	---	---	---
10620	V	45.67	---	1.92	47.59	---	74	54	-6.41
15930	V	39.89	---	4.88	44.77	---	74	54	-9.23
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: Band 2C									
11a CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	44.38	---	2.21	46.59	---	74	54	-7.41
16500	H	39.05	---	5.32	44.37	---	68.2	---	-23.83
---	H	---	---	---	---	---	---	---	---
11000	V	45.67	---	2.21	47.88	---	74	54	-6.12
16500	V	40.47	---	5.32	45.79	---	68.2	---	-22.41
---	V	---	---	---	---	---	---	---	---
11a CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	44.97	---	2.34	47.31	---	74	54	-6.69
16800	H	40.46	---	5.62	46.08	---	68.2	---	-22.12
---	H	---	---	---	---	---	---	---	---
11200	V	44.61	---	2.34	46.95	---	74	54	-7.05
16800	V	38.74	---	5.62	44.36	---	68.2	---	-23.84
---	V	---	---	---	---	---	---	---	---
11a CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	42.02	---	2.47	44.49	---	74	54	-9.51
17100	H	40.46	---	6.00	46.46	---	68.2	---	-21.74
---	H	---	---	---	---	---	---	---	---
11400	V	42.97	---	2.47	45.44	---	74	54	-8.56
17100	V	40.36	---	6.00	46.36	---	68.2	---	-21.84
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	45.43	---	2.21	47.64	---	74	54	-6.36
16500	H	39.21	---	5.32	44.53	---	68.2	---	-23.67
---	H	---	---	---	---	---	---	---	---
11000	V	45.97	---	2.21	48.18	---	74	54	-5.82
16500	V	41.63	---	5.32	46.95	---	68.2	---	-21.25
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	45.15	---	2.34	47.49	---	74	54	-6.51
16800	H	39.87	---	5.62	45.49	---	68.2	---	-22.71
---	H	---	---	---	---	---	---	---	---
11200	V	44.25	---	2.34	46.59	---	74	54	-7.41
16800	V	39.56	---	5.62	45.18	---	68.2	---	-23.02
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	44.42	---	2.47	46.89	---	74	54	-7.11
17100	H	40.03	---	6.00	46.03	---	68.2	---	-22.17
---	H	---	---	---	---	---	---	---	---
11400	V	44.73	---	2.47	47.20	---	74	54	-6.80
17100	V	39.21	---	6.00	45.21	---	68.2	---	-22.99
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	44.95	---	2.21	47.16	---	74	54	-6.84
16530	H	39.76	---	5.34	45.10	---	68.2	---	-23.10
---	H	---	---	---	---	---	---	---	---
11020	V	45.09	---	2.21	47.30	---	74	54	-6.70
16530	V	37.38	---	5.34	42.72	---	68.2	---	-25.48
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	44.64	---	2.32	46.96	---	74	54	-7.04
16770	H	39.16	---	5.60	44.76	---	68.2	---	-23.44
---	H	---	---	---	---	---	---	---	---
11180	V	44.54	---	2.32	46.86	---	74	54	-7.14
16770	V	41.03	---	5.60	46.63	---	68.2	---	-21.57
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	44.65	---	2.40	47.05	---	74	54	-6.95
17010	H	40.93	---	5.96	46.89	---	68.2	---	-21.31
---	H	---	---	---	---	---	---	---	---
11340	V	45.47	---	2.40	47.87	---	74	54	-6.13
17010	V	38.18	---	5.96	44.14	---	68.2	---	-24.06
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	45.22	---	2.21	47.43	---	74	54	-6.57
16500	H	39.59	---	5.32	44.91	---	68.2	---	-23.29
---	H	---	---	---	---	---	---	---	---
11000	V	44.14	---	2.21	46.35	---	74	54	-7.65
16500	V	39.53	---	5.32	44.85	---	68.2	---	-23.35
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	44.62	---	2.34	46.96	---	74	54	-7.04
16800	H	39.23	---	5.62	44.85	---	68.2	---	-23.35
---	H	---	---	---	---	---	---	---	---
11200	V	43.74	---	2.34	46.08	---	74	54	-7.92
16800	V	38.78	---	5.62	44.40	---	68.2	---	-23.80
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	43.54	---	2.47	46.01	---	74	54	-7.99
17100	H	37.98	---	6.00	43.98	---	68.2	---	-24.22
---	H	---	---	---	---	---	---	---	---
11400	V	43.07	---	2.47	45.54	---	74	54	-8.46
17100	V	39.14	---	6.00	45.14	---	68.2	---	-23.06
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	44.72	---	2.21	46.93	---	74	54	-7.07
16530	H	39.16	---	5.34	44.50	---	68.2	---	-23.70
---	H	---	---	---	---	---	---	---	---
11020	V	43.49	---	2.21	45.70	---	74	54	-8.30
16530	V	37.86	---	5.34	43.20	---	68.2	---	-25.00
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	45.32	---	2.32	47.64	---	74	54	-6.36
16770	H	36.45	---	5.60	42.05	---	68.2	---	-26.15
---	H	---	---	---	---	---	---	---	---
11180	V	44.65	---	2.32	46.97	---	74	54	-7.03
16770	V	37.73	---	5.60	43.33	---	68.2	---	-24.87
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	44.89	---	2.40	47.29	---	74	54	-6.71
17010	H	36.72	---	5.96	42.68	---	68.2	---	-25.52
---	H	---	---	---	---	---	---	---	---
11340	V	44.53	---	2.40	46.93	---	74	54	-7.07
17010	V	39.18	---	5.96	45.14	---	68.2	---	-23.06
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	43.27	---	2.21	45.48	---	74	54	-8.52
16500	H	39.62	---	5.32	44.94	---	68.2	---	-23.26
---	H	---	---	---	---	---	---	---	---
11000	V	44.17	---	2.21	46.38	---	74	54	-7.62
16500	V	39.43	---	5.32	44.75	---	68.2	---	-23.45
---	V	---	---	---	---	---	---	---	---

11ax(HE20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	43.64	---	2.34	45.98	---	74	54	-8.02
16800	H	39.25	---	5.62	44.87	---	68.2	---	-23.33
---	H	---	---	---	---	---	---	---	---
11200	V	42.37	---	2.34	44.71	---	74	54	-9.29
16800	V	39.56	---	5.62	45.18	---	68.2	---	-23.02
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	44.44	---	2.47	46.91	---	74	54	-7.09
17100	H	38.14	---	6.00	44.14	---	68.2	---	-24.06
---	H	---	---	---	---	---	---	---	---
11400	V	43.72	---	2.47	46.19	---	74	54	-7.81
17100	V	39.52	---	6.00	45.52	---	68.2	---	-22.68
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	43.37	---	2.21	45.58	---	74	54	-8.42
16530	H	39.64	---	5.34	44.98	---	68.2	---	-23.22
---	H	---	---	---	---	---	---	---	---
11020	V	43.23	---	2.21	45.44	---	74	54	-8.56
16530	V	37.86	---	5.34	43.20	---	68.2	---	-25.00
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	44.75	---	2.32	47.07	---	74	54	-6.93
16770	H	36.62	---	5.60	42.22	---	68.2	---	-25.98
---	H	---	---	---	---	---	---	---	---
11180	V	44.04	---	2.32	46.36	---	74	54	-7.64
16770	V	36.96	---	5.60	42.56	---	68.2	---	-25.64
---	V	---	---	---	---	---	---	---	---

11ax(HE40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	45.05	---	2.40	47.45	---	74	54	-6.55
17010	H	36.17	---	5.96	42.13	---	68.2	---	-26.07
---	H	---	---	---	---	---	---	---	---
11340	V	44.65	---	2.40	47.05	---	74	54	-6.95
17010	V	39.34	---	5.96	45.3	---	68.2	---	-22.9
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	44.53	---	2.48	47.01	---	74	54	-6.99
17235	H	37.32	---	6.50	43.82	---	68.2	---	-24.38
---	H	---	---	---	---	---	---	---	---
11490	V	44.98	---	2.48	47.46	---	74	54	-6.54
17235	V	38.16	---	6.50	44.66	---	68.2	---	-23.54
---	V	---	---	---	---	---	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	43.21	---	2.42	45.63	---	74	54	-8.37
17355	H	38.54	---	7.03	45.57	---	68.2	---	-22.63
---	H	---	---	---	---	---	---	---	---
11570	V	43.62	---	2.42	46.04	---	74	54	-7.96
17355	V	39.05	---	7.03	46.08	---	68.2	---	-22.12
---	V	---	---	---	---	---	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	43.21	---	2.41	45.62	---	74	54	-8.38
17475	H	35.98	---	7.41	43.39	---	68.2	---	-24.81
---	H	---	---	---	---	---	---	---	---
11650	V	43.42	---	2.41	45.83	---	74	54	-8.17
17475	V	38.01	---	7.41	45.42	---	68.2	---	-22.78
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	44.36	---	2.48	46.84	---	74	54	-7.16
17235	H	37.98	---	6.50	44.48	---	68.2	---	-23.72
---	H	---	---	---	---	---	---	---	---
11490	V	44.23	---	2.48	46.71	---	74	54	-7.29
17235	V	36.78	---	6.50	43.28	---	68.2	---	-24.92
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	44.45	---	2.42	46.87	---	74	54	-7.13
17355	H	38.79	---	7.03	45.82	---	68.2	---	-22.38
---	H	---	---	---	---	---	---	---	---
11570	V	44.72	---	2.42	47.14	---	74	54	-6.86
17355	V	39.25	---	7.03	46.28	---	68.2	---	-21.92
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	45.02	---	2.41	47.43	---	74	54	-6.57
17475	H	37.42	---	7.41	44.83	---	68.2	---	-23.37
---	H	---	---	---	---	---	---	---	---
11650	V	44.97	---	2.41	47.38	---	74	54	-6.62
17475	V	39.73	---	7.41	47.14	---	68.2	---	-21.06
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	44.55	---	2.47	47.02	---	74	54	-6.98
17265	H	37.03	---	6.62	43.65	---	68.2	---	-24.55
---	H	---	---	---	---	---	---	---	---
11510	V	44.23	---	2.47	46.70	---	74	54	-7.30
17265	V	38.24	---	6.62	44.86	---	68.2	---	-23.34
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	44.17	---	2.40	46.57	---	74	54	-7.43
17385	H	38.53	---	7.15	45.68	---	68.2	---	-22.52
---	H	---	---	---	---	---	---	---	---
11590	V	44.02	---	2.40	46.42	---	74	54	-7.58
17385	V	37.64	---	7.15	44.79	---	68.2	---	-23.41
---	V	---	---	---	---	---	---	---	---