

TEST REPORT

Applicant Name : Zhuhai Glory Technology Co., Ltd
Address : 8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, China
Report Number : 2504T18085E-RF-00D
FCC ID: 2BMPT-W1E

Test Standard (s)

FCC PART 15.407

Sample Description

Product Type: 5MP Indoor 2.4/5GHz WiFi PT Camera
Model No.: W1E, GL-285BA-N1V1BY, C2
Trade Mark: N/A
Date Received: 2025-08-26
Report Date: 2025-12-04

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Roger Ling

Roger Ling
EMC Engineer

Approved By:

Bob Liao

Bob Liao
EMC Engineer

The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY..... 3

GENERAL INFORMATION..... 4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

 OBJECTIVE 4

 TEST METHODOLOGY 4

 TEST FACILITY 4

SYSTEM TEST CONFIGURATION 5

 DESCRIPTION OF TEST CONFIGURATION..... 5

 EUT EXERCISE SOFTWARE # 5

 EQUIPMENT MODIFICATIONS..... 5

 SUPPORT EQUIPMENT LIST AND DETAILS 5

 EXTERNAL I/O CABLE..... 5

SUMMARY OF TEST RESULTS 6

TEST EQUIPMENT LIST 7

APPLICABLE STANDARDS..... 8

 DFS REQUIREMENT 8

 DFS MEASUREMENT SYSTEM..... 12

 SYSTEM BLOCK DIAGRAM..... 12

 CONDUCTED METHOD 13

 RADIATED METHOD..... 14

 TEST PROCEDURE 14

TEST RESULTS..... 15

 DESCRIPTION OF EUT 15

 TEST DATA 15

CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME 16

 TEST PROCEDURE 16

 TEST DATA..... 16

NON-OCCUPANCY PERIOD 17

 TEST PROCEDURE 17

 TEST DATA..... 17

APPENDIX (TEST RESULTS)..... 18

 APPENDIX A: DFS DETECTION THRESHOLDS 18

 APPENDIX B: CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME 22

 APPENDIX C: NON-OCCUPANCY PERIOD 26

EXHIBIT A-EUT PHOTOGRAPHS 30

EXHIBIT B-TEST SETUP PHOTOGRAPHS 31

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504T18085E-RF-00D	Original Report	2025-12-04

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	5MP Indoor 2.4/5GHz WiFi PT Camera
Tested Model	W1E
Multiple Model	GL-285BA-N1V1BY, C2
Model Difference [#]	Only difference is the model name. Please refer to DOS letter. The applicant provided model "W1E" for testing.
Voltage Range [#]	DC 5V from adapter

Frequency Range	5G Wi-Fi: 5250-5350MHz; 5470-5725MHz
Mode	802.11 a/n20/n40/ac20/ac40/ax20/ax40
Maximum Conducted Average Output Power	5250-5350MHz: 8.82dBm
	5470-5725MHz: 10.07dBm
Modulation Technique	OFDM, OFDMA
Sample Serial Number	330Z-2 (RF Conducted Test) (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition
Note: The device is belong a client device.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC Part 15, Subpart E, section 15.407 Dynamic Frequency Selection (DFS) for devices operating in the bands 5250-5350 MHz, 5470-5725 MHz.

Test Methodology

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02.

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

EUT Exercise Software #

Exercise Software:	Iperf
WLAN traffic is generated by software " Iperf ", software is used by IP and Frame based systems for loading the test channel during the In-service compliance testing of the U-NII device. Data packet streamed from the Access Point to the Client using the software "Iperf".	

Note: The information in the above table is provided by the applicant.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
LENOVO	Laptop	ThinkPad x240	SL10F31638JS
Grand stream Networks, Inc	Router	GWN7665 (FCC ID: YZZGWN7665)	C074AB240E1B

External I/O Cable

Cable Description	Shielding Type	Length (m)	From Port	To
RJ45 cable	NO	1.0	Laptop	Router

SUMMARY OF TEST RESULTS

The following result table represents the list of measurements required under the CFR §47 Part 15.407(h)and KDB: 905462 D02 UNII DFS Compliance Procedures New Rules v02

FCC Rules	Description of Test	Result
Detection Bandwidth	UNII Detection Bandwidth	Not Applicable
Performance Requirements Check	Initial Channel Availability Check Time (CAC)	Not Applicable
	Radar Burst at the Beginning of the CAC	Not Applicable
	Radar Burst at the End of the CAC	Not Applicable
In-Service Monitoring	Channel Move Time	Compliance
	Channel Closing Transmission Time	Compliance
	Non-Occupancy Period	Compliance
Radar Detection	Statistical Performance Check	Not Applicable

Note: EUT is a client without radar detection.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2025/09/17	2026/09/16
AGILENT	Vector Signal Generator	N5182A	MY50143401	2025/09/17	2026/09/16
Rohde & Schwarz	Open Switch and Control Unit	OSP120+OSP-B157	101244+100866	2025/09/17	2026/09/16
Agilent	10dB Attenuator	8491B	A5825	2025/09/18	2026/09/17
HEWLETT PACKARD	20dB Attenuator	8491A	53857	2025/09/18	2026/09/17
Unknown	RF Coaxial Cable	No.31	RF-01	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.32	RF-02	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.33	RF-03	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.34	RF-04	2025/05/30	2026/05/29
Test Software: Tonscend JS1120-3 Test System V3.3.38					

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

APPLICABLE STANDARDS

DFS Requirement

CFR §47 Part 15.407(h) & FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{SEC}}} \right) \right\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

For example if in Short Pulse Radar Type 1 Test B a PRI of 3066 μsec is selected, the number of pulses

would be $\text{Roundup} \left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{3066} \right) \right\} = \text{Roundup} \{17.2\} = 18$.

Table 5a - Pulse Repetition Intervals Values for Test A

Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
1	1930.5	518
2	1858.7	538
3	1792.1	558
4	1730.1	578
5	1672.2	598
6	1618.1	618
7	1567.4	638
8	1519.8	658
9	1474.9	678
10	1432.7	698
11	1392.8	718
12	1355	738
13	1319.3	758
14	1285.3	778
15	1253.1	798
16	1222.5	818
17	1193.3	838
18	1165.6	858
19	1139	878
20	1113.6	898
21	1089.3	918
22	1066.1	938
23	326.2	3066

The aggregate is the average of the percentage of successful detections of Short Pulse Radar Types 1-4. For example, the following table indicates how to compute the aggregate of percentage of successful detections.

Radar Type	Number of Trials	Number of Successful Detections	Minimum Percentage of Successful Detection
1	35	29	82.9%
2	30	18	60%
3	30	27	90%
4	50	44	88%
Aggregate $(82.9\% + 60\% + 90\% + 88\%)/4 = 80.2\%$			

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per <i>Burst</i>	Number of <i>Bursts</i>	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30


Table 7 – Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30


DFS Measurement System

DFS measurement system consists of two subsystems: (1) The radar signal generating subsystem and (2) the traffic monitoring subsystem.


System Block Diagram




Conducted Method



Setup for Master with injection at the Master




Setup for Client with injection at the Master



Setup for Client with injection at the Client

Radiated Method



Test Procedure

A spectrum analyzer is used as a monitor verifies that the EUT status including Channel Closing Transmission Time, Channel Move Time and Non-Occupancy Period.

TEST RESULTS

Description of EUT

The calibrated radiated DFS detection threshold level is set to -62 dBm.

Test Data

Please refer to the Appendix A.

CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME

Test Procedure

Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. repeat using a long pulse radar type5 waveform.

The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time = $N \times \text{Dwell Time}$

N is the number of spectrum analyzer bins showing a device transmission Dwell Time is the dwell time per bin (i.e. $\text{Dwell Time} = S/B$, S is the sweep time and B is the number of bin, i.e. 8192)

Test Data

Please refer to the Appendix B.

NON-OCCUPANCY PERIOD

Test Procedure

Measure the EUT for more than 30 minutes following the channel close/move time to verify that the EUT does not resume any transmissions on this channel. Provide one plot to demonstrate no transmission on the channel for the non-occupancy period (30 minutes observation time)

Test Data

Please refer to the Appendix C.

APPENDIX (TEST RESULTS)

Appendix A: DFS Detection Thresholds

Test Information:

Sample No.:	330Z-2	Test Date:	2025/12/03
Test Site:	RF	Test Mode:	Traffic
Tester:	Cayde Hou	Test Result:	Pass


Environmental Conditions:


Temperature: (°C)	23.6	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	----	------------------------	-------

Test Result

Frequency[MHz]	Radar Type	Result	Limit[dBm]	Verdict
5260	Type0	-62.05	-62.00	PASS
5500	Type0	-62.07	-62.00	PASS
5270	Type0	-62.46	-62.00	PASS
5510	Type0	-62.29	-62.00	PASS

Test Graphs





Appendix B: Channel Move Time and Channel Closing Transmission Time

Test Information:

Sample No.:	330Z-2	Test Date:	2025/12/03
Test Site:	RF	Test Mode:	Traffic
Tester:	Cayde Hou	Test Result:	Pass


Environmental Conditions:


Temperature: (°C)	23.6	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	----	------------------------	-------

Test Result

Test Mode	Frequency[MHz]	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
11AX20SISO	5260	200+9.1	200+60	431.5	10000	PASS
	5500	200+9.1	200+60	425	10000	PASS
11AX40SISO	5270	200+11.7	200+60	564.2	10000	PASS
	5510	200+32.5	200+60	624	10000	PASS

Test Graphs





Appendix C: Non-Occupancy Period

Test Information:

Sample No.:	330Z-2	Test Date:	2025/12/03
Test Site:	RF	Test Mode:	Traffic
Tester:	Cayde Hou	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	23.6	Relative Humidity: (%)	49	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	----	------------------------	-------

Test Result

Test Mode	Frequency[MHz]	Result	Limit[s]	Verdict
11AX20SISO	5260	see test graph	≥1800	PASS
	5500	see test graph	≥1800	PASS
11AX40SISO	5270	see test graph	≥1800	PASS
	5510	see test graph	≥1800	PASS

Test Graphs






EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2504T18085E-RF EUT External Photos and Attachment No.2 2504T18085E-RF EUT Internal Photos.

EXHIBIT B-TEST SETUP PHOTOGRAPHS

Please refer to the Attachment No.4 2504T18085E-RF-00D Test Photos.

******* END OF REPORT *******