



FCC RF EXPOSURE REPORT

Applicant	:	Hunter Douglas Europe B.V.
Address of Applicant	:	Blaak 555, 3011 GB Rotterdam, The Netherlands
Manufacturer	:	Hunter Douglas Europe B.V.
Address of Manufacturer	:	Blaak 555, 3011 GB Rotterdam, The Netherlands
Equipment under Test	:	Remote control
Model No.	:	RW5-G2, RW14-G2
FCC ID	:	2BMQ2RW5RW14
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-Q24111123-1E02
Issue Date	:	2024/12/23
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd.
Address of Laboratory	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

Test report declares.....3

1. General Information 5

1.1. Description of equipment 5

1.2. Assess laboratory..... 5

2. RF Exposure evaluation for FCC 6

Test Report Declare

Applicant	:	Hunter Douglas Europe B.V.
Address of Applicant	:	Blaak 555, 3011 GB Rotterdam, The Netherlands
Equipment under Test	:	Remote control
Model No.	:	RW5-G2, RW14-G2
Manufacturer	:	Hunter Douglas Europe B.V.
Address of Manufacturer	:	Blaak 555, 3011 GB Rotterdam, The Netherlands

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-Q24111123-1E		
Date of Receipt:	2024/11/21	Date of Test:	2024/11/21~2024/12/23

Prepared By:

Johnson Huang

Johnson Huang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/12/23	

1. General Information

1.1. Description of equipment

EUT Name	: Remote control
Model Number	: RW5-G2, RW14-G2
Difference of model number	: All models are identical except the display screen and model name, therefore the test performed on the model RW14-G2.
EUT function description	: Please reference user manual of this device
Power supply	: DC 3V From Button cell
Operation frequency	: 433.92MHz
Modulation	: ASK
Antenna Type	: PCB
Sample Number	: S24111123-003

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance

SRD

GFSK (Peak)	
Frequency (MHz)	433.92
Target (dBm)	-13.59
Tolerance $\pm$ (dB)	2

Note:

PK Output Power=81.61dBuV/m@3m-95.2= -13.59dBm

Please refer to the test report "DDT-Q24111123-1E01"

Estimtion Result

Worse case is as below: [433.92 MHz, -11.59 dBm, (0.0693 mW) output power]

$(0.0693 / 5) \cdot [\sqrt{0.43392(\text{GHz})}] = 0.00913 < 3.0$ for 1-g SAR

Then SAR evaluation is not required.

END OF REPORT