

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: **2BMUF-TL-4KTG**

EUT Specification

EUT	TG MAXX
Frequency band (Operating)	☒ BT: 2.402GHz ~ 2.480GHz ☒ BLE: 2.402GHz ~ 2.480GHz ☒ WIFI: 2.412GHz ~ 2.462GHz ☒ WIFI: 5.180GHz ~ 5.240GHz ☒ WIFI: 5.260GHz ~ 5.320GHz ☒ WIFI: 5.500GHz ~ 5.700GHz ☒ WIFI: 5.745GHz ~ 5.825GHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	BT DH5: 4.81 dBm 2DH5: 5.72 dBm 3DH5: 6.00 dBm BLE BLE 1M: -2.65 dBm BLE 2M: -2.63 dBm 2.4G WIFI IEEE 802.11b: 14.52 dBm IEEE 802.11g: 14.26 dBm IEEE 802.11n HT20: 14.77 dBm IEEE 802.11n HT40: 14.64 dBm IEEE 802.11ax HE20: 14.58 dBm IEEE 802.11ax HE40: 13.85 dBm 5G WIFI

	U-NII-1 IEEE 802.11a: 13.88 dBm IEEE 802.11n HT20: 15.46 dBm IEEE 802.11n HT40: 14.58 dBm IEEE 802.11ac VHT20: 14.69 dBm IEEE 802.11ac VHT40: 13.52 dBm IEEE 802.11ac VHT80: 14.14 dBm IEEE 802.11ax HE20: 15.05 dBm IEEE 802.11ax HE40: 13.87 dBm IEEE 802.11ax HE80: 12.91 dBm U-NII-2A IEEE 802.11a: 15.01 dBm IEEE 802.11n HT20: 15.69 dBm IEEE 802.11n HT40: 14.40 dBm IEEE 802.11ac VHT20: 13.54 dBm IEEE 802.11ac VHT40: 13.07 dBm IEEE 802.11ac VHT80: 14.13 dBm IEEE 802.11ax HE20: 14.20 dBm IEEE 802.11ax HE40: 14.11 dBm IEEE 802.11ax HE80: 12.85 dBm U-NII-2C IEEE 802.11a: 14.38 dBm IEEE 802.11n HT20: 15.64 dBm IEEE 802.11n HT40: 14.47 dBm IEEE 802.11ac VHT20: 15.45 dBm IEEE 802.11ac VHT40: 15.14 dBm IEEE 802.11ac VHT80: 14.06 dBm IEEE 802.11ax HE20: 14.20 dBm IEEE 802.11ax HE40: 14.63 dBm IEEE 802.11ax HE80: 14.11 dBm U-NII-3 IEEE 802.11a: 14.52 dBm IEEE 802.11n HT20: 15.67 dBm IEEE 802.11n HT40: 14.97 dBm IEEE 802.11ac VHT20: 15.25 dBm IEEE 802.11ac VHT40: 15.17 dBm IEEE 802.11ac VHT80: 13.08 dBm IEEE 802.11ax HE20: 14.81 dBm IEEE 802.11ax HE40: 13.76 dBm IEEE 802.11ax HE80: 13.54 dBm
Antenna gain (Max)	BT: 1.11 dBi BLE: 1.11 dBi 2.4G WIFI 3.56 dBi for antenna 1,

	2.26 dBi for antenna 2, 5G WIFI 4.32 dBi for antenna 1, 3.74 dBi for antenna 2,
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm², P_{out} = output power to antenna in mW.

G = gain of antenna in linear scale, $\pi = 3.1416$

R = distance between observation point and center of the radiator in cm = 20cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$Evaluated_k$: the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure Limit_k$: either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each

fixed, mobile, or portable RF source k.

Measurement Result

BT:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
DH5	4.81	5±1	6	3.981	1.11	1.291	0.001023	1	PASS
2DH5	5.72	6±1	7	5.012	1.11	1.291	0.001287	1	PASS
3DH5	6.00	6±1	7	5.012	1.11	1.291	0.001287	1	PASS

BLE:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
BLE 1M	-2.65	-3±1	-2	0.631	1.11	1.291	0.000162	1	PASS
BLE 2M	-2.63	-3±1	-2	0.631	1.11	1.291	0.000162	1	PASS

2.4G WIFI:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
802.11b	14.52	15±1	16	39.811	3.56	2.270	0.017977	1	PASS
802.11g	14.26	14±1	15	31.623	3.56	2.270	0.014280	1	PASS
802.11n HT20	14.77	15±1	16	39.811	3.56	2.270	0.017977	1	PASS
802.11n HT40	14.64	15±1	16	39.811	3.56	2.270	0.017977	1	PASS
802.11ax HE20	14.58	15±1	16	39.811	3.56	2.270	0.017977	1	PASS
802.11ax HE40	13.85	14±1	15	31.623	3.56	2.270	0.014280	1	PASS

5G WIFI:

U-NII-1

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
802.11a	13.88	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11n HT20	15.46	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11n HT40	14.58	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT20	14.69	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT40	13.52	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ac VHT80	14.14	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE20	15.05	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ax HE40	13.87	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE80	12.91	13±1	14	25.119	4.32	2.704	0.013512	1	PASS

U-NII-2A

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
802.11a	15.01	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11n HT20	15.69	16±1	17	50.119	4.32	2.704	0.026960	1	PASS
802.11n HT40	14.40	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ac VHT20	13.54	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ac VHT40	13.07	13±1	14	25.119	4.32	2.704	0.013512	1	PASS
802.11ac VHT80	14.13	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE20	14.20	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE40	14.11	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE80	12.85	13±1	14	25.119	4.32	2.704	0.013512	1	PASS

U-NII-2C

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
802.11a	14.38	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11n HT20	15.64	16±1	17	50.119	4.32	2.704	0.026960	1	PASS
802.11n HT40	14.47	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ac VHT20	15.45	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT40	15.14	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT80	14.06	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE20	14.20	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE40	14.63	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ax HE80	14.11	14±1	15	31.623	4.32	2.704	0.017011	1	PASS

U-NII-3

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)	Results
802.11a	14.52	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11n HT20	15.67	16±1	17	50.119	4.32	2.704	0.026960	1	PASS
802.11n HT40	14.97	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT20	15.25	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT40	15.17	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ac VHT80	13.08	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE20	14.81	15±1	16	39.811	4.32	2.704	0.021415	1	PASS
802.11ax HE40	13.76	14±1	15	31.623	4.32	2.704	0.017011	1	PASS
802.11ax HE80	13.54	14±1	15	31.623	4.32	2.704	0.017011	1	PASS

Maximum Simultaneous transmission MPE Ratio for Bluetooth & 2.4G WIFI & 5G WIFI

Maximum MPE ratio (Bluetooth)	Maximum MPE ratio (2.4G WIFI)	Maximum MPE ratio (5G WIFI)	Σ MPE ratios	Limit	Results
0.001287	0.017977	0.026960	0.046224	1.000	Pass

Signature:



Shawn Wen

Date: 2025-11-14