



深圳市楚风通讯技术有限公司

Shenzhen ChuFeng communication technology co., LTD

深圳市宝安区石岩街道羊台山路51号黎光新永丰工业园5楼A

5F A, Licuang XinYongfeng Industrial Park, No.51 Yangtaishan Road, Shiyan Street, Baoan District, Shenzhen

产品规格书

SPECIFICATION FOR APPROVAL

目录

Directory

1 、产品说明	Product Description.....	3
2 、产品图片	Product Picture.....	3
3 、产品规格	Product Specifications.....	4
4 、测试环境	Test environment.....	5
5 、环境可靠性测试	Environmental Performance.....	6
6 、测试数据	Test data.....	7

1 、产品说明 Product Description

客户名:	
整机类型 type:	胶棒天线 Glue stick antenna
天线频段Band:	2400-2500MHZ
天线形式 type:	外置天线External antenna
馈电形式:	焊接 w e l d i n g
馈脚数量:	/
硬件版本:	V1

2 、产品图片 Product Picture



3 、产品规格 Product Specifications

无源电性能指标 Passive Electrical Specifications	
频率范围 Frequency Range (MHz)	2400-2500
输入阻抗 Input Impedence (Ω)	50
电压驻波比 VSWR	≤ 2
增益 GAIN(dBi)	2.73

机械指标 Mechanical Specifications	
工作温度 Working Temperature ($^{\circ}$ C)	-30—+80
颜色 Line color	黑色
天线尺寸 Antenna size (MM)	84
接口型号 Interface type	IPEX1
连接总线长Connection bus length(MM)	100

4 、测试环境 Test environment


网络分析仪：ZVB8

Network Analyzer:5071c

综合测试仪：Comprehensive tester: R&S CMW500(2/3/4G/NB-IoT/WIFI/BT);

微波暗室：5G SISO/MIMO, 400 MHz - 8.0 GHz

RayZone® 2800 Chamber 5G (FR1) SISO/MIMO, 400 MHz - 8.0 GHz



5 、环境可靠性测试 Environmental Performance


环境可靠性测试/Environmental Performance		
测试项目 Test Description	测试程序和条件 Test Procedures & Condition	测试要求 Requirements
温湿测试 Humidity Temperature Cycling	(Decay Test Conditions) : 温度:-20°C-80 °C Temperature : -20°C-80 °C 湿度: 0%-90% (Humidity:0%-90% R.H) 持续时间:持续时间:室内72 小时室外96小时 Duration : 72 hours indoors 96 hours outdoors	1, 外观良好 (No evidence of damage) 2, 电气性能符合产品规格要 求 (The electrical performances should meet the spec. specified)
高温试验 High temperature test	测试条件 (Decay Test Conditions) : 温 度: 60°C- 80°C (Temperature:60°C- 85°C) 持续时间:室内72小时 室外96小时 Duration : 72 hours indoors 96 hours outdoors	1. 外观良好 (No evidence of damage) 2. 电气性能符合产品规格要 求 (The electrical performances should meet the spec. specified)
低温试验 Low Temperature test	测试条件 (Decay Test Conditions) : 温 度:-20°C-40°C (Temperature:-20°C-40°C) 持续时间:室内72小时 室外96小时 Duration : 72 hours indoors 96 hours outdoors	1. 外观良好 (No evidence of damage) 2. 电气性能符合产品规格要 求 (The electrical performances should meet the spec. specified)

6 、测试数据 Test data

VSWR/LOSS/电压驻波/损失

E5071C Network Analyzer


1 Active Ch/Trace 2 Response 3 Stimulus 4 Mkr/Analysis 5 Instr State




Frequency/Mhz	MaxGain/dBi	Efficiency / %
2400	2.04	67.61
2410	1.38	62.23
2420	2.16	68.71
2430	1.26	65.31
2440	1.88	69.02
2450	1.8	69.34
2460	1.49	68.39
2470	2.21	72.78
2480	1.71	67.14
2490	2.73	72.78
2500	1.72	67.76

方向辐射图 Radiation Patterns

2400MHZ



2450MHZ



2500MHZ

