

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.137	73.08	-20.24	52.84	74	-21.16	PK
Vertical	4679.137	59.22	-20.24	38.98	54	-15.02	AV
Vertical	11490.138	64.39	-8.79	55.60	68.2	-12.60	PK
Vertical	11490.138	49.66	-8.79	40.87	54	-13.13	AV
Vertical	17235.048	58.71	-3.18	55.53	68.2	-12.67	PK
Vertical	17235.048	44.11	-3.18	40.93	54	-13.07	AV
Horizontal	4679.016	70.81	-20.73	50.08	74	-23.92	PK
Horizontal	4679.016	59.70	-20.73	38.97	54	-15.03	AV
Horizontal	11490.039	64.23	-8.79	55.44	68.2	-12.76	PK
Horizontal	11490.039	49.40	-8.79	40.61	54	-13.39	AV
Horizontal	17235.011	59.08	-3.18	55.90	68.2	-12.30	PK
Horizontal	17235.011	44.51	-3.18	41.33	54	-12.67	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.168	70.31	-20.42	49.89	74	-24.11	PK
Vertical	4592.168	59.91	-20.42	39.49	54	-14.51	AV
Vertical	11570.084	62.75	-8.86	53.89	68.2	-14.31	PK
Vertical	11570.084	49.35	-8.86	40.49	54	-13.51	AV
Vertical	17355.197	57.71	-2.52	55.19	68.2	-13.01	PK
Vertical	17355.197	44.19	-2.52	41.67	54	-12.33	AV
Horizontal	4592.154	74.13	-20.42	53.72	74	-20.28	PK
Horizontal	4592.154	59.89	-20.42	39.48	54	-14.52	AV
Horizontal	11570.034	60.67	-8.86	51.81	68.2	-16.39	PK
Horizontal	11570.034	49.77	-8.86	40.91	54	-13.09	AV
Horizontal	17355.021	55.35	-2.52	52.83	68.2	-15.37	PK
Horizontal	17355.021	44.58	-2.52	42.06	54	-11.94	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.176	74.33	-18.93	55.40	68.2	-12.80	PK
Vertical	6039.176	60.00	-18.93	41.07	54	-12.93	AV
Vertical	11650.193	60.70	-8.92	51.78	74	-22.22	PK
Vertical	11650.193	49.44	-8.92	40.52	54	-13.48	AV
Vertical	17475.002	58.61	-1.86	56.75	68.2	-11.45	PK
Vertical	17475.002	44.86	-1.86	43.00	54	-11.00	AV
Horizontal	6039.171	70.38	-18.93	51.45	68.2	-16.75	PK
Horizontal	6039.171	59.11	-18.93	40.18	54	-13.82	AV
Horizontal	11650.152	64.11	-8.92	55.19	74	-18.81	PK
Horizontal	11650.152	49.19	-8.92	40.27	54	-13.73	AV
Horizontal	17475.124	55.77	-1.86	53.91	68.2	-14.29	PK
Horizontal	17475.124	44.64	-1.86	42.78	54	-11.22	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.018	72.49	-20.24	52.25	74	-21.75	PK
Vertical	4679.018	59.23	-20.24	38.99	54	-15.01	AV
Vertical	11490.165	61.73	-8.79	52.94	68.2	-15.26	PK
Vertical	11490.165	49.19	-8.79	40.40	54	-13.60	AV
Vertical	17235.165	58.80	-3.18	55.62	68.2	-12.58	PK
Vertical	17235.165	44.89	-3.18	41.71	54	-12.29	AV
Horizontal	4679.112	73.71	-20.24	53.46	74	-20.54	PK
Horizontal	4679.112	59.99	-20.24	39.75	54	-14.25	AV
Horizontal	11490.128	63.71	-8.79	54.92	68.2	-13.28	PK
Horizontal	11490.128	49.78	-8.79	40.99	54	-13.01	AV
Horizontal	17235.044	59.29	-3.18	56.11	68.2	-12.09	PK
Horizontal	17235.044	44.31	-3.18	41.13	54	-12.87	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.050	73.63	-20.42	53.21	74	-20.79	PK
Vertical	4592.050	59.68	-20.42	39.26	54	-14.74	AV
Vertical	11570.137	60.86	-8.86	52.00	68.2	-16.20	PK
Vertical	11570.137	49.82	-8.86	40.96	54	-13.04	AV
Vertical	17355.189	59.24	-2.52	56.72	68.2	-11.48	PK
Vertical	17355.189	44.74	-2.52	42.22	54	-11.78	AV
Horizontal	4592.159	72.73	-20.42	52.31	74	-21.69	PK
Horizontal	4592.159	59.26	-20.42	38.85	54	-15.15	AV
Horizontal	11570.008	64.22	-8.86	55.36	68.2	-12.84	PK
Horizontal	11570.008	49.98	-8.86	41.12	54	-12.88	AV
Horizontal	17355.009	57.31	-2.52	54.79	68.2	-13.41	PK
Horizontal	17355.009	44.23	-2.52	41.71	54	-12.29	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.034	70.15	-18.93	51.22	68.2	-16.98	PK
Vertical	6039.034	59.41	-18.93	40.47	54	-13.53	AV
Vertical	11650.026	60.80	-8.92	51.88	74	-22.12	PK
Vertical	11650.026	49.98	-8.92	41.06	54	-12.94	AV
Vertical	17475.186	56.40	-1.86	54.54	68.2	-13.66	PK
Vertical	17475.186	44.59	-1.86	42.73	54	-11.27	AV
Horizontal	6039.092	73.72	-18.93	54.78	68.2	-13.42	PK
Horizontal	6039.092	59.48	-18.93	40.55	54	-13.45	AV
Horizontal	11650.168	62.90	-8.92	53.98	74	-20.02	PK
Horizontal	11650.168	49.09	-8.92	40.17	54	-13.83	AV
Horizontal	17475.037	58.28	-1.86	56.42	68.2	-11.78	PK
Horizontal	17475.037	44.73	-1.86	42.87	54	-11.13	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.159	74.49	-20.24	54.25	74	-19.75	PK
Vertical	4679.159	59.49	-20.24	39.25	54	-14.75	AV
Vertical	11510.180	64.73	-8.81	55.92	74	-18.08	PK
Vertical	11510.180	49.79	-8.81	40.98	54	-13.02	AV
Vertical	17265.081	59.13	-3.01	56.12	68.2	-12.08	PK
Vertical	17265.081	44.23	-3.01	41.22	54	-12.78	AV
Horizontal	4679.075	72.20	-20.24	51.96	74	-22.04	PK
Horizontal	4679.075	59.48	-20.24	39.23	54	-14.77	AV
Horizontal	11510.063	61.88	-8.81	53.07	74	-20.93	PK
Horizontal	11510.063	49.86	-8.81	41.05	54	-12.95	AV
Horizontal	17265.117	58.79	-3.01	55.78	68.2	-12.42	PK
Horizontal	17265.117	44.29	-3.01	41.28	54	-12.72	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.134	70.18	-18.93	51.25	68.2	-16.95	PK
Vertical	6039.134	59.97	-18.93	41.04	54	-12.96	AV
Vertical	11590.139	63.56	-8.87	54.69	74	-19.31	PK
Vertical	11590.139	49.20	-8.87	40.33	54	-13.67	AV
Vertical	17385.062	57.75	-2.35	55.40	68.2	-12.80	PK
Vertical	17385.062	44.63	-2.35	42.28	54	-11.72	AV
Horizontal	6039.194	73.37	-18.93	54.43	68.2	-13.77	PK
Horizontal	6039.194	59.43	-18.93	40.50	54	-13.50	AV
Horizontal	11590.076	64.85	-8.87	55.98	74	-18.02	PK
Horizontal	11590.076	50.00	-8.87	41.13	54	-12.87	AV
Horizontal	17385.145	57.57	-2.35	55.22	68.2	-12.98	PK
Horizontal	17385.145	44.61	-2.35	42.26	54	-11.74	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ac-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.184	70.99	-20.24	50.75	74	-23.25	PK
Vertical	4679.184	59.33	-20.24	39.09	54	-14.91	AV
Vertical	11490.089	61.46	-8.79	52.67	68.2	-15.53	PK
Vertical	11490.089	49.76	-8.79	40.97	54	-13.03	AV
Vertical	17235.130	57.09	-3.18	53.91	68.2	-14.29	PK
Vertical	17235.130	44.86	-3.18	41.68	54	-12.32	AV
Horizontal	4679.052	73.83	-20.24	53.58	74	-20.42	PK
Horizontal	4679.052	59.88	-20.24	39.63	54	-14.37	AV
Horizontal	11490.124	63.88	-8.79	55.09	68.2	-13.11	PK
Horizontal	11490.124	49.15	-8.79	40.36	54	-13.64	AV
Horizontal	17235.174	57.90	-3.18	54.72	68.2	-13.48	PK
Horizontal	17235.174	44.45	-3.18	41.27	54	-12.73	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.062	72.27	-20.42	51.85	74	-22.15	PK
Vertical	4592.062	59.26	-20.42	38.85	54	-15.15	AV
Vertical	11570.176	64.23	-8.86	55.37	68.2	-12.83	PK
Vertical	11570.176	49.82	-8.86	40.96	54	-13.04	AV
Vertical	17355.034	56.76	-2.52	54.24	68.2	-13.96	PK
Vertical	17355.034	44.96	-2.52	42.44	54	-11.56	AV
Horizontal	4592.108	70.02	-20.42	49.61	74	-24.39	PK
Horizontal	4592.108	59.54	-20.42	39.12	54	-14.88	AV
Horizontal	11570.077	62.17	-8.86	53.31	68.2	-14.89	PK
Horizontal	11570.077	49.22	-8.86	40.36	54	-13.64	AV
Horizontal	17355.141	59.98	-2.52	57.46	68.2	-10.74	PK
Horizontal	17355.141	44.53	-2.52	42.01	54	-11.99	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.149	70.11	-18.93	51.18	68.2	-17.02	PK
Vertical	6039.149	59.62	-18.93	40.68	54	-13.32	AV
Vertical	11650.198	62.26	-8.92	53.34	74	-20.66	PK
Vertical	11650.198	49.83	-8.92	40.91	54	-13.09	AV
Vertical	17475.063	59.04	-1.86	57.18	68.2	-11.02	PK
Vertical	17475.063	44.02	-1.86	42.16	54	-11.84	AV
Horizontal	6039.183	73.42	-18.93	54.49	68.2	-13.71	PK
Horizontal	6039.183	59.82	-18.93	40.89	54	-13.11	AV
Horizontal	11650.050	63.66	-8.92	54.74	74	-19.26	PK
Horizontal	11650.050	49.09	-8.92	40.17	54	-13.83	AV
Horizontal	17475.136	57.73	-1.86	55.87	68.2	-12.33	PK
Horizontal	17475.136	44.07	-1.86	42.21	54	-11.79	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ac-HT40
-------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.050	70.75	-20.24	50.51	74	-23.49	PK
Vertical	4679.050	59.28	-20.24	39.04	54	-14.96	AV
Vertical	11510.061	60.66	-8.81	51.85	74	-22.15	PK
Vertical	11510.061	49.52	-8.81	40.71	54	-13.29	AV
Vertical	17265.160	56.81	-3.01	53.80	68.2	-14.40	PK
Vertical	17265.160	44.62	-3.01	41.61	54	-12.39	AV
Horizontal	4679.001	70.34	-20.24	50.10	74	-23.90	PK
Horizontal	4679.001	59.99	-20.24	39.75	54	-14.25	AV
Horizontal	11510.036	61.85	-8.81	53.04	74	-20.96	PK
Horizontal	11510.036	49.69	-8.81	40.88	54	-13.12	AV
Horizontal	17265.109	59.97	-3.01	56.96	68.2	-11.24	PK
Horizontal	17265.109	44.54	-3.01	41.53	54	-12.47	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.131	73.68	-18.93	54.75	68.2	-13.45	PK
Vertical	6039.131	59.58	-18.93	40.64	54	-13.36	AV
Vertical	11590.041	62.97	-8.87	54.10	74	-19.90	PK
Vertical	11590.041	49.66	-8.87	40.79	54	-13.21	AV
Vertical	17385.081	56.14	-2.35	53.79	68.2	-14.41	PK
Vertical	17385.081	44.35	-2.35	42.00	54	-12.00	AV
Horizontal	6039.050	74.29	-18.93	55.35	68.2	-12.85	PK
Horizontal	6039.050	59.64	-18.93	40.71	54	-13.29	AV
Horizontal	11590.142	60.21	-8.87	51.34	74	-22.66	PK
Horizontal	11590.142	49.78	-8.87	40.91	54	-13.09	AV
Horizontal	17385.153	55.37	-2.35	53.02	68.2	-15.18	PK
Horizontal	17385.153	44.13	-2.35	41.78	54	-12.22	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ac 80
-------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5775 MHz)-Above 1G							
Vertical	4679.023	70.45	-20.24	50.21	74	-23.79	PK
Vertical	4679.023	59.55	-20.24	39.31	54	-14.69	AV
Vertical	11550.097	64.28	-8.84	55.44	74	-18.56	PK
Vertical	11550.097	49.17	-8.84	40.33	54	-13.67	AV
Vertical	17325.198	59.11	-2.68	56.43	68.2	-11.77	PK
Vertical	17325.198	44.56	-2.68	41.88	54	-12.12	AV
Horizontal	4679.048	73.87	-20.24	53.63	74	-20.37	PK
Horizontal	4679.048	59.34	-20.24	39.09	54	-14.91	AV
Horizontal	11550.063	61.48	-8.84	52.64	74	-21.36	PK
Horizontal	11550.063	49.55	-8.84	40.71	54	-13.29	AV
Horizontal	17325.193	59.66	-2.68	56.98	68.2	-11.22	PK
Horizontal	17325.193	44.18	-2.68	41.50	54	-12.50	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ax-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.060	73.89	-20.24	53.65	74	-20.35	PK
Vertical	4679.060	59.73	-20.24	39.49	54	-14.51	AV
Vertical	11490.035	60.64	-8.79	51.85	68.2	-16.35	PK
Vertical	11490.035	49.55	-8.79	40.76	54	-13.24	AV
Vertical	17235.041	56.01	-3.18	52.83	68.2	-15.37	PK
Vertical	17235.041	44.44	-3.18	41.26	54	-12.74	AV
Horizontal	4679.110	71.09	-20.24	50.85	74	-23.15	PK
Horizontal	4679.110	59.66	-20.24	39.42	54	-14.58	AV
Horizontal	11490.013	64.94	-8.79	56.15	68.2	-12.05	PK
Horizontal	11490.013	49.56	-8.79	40.77	54	-13.23	AV
Horizontal	17235.029	59.25	-3.18	56.07	68.2	-12.13	PK
Horizontal	17235.029	44.21	-3.18	41.03	54	-12.97	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.148	73.21	-20.42	52.80	74	-21.20	PK
Vertical	4592.148	59.57	-20.42	39.15	54	-14.85	AV
Vertical	11570.187	63.83	-8.86	54.97	68.2	-13.23	PK
Vertical	11570.187	49.44	-8.86	40.58	54	-13.42	AV
Vertical	17355.139	59.39	-2.52	56.87	68.2	-11.33	PK
Vertical	17355.139	44.60	-2.52	42.08	54	-11.92	AV
Horizontal	4592.165	71.06	-20.42	50.64	74	-23.36	PK
Horizontal	4592.165	59.83	-20.42	39.41	54	-14.59	AV
Horizontal	11570.146	63.10	-8.86	54.24	68.2	-13.96	PK
Horizontal	11570.146	49.01	-8.86	40.15	54	-13.85	AV
Horizontal	17355.095	55.50	-2.52	52.98	68.2	-15.22	PK
Horizontal	17355.095	44.41	-2.52	41.89	54	-12.11	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.064	71.28	-18.93	52.35	68.2	-15.85	PK
Vertical	6039.064	59.18	-18.93	40.25	54	-13.75	AV
Vertical	11650.150	60.55	-8.92	51.63	74	-22.37	PK
Vertical	11650.150	49.19	-8.92	40.27	54	-13.73	AV
Vertical	17475.055	58.91	-1.86	57.05	68.2	-11.15	PK
Vertical	17475.055	44.43	-1.86	42.57	54	-11.43	AV
Horizontal	6039.106	74.10	-18.93	55.17	68.2	-13.03	PK
Horizontal	6039.106	59.60	-18.93	40.67	54	-13.33	AV
Horizontal	11650.024	63.14	-8.92	54.22	74	-19.78	PK
Horizontal	11650.024	49.20	-8.92	40.28	54	-13.72	AV
Horizontal	17475.029	57.91	-1.86	56.05	68.2	-12.15	PK
Horizontal	17475.029	44.14	-1.86	42.28	54	-11.72	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ax-HT40
-------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.038	70.60	-20.24	50.36	74	-23.64	PK
Vertical	4679.038	59.60	-20.24	39.36	54	-14.64	AV
Vertical	11510.153	63.55	-8.81	54.74	74	-19.26	PK
Vertical	11510.153	49.76	-8.81	40.95	54	-13.05	AV
Vertical	17265.056	56.71	-3.01	53.70	68.2	-14.50	PK
Vertical	17265.056	44.96	-3.01	41.95	54	-12.05	AV
Horizontal	4679.015	74.38	-20.24	54.14	74	-19.86	PK
Horizontal	4679.015	59.20	-20.24	38.95	54	-15.05	AV
Horizontal	11510.009	64.16	-8.81	55.35	74	-18.65	PK
Horizontal	11510.009	49.77	-8.81	40.96	54	-13.04	AV
Horizontal	17265.103	57.95	-3.01	54.94	68.2	-13.26	PK
Horizontal	17265.103	44.33	-3.01	41.32	54	-12.68	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.144	72.77	-18.93	53.84	68.2	-14.36	PK
Vertical	6039.144	59.78	-18.93	40.85	54	-13.15	AV
Vertical	11590.057	64.88	-8.87	56.01	74	-17.99	PK
Vertical	11590.057	49.77	-8.87	40.90	54	-13.10	AV
Vertical	17385.084	57.24	-2.35	54.89	68.2	-13.31	PK
Vertical	17385.084	44.20	-2.35	41.85	54	-12.15	AV
Horizontal	6039.007	73.84	-18.93	54.91	68.2	-13.29	PK
Horizontal	6039.007	59.42	-18.93	40.49	54	-13.51	AV
Horizontal	11590.188	63.78	-8.87	54.91	74	-19.09	PK
Horizontal	11590.188	49.67	-8.87	40.80	54	-13.20	AV
Horizontal	17385.198	58.19	-2.35	55.84	68.2	-12.36	PK
Horizontal	17385.198	44.82	-2.35	42.47	54	-11.53	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ax 80
-------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5775 MHz)-Above 1G							
Vertical	4679.160	73.14	-20.24	52.90	74	-21.10	PK
Vertical	4679.160	59.20	-20.24	38.96	54	-15.04	AV
Vertical	11550.051	60.79	-8.84	51.95	74	-22.05	PK
Vertical	11550.051	49.27	-8.84	40.43	54	-13.57	AV
Vertical	17325.149	58.80	-2.68	56.12	68.2	-12.08	PK
Vertical	17325.149	44.04	-2.68	41.36	54	-12.64	AV
Horizontal	4679.005	74.11	-20.24	53.86	74	-20.14	PK
Horizontal	4679.005	59.89	-20.24	39.64	54	-14.36	AV
Horizontal	11550.188	63.60	-8.84	54.76	74	-19.24	PK
Horizontal	11550.188	49.54	-8.84	40.70	54	-13.30	AV
Horizontal	17325.033	58.10	-2.68	55.42	68.2	-12.78	PK
Horizontal	17325.033	44.15	-2.68	41.47	54	-12.53	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Between 1GHz – 40GHz

ANT 2

Test Mode:	TX(5.1G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.119	70.06	-20.73	49.33	68.20	-18.87	PK
Vertical	4434.119	59.48	-20.73	38.75	54.00	-15.25	AV
Vertical	10360.063	63.98	-9.36	54.62	68.20	-13.58	PK
Vertical	10360.063	49.53	-9.36	40.17	54.00	-13.83	AV
Vertical	15540.186	63.91	-7.84	56.07	74.00	-17.93	PK
Vertical	15540.186	49.01	-7.84	41.17	54.00	-12.83	AV
Horizontal	4434.042	70.72	-20.73	49.99	68.20	-18.21	PK
Horizontal	4434.042	59.58	-20.73	38.85	54.00	-15.15	AV
Horizontal	10360.073	63.70	-9.36	54.34	68.20	-13.86	PK
Horizontal	10360.073	49.30	-9.36	39.94	54.00	-14.06	AV
Horizontal	15540.031	61.34	-7.84	53.50	74.00	-20.50	PK
Horizontal	15540.031	49.16	-7.84	41.32	54.00	-12.68	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.068	69.31	-20.42	48.89	74.00	-25.11	PK
Vertical	4592.068	59.03	-20.42	38.61	54.00	-15.39	AV
Vertical	10400.180	61.87	-9.30	52.57	68.20	-15.63	PK
Vertical	10400.180	49.86	-9.30	40.56	54.00	-13.44	AV
Vertical	15600.155	64.42	-7.82	56.60	74.00	-17.40	PK
Vertical	15600.155	49.06	-7.82	41.24	54.00	-12.76	AV
Horizontal	4592.176	74.52	-20.42	54.10	74.00	-19.90	PK
Horizontal	4592.176	59.33	-20.42	38.91	54.00	-15.09	AV
Horizontal	10400.040	63.03	-9.30	53.73	68.20	-14.47	PK
Horizontal	10400.040	49.37	-9.30	40.07	54.00	-13.93	AV
Horizontal	15600.077	60.09	-7.82	52.27	74.00	-21.73	PK
Horizontal	15600.077	49.58	-7.82	41.76	54.00	-12.24	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.197	69.41	-20.12	49.29	74.00	-24.71	PK
Vertical	4739.197	59.69	-20.12	39.56	54.00	-14.44	AV
Vertical	10480.189	62.71	-9.18	53.53	68.20	-14.67	PK
Vertical	10480.189	49.05	-9.18	39.87	54.00	-14.13	AV
Vertical	15720.103	61.78	-7.78	54.00	74.00	-20.00	PK
Vertical	15720.103	49.04	-7.78	41.26	54.00	-12.74	AV
Horizontal	4739.188	74.10	-20.12	53.97	74.00	-20.03	PK
Horizontal	4739.188	59.06	-20.12	38.94	54.00	-15.06	AV
Horizontal	10480.069	64.53	-9.18	55.35	68.20	-12.85	PK
Horizontal	10480.069	49.09	-9.18	39.91	54.00	-14.09	AV
Horizontal	15720.082	60.64	-7.78	52.86	74.00	-21.14	PK
Horizontal	15720.082	49.71	-7.78	41.93	54.00	-12.07	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.061	70.39	-20.73	49.66	68.20	-18.54	PK
Vertical	4434.061	59.31	-20.73	38.57	54.00	-15.43	AV
Vertical	10360.075	64.71	-9.36	55.35	68.20	-12.85	PK
Vertical	10360.075	49.25	-9.36	39.89	54.00	-14.11	AV
Vertical	15540.126	63.30	-7.84	55.46	74.00	-18.54	PK
Vertical	15540.126	49.30	-7.84	41.46	54.00	-12.54	AV
Horizontal	4434.061	73.05	-20.73	52.32	68.20	-15.88	PK
Horizontal	4434.061	59.17	-20.73	38.44	54.00	-15.56	AV
Horizontal	10360.193	63.84	-9.36	54.48	68.20	-13.72	PK
Horizontal	10360.193	49.70	-9.36	40.34	54.00	-13.66	AV
Horizontal	15540.138	64.59	-7.84	56.75	74.00	-17.25	PK
Horizontal	15540.138	49.49	-7.84	41.65	54.00	-12.35	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.009	71.05	-20.42	50.64	74.00	-23.36	PK
Vertical	4592.009	59.54	-20.42	39.12	54.00	-14.88	AV
Vertical	10400.051	64.56	-9.30	55.26	68.20	-12.94	PK
Vertical	10400.051	49.82	-9.30	40.52	54.00	-13.48	AV
Vertical	15600.011	61.92	-7.82	54.10	74.00	-19.90	PK
Vertical	15600.011	49.73	-7.82	41.91	54.00	-12.09	AV
Horizontal	4592.103	72.06	-20.42	51.64	74.00	-22.36	PK
Horizontal	4592.103	59.05	-20.42	38.63	54.00	-15.37	AV
Horizontal	10400.183	61.47	-9.30	52.17	68.20	-16.03	PK
Horizontal	10400.183	49.43	-9.30	40.13	54.00	-13.87	AV
Horizontal	15600.014	64.93	-7.82	57.11	74.00	-16.89	PK
Horizontal	15600.014	49.08	-7.82	41.26	54.00	-12.74	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.025	71.51	-20.12	51.39	74.00	-22.61	PK
Vertical	4739.025	59.82	-20.12	39.69	54.00	-14.31	AV
Vertical	10480.144	60.30	-9.18	51.12	68.20	-17.08	PK
Vertical	10480.144	49.63	-9.18	40.45	54.00	-13.55	AV
Vertical	15720.036	64.35	-7.78	56.57	74.00	-17.43	PK
Vertical	15720.036	49.06	-7.78	41.28	54.00	-12.72	AV
Horizontal	4739.112	70.44	-20.12	50.32	74.00	-23.68	PK
Horizontal	4739.112	59.50	-20.12	39.38	54.00	-14.62	AV
Horizontal	10480.199	62.06	-9.18	52.88	68.20	-15.32	PK
Horizontal	10480.199	49.79	-9.18	40.61	54.00	-13.39	AV
Horizontal	15720.135	63.99	-7.78	56.21	74.00	-17.79	PK
Horizontal	15720.135	49.81	-7.78	42.03	54.00	-11.97	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.080	69.15	-20.73	48.42	68.20	-19.78	PK
Vertical	4434.080	59.93	-20.73	39.20	54.00	-14.80	AV
Vertical	10380.107	61.81	-9.33	52.48	68.20	-15.72	PK
Vertical	10380.107	49.92	-9.33	40.59	54.00	-13.41	AV
Vertical	15570.068	64.46	-7.83	56.63	74.00	-17.37	PK
Vertical	15570.068	49.01	-7.83	41.18	54.00	-12.82	AV
Horizontal	4434.115	73.06	-20.73	52.33	74.00	-21.67	PK
Horizontal	4434.115	59.03	-20.73	38.30	54.00	-15.70	AV
Horizontal	10380.020	60.49	-9.33	51.16	68.20	-17.04	PK
Horizontal	10380.020	49.04	-9.33	39.71	54.00	-14.29	AV
Horizontal	15570.047	61.45	-7.83	53.62	74.00	-20.38	PK
Horizontal	15570.047	49.78	-7.83	41.95	54.00	-12.05	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.158	67.29	-20.12	47.17	68.20	-21.03	PK
Vertical	4739.158	59.22	-20.12	39.09	54.00	-14.91	AV
Vertical	10460.154	64.40	-9.21	55.19	68.20	-13.01	PK
Vertical	10460.154	49.37	-9.21	40.16	54.00	-13.84	AV
Vertical	15690.038	60.20	-7.79	52.41	74.00	-21.59	PK
Vertical	15690.038	49.80	-7.79	42.01	54.00	-11.99	AV
Horizontal	4739.143	70.71	-20.12	50.59	68.20	-17.61	PK
Horizontal	4739.143	59.35	-20.12	39.23	54.00	-14.77	AV
Horizontal	10460.022	62.57	-9.21	53.36	68.20	-14.84	PK
Horizontal	10460.022	49.92	-9.21	40.71	54.00	-13.29	AV
Horizontal	15690.111	61.54	-7.79	53.75	74.00	-20.25	PK
Horizontal	15690.111	49.36	-7.79	41.57	54.00	-12.43	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.095	4434.174	70.24	-20.73	49.51	68.20	PK
Vertical	4434.095	4434.174	59.52	-20.73	38.79	54.00	AV
Vertical	10360.010	10360.034	61.38	-9.36	52.02	68.20	PK
Vertical	10360.010	10360.034	49.41	-9.36	40.05	54.00	AV
Vertical	15540.025	15540.190	61.61	-7.84	53.77	74.00	PK
Vertical	15540.025	15540.190	49.29	-7.84	41.45	54.00	AV
Horizontal	4434.165	4434.031	72.68	-20.73	51.95	68.20	PK
Horizontal	4434.165	4434.031	59.28	-20.73	38.55	54.00	AV
Horizontal	10360.074	10360.145	63.28	-9.36	53.92	68.20	PK
Horizontal	10360.074	10360.145	49.74	-9.36	40.38	54.00	AV
Horizontal	15540.159	15540.144	61.42	-7.84	53.58	74.00	PK
Horizontal	15540.159	15540.144	49.85	-7.84	42.01	54.00	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.169	68.52	-20.42	48.10	74.00	-25.90	PK
Vertical	4592.169	59.02	-20.42	38.60	54.00	-15.40	AV
Vertical	10400.125	64.48	-9.30	55.18	68.20	-13.02	PK
Vertical	10400.125	49.16	-9.30	39.86	54.00	-14.14	AV
Vertical	15600.094	62.50	-7.82	54.68	74.00	-19.32	PK
Vertical	15600.094	49.34	-7.82	41.52	54.00	-12.48	AV
Horizontal	4592.173	74.06	-20.42	53.65	74.00	-20.35	PK
Horizontal	4592.173	59.70	-20.42	39.28	54.00	-14.72	AV
Horizontal	10400.148	63.97	-9.30	54.67	68.20	-13.53	PK
Horizontal	10400.148	49.77	-9.30	40.47	54.00	-13.53	AV
Horizontal	15600.190	64.13	-7.82	56.31	74.00	-17.69	PK
Horizontal	15600.190	49.99	-7.82	42.17	54.00	-11.83	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.022	68.03	-20.12	47.91	74.00	-26.09	PK
Vertical	4739.022	59.59	-20.12	39.46	54.00	-14.54	AV
Vertical	10480.154	64.62	-9.18	55.44	68.20	-12.76	PK
Vertical	10480.154	49.07	-9.18	39.89	54.00	-14.11	AV
Vertical	15720.200	60.81	-7.78	53.03	74.00	-20.97	PK
Vertical	15720.200	49.48	-7.78	41.70	54.00	-12.30	AV
Horizontal	4739.114	71.81	-20.12	51.69	74.00	-22.31	PK
Horizontal	4739.114	59.91	-20.12	39.79	54.00	-14.21	AV
Horizontal	10480.150	64.51	-9.18	55.33	68.20	-12.87	PK
Horizontal	10480.150	49.18	-9.18	40.00	54.00	-14.00	AV
Horizontal	15720.138	61.93	-7.78	54.15	74.00	-19.85	PK
Horizontal	15720.138	49.23	-7.78	41.45	54.00	-12.55	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.150	71.68	-20.73	50.95	68.20	-17.25	PK
Vertical	4434.150	59.50	-20.73	38.76	54.00	-15.24	AV
Vertical	10380.167	63.81	-9.33	54.48	68.20	-13.72	PK
Vertical	10380.167	49.91	-9.33	40.58	54.00	-13.42	AV
Vertical	15570.138	63.52	-7.83	55.69	74.00	-18.31	PK
Vertical	15570.138	49.11	-7.83	41.28	54.00	-12.72	AV
Horizontal	4434.162	72.50	-20.73	51.77	74.00	-22.23	PK
Horizontal	4434.162	59.43	-20.73	38.70	54.00	-15.30	AV
Horizontal	10380.041	64.26	-9.33	54.93	68.20	-13.27	PK
Horizontal	10380.041	49.45	-9.33	40.12	54.00	-13.88	AV
Horizontal	15570.105	61.76	-7.83	53.93	74.00	-20.07	PK
Horizontal	15570.105	49.45	-7.83	41.62	54.00	-12.38	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.161	68.25	-20.12	48.13	68.20	-20.07	PK
Vertical	4739.161	59.66	-20.12	39.54	54.00	-14.46	AV
Vertical	10460.000	62.20	-9.21	52.99	68.20	-15.21	PK
Vertical	10460.000	49.44	-9.21	40.23	54.00	-13.77	AV
Vertical	15690.013	63.03	-7.79	55.24	74.00	-18.76	PK
Vertical	15690.013	49.08	-7.79	41.29	54.00	-12.71	AV
Horizontal	4739.038	71.65	-20.12	51.52	68.20	-16.68	PK
Horizontal	4739.038	59.14	-20.12	39.01	54.00	-14.99	AV
Horizontal	10460.144	61.82	-9.21	52.61	68.20	-15.59	PK
Horizontal	10460.144	49.38	-9.21	40.17	54.00	-13.83	AV
Horizontal	15690.002	60.73	-7.79	52.94	74.00	-21.06	PK
Horizontal	15690.002	49.87	-7.79	42.08	54.00	-11.92	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac 80
------------	------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5210 MHz)-Above 1G							
Vertical	4434.040	70.25	-20.73	49.52	68.20	-18.68	PK
Vertical	4434.040	59.81	-20.73	39.08	54.00	-14.92	AV
Vertical	10420.196	61.75	-9.27	52.48	68.20	-15.72	PK
Vertical	10420.196	49.97	-9.27	40.70	54.00	-13.30	AV
Vertical	15630.179	61.26	-7.81	53.45	74.00	-20.55	PK
Vertical	15630.179	49.62	-7.81	41.81	54.00	-12.19	AV
Horizontal	4434.014	71.36	-20.73	50.63	68.20	-17.57	PK
Horizontal	4434.014	59.61	-20.73	38.88	54.00	-15.12	AV
Horizontal	10420.152	41.04	9.27	50.31	68.20	-17.89	PK
Horizontal	10420.152	29.40	9.27	38.67	54.00	-15.33	AV
Horizontal	15630.152	60.62	-7.81	52.81	74.00	-21.19	PK
Horizontal	15630.152	49.05	-7.81	41.24	54.00	-12.76	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.034	70.26	-20.73	49.53	68.20	-18.67	PK
Vertical	4434.034	59.83	-20.73	39.09	54.00	-14.91	AV
Vertical	10360.037	63.82	-9.36	54.46	68.20	-13.74	PK
Vertical	10360.037	49.28	-9.36	39.92	54.00	-14.08	AV
Vertical	15540.101	61.07	-7.84	53.23	74.00	-20.77	PK
Vertical	15540.101	49.61	-7.84	41.77	54.00	-12.23	AV
Horizontal	4434.114	72.55	-20.73	51.82	68.20	-16.38	PK
Horizontal	4434.114	59.09	-20.73	38.36	54.00	-15.64	AV
Horizontal	10360.009	60.52	-9.36	51.16	68.20	-17.04	PK
Horizontal	10360.009	49.91	-9.36	40.55	54.00	-13.45	AV
Horizontal	15540.022	63.81	-7.84	55.97	74.00	-18.03	PK
Horizontal	15540.022	49.96	-7.84	42.12	54.00	-11.88	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.086	71.51	-20.42	51.10	74.00	-22.90	PK
Vertical	4592.086	59.67	-20.42	39.26	54.00	-14.74	AV
Vertical	10400.175	63.12	-9.30	53.82	68.20	-14.38	PK
Vertical	10400.175	49.71	-9.30	40.41	54.00	-13.59	AV
Vertical	15600.155	64.23	-7.82	56.41	74.00	-17.59	PK
Vertical	15600.155	49.43	-7.82	41.61	54.00	-12.39	AV
Horizontal	4592.193	72.72	-20.42	52.30	74.00	-21.70	PK
Horizontal	4592.193	59.22	-20.42	38.80	54.00	-15.20	AV
Horizontal	10400.024	64.64	-9.30	55.34	68.20	-12.86	PK
Horizontal	10400.024	49.37	-9.30	40.07	54.00	-13.93	AV
Horizontal	15600.093	62.67	-7.82	54.85	74.00	-19.15	PK
Horizontal	15600.093	49.77	-7.82	41.95	54.00	-12.05	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.138	68.30	-20.12	48.18	74.00	-25.82	PK
Vertical	4739.138	59.94	-20.12	39.82	54.00	-14.18	AV
Vertical	10480.016	62.24	-9.18	53.06	68.20	-15.14	PK
Vertical	10480.016	49.21	-9.18	40.03	54.00	-13.97	AV
Vertical	15720.009	62.53	-7.78	54.75	74.00	-19.25	PK
Vertical	15720.009	49.92	-7.78	42.14	54.00	-11.86	AV
Horizontal	4739.166	73.48	-20.12	53.36	74.00	-20.64	PK
Horizontal	4739.166	59.11	-20.12	38.99	54.00	-15.01	AV
Horizontal	10480.144	62.26	-9.18	53.08	68.20	-15.12	PK
Horizontal	10480.144	49.32	-9.18	40.14	54.00	-13.86	AV
Horizontal	15720.130	62.84	-7.78	55.06	74.00	-18.94	PK
Horizontal	15720.130	49.47	-7.78	41.69	54.00	-12.31	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.166	71.84	-20.73	51.11	68.20	-17.09	PK
Vertical	4434.166	59.29	-20.73	38.55	54.00	-15.45	AV
Vertical	10380.020	63.20	-9.33	53.87	68.20	-14.33	PK
Vertical	10380.020	49.09	-9.33	39.76	54.00	-14.24	AV
Vertical	15570.182	61.08	-7.83	53.25	74.00	-20.75	PK
Vertical	15570.182	49.95	-7.83	42.12	54.00	-11.88	AV
Horizontal	4434.187	73.69	-20.73	52.96	74.00	-21.04	PK
Horizontal	4434.187	59.15	-20.73	38.41	54.00	-15.59	AV
Horizontal	10380.018	61.25	-9.33	51.92	68.20	-16.28	PK
Horizontal	10380.018	49.82	-9.33	40.49	54.00	-13.51	AV
Horizontal	15570.196	62.15	-7.83	54.32	74.00	-19.68	PK
Horizontal	15570.196	49.78	-7.83	41.95	54.00	-12.05	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.150	67.23	-20.12	47.11	68.20	-21.09	PK
Vertical	4739.150	59.54	-20.12	39.42	54.00	-14.58	AV
Vertical	10460.167	64.57	-9.21	55.36	68.20	-12.84	PK
Vertical	10460.167	49.74	-9.21	40.53	54.00	-13.47	AV
Vertical	15690.166	61.54	-7.79	53.75	74.00	-20.25	PK
Vertical	15690.166	49.41	-7.79	41.62	54.00	-12.38	AV
Horizontal	4739.119	70.06	-20.12	49.94	68.20	-18.26	PK
Horizontal	4739.119	59.45	-20.12	39.33	54.00	-14.67	AV
Horizontal	10460.088	64.64	-9.21	55.43	68.20	-12.77	PK
Horizontal	10460.088	49.71	-9.21	40.50	54.00	-13.50	AV
Horizontal	15690.007	62.43	-7.79	54.64	74.00	-19.36	PK
Horizontal	15690.007	49.96	-7.79	42.17	54.00	-11.83	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax 80
------------	------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5210 MHz)-Above 1G							
Vertical	4434.063	67.36	-20.73	46.63	68.20	-21.57	PK
Vertical	4434.063	59.04	-20.73	38.31	54.00	-15.69	AV
Vertical	10420.019	62.85	-9.27	53.58	68.20	-14.62	PK
Vertical	10420.019	49.77	-9.27	40.50	54.00	-13.50	AV
Vertical	15630.095	62.36	-7.81	54.55	74.00	-19.45	PK
Vertical	15630.095	49.38	-7.81	41.57	54.00	-12.43	AV
Horizontal	4434.089	72.89	-20.73	52.16	68.20	-16.04	PK
Horizontal	4434.089	59.06	-20.73	38.32	54.00	-15.68	AV
Horizontal	10420.047	41.62	9.27	50.89	68.20	-17.31	PK
Horizontal	10420.047	29.72	9.27	38.99	54.00	-15.01	AV
Horizontal	15630.077	60.12	-7.81	52.31	74.00	-21.69	PK
Horizontal	15630.077	49.45	-7.81	41.64	54.00	-12.36	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.051	74.87	-20.73	54.14	68.2	-14.06	PK
Vertical	4434.051	59.14	-20.73	38.41	54	-15.59	AV
Vertical	10520.131	63.03	-9.12	53.91	68.2	-14.29	PK
Vertical	10520.131	49.74	-9.12	40.62	54	-13.38	AV
Vertical	15780.042	60.22	-7.77	52.45	74	-21.55	PK
Vertical	15780.042	49.01	-7.77	41.24	54	-12.76	AV
Horizontal	4434.106	72.27	-20.73	51.54	68.2	-16.66	PK
Horizontal	4434.106	59.81	-20.73	39.08	54	-14.92	AV
Horizontal	10520.045	63.44	-9.12	54.32	68.2	-13.88	PK
Horizontal	10520.045	49.52	-9.12	40.40	54	-13.60	AV
Horizontal	15780.059	61.34	-7.77	53.57	74	-20.43	PK
Horizontal	15780.059	49.27	-7.77	41.50	54	-12.50	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.043	72.79	-20.42	52.37	74	-21.63	PK
Vertical	4592.043	59.05	-20.42	38.63	54	-15.37	AV
Vertical	10560.050	61.50	-9.06	52.44	68.2	-15.76	PK
Vertical	10560.050	49.54	-9.06	40.48	54	-13.52	AV
Vertical	15840.129	62.76	-7.75	55.01	74	-18.99	PK
Vertical	15840.129	49.39	-7.75	41.64	54	-12.36	AV
Horizontal	4592.116	70.10	-20.42	49.69	74	-24.31	PK
Horizontal	4592.116	59.51	-20.42	39.10	54	-14.90	AV
Horizontal	10560.061	62.16	-9.06	53.10	68.2	-15.10	PK
Horizontal	10560.061	49.67	-9.06	40.61	54	-13.39	AV
Horizontal	15840.145	62.00	-7.75	54.25	74	-19.75	PK
Horizontal	15840.145	49.91	-7.75	42.16	54	-11.84	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.141	72.35	-20.12	52.23	74	-21.77	PK
Vertical	4739.141	59.98	-20.12	39.86	54	-14.14	AV
Vertical	10640.141	60.17	-8.94	51.23	68.2	-16.97	PK
Vertical	10640.141	49.04	-8.94	40.10	54	-13.90	AV
Vertical	15960.188	64.23	-7.71	56.52	74	-17.48	PK
Vertical	15960.188	49.18	-7.71	41.47	54	-12.53	AV
Horizontal	4739.104	72.11	-20.12	51.99	74	-22.01	PK
Horizontal	4739.104	59.50	-20.12	39.38	54	-14.62	AV
Horizontal	10640.097	64.80	-8.94	55.86	68.2	-12.34	PK
Horizontal	10640.097	49.64	-8.94	40.70	54	-13.30	AV
Horizontal	15960.094	60.79	-7.71	53.08	74	-20.92	PK
Horizontal	15960.094	49.15	-7.71	41.44	54	-12.56	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.112	74.14	-20.73	53.41	68.2	-14.79	PK
Vertical	4434.112	59.29	-20.73	38.56	54	-15.44	AV
Vertical	10520.099	62.14	-9.12	53.02	68.2	-15.18	PK
Vertical	10520.099	49.18	-9.12	40.06	54	-13.94	AV
Vertical	15780.021	63.93	-7.77	56.16	74	-17.84	PK
Vertical	15780.021	49.44	-7.77	41.67	54	-12.33	AV
Horizontal	4434.056	72.79	-20.73	52.06	68.2	-16.14	PK
Horizontal	4434.056	59.98	-20.73	39.25	54	-14.75	AV
Horizontal	10520.020	60.36	-9.12	51.24	68.2	-16.96	PK
Horizontal	10520.020	49.30	-9.12	40.18	54	-13.82	AV
Horizontal	15780.166	63.78	-7.77	56.01	74	-17.99	PK
Horizontal	15780.166	49.85	-7.77	42.08	54	-11.92	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.063	74.61	-20.42	54.19	74	-19.81	PK
Vertical	4592.063	59.79	-20.42	39.37	54	-14.63	AV
Vertical	10560.131	60.43	-9.06	51.37	68.2	-16.83	PK
Vertical	10560.131	49.23	-9.06	40.17	54	-13.83	AV
Vertical	15840.144	63.72	-7.75	55.97	74	-18.03	PK
Vertical	15840.144	49.37	-7.75	41.62	54	-12.38	AV
Horizontal	4592.044	71.28	-20.42	50.87	74	-23.13	PK
Horizontal	4592.044	59.31	-20.42	38.89	54	-15.11	AV
Horizontal	10560.151	63.88	-9.06	54.82	68.2	-13.38	PK
Horizontal	10560.151	49.98	-9.06	40.92	54	-13.08	AV
Horizontal	15840.049	60.51	-7.75	52.76	74	-21.24	PK
Horizontal	15840.049	49.70	-7.75	41.95	54	-12.05	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.072	72.84	-20.12	52.72	74	-21.28	PK
Vertical	4739.072	59.79	-20.12	39.67	54	-14.33	AV
Vertical	10640.092	63.56	-8.94	54.62	68.2	-13.58	PK
Vertical	10640.092	49.02	-8.94	40.08	54	-13.92	AV
Vertical	15960.073	62.09	-7.71	54.38	74	-19.62	PK
Vertical	15960.073	49.38	-7.71	41.67	54	-12.33	AV
Horizontal	4739.196	72.44	-20.12	52.32	74	-21.68	PK
Horizontal	4739.196	59.79	-20.12	39.67	54	-14.33	AV
Horizontal	10640.135	63.43	-8.94	54.49	68.2	-13.71	PK
Horizontal	10640.135	49.07	-8.94	40.13	54	-13.87	AV
Horizontal	15960.073	60.92	-7.71	53.21	74	-20.79	PK
Horizontal	15960.073	49.13	-7.71	41.42	54	-12.58	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.065	74.54	-20.73	53.81	68.2	-14.39	PK
Vertical	4434.065	59.55	-20.73	38.82	54	-15.18	AV
Vertical	10540.033	63.16	-9.09	54.07	68.2	-14.13	PK
Vertical	10540.033	49.94	-9.09	40.85	54	-13.15	AV
Vertical	15810.004	60.24	-7.76	52.48	74	-21.52	PK
Vertical	15810.004	49.65	-7.76	41.89	54	-12.11	AV
Horizontal	4434.028	72.30	-20.73	51.57	74	-22.43	PK
Horizontal	4434.028	59.47	-20.73	38.74	54	-15.26	AV
Horizontal	10540.085	62.36	-9.09	53.27	68.2	-14.93	PK
Horizontal	10540.085	49.40	-9.09	40.31	54	-13.69	AV
Horizontal	15810.013	63.38	-7.76	55.62	74	-18.38	PK
Horizontal	15810.013	49.53	-7.76	41.77	54	-12.23	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.012	74.22	-20.12	54.09	68.2	-14.11	PK
Vertical	4739.012	59.67	-20.12	39.55	54	-14.45	AV
Vertical	10620.106	60.08	-8.97	51.11	68.2	-17.09	PK
Vertical	10620.106	49.32	-8.97	40.35	54	-13.65	AV
Vertical	15930.042	61.54	-7.72	53.82	74	-20.18	PK
Vertical	15930.042	49.35	-7.72	41.63	54	-12.37	AV
Horizontal	4739.023	72.15	-20.12	52.03	68.2	-16.17	PK
Horizontal	4739.023	59.14	-20.12	39.02	54	-14.98	AV
Horizontal	10620.160	64.02	-8.97	55.05	68.2	-13.15	PK
Horizontal	10620.160	49.31	-8.97	40.34	54	-13.66	AV
Horizontal	15930.104	60.69	-7.72	52.97	74	-21.03	PK
Horizontal	15930.104	49.27	-7.72	41.55	54	-12.45	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.118	70.98	-20.73	50.25	68.2	-17.95	PK
Vertical	4434.118	59.87	-20.73	39.13	54	-14.87	AV
Vertical	10520.049	62.06	-9.12	52.94	68.2	-15.26	PK
Vertical	10520.049	49.36	-9.12	40.24	54	-13.76	AV
Vertical	15780.005	60.24	-7.77	52.47	74	-21.53	PK
Vertical	15780.005	49.75	-7.77	41.98	54	-12.02	AV
Horizontal	4434.033	71.04	-20.73	50.31	68.2	-17.89	PK
Horizontal	4434.033	59.59	-20.73	38.86	54	-15.14	AV
Horizontal	10520.163	61.47	-9.12	52.35	68.2	-15.85	PK
Horizontal	10520.163	49.80	-9.12	40.68	54	-13.32	AV
Horizontal	15780.090	63.40	-7.77	55.63	74	-18.37	PK
Horizontal	15780.090	49.35	-7.77	41.58	54	-12.42	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.036	73.95	-20.42	53.54	74	-20.46	PK
Vertical	4592.036	59.51	-20.42	39.10	54	-14.90	AV
Vertical	10560.114	64.79	-9.06	55.73	68.2	-12.47	PK
Vertical	10560.114	49.37	-9.06	40.31	54	-13.69	AV
Vertical	15840.021	62.64	-7.75	54.89	74	-19.11	PK
Vertical	15840.021	49.93	-7.75	42.18	54	-11.82	AV
Horizontal	4592.071	70.45	-20.42	50.04	74	-23.96	PK
Horizontal	4592.071	59.29	-20.42	38.87	54	-15.13	AV
Horizontal	10560.094	62.65	-9.06	53.59	68.2	-14.61	PK
Horizontal	10560.094	49.52	-9.06	40.46	54	-13.54	AV
Horizontal	15840.091	63.97	-7.75	56.22	74	-17.78	PK
Horizontal	15840.091	49.13	-7.75	41.38	54	-12.62	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.025	70.44	-20.12	50.32	74	-23.68	PK
Vertical	4739.025	59.40	-20.12	39.28	54	-14.72	AV
Vertical	10640.050	64.04	-8.94	55.10	68.2	-13.10	PK
Vertical	10640.050	49.65	-8.94	40.71	54	-13.29	AV
Vertical	15960.188	60.46	-7.71	52.75	74	-21.25	PK
Vertical	15960.188	49.40	-7.71	41.69	54	-12.31	AV
Horizontal	4739.056	74.27	-20.12	54.15	74	-19.85	PK
Horizontal	4739.056	59.09	-20.12	38.97	54	-15.03	AV
Horizontal	10640.062	64.95	-8.94	56.01	68.2	-12.19	PK
Horizontal	10640.062	49.84	-8.94	40.90	54	-13.10	AV
Horizontal	15960.189	63.06	-7.71	55.35	74	-18.65	PK
Horizontal	15960.189	49.78	-7.71	42.07	54	-11.93	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.159	72.80	-20.73	52.07	68.2	-16.13	PK
Vertical	4434.159	59.40	-20.73	38.67	54	-15.33	AV
Vertical	10540.141	62.13	-9.09	53.04	68.2	-15.16	PK
Vertical	10540.141	49.43	-9.09	40.34	54	-13.66	AV
Vertical	15810.007	63.44	-7.76	55.68	74	-18.32	PK
Vertical	15810.007	49.62	-7.76	41.86	54	-12.14	AV
Horizontal	4434.186	74.58	-20.73	53.85	74	-20.15	PK
Horizontal	4434.186	59.84	-20.73	39.10	54	-14.90	AV
Horizontal	10540.188	64.70	-9.09	55.61	68.2	-12.59	PK
Horizontal	10540.188	49.52	-9.09	40.43	54	-13.57	AV
Horizontal	15810.113	61.66	-7.76	53.90	74	-20.10	PK
Horizontal	15810.113	49.70	-7.76	41.94	54	-12.06	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.045	73.50	-20.12	53.38	68.2	-14.82	PK
Vertical	4739.045	59.43	-20.12	39.30	54	-14.70	AV
Vertical	10620.109	62.82	-8.97	53.85	68.2	-14.35	PK
Vertical	10620.109	49.07	-8.97	40.10	54	-13.90	AV
Vertical	15930.151	64.30	-7.72	56.58	74	-17.42	PK
Vertical	15930.151	49.48	-7.72	41.76	54	-12.24	AV
Horizontal	4739.117	74.12	-20.12	54.00	68.2	-14.20	PK
Horizontal	4739.117	59.68	-20.12	39.55	54	-14.45	AV
Horizontal	10620.131	63.97	-8.97	55.00	68.2	-13.20	PK
Horizontal	10620.131	49.66	-8.97	40.69	54	-13.31	AV
Horizontal	15930.018	61.91	-7.72	54.19	74	-19.81	PK
Horizontal	15930.018	49.94	-7.72	42.22	54	-11.78	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac 80
------------	------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5290 MHz)-Above 1G							
Vertical	4434.147	72.62	-20.73	51.89	68.2	-16.31	PK
Vertical	4434.147	59.57	-20.73	38.83	54	-15.17	AV
Vertical	10580.031	61.00	-9.03	51.97	68.2	-16.23	PK
Vertical	10580.031	49.65	-9.03	40.62	54	-13.38	AV
Vertical	15870.077	63.58	-7.74	55.84	74	-18.16	PK
Vertical	15870.077	49.36	-7.74	41.62	54	-12.38	AV
Horizontal	4434.081	70.12	-20.73	49.39	68.2	-18.81	PK
Horizontal	4434.081	59.17	-20.73	38.44	54	-15.56	AV
Horizontal	10580.062	64.01	-9.03	54.98	68.2	-13.22	PK
Horizontal	10580.062	49.18	-9.03	40.15	54	-13.85	AV
Horizontal	15870.180	63.48	-7.74	55.74	74	-18.26	PK
Horizontal	15870.180	49.94	-7.74	42.20	54	-11.80	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.114	70.43	-20.73	49.70	68.20	-18.50	PK
Vertical	4434.114	59.79	-20.73	39.05	54.00	-14.95	AV
Vertical	10520.102	62.05	-9.12	52.93	68.20	-15.27	PK
Vertical	10520.102	49.22	-9.12	40.10	54.00	-13.90	AV
Vertical	15780.145	61.25	-7.77	53.48	74.00	-20.52	PK
Vertical	15780.145	49.52	-7.77	41.75	54.00	-12.25	AV
Horizontal	4434.019	69.74	-20.73	49.01	68.20	-19.19	PK
Horizontal	4434.019	59.87	-20.73	39.14	54.00	-14.86	AV
Horizontal	10520.039	64.06	-9.12	54.94	68.20	-13.26	PK
Horizontal	10520.039	49.99	-9.12	40.87	54.00	-13.13	AV
Horizontal	15780.018	64.74	-7.77	56.97	74.00	-17.03	PK
Horizontal	15780.018	49.86	-7.77	42.09	54.00	-11.91	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.196	71.63	-20.42	51.21	74.00	-22.79	PK
Vertical	4592.196	59.79	-20.42	39.38	54.00	-14.62	AV
Vertical	10560.007	62.54	-9.06	53.48	68.20	-14.72	PK
Vertical	10560.007	49.92	-9.06	40.86	54.00	-13.14	AV
Vertical	15840.090	62.09	-7.75	54.34	74.00	-19.66	PK
Vertical	15840.090	49.86	-7.75	42.11	54.00	-11.89	AV
Horizontal	4592.154	69.68	-20.42	49.27	74.00	-24.73	PK
Horizontal	4592.154	59.78	-20.42	39.37	54.00	-14.63	AV
Horizontal	10560.162	64.84	-9.06	55.78	68.20	-12.42	PK
Horizontal	10560.162	49.59	-9.06	40.53	54.00	-13.47	AV
Horizontal	15840.174	63.46	-7.75	55.71	74.00	-18.29	PK
Horizontal	15840.174	49.83	-7.75	42.08	54.00	-11.92	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.134	69.28	-20.12	49.16	74.00	-24.84	PK
Vertical	4739.134	59.23	-20.12	39.11	54.00	-14.89	AV
Vertical	10640.149	63.57	-8.94	54.63	68.20	-13.57	PK
Vertical	10640.149	49.86	-8.94	40.92	54.00	-13.08	AV
Vertical	15960.021	64.75	-7.71	57.04	74.00	-16.96	PK
Vertical	15960.021	49.45	-7.71	41.74	54.00	-12.26	AV
Horizontal	4739.000	71.37	-20.12	51.25	74.00	-22.75	PK
Horizontal	4739.000	59.19	-20.12	39.07	54.00	-14.93	AV
Horizontal	10640.199	60.99	-8.94	52.05	68.20	-16.15	PK
Horizontal	10640.199	49.51	-8.94	40.57	54.00	-13.43	AV
Horizontal	15960.185	60.72	-7.71	53.01	74.00	-20.99	PK
Horizontal	15960.185	49.20	-7.71	41.49	54.00	-12.51	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.140	73.89	-20.73	53.16	68.2	-15.04	PK
Vertical	4434.140	59.82	-20.73	39.09	54	-14.91	AV
Vertical	10540.038	64.33	-9.09	55.24	68.2	-12.96	PK
Vertical	10540.038	49.29	-9.09	40.20	54	-13.80	AV
Vertical	15810.182	62.59	-7.76	54.83	74	-19.17	PK
Vertical	15810.182	49.58	-7.76	41.82	54	-12.18	AV
Horizontal	4434.073	72.80	-20.73	52.07	74	-21.93	PK
Horizontal	4434.073	59.04	-20.73	38.30	54	-15.70	AV
Horizontal	10540.003	64.75	-9.09	55.66	68.2	-12.54	PK
Horizontal	10540.003	49.15	-9.09	40.06	54	-13.94	AV
Horizontal	15810.055	61.51	-7.76	53.75	74	-20.25	PK
Horizontal	15810.055	49.40	-7.76	41.64	54	-12.36	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.073	73.86	-20.12	53.74	68.20	-14.46	PK
Vertical	4739.073	59.70	-20.12	39.58	54.00	-14.42	AV
Vertical	10620.018	63.78	-8.97	54.81	68.20	-13.39	PK
Vertical	10620.018	49.32	-8.97	40.35	54.00	-13.65	AV
Vertical	15930.120	63.91	-7.72	56.19	74.00	-17.81	PK
Vertical	15930.120	49.66	-7.72	41.94	54.00	-12.06	AV
Horizontal	4739.020	71.73	-20.12	51.61	68.20	-16.59	PK
Horizontal	4739.020	59.53	-20.12	39.41	54.00	-14.59	AV
Horizontal	10620.073	63.75	-8.97	54.78	68.20	-13.42	PK
Horizontal	10620.073	49.81	-8.97	40.84	54.00	-13.16	AV
Horizontal	15930.127	60.25	-7.72	52.53	74.00	-21.47	PK
Horizontal	15930.127	49.75	-7.72	42.03	54.00	-11.97	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax 80
------------	------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5290 MHz)-Above 1G							
Vertical	4434.087	69.72	-20.73	48.99	68.20	-19.21	PK
Vertical	4434.087	59.00	-20.73	38.27	54.00	-15.73	AV
Vertical	10580.097	63.20	-9.03	54.17	68.20	-14.03	PK
Vertical	10580.097	49.25	-9.03	40.22	54.00	-13.78	AV
Vertical	15870.037	60.35	-7.74	52.61	74.00	-21.39	PK
Vertical	15870.037	49.56	-7.74	41.82	54.00	-12.18	AV
Horizontal	4434.149	71.10	-20.73	50.37	68.20	-17.83	PK
Horizontal	4434.149	59.76	-20.73	39.03	54.00	-14.97	AV
Horizontal	10580.155	61.65	-9.03	52.62	68.20	-15.58	PK
Horizontal	10580.155	49.45	-9.03	40.42	54.00	-13.58	AV
Horizontal	15870.021	61.06	-7.74	53.32	74.00	-20.68	PK
Horizontal	15870.021	49.06	-7.74	41.32	54.00	-12.68	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11a
------------	--------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.051	72.88	-20.73	52.15	68.20	-16.05	PK
Vertical	4434.051	66.73	-20.73	45.99	54.00	-8.01	AV
Vertical	11000.140	62.75	-8.40	54.35	68.20	-13.85	PK
Vertical	11000.140	49.40	-8.40	41.00	54.00	-13.00	AV
Vertical	16500.049	60.30	-6.09	54.21	74.00	-19.79	PK
Vertical	16500.049	49.09	-6.09	43.00	54.00	-11.00	AV
Horizontal	4434.132	70.42	-20.73	49.69	68.20	-18.51	PK
Horizontal	4434.132	59.30	-20.73	38.56	54.00	-15.44	AV
Horizontal	11000.119	64.72	-8.40	56.32	68.20	-11.88	PK
Horizontal	11000.119	49.82	-8.40	41.42	54.00	-12.58	AV
Horizontal	16500.029	61.86	-6.09	55.77	74.00	-18.23	PK
Horizontal	16500.029	49.54	-6.09	43.45	54.00	-10.55	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.029	68.72	-20.42	48.31	74.00	-25.69	PK
Vertical	4592.029	59.64	-20.42	39.23	54.00	-14.77	AV
Vertical	11160.067	61.10	-8.53	52.57	68.20	-15.63	PK
Vertical	11160.067	49.81	-8.53	41.28	54.00	-12.72	AV
Vertical	16740.033	61.64	-5.31	56.33	74.00	-17.67	PK
Vertical	16740.033	49.26	-5.31	43.95	54.00	-10.05	AV
Horizontal	4592.130	70.20	-20.42	49.78	74.00	-24.22	PK
Horizontal	4592.130	59.88	-20.42	39.47	54.00	-14.53	AV
Horizontal	11160.128	63.37	-8.53	54.84	68.20	-13.36	PK
Horizontal	11160.128	49.24	-8.53	40.71	54.00	-13.29	AV
Horizontal	16740.029	64.54	-5.31	59.23	74.00	-14.77	PK
Horizontal	16740.029	49.91	-5.31	44.60	54.00	-9.40	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.182	67.99	-20.12	47.87	74.00	-26.13	PK
Vertical	4739.182	59.42	-20.12	39.30	54.00	-14.70	AV
Vertical	11400.105	61.68	-8.72	52.96	68.20	-15.24	PK
Vertical	11400.105	49.68	-8.72	40.96	54.00	-13.04	AV
Vertical	17100.124	60.68	-3.92	56.76	74.00	-17.24	PK
Vertical	17100.124	49.31	-3.92	45.39	54.00	-8.61	AV
Horizontal	4739.144	71.39	-20.12	51.27	74.00	-22.73	PK
Horizontal	4739.144	59.53	-20.12	39.41	54.00	-14.59	AV
Horizontal	11400.031	63.66	-8.72	54.94	68.20	-13.26	PK
Horizontal	11400.031	49.71	-8.72	40.99	54.00	-13.01	AV
Horizontal	17100.095	62.56	-3.92	58.64	74.00	-15.36	PK
Horizontal	17100.095	49.94	-3.92	46.02	54.00	-7.98	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11n-HT20
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.016	72.23	-20.73	51.50	68.20	-16.70	PK
Vertical	4434.016	66.70	-20.73	45.97	54.00	-8.03	AV
Vertical	11000.035	62.22	-8.40	53.82	68.20	-14.38	PK
Vertical	11000.035	49.48	-8.40	41.08	54.00	-12.92	AV
Vertical	16500.002	64.43	-6.09	58.34	74.00	-15.66	PK
Vertical	16500.002	49.66	-6.09	43.57	54.00	-10.43	AV
Horizontal	4434.068	67.57	-20.73	46.84	68.20	-21.36	PK
Horizontal	4434.068	59.50	-20.73	38.77	54.00	-15.23	AV
Horizontal	11000.093	60.69	-8.40	52.29	68.20	-15.91	PK
Horizontal	11000.093	49.00	-8.40	40.60	54.00	-13.40	AV
Horizontal	16500.159	61.48	-6.09	55.39	74.00	-18.61	PK
Horizontal	16500.159	49.91	-6.09	43.82	54.00	-10.18	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.136	70.46	-20.42	50.05	74.00	-23.95	PK
Vertical	4592.136	59.42	-20.42	39.00	54.00	-15.00	AV
Vertical	11160.128	62.11	-8.53	53.58	68.20	-14.62	PK
Vertical	11160.128	49.11	-8.53	40.58	54.00	-13.42	AV
Vertical	16740.183	64.74	-5.31	59.43	74.00	-14.57	PK
Vertical	16740.183	49.05	-5.31	43.74	54.00	-10.26	AV
Horizontal	4592.129	68.30	-20.42	47.89	74.00	-26.11	PK
Horizontal	4592.129	59.13	-20.42	38.71	54.00	-15.29	AV
Horizontal	11160.150	63.93	-8.53	55.40	68.20	-12.80	PK
Horizontal	11160.150	49.97	-8.53	41.44	54.00	-12.56	AV
Horizontal	16740.187	60.05	-5.31	54.74	74.00	-19.26	PK
Horizontal	16740.187	49.76	-5.31	44.45	54.00	-9.55	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.044	69.96	-20.12	49.83	74.00	-24.17	PK
Vertical	4739.044	59.45	-20.12	39.33	54.00	-14.67	AV
Vertical	11400.023	62.24	-8.72	53.52	68.20	-14.68	PK
Vertical	11400.023	49.18	-8.72	40.46	54.00	-13.54	AV
Vertical	17100.050	60.64	-3.92	56.72	74.00	-17.28	PK
Vertical	17100.050	49.76	-3.92	45.84	54.00	-8.16	AV
Horizontal	4739.013	70.21	-20.12	50.09	74.00	-23.91	PK
Horizontal	4739.013	59.92	-20.12	39.80	54.00	-14.20	AV
Horizontal	11400.081	60.15	-8.72	51.43	68.20	-16.77	PK
Horizontal	11400.081	49.41	-8.72	40.69	54.00	-13.31	AV
Horizontal	17100.116	63.19	-3.92	59.27	74.00	-14.73	PK
Horizontal	17100.116	49.70	-3.92	45.78	54.00	-8.22	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11n-HT40
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.071	61.54	-20.73	40.81	68.20	-27.39	PK
Vertical	4434.071	43.75	-20.73	23.02	54.00	-30.98	AV
Vertical	11020.103	61.34	-8.42	52.92	68.20	-15.28	PK
Vertical	11020.103	43.27	-8.42	34.85	54.00	-19.15	AV
Vertical	16530.116	63.27	-5.99	57.28	74.00	-16.72	PK
Vertical	16530.116	43.40	-5.99	37.41	54.00	-16.59	AV
Horizontal	4434.173	60.41	-20.73	39.68	74.00	-34.32	PK
Horizontal	4434.173	43.79	-20.73	23.06	54.00	-30.94	AV
Horizontal	11020.151	51.10	-8.42	42.68	68.20	-25.52	PK
Horizontal	11020.151	40.88	-8.42	32.46	54.00	-21.54	AV
Horizontal	16530.076	54.69	-5.99	48.70	74.00	-25.30	PK
Horizontal	16530.076	42.46	-5.99	36.47	54.00	-17.53	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.105	61.45	-20.42	41.03	74.00	-32.97	PK
Vertical	4592.105	43.47	-20.42	23.05	54.00	-30.95	AV
Vertical	11100.164	62.61	-8.40	54.21	68.20	-13.99	PK
Vertical	11100.164	43.35	-8.40	34.95	54.00	-19.05	AV
Vertical	16650.043	60.65	-5.60	55.05	74.00	-18.95	PK
Vertical	16650.043	43.75	-5.60	38.15	54.00	-15.85	AV
Horizontal	4592.097	60.77	-20.42	40.35	74.00	-33.65	PK
Horizontal	4592.097	43.88	-20.42	23.46	54.00	-30.54	AV
Horizontal	11100.063	50.64	-8.40	42.24	68.20	-25.96	PK
Horizontal	11100.063	43.05	-8.40	34.65	54.00	-19.35	AV
Horizontal	16650.198	50.52	-5.60	44.92	74.00	-29.08	PK
Horizontal	16650.198	43.95	-5.60	38.35	54.00	-15.65	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.050	62.14	-20.12	42.02	68.20	-26.18	PK
Vertical	4739.050	43.10	-20.12	22.98	54.00	-31.02	AV
Vertical	11340.036	62.50	-8.67	53.83	68.20	-14.37	PK
Vertical	11340.036	43.45	-8.67	34.78	54.00	-19.22	AV
Vertical	17010.173	60.67	-4.41	56.26	74.00	-17.74	PK
Vertical	17010.173	43.13	-4.41	38.72	54.00	-15.28	AV
Horizontal	4739.070	61.03	-20.12	40.90	68.20	-27.30	PK
Horizontal	4739.070	43.95	-20.12	23.83	54.00	-30.17	AV
Horizontal	11340.087	50.92	-8.67	42.25	68.20	-25.95	PK
Horizontal	11340.087	41.69	-8.67	33.02	54.00	-20.98	AV
Horizontal	17010.032	54.46	-4.41	50.05	74.00	-23.95	PK
Horizontal	17010.032	43.79	-4.41	39.38	54.00	-14.62	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT20
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.003	72.15	-20.73	51.42	68.20	-16.78	PK
Vertical	4434.003	66.18	-20.73	45.45	54.00	-8.55	AV
Vertical	11000.114	62.05	-8.40	53.65	68.20	-14.55	PK
Vertical	11000.114	49.08	-8.40	40.68	54.00	-13.32	AV
Vertical	16500.154	63.15	-6.09	57.06	74.00	-16.94	PK
Vertical	16500.154	49.58	-6.09	43.49	54.00	-10.51	AV
Horizontal	4434.151	71.76	-20.73	51.03	68.20	-17.17	PK
Horizontal	4434.151	59.71	-20.73	38.98	54.00	-15.02	AV
Horizontal	11000.137	63.20	-8.40	54.80	68.20	-13.40	PK
Horizontal	11000.137	49.25	-8.40	40.85	54.00	-13.15	AV
Horizontal	16500.063	60.59	-6.09	54.50	74.00	-19.50	PK
Horizontal	16500.063	49.21	-6.09	43.12	54.00	-10.88	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.086	67.48	-20.42	47.07	74.00	-26.93	PK
Vertical	4592.086	59.38	-20.42	38.97	54.00	-15.03	AV
Vertical	11160.042	63.79	-8.53	55.26	68.20	-12.94	PK
Vertical	11160.042	49.28	-8.53	40.75	54.00	-13.25	AV
Vertical	16740.096	60.13	-5.31	54.82	74.00	-19.18	PK
Vertical	16740.096	49.26	-5.31	43.95	54.00	-10.05	AV
Horizontal	4592.072	70.93	-20.42	50.52	74.00	-23.48	PK
Horizontal	4592.072	59.58	-20.42	39.16	54.00	-14.84	AV
Horizontal	11160.076	64.85	-8.53	56.32	68.20	-11.88	PK
Horizontal	11160.076	49.69	-8.53	41.16	54.00	-12.84	AV
Horizontal	16740.005	62.40	-5.31	57.09	74.00	-16.91	PK
Horizontal	16740.005	49.02	-5.31	43.71	54.00	-10.29	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.091	69.10	-20.12	48.98	74.00	-25.02	PK
Vertical	4739.091	59.06	-20.12	38.94	54.00	-15.06	AV
Vertical	11400.196	64.58	-8.72	55.86	68.20	-12.34	PK
Vertical	11400.196	49.65	-8.72	40.93	54.00	-13.07	AV
Vertical	17100.149	60.94	-3.92	57.02	74.00	-16.98	PK
Vertical	17100.149	49.38	-3.92	45.46	54.00	-8.54	AV
Horizontal	4739.105	70.74	-20.12	50.62	74.00	-23.38	PK
Horizontal	4739.105	59.27	-20.12	39.15	54.00	-14.85	AV
Horizontal	11400.092	60.16	-8.72	51.44	68.20	-16.76	PK
Horizontal	11400.092	49.37	-8.72	40.65	54.00	-13.35	AV
Horizontal	17100.100	62.86	-3.92	58.94	74.00	-15.06	PK
Horizontal	17100.100	49.19	-3.92	45.27	54.00	-8.73	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.197	61.43	-20.73	40.70	68.20	-27.50	PK
Vertical	4434.197	43.95	-20.73	23.22	54.00	-30.78	AV
Vertical	11020.061	62.27	-8.42	53.85	68.20	-14.35	PK
Vertical	11020.061	43.57	-8.42	35.15	54.00	-18.85	AV
Vertical	16530.008	60.42	-5.99	54.43	74.00	-19.57	PK
Vertical	16530.008	43.90	-5.99	37.91	54.00	-16.09	AV
Horizontal	4434.121	64.56	-20.73	43.83	74.00	-30.17	PK
Horizontal	4434.121	43.90	-20.73	23.17	54.00	-30.83	AV
Horizontal	11020.160	53.65	-8.42	45.23	68.20	-22.97	PK
Horizontal	11020.160	43.61	-8.42	35.19	54.00	-18.81	AV
Horizontal	16530.166	54.72	-5.99	48.73	74.00	-25.27	PK
Horizontal	16530.166	44.83	-5.99	38.84	54.00	-15.16	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.070	63.20	-20.42	42.78	74.00	-31.22	PK
Vertical	4592.070	43.52	-20.42	23.11	54.00	-30.89	AV
Vertical	11100.124	63.58	-8.40	55.18	68.20	-13.02	PK
Vertical	11100.124	43.02	-8.40	34.62	54.00	-19.38	AV
Vertical	16650.019	64.90	-5.60	59.30	74.00	-14.70	PK
Vertical	16650.019	43.84	-5.60	38.24	54.00	-15.76	AV
Horizontal	4592.148	62.41	-20.42	41.99	74.00	-32.01	PK
Horizontal	4592.148	43.13	-20.42	22.71	54.00	-31.29	AV
Horizontal	11100.009	51.64	-8.40	43.24	68.20	-24.96	PK
Horizontal	11100.009	40.61	-8.40	32.21	54.00	-21.79	AV
Horizontal	16650.166	54.13	-5.60	48.53	74.00	-25.47	PK
Horizontal	16650.166	42.04	-5.60	36.44	54.00	-17.56	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.173	63.52	-20.12	43.40	68.20	-24.80	PK
Vertical	4739.173	43.27	-20.12	23.15	54.00	-30.85	AV
Vertical	11340.003	62.12	-8.67	53.45	68.20	-14.75	PK
Vertical	11340.003	43.14	-8.67	34.47	54.00	-19.53	AV
Vertical	17010.188	62.59	-4.41	58.18	74.00	-15.82	PK
Vertical	17010.188	43.03	-4.41	38.62	54.00	-15.38	AV
Horizontal	4739.153	62.18	-20.12	42.06	68.20	-26.14	PK
Horizontal	4739.153	43.60	-20.12	23.48	54.00	-30.52	AV
Horizontal	11340.048	54.53	-8.67	45.86	68.20	-22.34	PK
Horizontal	11340.048	41.53	-8.67	32.86	54.00	-21.14	AV
Horizontal	17010.048	52.16	-4.41	47.75	74.00	-26.25	PK
Horizontal	17010.048	43.83	-4.41	39.42	54.00	-14.58	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.074	63.12	-20.73	42.39	68.20	-25.81	PK
Vertical	4434.074	43.59	-20.73	22.86	54.00	-31.14	AV
Vertical	11060.200	60.86	-8.45	52.41	68.20	-15.79	PK
Vertical	11060.200	43.82	-8.45	35.37	54.00	-18.63	AV
Vertical	16590.164	61.29	-5.79	55.50	74.00	-18.50	PK
Vertical	16590.164	43.15	-5.79	37.36	54.00	-16.64	AV
Horizontal	4434.128	60.95	-20.73	40.22	68.20	-27.98	PK
Horizontal	4434.128	43.43	-20.73	22.69	54.00	-31.31	AV
Horizontal	11060.171	51.09	-8.45	42.64	68.20	-25.56	PK
Horizontal	11060.171	42.22	-8.45	33.77	54.00	-20.23	AV
Horizontal	16590.105	54.38	-5.79	48.59	74.00	-25.41	PK
Horizontal	16590.105	42.56	-5.79	36.77	54.00	-17.23	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.054	74.68	-20.73	53.95	68.20	-14.25	PK
Vertical	4434.054	66.14	-20.73	45.41	54.00	-8.59	AV
Vertical	11000.017	64.28	-8.40	55.88	68.20	-12.32	PK
Vertical	11000.017	49.10	-8.40	40.70	54.00	-13.30	AV
Vertical	16500.166	60.22	-6.09	54.13	74.00	-19.87	PK
Vertical	16500.166	49.69	-6.09	43.60	54.00	-10.40	AV
Horizontal	4434.022	69.69	-20.73	48.96	68.20	-19.24	PK
Horizontal	4434.022	59.11	-20.73	38.37	54.00	-15.63	AV
Horizontal	11000.061	60.57	-8.40	52.17	68.20	-16.03	PK
Horizontal	11000.061	49.24	-8.40	40.84	54.00	-13.16	AV
Horizontal	16500.109	64.00	-6.09	57.91	74.00	-16.09	PK
Horizontal	16500.109	49.89	-6.09	43.80	54.00	-10.20	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.064	70.02	-20.42	49.61	74.00	-24.39	PK
Vertical	4592.064	59.16	-20.42	38.74	54.00	-15.26	AV
Vertical	11160.105	60.39	-8.53	51.86	68.20	-16.34	PK
Vertical	11160.105	49.09	-8.53	40.56	54.00	-13.44	AV
Vertical	16740.082	61.11	-5.31	55.80	74.00	-18.20	PK
Vertical	16740.082	49.02	-5.31	43.71	54.00	-10.29	AV
Horizontal	4592.075	70.12	-20.42	49.70	74.00	-24.30	PK
Horizontal	4592.075	59.12	-20.42	38.70	54.00	-15.30	AV
Horizontal	11160.071	62.65	-8.53	54.12	68.20	-14.08	PK
Horizontal	11160.071	49.06	-8.53	40.53	54.00	-13.47	AV
Horizontal	16740.125	61.98	-5.31	56.67	74.00	-17.33	PK
Horizontal	16740.125	49.25	-5.31	43.94	54.00	-10.06	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.185	68.15	-20.12	48.03	74.00	-25.97	PK
Vertical	4739.185	59.68	-20.12	39.56	54.00	-14.44	AV
Vertical	11400.187	60.15	-8.72	51.43	68.20	-16.77	PK
Vertical	11400.187	49.16	-8.72	40.44	54.00	-13.56	AV
Vertical	17100.091	60.50	-3.92	56.58	74.00	-17.42	PK
Vertical	17100.091	49.50	-3.92	45.58	54.00	-8.42	AV
Horizontal	4739.078	67.02	-20.12	46.90	74.00	-27.10	PK
Horizontal	4739.078	59.55	-20.12	39.43	54.00	-14.57	AV
Horizontal	11400.155	60.70	-8.72	51.98	68.20	-16.22	PK
Horizontal	11400.155	49.53	-8.72	40.81	54.00	-13.19	AV
Horizontal	17100.069	63.44	-3.92	59.52	74.00	-14.48	PK
Horizontal	17100.069	49.61	-3.92	45.69	54.00	-8.31	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.194	64.08	-20.73	43.35	68.20	-24.85	PK
Vertical	4434.194	43.08	-20.73	22.34	54.00	-31.66	AV
Vertical	11020.018	60.18	-8.42	51.76	68.20	-16.44	PK
Vertical	11020.018	43.21	-8.42	34.79	54.00	-19.21	AV
Vertical	16530.179	61.11	-5.99	55.12	74.00	-18.88	PK
Vertical	16530.179	43.33	-5.99	37.34	54.00	-16.66	AV
Horizontal	4434.190	60.77	-20.73	40.04	74.00	-33.96	PK
Horizontal	4434.190	43.65	-20.73	22.92	54.00	-31.08	AV
Horizontal	11020.169	50.13	-8.42	41.71	68.20	-26.49	PK
Horizontal	11020.169	41.01	-8.42	32.59	54.00	-21.41	AV
Horizontal	16530.065	52.70	-5.99	46.71	74.00	-27.29	PK
Horizontal	16530.065	41.21	-5.99	35.22	54.00	-18.78	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.044	63.49	-20.42	43.07	74.00	-30.93	PK
Vertical	4592.044	43.75	-20.42	23.34	54.00	-30.66	AV
Vertical	11100.133	62.60	-8.40	54.20	68.20	-14.00	PK
Vertical	11100.133	43.52	-8.40	35.12	54.00	-18.88	AV
Vertical	16650.008	63.67	-5.60	58.07	74.00	-15.93	PK
Vertical	16650.008	43.40	-5.60	37.80	54.00	-16.20	AV
Horizontal	4592.029	61.43	-20.42	41.01	74.00	-32.99	PK
Horizontal	4592.029	43.58	-20.42	23.16	54.00	-30.84	AV
Horizontal	11100.149	54.25	-8.40	45.85	68.20	-22.35	PK
Horizontal	11100.149	41.89	-8.40	33.49	54.00	-20.51	AV
Horizontal	16650.137	50.89	-5.60	45.29	74.00	-28.71	PK
Horizontal	16650.137	42.89	-5.60	37.29	54.00	-16.71	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.046	63.75	-20.12	43.62	68.20	-24.58	PK
Vertical	4739.046	43.24	-20.12	23.11	54.00	-30.89	AV
Vertical	11340.183	64.65	-8.67	55.98	68.20	-12.22	PK
Vertical	11340.183	43.11	-8.67	34.44	54.00	-19.56	AV
Vertical	17010.078	60.16	-4.41	55.75	74.00	-18.25	PK
Vertical	17010.078	43.43	-4.41	39.02	54.00	-14.98	AV
Horizontal	4739.013	63.70	-20.12	43.58	68.20	-24.62	PK
Horizontal	4739.013	43.06	-20.12	22.94	54.00	-31.06	AV
Horizontal	11340.070	54.94	-8.67	46.27	68.20	-21.93	PK
Horizontal	11340.070	40.58	-8.67	31.91	54.00	-22.09	AV
Horizontal	17010.104	51.70	-4.41	47.29	74.00	-26.71	PK
Horizontal	17010.104	40.57	-4.41	36.16	54.00	-17.84	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.038	63.56	-20.73	42.83	68.20	-25.37	PK
Vertical	4434.038	43.55	-20.73	22.81	54.00	-31.19	AV
Vertical	11060.030	62.73	-8.45	54.28	68.20	-13.92	PK
Vertical	11060.030	43.56	-8.45	35.11	54.00	-18.89	AV
Vertical	16590.016	63.53	-5.79	57.74	74.00	-16.26	PK
Vertical	16590.016	43.05	-5.79	37.26	54.00	-16.74	AV
Horizontal	4434.053	61.69	-20.73	40.96	68.20	-27.24	PK
Horizontal	4434.053	43.34	-20.73	22.61	54.00	-31.39	AV
Horizontal	11060.109	50.55	-8.45	42.10	68.20	-26.10	PK
Horizontal	11060.109	41.72	-8.45	33.27	54.00	-20.73	AV
Horizontal	16590.092	53.56	-5.79	47.77	74.00	-26.23	PK
Horizontal	16590.092	43.07	-5.79	37.28	54.00	-16.72	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.108	70.66	-20.24	50.42	74	-23.58	PK
Vertical	4679.108	59.19	-20.24	38.95	54	-15.05	AV
Vertical	11490.174	61.94	-8.79	53.15	68.2	-15.05	PK
Vertical	11490.174	49.39	-8.79	40.60	54	-13.40	AV
Vertical	17235.197	57.80	-3.18	54.62	68.2	-13.58	PK
Vertical	17235.197	44.83	-3.18	41.65	54	-12.35	AV
Horizontal	4679.078	71.24	-20.73	50.51	74	-23.49	PK
Horizontal	4679.078	59.73	-20.73	39.00	54	-15.00	AV
Horizontal	11490.120	60.37	-8.79	51.58	68.2	-16.62	PK
Horizontal	11490.120	49.93	-8.79	41.14	54	-12.86	AV
Horizontal	17235.076	57.26	-3.18	54.08	68.2	-14.12	PK
Horizontal	17235.076	44.85	-3.18	41.67	54	-12.33	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.061	73.65	-20.42	53.23	74	-20.77	PK
Vertical	4592.061	59.39	-20.42	38.97	54	-15.03	AV
Vertical	11570.007	64.32	-8.86	55.46	68.2	-12.74	PK
Vertical	11570.007	49.57	-8.86	40.71	54	-13.29	AV
Vertical	17355.042	57.83	-2.52	55.31	68.2	-12.89	PK
Vertical	17355.042	44.88	-2.52	42.36	54	-11.64	AV
Horizontal	4592.096	71.01	-20.42	50.60	74	-23.40	PK
Horizontal	4592.096	59.66	-20.42	39.25	54	-14.75	AV
Horizontal	11570.156	60.49	-8.86	51.63	68.2	-16.57	PK
Horizontal	11570.156	49.97	-8.86	41.11	54	-12.89	AV
Horizontal	17355.170	59.46	-2.52	56.94	68.2	-11.26	PK
Horizontal	17355.170	44.26	-2.52	41.74	54	-12.26	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.149	73.74	-18.93	54.81	68.2	-13.39	PK
Vertical	6039.149	59.45	-18.93	40.52	54	-13.48	AV
Vertical	11650.067	62.64	-8.92	53.72	74	-20.28	PK
Vertical	11650.067	49.82	-8.92	40.90	54	-13.10	AV
Vertical	17475.147	57.79	-1.86	55.93	68.2	-12.27	PK
Vertical	17475.147	44.34	-1.86	42.48	54	-11.52	AV
Horizontal	6039.148	73.79	-18.93	54.86	68.2	-13.34	PK
Horizontal	6039.148	59.85	-18.93	40.92	54	-13.08	AV
Horizontal	11650.156	62.21	-8.92	53.29	74	-20.71	PK
Horizontal	11650.156	49.41	-8.92	40.49	54	-13.51	AV
Horizontal	17475.044	56.88	-1.86	55.02	68.2	-13.18	PK
Horizontal	17475.044	44.82	-1.86	42.96	54	-11.04	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.123	74.75	-20.24	54.51	74	-19.49	PK
Vertical	4679.123	59.26	-20.24	39.02	54	-14.98	AV
Vertical	11490.034	63.17	-8.79	54.38	68.2	-13.82	PK
Vertical	11490.034	49.29	-8.79	40.50	54	-13.50	AV
Vertical	17235.196	56.92	-3.18	53.74	68.2	-14.46	PK
Vertical	17235.196	44.97	-3.18	41.79	54	-12.21	AV
Horizontal	4679.008	74.72	-20.24	54.48	74	-19.52	PK
Horizontal	4679.008	59.83	-20.24	39.58	54	-14.42	AV
Horizontal	11490.045	60.63	-8.79	51.84	68.2	-16.36	PK
Horizontal	11490.045	49.77	-8.79	40.98	54	-13.02	AV
Horizontal	17235.017	58.74	-3.18	55.56	68.2	-12.64	PK
Horizontal	17235.017	44.73	-3.18	41.55	54	-12.45	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.050	73.46	-20.42	53.05	74	-20.95	PK
Vertical	4592.050	59.14	-20.42	38.72	54	-15.28	AV
Vertical	11570.067	64.47	-8.86	55.61	68.2	-12.59	PK
Vertical	11570.067	49.89	-8.86	41.03	54	-12.97	AV
Vertical	17355.194	57.06	-2.52	54.54	68.2	-13.66	PK
Vertical	17355.194	44.23	-2.52	41.71	54	-12.29	AV
Horizontal	4592.166	73.98	-20.42	53.57	74	-20.43	PK
Horizontal	4592.166	59.01	-20.42	38.59	54	-15.41	AV
Horizontal	11570.130	63.84	-8.86	54.98	68.2	-13.22	PK
Horizontal	11570.130	49.51	-8.86	40.65	54	-13.35	AV
Horizontal	17355.016	58.87	-2.52	56.35	68.2	-11.85	PK
Horizontal	17355.016	44.65	-2.52	42.13	54	-11.87	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.081	70.20	-18.93	51.27	68.2	-16.93	PK
Vertical	6039.081	59.18	-18.93	40.25	54	-13.75	AV
Vertical	11650.166	60.58	-8.92	51.66	74	-22.34	PK
Vertical	11650.166	49.81	-8.92	40.89	54	-13.11	AV
Vertical	17475.023	57.56	-1.86	55.70	68.2	-12.50	PK
Vertical	17475.023	44.16	-1.86	42.30	54	-11.70	AV
Horizontal	6039.168	74.68	-18.93	55.75	68.2	-12.45	PK
Horizontal	6039.168	59.22	-18.93	40.28	54	-13.72	AV
Horizontal	11650.006	60.72	-8.92	51.80	74	-22.20	PK
Horizontal	11650.006	49.20	-8.92	40.28	54	-13.72	AV
Horizontal	17475.147	55.92	-1.86	54.06	68.2	-14.14	PK
Horizontal	17475.147	44.85	-1.86	42.99	54	-11.01	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.186	74.95	-20.24	54.71	74	-19.29	PK
Vertical	4679.186	59.59	-20.24	39.35	54	-14.65	AV
Vertical	11510.056	61.83	-8.81	53.02	74	-20.98	PK
Vertical	11510.056	49.44	-8.81	40.63	54	-13.37	AV
Vertical	17265.051	59.43	-3.01	56.42	68.2	-11.78	PK
Vertical	17265.051	44.05	-3.01	41.04	54	-12.96	AV
Horizontal	4679.093	70.31	-20.24	50.07	74	-23.93	PK
Horizontal	4679.093	59.13	-20.24	38.88	54	-15.12	AV
Horizontal	11510.044	60.68	-8.81	51.87	74	-22.13	PK
Horizontal	11510.044	49.84	-8.81	41.03	54	-12.97	AV
Horizontal	17265.028	56.82	-3.01	53.81	68.2	-14.39	PK
Horizontal	17265.028	44.32	-3.01	41.31	54	-12.69	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.122	72.96	-18.93	54.02	68.2	-14.18	PK
Vertical	6039.122	59.90	-18.93	40.97	54	-13.03	AV
Vertical	11590.141	63.57	-8.87	54.70	74	-19.30	PK
Vertical	11590.141	49.07	-8.87	40.20	54	-13.80	AV
Vertical	17385.189	57.98	-2.35	55.63	68.2	-12.57	PK
Vertical	17385.189	44.09	-2.35	41.74	54	-12.26	AV
Horizontal	6039.084	70.97	-18.93	52.04	68.2	-16.16	PK
Horizontal	6039.084	59.65	-18.93	40.72	54	-13.28	AV
Horizontal	11590.116	63.19	-8.87	54.32	74	-19.68	PK
Horizontal	11590.116	49.57	-8.87	40.70	54	-13.30	AV
Horizontal	17385.051	57.51	-2.35	55.16	68.2	-13.04	PK
Horizontal	17385.051	44.66	-2.35	42.31	54	-11.69	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ac-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.071	74.59	-20.24	54.35	74	-19.65	PK
Vertical	4679.071	59.36	-20.24	39.12	54	-14.88	AV
Vertical	11490.132	61.73	-8.79	52.94	68.2	-15.26	PK
Vertical	11490.132	49.59	-8.79	40.80	54	-13.20	AV
Vertical	17235.055	56.39	-3.18	53.21	68.2	-14.99	PK
Vertical	17235.055	44.66	-3.18	41.48	54	-12.52	AV
Horizontal	4679.081	72.93	-20.24	52.69	74	-21.31	PK
Horizontal	4679.081	59.96	-20.24	39.72	54	-14.28	AV
Horizontal	11490.029	63.30	-8.79	54.51	68.2	-13.69	PK
Horizontal	11490.029	49.75	-8.79	40.96	54	-13.04	AV
Horizontal	17235.171	55.12	-3.18	51.94	68.2	-16.26	PK
Horizontal	17235.171	44.07	-3.18	40.89	54	-13.11	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.003	72.25	-20.42	51.84	74	-22.16	PK
Vertical	4592.003	59.26	-20.42	38.85	54	-15.15	AV
Vertical	11570.118	63.16	-8.86	54.30	68.2	-13.90	PK
Vertical	11570.118	49.94	-8.86	41.08	54	-12.92	AV
Vertical	17355.079	59.78	-2.52	57.26	68.2	-10.94	PK
Vertical	17355.079	44.53	-2.52	42.01	54	-11.99	AV
Horizontal	4592.049	72.65	-20.42	52.24	74	-21.76	PK
Horizontal	4592.049	59.76	-20.42	39.34	54	-14.66	AV
Horizontal	11570.044	61.38	-8.86	52.52	68.2	-15.68	PK
Horizontal	11570.044	49.11	-8.86	40.25	54	-13.75	AV
Horizontal	17355.101	55.59	-2.52	53.07	68.2	-15.13	PK
Horizontal	17355.101	44.55	-2.52	42.03	54	-11.97	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.019	70.93	-18.93	52.00	68.2	-16.20	PK
Vertical	6039.019	59.36	-18.93	40.43	54	-13.57	AV
Vertical	11650.094	62.14	-8.92	53.22	74	-20.78	PK
Vertical	11650.094	49.16	-8.92	40.24	54	-13.76	AV
Vertical	17475.178	59.77	-1.86	57.91	68.2	-10.29	PK
Vertical	17475.178	44.89	-1.86	43.03	54	-10.97	AV
Horizontal	6039.123	72.98	-18.93	54.05	68.2	-14.15	PK
Horizontal	6039.123	59.10	-18.93	40.17	54	-13.83	AV
Horizontal	11650.192	61.86	-8.92	52.94	74	-21.06	PK
Horizontal	11650.192	49.78	-8.92	40.86	54	-13.14	AV
Horizontal	17475.067	59.48	-1.86	57.62	68.2	-10.58	PK
Horizontal	17475.067	44.48	-1.86	42.62	54	-11.38	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ac-HT40
-------------	----------------------------

Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.033	70.58	-20.24	50.34	74	-23.66	PK
Vertical	4679.033	59.81	-20.24	39.57	54	-14.43	AV
Vertical	11510.167	63.69	-8.81	54.88	74	-19.12	PK
Vertical	11510.167	49.89	-8.81	41.08	54	-12.92	AV
Vertical	17265.176	55.02	-3.01	52.01	68.2	-16.19	PK
Vertical	17265.176	44.65	-3.01	41.64	54	-12.36	AV
Horizontal	4679.139	73.63	-20.24	53.39	74	-20.61	PK
Horizontal	4679.139	59.94	-20.24	39.70	54	-14.30	AV
Horizontal	11510.154	64.66	-8.81	55.85	74	-18.15	PK
Horizontal	11510.154	49.77	-8.81	40.96	54	-13.04	AV
Horizontal	17265.114	59.52	-3.01	56.51	68.2	-11.69	PK
Horizontal	17265.114	44.44	-3.01	41.43	54	-12.57	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.174	74.91	-18.93	55.97	68.2	-12.23	PK
Vertical	6039.174	59.19	-18.93	40.26	54	-13.74	AV
Vertical	11590.111	63.50	-8.87	54.63	74	-19.37	PK
Vertical	11590.111	49.09	-8.87	40.22	54	-13.78	AV
Vertical	17385.157	55.13	-2.35	52.78	68.2	-15.42	PK
Vertical	17385.157	44.56	-2.35	42.21	54	-11.79	AV
Horizontal	6039.184	70.23	-18.93	51.30	68.2	-16.90	PK
Horizontal	6039.184	59.10	-18.93	40.17	54	-13.83	AV
Horizontal	11590.086	63.70	-8.87	54.83	74	-19.17	PK
Horizontal	11590.086	49.41	-8.87	40.54	54	-13.46	AV
Horizontal	17385.005	55.69	-2.35	53.34	68.2	-14.86	PK
Horizontal	17385.005	44.54	-2.35	42.19	54	-11.81	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ac 80
-------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5775 MHz)-Above 1G							
Vertical	4679.128	72.34	-20.24	52.10	74	-21.90	PK
Vertical	4679.128	59.79	-20.24	39.55	54	-14.45	AV
Vertical	11550.196	63.30	-8.84	54.46	74	-19.54	PK
Vertical	11550.196	49.04	-8.84	40.20	54	-13.80	AV
Vertical	17325.072	57.42	-2.68	54.74	68.2	-13.46	PK
Vertical	17325.072	44.12	-2.68	41.44	54	-12.56	AV
Horizontal	4679.173	71.59	-20.24	51.35	74	-22.65	PK
Horizontal	4679.173	59.84	-20.24	39.60	54	-14.40	AV
Horizontal	11550.077	61.15	-8.84	52.31	74	-21.69	PK
Horizontal	11550.077	49.21	-8.84	40.37	54	-13.63	AV
Horizontal	17325.154	59.16	-2.68	56.48	68.2	-11.72	PK
Horizontal	17325.154	44.85	-2.68	42.17	54	-11.83	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ax-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.060	71.98	-20.24	51.73	74.00	-22.27	PK
Vertical	4679.060	59.56	-20.24	39.31	54.00	-14.69	AV
Vertical	11490.035	62.54	-8.79	53.75	68.20	-14.45	PK
Vertical	11490.035	49.31	-8.79	40.52	54.00	-13.48	AV
Vertical	17235.041	55.39	-3.18	52.21	68.20	-15.99	PK
Vertical	17235.041	44.81	-3.18	41.63	54.00	-12.37	AV
Horizontal	4679.110	73.87	-20.73	53.14	74.00	-20.86	PK
Horizontal	4679.110	59.08	-20.73	38.35	54.00	-15.65	AV
Horizontal	11490.013	63.95	-8.79	55.16	68.20	-13.04	PK
Horizontal	11490.013	49.15	-8.79	40.36	54.00	-13.64	AV
Horizontal	17235.029	56.92	-3.18	53.74	68.20	-14.46	PK
Horizontal	17235.029	44.95	-3.18	41.77	54.00	-12.23	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.148	70.49	-20.42	50.08	74.00	-23.92	PK
Vertical	4592.148	59.86	-20.42	39.44	54.00	-14.56	AV
Vertical	11570.187	62.29	-8.86	53.43	68.20	-14.77	PK
Vertical	11570.187	49.52	-8.86	40.66	54.00	-13.34	AV
Vertical	17355.139	59.39	-2.52	56.87	68.20	-11.33	PK
Vertical	17355.139	44.92	-2.52	42.40	54.00	-11.60	AV
Horizontal	4592.165	73.90	-20.42	53.48	74.00	-20.52	PK
Horizontal	4592.165	59.23	-20.42	38.82	54.00	-15.18	AV
Horizontal	11570.146	63.98	-8.86	55.12	68.20	-13.08	PK
Horizontal	11570.146	49.87	-8.86	41.01	54.00	-12.99	AV
Horizontal	17355.095	56.98	-2.52	54.46	68.20	-13.74	PK
Horizontal	17355.095	44.11	-2.52	41.59	54.00	-12.41	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.064	71.18	-18.93	52.25	68.20	-15.95	PK
Vertical	6039.064	59.37	-18.93	40.44	54.00	-13.56	AV
Vertical	11650.150	61.64	-8.92	52.72	74.00	-21.28	PK
Vertical	11650.150	49.21	-8.92	40.29	54.00	-13.71	AV
Vertical	17475.055	59.11	-1.86	57.25	68.20	-10.95	PK
Vertical	17475.055	44.92	-1.86	43.06	54.00	-10.94	AV
Horizontal	6039.106	73.81	-18.93	54.87	68.20	-13.33	PK
Horizontal	6039.106	59.20	-18.93	40.27	54.00	-13.73	AV
Horizontal	11650.024	61.50	-8.92	52.58	74.00	-21.42	PK
Horizontal	11650.024	49.92	-8.92	41.00	54.00	-13.00	AV
Horizontal	17475.029	55.03	-1.86	53.17	68.20	-15.03	PK
Horizontal	17475.029	44.67	-1.86	42.81	54.00	-11.19	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ax-HT40
-------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.038	73.44	-20.24	53.20	74.00	-20.80	PK
Vertical	4679.038	59.11	-20.24	38.86	54.00	-15.14	AV
Vertical	11510.153	61.25	-8.81	52.44	74.00	-21.56	PK
Vertical	11510.153	49.59	-8.81	40.78	54.00	-13.22	AV
Vertical	17265.056	56.17	-3.01	53.16	68.20	-15.04	PK
Vertical	17265.056	44.82	-3.01	41.81	54.00	-12.19	AV
Horizontal	4679.015	74.20	-20.24	53.95	74.00	-20.05	PK
Horizontal	4679.015	59.14	-20.24	38.90	54.00	-15.10	AV
Horizontal	11510.009	62.19	-8.81	53.38	74.00	-20.62	PK
Horizontal	11510.009	49.10	-8.81	40.29	54.00	-13.71	AV
Horizontal	17265.103	57.81	-3.01	54.80	68.20	-13.40	PK
Horizontal	17265.103	44.50	-3.01	41.49	54.00	-12.51	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.144	72.63	-18.93	53.70	68.20	-14.50	PK
Vertical	6039.144	59.71	-18.93	40.78	54.00	-13.22	AV
Vertical	11590.057	64.51	-8.87	55.64	74.00	-18.36	PK
Vertical	11590.057	49.81	-8.87	40.94	54.00	-13.06	AV
Vertical	17385.084	58.82	-2.35	56.47	68.20	-11.73	PK
Vertical	17385.084	44.60	-2.35	42.25	54.00	-11.75	AV
Horizontal	6039.007	70.91	-18.93	51.98	68.20	-16.22	PK
Horizontal	6039.007	59.46	-18.93	40.53	54.00	-13.47	AV
Horizontal	11590.188	62.18	-8.87	53.31	74.00	-20.69	PK
Horizontal	11590.188	49.04	-8.87	40.17	54.00	-13.83	AV
Horizontal	17385.198	59.76	-2.35	57.41	68.20	-10.79	PK
Horizontal	17385.198	44.44	-2.35	42.09	54.00	-11.91	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ax 80
-------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5775 MHz)-Above 1G							
Vertical	4679.160	73.79	-20.24	53.55	74.00	-20.45	PK
Vertical	4679.160	59.29	-20.24	39.05	54.00	-14.95	AV
Vertical	11550.051	63.66	-8.84	54.82	74.00	-19.18	PK
Vertical	11550.051	49.16	-8.84	40.32	54.00	-13.68	AV
Vertical	17325.149	56.77	-2.68	54.09	68.20	-14.11	PK
Vertical	17325.149	44.34	-2.68	41.66	54.00	-12.34	AV
Horizontal	4679.005	70.21	-20.24	49.96	74.00	-24.04	PK
Horizontal	4679.005	59.80	-20.24	39.56	54.00	-14.44	AV
Horizontal	11550.188	61.96	-8.84	53.12	74.00	-20.88	PK
Horizontal	11550.188	49.15	-8.84	40.31	54.00	-13.69	AV
Horizontal	17325.033	57.75	-2.68	55.07	68.20	-13.13	PK
Horizontal	17325.033	44.01	-2.68	41.33	54.00	-12.67	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Between 1GHz – 40GHz

ANT 3

Test Mode:	TX(5.1G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.184	71.04	-20.73	50.30	68.2	-17.90	PK
Vertical	4434.184	59.09	-20.73	38.36	54	-15.64	AV
Vertical	10360.135	62.50	-9.36	53.14	68.2	-15.06	PK
Vertical	10360.135	49.95	-9.36	40.59	54	-13.41	AV
Vertical	15540.162	62.72	-7.84	54.88	74	-19.12	PK
Vertical	15540.162	49.88	-7.84	42.04	54	-11.96	AV
Horizontal	4434.022	70.15	-20.73	49.42	68.2	-18.78	PK
Horizontal	4434.022	59.85	-20.73	39.12	54	-14.88	AV
Horizontal	10360.198	62.55	-9.36	53.19	68.2	-15.01	PK
Horizontal	10360.198	49.56	-9.36	40.20	54	-13.80	AV
Horizontal	15540.163	63.86	-7.84	56.02	74	-17.98	PK
Horizontal	15540.163	49.76	-7.84	41.92	54	-12.08	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.103	70.55	-20.42	50.13	74	-23.87	PK
Vertical	4592.103	59.29	-20.42	38.87	54	-15.13	AV
Vertical	10400.048	62.58	-9.30	53.28	68.2	-14.92	PK
Vertical	10400.048	49.65	-9.30	40.35	54	-13.65	AV
Vertical	15600.102	61.13	-7.82	53.31	74	-20.69	PK
Vertical	15600.102	49.27	-7.82	41.45	54	-12.55	AV
Horizontal	4592.037	72.13	-20.42	51.72	74	-22.28	PK
Horizontal	4592.037	59.07	-20.42	38.66	54	-15.34	AV
Horizontal	10400.097	61.24	-9.30	51.94	68.2	-16.26	PK
Horizontal	10400.097	49.40	-9.30	40.10	54	-13.90	AV
Horizontal	15600.032	63.76	-7.82	55.94	74	-18.06	PK
Horizontal	15600.032	49.80	-7.82	41.98	54	-12.02	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.029	73.77	-20.12	53.64	74	-20.36	PK
Vertical	4739.029	59.33	-20.12	39.21	54	-14.79	AV
Vertical	10480.104	63.73	-9.18	54.55	68.2	-13.65	PK
Vertical	10480.104	49.75	-9.18	40.57	54	-13.43	AV
Vertical	15720.055	60.60	-7.78	52.82	74	-21.18	PK
Vertical	15720.055	49.46	-7.78	41.68	54	-12.32	AV
Horizontal	4739.000	72.30	-20.12	52.18	74	-21.82	PK
Horizontal	4739.000	59.02	-20.12	38.90	54	-15.10	AV
Horizontal	10480.058	60.55	-9.18	51.37	68.2	-16.83	PK
Horizontal	10480.058	49.15	-9.18	39.97	54	-14.03	AV
Horizontal	15720.175	64.86	-7.78	57.08	74	-16.92	PK
Horizontal	15720.175	49.93	-7.78	42.15	54	-11.85	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.146	70.04	-20.73	49.31	68.2	-18.89	PK
Vertical	4434.146	59.01	-20.73	38.28	54	-15.72	AV
Vertical	10360.026	60.77	-9.36	51.41	68.2	-16.79	PK
Vertical	10360.026	49.97	-9.36	40.61	54	-13.39	AV
Vertical	15540.098	62.76	-7.84	54.92	74	-19.08	PK
Vertical	15540.098	49.45	-7.84	41.61	54	-12.39	AV
Horizontal	4434.058	72.39	-20.73	51.66	68.2	-16.54	PK
Horizontal	4434.058	59.71	-20.73	38.98	54	-15.02	AV
Horizontal	10360.116	61.04	-9.36	51.68	68.2	-16.52	PK
Horizontal	10360.116	49.35	-9.36	39.99	54	-14.01	AV
Horizontal	15540.128	63.76	-7.84	55.92	74	-18.08	PK
Horizontal	15540.128	49.31	-7.84	41.47	54	-12.53	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.089	72.84	-20.42	52.42	74	-21.58	PK
Vertical	4592.089	59.17	-20.42	38.75	54	-15.25	AV
Vertical	10400.022	63.93	-9.30	54.63	68.2	-13.57	PK
Vertical	10400.022	49.66	-9.30	40.36	54	-13.64	AV
Vertical	15600.189	60.21	-7.82	52.39	74	-21.61	PK
Vertical	15600.189	49.50	-7.82	41.68	54	-12.32	AV
Horizontal	4592.021	73.96	-20.42	53.54	74	-20.46	PK
Horizontal	4592.021	59.34	-20.42	38.93	54	-15.07	AV
Horizontal	10400.160	61.61	-9.30	52.31	68.2	-15.89	PK
Horizontal	10400.160	49.47	-9.30	40.17	54	-13.83	AV
Horizontal	15600.038	63.12	-7.82	55.30	74	-18.70	PK
Horizontal	15600.038	49.09	-7.82	41.27	54	-12.73	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.033	74.87	-20.12	54.75	74	-19.25	PK
Vertical	4739.033	59.19	-20.12	39.07	54	-14.93	AV
Vertical	10480.151	60.55	-9.18	51.37	68.2	-16.83	PK
Vertical	10480.151	49.63	-9.18	40.45	54	-13.55	AV
Vertical	15720.051	62.80	-7.78	55.02	74	-18.98	PK
Vertical	15720.051	49.18	-7.78	41.40	54	-12.60	AV
Horizontal	4739.164	72.84	-20.12	52.72	74	-21.28	PK
Horizontal	4739.164	59.69	-20.12	39.57	54	-14.43	AV
Horizontal	10480.168	62.40	-9.18	53.22	68.2	-14.98	PK
Horizontal	10480.168	49.75	-9.18	40.57	54	-13.43	AV
Horizontal	15720.036	63.02	-7.78	55.24	74	-18.76	PK
Horizontal	15720.036	49.42	-7.78	41.64	54	-12.36	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.012	71.31	-20.73	50.58	68.2	-17.62	PK
Vertical	4434.012	59.20	-20.73	38.47	54	-15.53	AV
Vertical	10380.085	64.10	-9.33	54.77	68.2	-13.43	PK
Vertical	10380.085	49.65	-9.33	40.32	54	-13.68	AV
Vertical	15570.132	61.38	-7.83	53.55	74	-20.45	PK
Vertical	15570.132	49.25	-7.83	41.42	54	-12.58	AV
Horizontal	4434.039	72.44	-20.73	51.70	74	-22.30	PK
Horizontal	4434.039	59.43	-20.73	38.69	54	-15.31	AV
Horizontal	10380.057	61.04	-9.33	51.71	68.2	-16.49	PK
Horizontal	10380.057	49.47	-9.33	40.14	54	-13.86	AV
Horizontal	15570.102	61.72	-7.83	53.89	74	-20.11	PK
Horizontal	15570.102	49.68	-7.83	41.85	54	-12.15	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.168	71.82	-20.12	51.70	68.2	-16.50	PK
Vertical	4739.168	59.96	-20.12	39.84	54	-14.16	AV
Vertical	10460.109	61.82	-9.21	52.61	68.2	-15.59	PK
Vertical	10460.109	49.31	-9.21	40.10	54	-13.90	AV
Vertical	15690.148	61.32	-7.79	53.53	74	-20.47	PK
Vertical	15690.148	49.19	-7.79	41.40	54	-12.60	AV
Horizontal	4739.138	71.72	-20.12	51.60	68.2	-16.60	PK
Horizontal	4739.138	59.41	-20.12	39.28	54	-14.72	AV
Horizontal	10460.120	62.00	-9.21	52.79	68.2	-15.41	PK
Horizontal	10460.120	49.30	-9.21	40.09	54	-13.91	AV
Horizontal	15690.146	64.59	-7.79	56.80	74	-17.20	PK
Horizontal	15690.146	49.01	-7.79	41.22	54	-12.78	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.148	74.18	-20.73	53.45	68.2	-14.75	PK
Vertical	4434.148	59.58	-20.73	38.85	54	-15.15	AV
Vertical	10360.137	62.14	-9.36	52.78	68.2	-15.42	PK
Vertical	10360.137	49.50	-9.36	40.14	54	-13.86	AV
Vertical	15540.183	63.26	-7.84	55.42	74	-18.58	PK
Vertical	15540.183	49.64	-7.84	41.80	54	-12.20	AV
Horizontal	4434.106	73.08	-20.73	52.34	68.2	-15.86	PK
Horizontal	4434.106	59.82	-20.73	39.08	54	-14.92	AV
Horizontal	10360.041	60.82	-9.36	51.46	68.2	-16.74	PK
Horizontal	10360.041	49.90	-9.36	40.54	54	-13.46	AV
Horizontal	15540.036	63.37	-7.84	55.53	74	-18.47	PK
Horizontal	15540.036	49.70	-7.84	41.86	54	-12.14	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.058	74.27	-20.42	53.86	74	-20.14	PK
Vertical	4592.058	59.01	-20.42	38.59	54	-15.41	AV
Vertical	10400.178	61.66	-9.30	52.36	68.2	-15.84	PK
Vertical	10400.178	49.90	-9.30	40.60	54	-13.40	AV
Vertical	15600.129	63.89	-7.82	56.07	74	-17.93	PK
Vertical	15600.129	49.44	-7.82	41.62	54	-12.38	AV
Horizontal	4592.042	73.08	-20.42	52.67	74	-21.33	PK
Horizontal	4592.042	59.53	-20.42	39.11	54	-14.89	AV
Horizontal	10400.047	60.54	-9.30	51.24	68.2	-16.96	PK
Horizontal	10400.047	49.70	-9.30	40.40	54	-13.60	AV
Horizontal	15600.129	62.19	-7.82	54.37	74	-19.63	PK
Horizontal	15600.129	49.81	-7.82	41.99	54	-12.01	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.193	74.74	-20.12	54.62	74	-19.38	PK
Vertical	4739.193	59.65	-20.12	39.53	54	-14.47	AV
Vertical	10480.199	64.19	-9.18	55.01	68.2	-13.19	PK
Vertical	10480.199	49.33	-9.18	40.15	54	-13.85	AV
Vertical	15720.180	61.69	-7.78	53.91	74	-20.09	PK
Vertical	15720.180	49.41	-7.78	41.63	54	-12.37	AV
Horizontal	4739.010	74.17	-20.12	54.05	74	-19.95	PK
Horizontal	4739.010	59.49	-20.12	39.37	54	-14.63	AV
Horizontal	10480.019	62.15	-9.18	52.97	68.2	-15.23	PK
Horizontal	10480.019	49.88	-9.18	40.70	54	-13.30	AV
Horizontal	15720.084	60.80	-7.78	53.02	74	-20.98	PK
Horizontal	15720.084	49.74	-7.78	41.96	54	-12.04	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.160	70.19	-20.73	49.46	68.2	-18.74	PK
Vertical	4434.160	59.92	-20.73	39.19	54	-14.81	AV
Vertical	10380.128	61.56	-9.33	52.23	68.2	-15.97	PK
Vertical	10380.128	49.31	-9.33	39.98	54	-14.02	AV
Vertical	15570.082	62.06	-7.83	54.23	74	-19.77	PK
Vertical	15570.082	49.49	-7.83	41.66	54	-12.34	AV
Horizontal	4434.123	70.35	-20.73	49.62	74	-24.38	PK
Horizontal	4434.123	59.34	-20.73	38.61	54	-15.39	AV
Horizontal	10380.058	64.97	-9.33	55.64	68.2	-12.56	PK
Horizontal	10380.058	49.10	-9.33	39.77	54	-14.23	AV
Horizontal	15570.172	60.55	-7.83	52.72	74	-21.28	PK
Horizontal	15570.172	49.78	-7.83	41.95	54	-12.05	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.081	72.96	-20.12	52.84	68.2	-15.36	PK
Vertical	4739.081	59.28	-20.12	39.16	54	-14.84	AV
Vertical	10460.109	64.15	-9.21	54.94	68.2	-13.26	PK
Vertical	10460.109	49.08	-9.21	39.87	54	-14.13	AV
Vertical	15690.007	63.63	-7.79	55.84	74	-18.16	PK
Vertical	15690.007	49.51	-7.79	41.72	54	-12.28	AV
Horizontal	4739.185	71.34	-20.12	51.21	68.2	-16.99	PK
Horizontal	4739.185	59.32	-20.12	39.20	54	-14.80	AV
Horizontal	10460.129	62.18	-9.21	52.97	68.2	-15.23	PK
Horizontal	10460.129	49.09	-9.21	39.88	54	-14.12	AV
Horizontal	15690.047	63.30	-7.79	55.51	74	-18.49	PK
Horizontal	15690.047	49.64	-7.79	41.85	54	-12.15	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5210 MHz)-Above 1G							
Vertical	4434.122	74.92	-20.73	54.19	68.2	-14.01	PK
Vertical	4434.122	59.36	-20.73	38.63	54	-15.37	AV
Vertical	10420.166	64.10	-9.27	54.83	68.2	-13.37	PK
Vertical	10420.166	49.81	-9.27	40.54	54	-13.46	AV
Vertical	15630.181	64.17	-7.81	56.36	74	-17.64	PK
Vertical	15630.181	49.74	-7.81	41.93	54	-12.07	AV
Horizontal	4434.130	70.63	-20.73	49.89	68.2	-18.31	PK
Horizontal	4434.130	59.53	-20.73	38.79	54	-15.21	AV
Horizontal	10420.051	44.48	9.27	53.75	68.2	-14.45	PK
Horizontal	10420.051	29.36	9.27	38.63	54	-15.37	AV
Horizontal	15630.136	60.59	-7.81	52.78	74	-21.22	PK
Horizontal	15630.136	49.21	-7.81	41.40	54	-12.60	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.115	73.43	-20.73	52.70	68.2	-15.50	PK
Vertical	4434.115	59.74	-20.73	39.01	54	-14.99	AV
Vertical	10360.046	61.85	-9.36	52.49	68.2	-15.71	PK
Vertical	10360.046	49.79	-9.36	40.43	54	-13.57	AV
Vertical	15540.061	60.90	-7.84	53.06	74	-20.94	PK
Vertical	15540.061	49.16	-7.84	41.32	54	-12.68	AV
Horizontal	4434.168	72.73	-20.73	52.00	68.2	-16.20	PK
Horizontal	4434.168	59.11	-20.73	38.37	54	-15.63	AV
Horizontal	10360.167	62.52	-9.36	53.16	68.2	-15.04	PK
Horizontal	10360.167	49.39	-9.36	40.03	54	-13.97	AV
Horizontal	15540.113	60.67	-7.84	52.83	74	-21.17	PK
Horizontal	15540.113	49.02	-7.84	41.18	54	-12.82	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.188	72.14	-20.42	51.73	74	-22.27	PK
Vertical	4592.188	59.88	-20.42	39.47	54	-14.53	AV
Vertical	10400.071	60.20	-9.30	50.90	68.2	-17.30	PK
Vertical	10400.071	49.15	-9.30	39.85	54	-14.15	AV
Vertical	15600.044	63.85	-7.82	56.03	74	-17.97	PK
Vertical	15600.044	49.57	-7.82	41.75	54	-12.25	AV
Horizontal	4592.180	74.06	-20.42	53.65	74	-20.35	PK
Horizontal	4592.180	59.34	-20.42	38.93	54	-15.07	AV
Horizontal	10400.162	61.40	-9.30	52.10	68.2	-16.10	PK
Horizontal	10400.162	49.45	-9.30	40.15	54	-13.85	AV
Horizontal	15600.120	64.39	-7.82	56.57	74	-17.43	PK
Horizontal	15600.120	49.55	-7.82	41.73	54	-12.27	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.052	73.51	-20.12	53.38	74	-20.62	PK
Vertical	4739.052	59.24	-20.12	39.11	54	-14.89	AV
Vertical	10480.189	63.19	-9.18	54.01	68.2	-14.19	PK
Vertical	10480.189	49.74	-9.18	40.56	54	-13.44	AV
Vertical	15720.144	62.78	-7.78	55.00	74	-19.00	PK
Vertical	15720.144	49.56	-7.78	41.78	54	-12.22	AV
Horizontal	4739.096	72.04	-20.12	51.92	74	-22.08	PK
Horizontal	4739.096	59.66	-20.12	39.53	54	-14.47	AV
Horizontal	10480.071	64.46	-9.18	55.28	68.2	-12.92	PK
Horizontal	10480.071	49.04	-9.18	39.86	54	-14.14	AV
Horizontal	15720.094	60.30	-7.78	52.52	74	-21.48	PK
Horizontal	15720.094	49.67	-7.78	41.89	54	-12.11	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.