

Test Mode:	TX(5.1G) - 802.11ax-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.013	74.28	-20.73	53.55	68.2	-14.65	PK
Vertical	4434.013	59.96	-20.73	39.23	54	-14.77	AV
Vertical	10380.105	62.15	-9.33	52.82	68.2	-15.38	PK
Vertical	10380.105	49.56	-9.33	40.23	54	-13.77	AV
Vertical	15570.154	64.93	-7.83	57.10	74	-16.90	PK
Vertical	15570.154	49.04	-7.83	41.21	54	-12.79	AV
Horizontal	4434.196	71.87	-20.73	51.13	74	-22.87	PK
Horizontal	4434.196	59.37	-20.73	38.63	54	-15.37	AV
Horizontal	10380.166	64.63	-9.33	55.30	68.2	-12.90	PK
Horizontal	10380.166	49.44	-9.33	40.11	54	-13.89	AV
Horizontal	15570.126	61.24	-7.83	53.41	74	-20.59	PK
Horizontal	15570.126	49.36	-7.83	41.53	54	-12.47	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.043	70.45	-20.12	50.33	68.2	-17.87	PK
Vertical	4739.043	59.31	-20.12	39.19	54	-14.81	AV
Vertical	10460.174	62.10	-9.21	52.89	68.2	-15.31	PK
Vertical	10460.174	49.04	-9.21	39.83	54	-14.17	AV
Vertical	15690.155	61.03	-7.79	53.24	74	-20.76	PK
Vertical	15690.155	49.50	-7.79	41.71	54	-12.29	AV
Horizontal	4739.189	70.44	-20.12	50.31	68.2	-17.89	PK
Horizontal	4739.189	60.00	-20.12	39.88	54	-14.12	AV
Horizontal	10460.127	62.08	-9.21	52.87	68.2	-15.33	PK
Horizontal	10460.127	49.46	-9.21	40.25	54	-13.75	AV
Horizontal	15690.107	64.72	-7.79	56.93	74	-17.07	PK
Horizontal	15690.107	49.19	-7.79	41.40	54	-12.60	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5210 MHz)-Above 1G							
Vertical	4434.015	72.12	-20.73	51.39	68.2	-16.81	PK
Vertical	4434.015	59.45	-20.73	38.72	54	-15.28	AV
Vertical	10420.083	60.91	-9.27	51.64	68.2	-16.56	PK
Vertical	10420.083	49.50	-9.27	40.23	54	-13.77	AV
Vertical	15630.044	63.63	-7.81	55.82	74	-18.18	PK
Vertical	15630.044	49.73	-7.81	41.92	54	-12.08	AV
Horizontal	4434.193	71.81	-20.73	51.08	68.2	-17.12	PK
Horizontal	4434.193	59.11	-20.73	38.38	54	-15.62	AV
Horizontal	10420.019	40.96	9.27	50.23	68.2	-17.97	PK
Horizontal	10420.019	29.90	9.27	39.17	54	-14.83	AV
Horizontal	15630.124	63.46	-7.81	55.65	74	-18.35	PK
Horizontal	15630.124	49.31	-7.81	41.50	54	-12.50	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.154	73.32	-20.73	52.58	68.2	-15.62	PK
Vertical	4434.154	59.66	-20.73	38.92	54	-15.08	AV
Vertical	10520.025	60.75	-9.12	51.63	68.2	-16.57	PK
Vertical	10520.025	49.16	-9.12	40.04	54	-13.96	AV
Vertical	15780.049	63.52	-7.77	55.75	74	-18.25	PK
Vertical	15780.049	49.21	-7.77	41.44	54	-12.56	AV
Horizontal	4434.114	70.14	-20.73	49.41	68.2	-18.79	PK
Horizontal	4434.114	59.16	-20.73	38.43	54	-15.57	AV
Horizontal	10520.180	64.41	-9.12	55.29	68.2	-12.91	PK
Horizontal	10520.180	49.81	-9.12	40.69	54	-13.31	AV
Horizontal	15780.131	64.88	-7.77	57.11	74	-16.89	PK
Horizontal	15780.131	49.85	-7.77	42.08	54	-11.92	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.113	73.29	-20.42	52.87	74	-21.13	PK
Vertical	4592.113	59.32	-20.42	38.91	54	-15.09	AV
Vertical	10560.135	62.11	-9.06	53.05	68.2	-15.15	PK
Vertical	10560.135	49.17	-9.06	40.11	54	-13.89	AV
Vertical	15840.078	62.28	-7.75	54.53	74	-19.47	PK
Vertical	15840.078	49.43	-7.75	41.68	54	-12.32	AV
Horizontal	4592.062	70.71	-20.42	50.30	74	-23.70	PK
Horizontal	4592.062	59.81	-20.42	39.39	54	-14.61	AV
Horizontal	10560.143	63.59	-9.06	54.53	68.2	-13.67	PK
Horizontal	10560.143	49.47	-9.06	40.41	54	-13.59	AV
Horizontal	15840.013	61.72	-7.75	53.97	74	-20.03	PK
Horizontal	15840.013	49.87	-7.75	42.12	54	-11.88	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.047	74.84	-20.12	54.71	74	-19.29	PK
Vertical	4739.047	59.63	-20.12	39.51	54	-14.49	AV
Vertical	10640.167	60.51	-8.94	51.57	68.2	-16.63	PK
Vertical	10640.167	49.03	-8.94	40.09	54	-13.91	AV
Vertical	15960.082	64.94	-7.71	57.23	74	-16.77	PK
Vertical	15960.082	49.94	-7.71	42.23	54	-11.77	AV
Horizontal	4739.096	74.80	-20.12	54.68	74	-19.32	PK
Horizontal	4739.096	59.31	-20.12	39.19	54	-14.81	AV
Horizontal	10640.059	62.30	-8.94	53.36	68.2	-14.84	PK
Horizontal	10640.059	49.59	-8.94	40.65	54	-13.35	AV
Horizontal	15960.083	62.96	-7.71	55.25	74	-18.75	PK
Horizontal	15960.083	49.78	-7.71	42.07	54	-11.93	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.085	72.73	-20.73	52.00	68.2	-16.20	PK
Vertical	4434.085	59.28	-20.73	38.55	54	-15.45	AV
Vertical	10520.164	62.83	-9.12	53.71	68.2	-14.49	PK
Vertical	10520.164	49.11	-9.12	39.99	54	-14.01	AV
Vertical	15780.134	61.18	-7.77	53.41	74	-20.59	PK
Vertical	15780.134	49.57	-7.77	41.80	54	-12.20	AV
Horizontal	4434.117	73.21	-20.73	52.48	68.2	-15.72	PK
Horizontal	4434.117	59.63	-20.73	38.90	54	-15.10	AV
Horizontal	10520.057	62.54	-9.12	53.42	68.2	-14.78	PK
Horizontal	10520.057	49.21	-9.12	40.09	54	-13.91	AV
Horizontal	15780.171	60.62	-7.77	52.85	74	-21.15	PK
Horizontal	15780.171	49.61	-7.77	41.84	54	-12.16	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.009	74.07	-20.42	53.65	74	-20.35	PK
Vertical	4592.009	59.85	-20.42	39.43	54	-14.57	AV
Vertical	10560.152	63.32	-9.06	54.26	68.2	-13.94	PK
Vertical	10560.152	49.55	-9.06	40.49	54	-13.51	AV
Vertical	15840.182	61.72	-7.75	53.97	74	-20.03	PK
Vertical	15840.182	49.85	-7.75	42.10	54	-11.90	AV
Horizontal	4592.160	71.16	-20.42	50.75	74	-23.25	PK
Horizontal	4592.160	59.55	-20.42	39.13	54	-14.87	AV
Horizontal	10560.163	61.74	-9.06	52.68	68.2	-15.52	PK
Horizontal	10560.163	49.28	-9.06	40.22	54	-13.78	AV
Horizontal	15840.120	62.62	-7.75	54.87	74	-19.13	PK
Horizontal	15840.120	50.00	-7.75	42.25	54	-11.75	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.050	70.87	-20.12	50.75	74	-23.25	PK
Vertical	4739.050	59.21	-20.12	39.09	54	-14.91	AV
Vertical	10640.064	61.36	-8.94	52.42	68.2	-15.78	PK
Vertical	10640.064	49.31	-8.94	40.37	54	-13.63	AV
Vertical	15960.100	63.17	-7.71	55.46	74	-18.54	PK
Vertical	15960.100	49.41	-7.71	41.70	54	-12.30	AV
Horizontal	4739.030	74.77	-20.12	54.64	74	-19.36	PK
Horizontal	4739.030	59.00	-20.12	38.88	54	-15.12	AV
Horizontal	10640.059	60.78	-8.94	51.84	68.2	-16.36	PK
Horizontal	10640.059	49.07	-8.94	40.13	54	-13.87	AV
Horizontal	15960.103	62.72	-7.71	55.01	74	-18.99	PK
Horizontal	15960.103	49.81	-7.71	42.10	54	-11.90	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.057	74.21	-20.73	53.48	68.2	-14.72	PK
Vertical	4434.057	59.53	-20.73	38.80	54	-15.20	AV
Vertical	10540.099	60.89	-9.09	51.80	68.2	-16.40	PK
Vertical	10540.099	49.25	-9.09	40.16	54	-13.84	AV
Vertical	15810.008	64.60	-7.76	56.84	74	-17.16	PK
Vertical	15810.008	49.20	-7.76	41.44	54	-12.56	AV
Horizontal	4434.182	73.95	-20.73	53.22	74	-20.78	PK
Horizontal	4434.182	59.45	-20.73	38.72	54	-15.28	AV
Horizontal	10540.060	61.84	-9.09	52.75	68.2	-15.45	PK
Horizontal	10540.060	49.29	-9.09	40.20	54	-13.80	AV
Horizontal	15810.136	61.25	-7.76	53.49	74	-20.51	PK
Horizontal	15810.136	49.81	-7.76	42.05	54	-11.95	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.005	71.23	-20.12	51.11	68.2	-17.09	PK
Vertical	4739.005	59.37	-20.12	39.25	54	-14.75	AV
Vertical	10620.087	62.29	-8.97	53.32	68.2	-14.88	PK
Vertical	10620.087	49.45	-8.97	40.48	54	-13.52	AV
Vertical	15930.159	64.01	-7.72	56.29	74	-17.71	PK
Vertical	15930.159	49.72	-7.72	42.00	54	-12.00	AV
Horizontal	4739.101	73.43	-20.12	53.30	68.2	-14.90	PK
Horizontal	4739.101	59.97	-20.12	39.85	54	-14.15	AV
Horizontal	10620.078	61.84	-8.97	52.87	68.2	-15.33	PK
Horizontal	10620.078	49.95	-8.97	40.98	54	-13.02	AV
Horizontal	15930.102	61.33	-7.72	53.61	74	-20.39	PK
Horizontal	15930.102	49.71	-7.72	41.99	54	-12.01	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.179	72.42	-20.73	51.69	68.2	-16.51	PK
Vertical	4434.179	59.80	-20.73	39.07	54	-14.93	AV
Vertical	10520.072	63.84	-9.12	54.72	68.2	-13.48	PK
Vertical	10520.072	49.62	-9.12	40.50	54	-13.50	AV
Vertical	15780.073	61.70	-7.77	53.93	74	-20.07	PK
Vertical	15780.073	49.68	-7.77	41.91	54	-12.09	AV
Horizontal	4434.174	71.47	-20.73	50.74	68.2	-17.46	PK
Horizontal	4434.174	59.44	-20.73	38.71	54	-15.29	AV
Horizontal	10520.174	60.62	-9.12	51.50	68.2	-16.70	PK
Horizontal	10520.174	49.34	-9.12	40.22	54	-13.78	AV
Horizontal	15780.199	60.04	-7.77	52.27	74	-21.73	PK
Horizontal	15780.199	49.92	-7.77	42.15	54	-11.85	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.177	73.12	-20.42	52.71	74	-21.29	PK
Vertical	4592.177	59.81	-20.42	39.39	54	-14.61	AV
Vertical	10560.075	63.93	-9.06	54.87	68.2	-13.33	PK
Vertical	10560.075	49.94	-9.06	40.88	54	-13.12	AV
Vertical	15840.064	63.36	-7.75	55.61	74	-18.39	PK
Vertical	15840.064	49.18	-7.75	41.43	54	-12.57	AV
Horizontal	4592.079	73.26	-20.42	52.84	74	-21.16	PK
Horizontal	4592.079	59.29	-20.42	38.87	54	-15.13	AV
Horizontal	10560.053	63.73	-9.06	54.67	68.2	-13.53	PK
Horizontal	10560.053	49.95	-9.06	40.89	54	-13.11	AV
Horizontal	15840.034	62.80	-7.75	55.05	74	-18.95	PK
Horizontal	15840.034	49.67	-7.75	41.92	54	-12.08	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.052	70.43	-20.12	50.31	74	-23.69	PK
Vertical	4739.052	59.16	-20.12	39.04	54	-14.96	AV
Vertical	10640.097	61.15	-8.94	52.21	68.2	-15.99	PK
Vertical	10640.097	49.50	-8.94	40.56	54	-13.44	AV
Vertical	15960.095	60.82	-7.71	53.11	74	-20.89	PK
Vertical	15960.095	49.81	-7.71	42.10	54	-11.90	AV
Horizontal	4739.199	72.39	-20.12	52.27	74	-21.73	PK
Horizontal	4739.199	59.26	-20.12	39.14	54	-14.86	AV
Horizontal	10640.061	64.44	-8.94	55.50	68.2	-12.70	PK
Horizontal	10640.061	49.64	-8.94	40.70	54	-13.30	AV
Horizontal	15960.071	61.43	-7.71	53.72	74	-20.28	PK
Horizontal	15960.071	49.56	-7.71	41.85	54	-12.15	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.097	71.68	-20.73	50.95	68.2	-17.25	PK
Vertical	4434.097	59.40	-20.73	38.67	54	-15.33	AV
Vertical	10540.148	61.75	-9.09	52.66	68.2	-15.54	PK
Vertical	10540.148	49.55	-9.09	40.46	54	-13.54	AV
Vertical	15810.124	63.18	-7.76	55.42	74	-18.58	PK
Vertical	15810.124	49.43	-7.76	41.67	54	-12.33	AV
Horizontal	4434.106	72.11	-20.73	51.38	74	-22.62	PK
Horizontal	4434.106	59.16	-20.73	38.43	54	-15.57	AV
Horizontal	10540.100	61.87	-9.09	52.78	68.2	-15.42	PK
Horizontal	10540.100	49.46	-9.09	40.37	54	-13.63	AV
Horizontal	15810.128	60.36	-7.76	52.60	74	-21.40	PK
Horizontal	15810.128	49.76	-7.76	42.00	54	-12.00	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.160	72.68	-20.12	52.55	68.2	-15.65	PK
Vertical	4739.160	59.03	-20.12	38.90	54	-15.10	AV
Vertical	10620.103	63.21	-8.97	54.24	68.2	-13.96	PK
Vertical	10620.103	49.99	-8.97	41.02	54	-12.98	AV
Vertical	15930.137	62.75	-7.72	55.03	74	-18.97	PK
Vertical	15930.137	49.25	-7.72	41.53	54	-12.47	AV
Horizontal	4739.015	73.05	-20.12	52.93	68.2	-15.27	PK
Horizontal	4739.015	59.26	-20.12	39.14	54	-14.86	AV
Horizontal	10620.116	62.27	-8.97	53.30	68.2	-14.90	PK
Horizontal	10620.116	49.90	-8.97	40.93	54	-13.07	AV
Horizontal	15930.134	64.58	-7.72	56.86	74	-17.14	PK
Horizontal	15930.134	49.25	-7.72	41.53	54	-12.47	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5290 MHz)-Above 1G							
Vertical	4434.056	71.91	-20.73	51.18	68.2	-17.02	PK
Vertical	4434.056	59.23	-20.73	38.50	54	-15.50	AV
Vertical	10580.110	63.52	-9.03	54.49	68.2	-13.71	PK
Vertical	10580.110	49.48	-9.03	40.45	54	-13.55	AV
Vertical	15870.024	61.82	-7.74	54.08	74	-19.92	PK
Vertical	15870.024	49.93	-7.74	42.19	54	-11.81	AV
Horizontal	4434.185	74.05	-20.73	53.32	68.2	-14.88	PK
Horizontal	4434.185	59.34	-20.73	38.61	54	-15.39	AV
Horizontal	10580.144	61.75	-9.03	52.72	68.2	-15.48	PK
Horizontal	10580.144	49.36	-9.03	40.33	54	-13.67	AV
Horizontal	15870.144	64.79	-7.74	57.05	74	-16.95	PK
Horizontal	15870.144	49.73	-7.74	41.99	54	-12.01	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.056	72.90	-20.73	52.17	68.2	-16.03	PK
Vertical	4434.056	59.89	-20.73	39.15	54	-14.85	AV
Vertical	10520.168	61.84	-9.12	52.72	68.2	-15.48	PK
Vertical	10520.168	49.34	-9.12	40.22	54	-13.78	AV
Vertical	15780.089	60.35	-7.77	52.58	74	-21.42	PK
Vertical	15780.089	49.04	-7.77	41.27	54	-12.73	AV
Horizontal	4434.087	71.23	-20.73	50.50	68.2	-17.70	PK
Horizontal	4434.087	59.91	-20.73	39.18	54	-14.82	AV
Horizontal	10520.055	61.33	-9.12	52.21	68.2	-15.99	PK
Horizontal	10520.055	49.78	-9.12	40.66	54	-13.34	AV
Horizontal	15780.148	62.88	-7.77	55.11	74	-18.89	PK
Horizontal	15780.148	49.23	-7.77	41.46	54	-12.54	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.134	74.42	-20.42	54.01	74	-19.99	PK
Vertical	4592.134	59.24	-20.42	38.82	54	-15.18	AV
Vertical	10560.082	62.47	-9.06	53.41	68.2	-14.79	PK
Vertical	10560.082	49.84	-9.06	40.78	54	-13.22	AV
Vertical	15840.101	63.21	-7.75	55.46	74	-18.54	PK
Vertical	15840.101	49.89	-7.75	42.14	54	-11.86	AV
Horizontal	4592.109	72.81	-20.42	52.39	74	-21.61	PK
Horizontal	4592.109	59.12	-20.42	38.70	54	-15.30	AV
Horizontal	10560.199	63.64	-9.06	54.58	68.2	-13.62	PK
Horizontal	10560.199	49.14	-9.06	40.08	54	-13.92	AV
Horizontal	15840.144	62.50	-7.75	54.75	74	-19.25	PK
Horizontal	15840.144	49.53	-7.75	41.78	54	-12.22	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.184	72.61	-20.12	52.48	74	-21.52	PK
Vertical	4739.184	59.12	-20.12	39.00	54	-15.00	AV
Vertical	10640.174	60.29	-8.94	51.35	68.2	-16.85	PK
Vertical	10640.174	49.54	-8.94	40.60	54	-13.40	AV
Vertical	15960.069	61.20	-7.71	53.49	74	-20.51	PK
Vertical	15960.069	49.42	-7.71	41.71	54	-12.29	AV
Horizontal	4739.018	70.48	-20.12	50.36	74	-23.64	PK
Horizontal	4739.018	59.26	-20.12	39.14	54	-14.86	AV
Horizontal	10640.080	60.58	-8.94	51.64	68.2	-16.56	PK
Horizontal	10640.080	49.01	-8.94	40.07	54	-13.93	AV
Horizontal	15960.125	62.80	-7.71	55.09	74	-18.91	PK
Horizontal	15960.125	49.52	-7.71	41.81	54	-12.19	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.123	73.20	-20.73	52.47	68.2	-15.73	PK
Vertical	4434.123	59.09	-20.73	38.36	54	-15.64	AV
Vertical	10540.085	62.12	-9.09	53.03	68.2	-15.17	PK
Vertical	10540.085	49.33	-9.09	40.24	54	-13.76	AV
Vertical	15810.010	60.52	-7.76	52.76	74	-21.24	PK
Vertical	15810.010	49.81	-7.76	42.05	54	-11.95	AV
Horizontal	4434.023	74.62	-20.73	53.89	74	-20.11	PK
Horizontal	4434.023	59.07	-20.73	38.34	54	-15.66	AV
Horizontal	10540.059	60.67	-9.09	51.58	68.2	-16.62	PK
Horizontal	10540.059	49.20	-9.09	40.11	54	-13.89	AV
Horizontal	15810.167	62.46	-7.76	54.70	74	-19.30	PK
Horizontal	15810.167	49.14	-7.76	41.38	54	-12.62	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.136	70.20	-20.12	50.08	68.2	-18.12	PK
Vertical	4739.136	59.57	-20.12	39.45	54	-14.55	AV
Vertical	10620.103	62.84	-8.97	53.87	68.2	-14.33	PK
Vertical	10620.103	49.10	-8.97	40.13	54	-13.87	AV
Vertical	15930.175	61.91	-7.72	54.19	74	-19.81	PK
Vertical	15930.175	49.25	-7.72	41.53	54	-12.47	AV
Horizontal	4739.020	70.23	-20.12	50.10	68.2	-18.10	PK
Horizontal	4739.020	59.61	-20.12	39.49	54	-14.51	AV
Horizontal	10620.072	61.43	-8.97	52.46	68.2	-15.74	PK
Horizontal	10620.072	49.84	-8.97	40.87	54	-13.13	AV
Horizontal	15930.052	61.13	-7.72	53.41	74	-20.59	PK
Horizontal	15930.052	49.14	-7.72	41.42	54	-12.58	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5290 MHz)-Above 1G							
Vertical	4434.041	70.90	-20.73	50.17	68.2	-18.03	PK
Vertical	4434.041	59.14	-20.73	38.41	54	-15.59	AV
Vertical	10580.069	63.90	-9.03	54.87	68.2	-13.33	PK
Vertical	10580.069	49.14	-9.03	40.11	54	-13.89	AV
Vertical	15870.075	62.86	-7.74	55.12	74	-18.88	PK
Vertical	15870.075	49.24	-7.74	41.50	54	-12.50	AV
Horizontal	4434.137	71.73	-20.73	51.00	68.2	-17.20	PK
Horizontal	4434.137	59.01	-20.73	38.28	54	-15.72	AV
Horizontal	10580.035	60.55	-9.03	51.52	68.2	-16.68	PK
Horizontal	10580.035	49.51	-9.03	40.48	54	-13.52	AV
Horizontal	15870.111	64.58	-7.74	56.84	74	-17.16	PK
Horizontal	15870.111	49.36	-7.74	41.62	54	-12.38	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11a
------------	--------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.097	71.01	-20.73	50.28	68.2	-17.92	PK
Vertical	4434.097	59.02	-20.73	38.29	54	-15.71	AV
Vertical	11000.040	60.97	-8.40	52.57	68.2	-15.63	PK
Vertical	11000.040	49.21	-8.40	40.81	54	-13.19	AV
Vertical	16500.099	62.97	-6.09	56.88	74	-17.12	PK
Vertical	16500.099	49.12	-6.09	43.03	54	-10.97	AV
Horizontal	4434.057	72.73	-20.73	52.00	68.2	-16.20	PK
Horizontal	4434.057	59.20	-20.73	38.46	54	-15.54	AV
Horizontal	11000.141	64.96	-8.40	56.56	68.2	-11.64	PK
Horizontal	11000.141	49.82	-8.40	41.42	54	-12.58	AV
Horizontal	16500.054	62.09	-6.09	56.00	74	-18.00	PK
Horizontal	16500.054	49.81	-6.09	43.72	54	-10.28	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.054	73.66	-20.42	53.25	74	-20.75	PK
Vertical	4592.054	59.64	-20.42	39.22	54	-14.78	AV
Vertical	11160.193	64.68	-8.53	56.15	68.2	-12.05	PK
Vertical	11160.193	49.45	-8.53	40.92	54	-13.08	AV
Vertical	16740.183	63.37	-5.31	58.06	74	-15.94	PK
Vertical	16740.183	49.70	-5.31	44.39	54	-9.61	AV
Horizontal	4592.156	73.51	-20.42	53.09	74	-20.91	PK
Horizontal	4592.156	59.33	-20.42	38.91	54	-15.09	AV
Horizontal	11160.014	60.06	-8.53	51.53	68.2	-16.67	PK
Horizontal	11160.014	49.28	-8.53	40.75	54	-13.25	AV
Horizontal	16740.148	61.87	-5.31	56.56	74	-17.44	PK
Horizontal	16740.148	49.60	-5.31	44.29	54	-9.71	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.192	74.08	-20.12	53.96	74	-20.04	PK
Vertical	4739.192	59.32	-20.12	39.20	54	-14.80	AV
Vertical	11400.127	64.90	-8.72	56.18	68.2	-12.02	PK
Vertical	11400.127	49.98	-8.72	41.26	54	-12.74	AV
Vertical	17100.181	61.61	-3.92	57.69	74	-16.31	PK
Vertical	17100.181	49.43	-3.92	45.51	54	-8.49	AV
Horizontal	4739.041	72.26	-20.12	52.14	74	-21.86	PK
Horizontal	4739.041	59.53	-20.12	39.41	54	-14.59	AV
Horizontal	11400.025	62.21	-8.72	53.49	68.2	-14.71	PK
Horizontal	11400.025	49.23	-8.72	40.51	54	-13.49	AV
Horizontal	17100.129	62.75	-3.92	58.83	74	-15.17	PK
Horizontal	17100.129	49.35	-3.92	45.43	54	-8.57	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11n-HT20
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.019	72.19	-20.73	51.46	68.2	-16.74	PK
Vertical	4434.019	59.08	-20.73	38.34	54	-15.66	AV
Vertical	11000.023	64.08	-8.40	55.68	68.2	-12.52	PK
Vertical	11000.023	49.22	-8.40	40.82	54	-13.18	AV
Vertical	16500.047	61.94	-6.09	55.85	74	-18.15	PK
Vertical	16500.047	49.18	-6.09	43.09	54	-10.91	AV
Horizontal	4434.039	74.19	-20.73	53.45	68.2	-14.75	PK
Horizontal	4434.039	59.48	-20.73	38.75	54	-15.25	AV
Horizontal	11000.124	60.31	-8.40	51.91	68.2	-16.29	PK
Horizontal	11000.124	49.27	-8.40	40.87	54	-13.13	AV
Horizontal	16500.094	63.68	-6.09	57.59	74	-16.41	PK
Horizontal	16500.094	49.42	-6.09	43.33	54	-10.67	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.141	72.72	-20.42	52.30	74	-21.70	PK
Vertical	4592.141	59.18	-20.42	38.76	54	-15.24	AV
Vertical	11160.073	61.32	-8.53	52.79	68.2	-15.41	PK
Vertical	11160.073	49.30	-8.53	40.77	54	-13.23	AV
Vertical	16740.179	61.09	-5.31	55.78	74	-18.22	PK
Vertical	16740.179	49.28	-5.31	43.97	54	-10.03	AV
Horizontal	4592.145	73.27	-20.42	52.85	74	-21.15	PK
Horizontal	4592.145	59.78	-20.42	39.36	54	-14.64	AV
Horizontal	11160.116	63.93	-8.53	55.40	68.2	-12.80	PK
Horizontal	11160.116	49.21	-8.53	40.68	54	-13.32	AV
Horizontal	16740.097	64.71	-5.31	59.40	74	-14.60	PK
Horizontal	16740.097	49.40	-5.31	44.09	54	-9.91	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.052	72.55	-20.12	52.43	74	-21.57	PK
Vertical	4739.052	59.31	-20.12	39.19	54	-14.81	AV
Vertical	11400.065	63.15	-8.72	54.43	68.2	-13.77	PK
Vertical	11400.065	49.85	-8.72	41.13	54	-12.87	AV
Vertical	17100.055	60.77	-3.92	56.85	74	-17.15	PK
Vertical	17100.055	49.69	-3.92	45.77	54	-8.23	AV
Horizontal	4739.121	74.99	-20.12	54.86	74	-19.14	PK
Horizontal	4739.121	59.45	-20.12	39.33	54	-14.67	AV
Horizontal	11400.028	62.77	-8.72	54.05	68.2	-14.15	PK
Horizontal	11400.028	49.36	-8.72	40.64	54	-13.36	AV
Horizontal	17100.023	62.79	-3.92	58.87	74	-15.13	PK
Horizontal	17100.023	49.45	-3.92	45.53	54	-8.47	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11n-HT40
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.177	60.98	-20.73	40.25	68.2	-27.95	PK
Vertical	4434.177	43.40	-20.73	22.67	54	-31.33	AV
Vertical	11020.166	62.18	-8.42	53.76	68.2	-14.44	PK
Vertical	11020.166	43.74	-8.42	35.32	54	-18.68	AV
Vertical	16530.034	64.63	-5.99	58.64	74	-15.36	PK
Vertical	16530.034	43.41	-5.99	37.42	54	-16.58	AV
Horizontal	4434.192	60.62	-20.73	39.89	74	-34.11	PK
Horizontal	4434.192	43.04	-20.73	22.31	54	-31.69	AV
Horizontal	11020.088	53.74	-8.42	45.32	68.2	-22.88	PK
Horizontal	11020.088	40.12	-8.42	31.70	54	-22.30	AV
Horizontal	16530.140	52.72	-5.99	46.73	74	-27.27	PK
Horizontal	16530.140	41.79	-5.99	35.80	54	-18.20	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.193	64.32	-20.42	43.90	74	-30.10	PK
Vertical	4592.193	43.90	-20.42	23.49	54	-30.51	AV
Vertical	11100.118	60.93	-8.40	52.53	68.2	-15.67	PK
Vertical	11100.118	43.08	-8.40	34.68	54	-19.32	AV
Vertical	16650.031	61.93	-5.60	56.33	74	-17.67	PK
Vertical	16650.031	43.94	-5.60	38.34	54	-15.66	AV
Horizontal	4592.061	63.06	-20.42	42.64	74	-31.36	PK
Horizontal	4592.061	43.61	-20.42	23.19	54	-30.81	AV
Horizontal	11100.110	53.89	-8.40	45.49	68.2	-22.71	PK
Horizontal	11100.110	42.41	-8.40	34.01	54	-19.99	AV
Horizontal	16650.074	51.03	-5.60	45.43	74	-28.57	PK
Horizontal	16650.074	43.00	-5.60	37.40	54	-16.60	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.193	60.03	-20.12	39.91	68.2	-28.29	PK
Vertical	4739.193	43.10	-20.12	22.98	54	-31.02	AV
Vertical	11340.026	62.84	-8.67	54.17	68.2	-14.03	PK
Vertical	11340.026	43.08	-8.67	34.41	54	-19.59	AV
Vertical	17010.133	63.49	-4.41	59.08	74	-14.92	PK
Vertical	17010.133	43.65	-4.41	39.24	54	-14.76	AV
Horizontal	4739.099	60.10	-20.12	39.98	68.2	-28.22	PK
Horizontal	4739.099	43.92	-20.12	23.80	54	-30.20	AV
Horizontal	11340.034	51.01	-8.67	42.34	68.2	-25.86	PK
Horizontal	11340.034	42.63	-8.67	33.96	54	-20.04	AV
Horizontal	17010.015	51.53	-4.41	47.12	74	-26.88	PK
Horizontal	17010.015	40.43	-4.41	36.02	54	-17.98	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.129	71.99	-20.73	51.26	68.2	-16.94	PK
Vertical	4434.129	59.60	-20.73	38.87	54	-15.13	AV
Vertical	11000.098	60.30	-8.40	51.90	68.2	-16.30	PK
Vertical	11000.098	49.69	-8.40	41.29	54	-12.71	AV
Vertical	16500.056	63.84	-6.09	57.75	74	-16.25	PK
Vertical	16500.056	49.46	-6.09	43.37	54	-10.63	AV
Horizontal	4434.132	70.74	-20.73	50.01	68.2	-18.19	PK
Horizontal	4434.132	59.91	-20.73	39.18	54	-14.82	AV
Horizontal	11000.144	63.42	-8.40	55.02	68.2	-13.18	PK
Horizontal	11000.144	49.61	-8.40	41.21	54	-12.79	AV
Horizontal	16500.078	62.30	-6.09	56.21	74	-17.79	PK
Horizontal	16500.078	49.42	-6.09	43.33	54	-10.67	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.116	74.07	-20.42	53.66	74	-20.34	PK
Vertical	4592.116	59.79	-20.42	39.37	54	-14.63	AV
Vertical	11160.067	64.57	-8.53	56.04	68.2	-12.16	PK
Vertical	11160.067	49.65	-8.53	41.12	54	-12.88	AV
Vertical	16740.151	63.92	-5.31	58.61	74	-15.39	PK
Vertical	16740.151	49.05	-5.31	43.74	54	-10.26	AV
Horizontal	4592.007	71.72	-20.42	51.31	74	-22.69	PK
Horizontal	4592.007	59.02	-20.42	38.61	54	-15.39	AV
Horizontal	11160.160	61.21	-8.53	52.68	68.2	-15.52	PK
Horizontal	11160.160	49.89	-8.53	41.36	54	-12.64	AV
Horizontal	16740.104	62.76	-5.31	57.45	74	-16.55	PK
Horizontal	16740.104	49.92	-5.31	44.61	54	-9.39	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.186	72.54	-20.12	52.42	74	-21.58	PK
Vertical	4739.186	59.73	-20.12	39.61	54	-14.39	AV
Vertical	11400.119	60.46	-8.72	51.74	68.2	-16.46	PK
Vertical	11400.119	49.72	-8.72	41.00	54	-13.00	AV
Vertical	17100.146	61.95	-3.92	58.03	74	-15.97	PK
Vertical	17100.146	49.84	-3.92	45.92	54	-8.08	AV
Horizontal	4739.029	72.82	-20.12	52.70	74	-21.30	PK
Horizontal	4739.029	59.08	-20.12	38.95	54	-15.05	AV
Horizontal	11400.083	60.95	-8.72	52.23	68.2	-15.97	PK
Horizontal	11400.083	49.77	-8.72	41.05	54	-12.95	AV
Horizontal	17100.031	60.95	-3.92	57.03	74	-16.97	PK
Horizontal	17100.031	49.06	-3.92	45.14	54	-8.86	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.158	60.37	-20.73	39.64	68.2	-28.56	PK
Vertical	4434.158	43.81	-20.73	23.08	54	-30.92	AV
Vertical	11020.093	62.19	-8.42	53.77	68.2	-14.43	PK
Vertical	11020.093	43.75	-8.42	35.33	54	-18.67	AV
Vertical	16530.162	62.62	-5.99	56.63	74	-17.37	PK
Vertical	16530.162	43.97	-5.99	37.98	54	-16.02	AV
Horizontal	4434.089	63.61	-20.73	42.88	74	-31.12	PK
Horizontal	4434.089	43.26	-20.73	22.53	54	-31.47	AV
Horizontal	11020.036	52.62	-8.42	44.20	68.2	-24.00	PK
Horizontal	11020.036	43.10	-8.42	34.68	54	-19.32	AV
Horizontal	16530.162	51.41	-5.99	45.42	74	-28.58	PK
Horizontal	16530.162	40.87	-5.99	34.88	54	-19.12	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.028	61.57	-20.42	41.15	74	-32.85	PK
Vertical	4592.028	43.13	-20.42	22.71	54	-31.29	AV
Vertical	11100.161	62.59	-8.40	54.19	68.2	-14.01	PK
Vertical	11100.161	43.34	-8.40	34.94	54	-19.06	AV
Vertical	16650.171	64.18	-5.60	58.58	74	-15.42	PK
Vertical	16650.171	43.27	-5.60	37.67	54	-16.33	AV
Horizontal	4592.060	64.52	-20.42	44.11	74	-29.89	PK
Horizontal	4592.060	43.18	-20.42	22.76	54	-31.24	AV
Horizontal	11100.164	51.86	-8.40	43.46	68.2	-24.74	PK
Horizontal	11100.164	44.71	-8.40	36.31	54	-17.69	AV
Horizontal	16650.018	50.83	-5.60	45.23	74	-28.77	PK
Horizontal	16650.018	40.95	-5.60	35.35	54	-18.65	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.079	64.96	-20.12	44.84	68.2	-23.36	PK
Vertical	4739.079	43.12	-20.12	22.99	54	-31.01	AV
Vertical	11340.064	62.27	-8.67	53.60	68.2	-14.60	PK
Vertical	11340.064	43.94	-8.67	35.27	54	-18.73	AV
Vertical	17010.089	64.18	-4.41	59.77	74	-14.23	PK
Vertical	17010.089	43.59	-4.41	39.18	54	-14.82	AV
Horizontal	4739.026	60.90	-20.12	40.78	68.2	-27.42	PK
Horizontal	4739.026	43.54	-20.12	23.41	54	-30.59	AV
Horizontal	11340.189	53.47	-8.67	44.80	68.2	-23.40	PK
Horizontal	11340.189	40.05	-8.67	31.38	54	-22.62	AV
Horizontal	17010.067	54.07	-4.41	49.66	74	-24.34	PK
Horizontal	17010.067	42.32	-4.41	37.91	54	-16.09	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.129	61.42	-20.73	40.69	68.2	-27.51	PK
Vertical	4434.129	43.36	-20.73	22.62	54	-31.38	AV
Vertical	11060.105	63.71	-8.45	55.26	68.2	-12.94	PK
Vertical	11060.105	43.74	-8.45	35.29	54	-18.71	AV
Vertical	16590.001	60.07	-5.79	54.28	74	-19.72	PK
Vertical	16590.001	43.47	-5.79	37.68	54	-16.32	AV
Horizontal	4434.044	60.04	-20.73	39.30	68.2	-28.90	PK
Horizontal	4434.044	43.47	-20.73	22.74	54	-31.26	AV
Horizontal	11060.190	50.89	-8.45	42.44	68.2	-25.76	PK
Horizontal	11060.190	40.05	-8.45	31.60	54	-22.40	AV
Horizontal	16590.157	51.42	-5.79	45.63	74	-28.37	PK
Horizontal	16590.157	40.72	-5.79	34.93	54	-19.07	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.056	74.88	-20.73	54.14	68.2	-14.06	PK
Vertical	4434.056	59.95	-20.73	39.22	54	-14.78	AV
Vertical	11000.191	60.31	-8.40	51.91	68.2	-16.29	PK
Vertical	11000.191	49.89	-8.40	41.49	54	-12.51	AV
Vertical	16500.018	62.85	-6.09	56.76	74	-17.24	PK
Vertical	16500.018	49.78	-6.09	43.69	54	-10.31	AV
Horizontal	4434.042	72.90	-20.73	52.17	68.2	-16.03	PK
Horizontal	4434.042	59.23	-20.73	38.50	54	-15.50	AV
Horizontal	11000.159	64.58	-8.40	56.18	68.2	-12.02	PK
Horizontal	11000.159	49.11	-8.40	40.71	54	-13.29	AV
Horizontal	16500.015	60.57	-6.09	54.48	74	-19.52	PK
Horizontal	16500.015	49.13	-6.09	43.04	54	-10.96	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.062	71.81	-20.42	51.40	74	-22.60	PK
Vertical	4592.062	59.60	-20.42	39.18	54	-14.82	AV
Vertical	11160.059	60.37	-8.53	51.84	68.2	-16.36	PK
Vertical	11160.059	49.53	-8.53	41.00	54	-13.00	AV
Vertical	16740.086	62.02	-5.31	56.71	74	-17.29	PK
Vertical	16740.086	49.69	-5.31	44.38	54	-9.62	AV
Horizontal	4592.146	70.72	-20.42	50.30	74	-23.70	PK
Horizontal	4592.146	59.02	-20.42	38.60	54	-15.40	AV
Horizontal	11160.139	61.63	-8.53	53.10	68.2	-15.10	PK
Horizontal	11160.139	49.71	-8.53	41.18	54	-12.82	AV
Horizontal	16740.154	60.70	-5.31	55.39	74	-18.61	PK
Horizontal	16740.154	49.21	-5.31	43.90	54	-10.10	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.117	70.77	-20.12	50.64	74	-23.36	PK
Vertical	4739.117	59.68	-20.12	39.56	54	-14.44	AV
Vertical	11400.031	63.33	-8.72	54.61	68.2	-13.59	PK
Vertical	11400.031	49.16	-8.72	40.44	54	-13.56	AV
Vertical	17100.175	61.34	-3.92	57.42	74	-16.58	PK
Vertical	17100.175	49.21	-3.92	45.29	54	-8.71	AV
Horizontal	4739.162	72.64	-20.12	52.51	74	-21.49	PK
Horizontal	4739.162	59.25	-20.12	39.13	54	-14.87	AV
Horizontal	11400.191	64.61	-8.72	55.89	68.2	-12.31	PK
Horizontal	11400.191	49.74	-8.72	41.02	54	-12.98	AV
Horizontal	17100.074	63.10	-3.92	59.18	74	-14.82	PK
Horizontal	17100.074	49.39	-3.92	45.47	54	-8.53	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.191	62.24	-20.73	41.51	68.2	-26.69	PK
Vertical	4434.191	43.93	-20.73	23.20	54	-30.80	AV
Vertical	11020.162	63.04	-8.42	54.62	68.2	-13.58	PK
Vertical	11020.162	43.59	-8.42	35.17	54	-18.83	AV
Vertical	16530.158	64.41	-5.99	58.42	74	-15.58	PK
Vertical	16530.158	43.10	-5.99	37.11	54	-16.89	AV
Horizontal	4434.058	64.17	-20.73	43.44	74	-30.56	PK
Horizontal	4434.058	43.47	-20.73	22.73	54	-31.27	AV
Horizontal	11020.095	52.53	-8.42	44.11	68.2	-24.09	PK
Horizontal	11020.095	40.20	-8.42	31.78	54	-22.22	AV
Horizontal	16530.106	50.80	-5.99	44.81	74	-29.19	PK
Horizontal	16530.106	42.18	-5.99	36.19	54	-17.81	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.192	60.75	-20.42	40.33	74	-33.67	PK
Vertical	4592.192	43.87	-20.42	23.45	54	-30.55	AV
Vertical	11100.011	64.29	-8.40	55.89	68.2	-12.31	PK
Vertical	11100.011	43.70	-8.40	35.30	54	-18.70	AV
Vertical	16650.086	60.31	-5.60	54.71	74	-19.29	PK
Vertical	16650.086	43.13	-5.60	37.53	54	-16.47	AV
Horizontal	4592.059	63.61	-20.42	43.20	74	-30.80	PK
Horizontal	4592.059	43.72	-20.42	23.30	54	-30.70	AV
Horizontal	11100.144	53.42	-8.40	45.02	68.2	-23.18	PK
Horizontal	11100.144	41.87	-8.40	33.47	54	-20.53	AV
Horizontal	16650.009	54.01	-5.60	48.41	74	-25.59	PK
Horizontal	16650.009	42.75	-5.60	37.15	54	-16.85	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.115	62.46	-20.12	42.34	68.2	-25.86	PK
Vertical	4739.115	43.97	-20.12	23.84	54	-30.16	AV
Vertical	11340.151	62.01	-8.67	53.34	68.2	-14.86	PK
Vertical	11340.151	43.21	-8.67	34.54	54	-19.46	AV
Vertical	17010.031	60.83	-4.41	56.42	74	-17.58	PK
Vertical	17010.031	43.81	-4.41	39.40	54	-14.60	AV
Horizontal	4739.103	63.56	-20.12	43.44	68.2	-24.76	PK
Horizontal	4739.103	43.93	-20.12	23.81	54	-30.19	AV
Horizontal	11340.020	51.48	-8.67	42.81	68.2	-25.39	PK
Horizontal	11340.020	43.53	-8.67	34.86	54	-19.14	AV
Horizontal	17010.071	53.94	-4.41	49.53	74	-24.47	PK
Horizontal	17010.071	44.74	-4.41	40.33	54	-13.67	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.047	60.64	-20.73	39.91	68.2	-28.29	PK
Vertical	4434.047	43.03	-20.73	22.30	54	-31.70	AV
Vertical	11060.047	63.29	-8.45	54.84	68.2	-13.36	PK
Vertical	11060.047	43.92	-8.45	35.47	54	-18.53	AV
Vertical	16590.008	61.32	-5.79	55.53	74	-18.47	PK
Vertical	16590.008	43.77	-5.79	37.98	54	-16.02	AV
Horizontal	4434.110	61.26	-20.73	40.53	68.2	-27.67	PK
Horizontal	4434.110	43.51	-20.73	22.78	54	-31.22	AV
Horizontal	11060.069	53.00	-8.45	44.55	68.2	-23.65	PK
Horizontal	11060.069	40.10	-8.45	31.65	54	-22.35	AV
Horizontal	16590.070	52.89	-5.79	47.10	74	-26.90	PK
Horizontal	16590.070	40.70	-5.79	34.91	54	-19.09	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.127	71.53	-20.24	51.29	74	-22.71	PK
Vertical	4679.127	59.71	-20.24	39.47	54	-14.53	AV
Vertical	11490.106	61.44	-8.79	52.65	68.2	-15.55	PK
Vertical	11490.106	49.97	-8.79	41.18	54	-12.82	AV
Vertical	17235.086	58.83	-3.18	55.65	68.2	-12.55	PK
Vertical	17235.086	44.53	-3.18	41.35	54	-12.65	AV
Horizontal	4679.033	73.18	-20.73	52.45	74	-21.55	PK
Horizontal	4679.033	59.49	-20.73	38.76	54	-15.24	AV
Horizontal	11490.169	63.89	-8.79	55.10	68.2	-13.10	PK
Horizontal	11490.169	49.13	-8.79	40.34	54	-13.66	AV
Horizontal	17235.090	55.37	-3.18	52.19	68.2	-16.01	PK
Horizontal	17235.090	44.41	-3.18	41.23	54	-12.77	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.112	72.08	-20.42	51.66	74	-22.34	PK
Vertical	4592.112	59.76	-20.42	39.34	54	-14.66	AV
Vertical	11570.089	63.48	-8.86	54.62	68.2	-13.58	PK
Vertical	11570.089	49.39	-8.86	40.53	54	-13.47	AV
Vertical	17355.172	59.80	-2.52	57.28	68.2	-10.92	PK
Vertical	17355.172	44.94	-2.52	42.42	54	-11.58	AV
Horizontal	4592.186	71.22	-20.42	50.81	74	-23.19	PK
Horizontal	4592.186	59.15	-20.42	38.73	54	-15.27	AV
Horizontal	11570.125	60.25	-8.86	51.39	68.2	-16.81	PK
Horizontal	11570.125	49.79	-8.86	40.93	54	-13.07	AV
Horizontal	17355.033	56.16	-2.52	53.64	68.2	-14.56	PK
Horizontal	17355.033	44.83	-2.52	42.31	54	-11.69	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.035	74.85	-18.93	55.92	68.2	-12.28	PK
Vertical	6039.035	59.27	-18.93	40.34	54	-13.66	AV
Vertical	11650.080	61.79	-8.92	52.87	74	-21.13	PK
Vertical	11650.080	49.38	-8.92	40.46	54	-13.54	AV
Vertical	17475.149	56.57	-1.86	54.71	68.2	-13.49	PK
Vertical	17475.149	44.25	-1.86	42.39	54	-11.61	AV
Horizontal	6039.025	74.20	-18.93	55.26	68.2	-12.94	PK
Horizontal	6039.025	59.75	-18.93	40.81	54	-13.19	AV
Horizontal	11650.130	63.37	-8.92	54.45	74	-19.55	PK
Horizontal	11650.130	49.23	-8.92	40.31	54	-13.69	AV
Horizontal	17475.077	57.03	-1.86	55.17	68.2	-13.03	PK
Horizontal	17475.077	44.65	-1.86	42.79	54	-11.21	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.067	72.55	-20.24	52.31	74	-21.69	PK
Vertical	4679.067	59.83	-20.24	39.59	54	-14.41	AV
Vertical	11490.101	61.23	-8.79	52.44	68.2	-15.76	PK
Vertical	11490.101	49.99	-8.79	41.20	54	-12.80	AV
Vertical	17235.059	55.96	-3.18	52.78	68.2	-15.42	PK
Vertical	17235.059	44.15	-3.18	40.97	54	-13.03	AV
Horizontal	4679.020	73.03	-20.24	52.79	74	-21.21	PK
Horizontal	4679.020	59.01	-20.24	38.76	54	-15.24	AV
Horizontal	11490.046	64.11	-8.79	55.32	68.2	-12.88	PK
Horizontal	11490.046	49.84	-8.79	41.05	54	-12.95	AV
Horizontal	17235.140	57.33	-3.18	54.15	68.2	-14.05	PK
Horizontal	17235.140	44.38	-3.18	41.20	54	-12.80	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.120	70.87	-20.42	50.46	74	-23.54	PK
Vertical	4592.120	59.59	-20.42	39.18	54	-14.82	AV
Vertical	11570.081	61.39	-8.86	52.53	68.2	-15.67	PK
Vertical	11570.081	49.61	-8.86	40.75	54	-13.25	AV
Vertical	17355.136	59.20	-2.52	56.68	68.2	-11.52	PK
Vertical	17355.136	44.80	-2.52	42.28	54	-11.72	AV
Horizontal	4592.008	72.69	-20.42	52.28	74	-21.72	PK
Horizontal	4592.008	59.87	-20.42	39.45	54	-14.55	AV
Horizontal	11570.175	64.02	-8.86	55.16	68.2	-13.04	PK
Horizontal	11570.175	49.70	-8.86	40.84	54	-13.16	AV
Horizontal	17355.051	57.32	-2.52	54.80	68.2	-13.40	PK
Horizontal	17355.051	44.72	-2.52	42.20	54	-11.80	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.100	74.62	-18.93	55.69	68.2	-12.51	PK
Vertical	6039.100	59.18	-18.93	40.25	54	-13.75	AV
Vertical	11650.172	63.07	-8.92	54.15	74	-19.85	PK
Vertical	11650.172	49.29	-8.92	40.37	54	-13.63	AV
Vertical	17475.027	57.12	-1.86	55.26	68.2	-12.94	PK
Vertical	17475.027	44.92	-1.86	43.06	54	-10.94	AV
Horizontal	6039.112	72.75	-18.93	53.82	68.2	-14.38	PK
Horizontal	6039.112	59.41	-18.93	40.47	54	-13.53	AV
Horizontal	11650.188	60.59	-8.92	51.67	74	-22.33	PK
Horizontal	11650.188	49.11	-8.92	40.19	54	-13.81	AV
Horizontal	17475.183	55.92	-1.86	54.06	68.2	-14.14	PK
Horizontal	17475.183	44.07	-1.86	42.21	54	-11.79	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.035	70.97	-20.24	50.72	74	-23.28	PK
Vertical	4679.035	59.25	-20.24	39.01	54	-14.99	AV
Vertical	11510.038	62.62	-8.81	53.81	74	-20.19	PK
Vertical	11510.038	49.13	-8.81	40.32	54	-13.68	AV
Vertical	17265.025	59.75	-3.01	56.74	68.2	-11.46	PK
Vertical	17265.025	44.87	-3.01	41.86	54	-12.14	AV
Horizontal	4679.068	71.28	-20.24	51.03	74	-22.97	PK
Horizontal	4679.068	59.12	-20.24	38.88	54	-15.12	AV
Horizontal	11510.079	63.14	-8.81	54.33	74	-19.67	PK
Horizontal	11510.079	49.13	-8.81	40.32	54	-13.68	AV
Horizontal	17265.021	58.32	-3.01	55.31	68.2	-12.89	PK
Horizontal	17265.021	44.87	-3.01	41.86	54	-12.14	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.163	73.58	-18.93	54.65	68.2	-13.55	PK
Vertical	6039.163	59.80	-18.93	40.87	54	-13.13	AV
Vertical	11590.005	64.69	-8.87	55.82	74	-18.18	PK
Vertical	11590.005	49.80	-8.87	40.93	54	-13.07	AV
Vertical	17385.198	56.62	-2.35	54.27	68.2	-13.93	PK
Vertical	17385.198	44.88	-2.35	42.53	54	-11.47	AV
Horizontal	6039.060	73.97	-18.93	55.04	68.2	-13.16	PK
Horizontal	6039.060	59.11	-18.93	40.18	54	-13.82	AV
Horizontal	11590.003	60.21	-8.87	51.34	74	-22.66	PK
Horizontal	11590.003	49.13	-8.87	40.26	54	-13.74	AV
Horizontal	17385.001	59.14	-2.35	56.79	68.2	-11.41	PK
Horizontal	17385.001	44.52	-2.35	42.17	54	-11.83	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ac-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.027	72.66	-20.24	52.41	74	-21.59	PK
Vertical	4679.027	59.14	-20.24	38.90	54	-15.10	AV
Vertical	11490.051	62.24	-8.79	53.45	68.2	-14.75	PK
Vertical	11490.051	49.22	-8.79	40.43	54	-13.57	AV
Vertical	17235.175	57.40	-3.18	54.22	68.2	-13.98	PK
Vertical	17235.175	44.18	-3.18	41.00	54	-13.00	AV
Horizontal	4679.034	74.11	-20.24	53.87	74	-20.13	PK
Horizontal	4679.034	59.49	-20.24	39.25	54	-14.75	AV
Horizontal	11490.043	61.30	-8.79	52.51	68.2	-15.69	PK
Horizontal	11490.043	49.74	-8.79	40.95	54	-13.05	AV
Horizontal	17235.182	55.41	-3.18	52.23	68.2	-15.97	PK
Horizontal	17235.182	44.70	-3.18	41.52	54	-12.48	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.092	74.53	-20.42	54.11	74	-19.89	PK
Vertical	4592.092	59.72	-20.42	39.31	54	-14.69	AV
Vertical	11570.000	61.61	-8.86	52.75	68.2	-15.45	PK
Vertical	11570.000	49.35	-8.86	40.49	54	-13.51	AV
Vertical	17355.089	57.86	-2.52	55.34	68.2	-12.86	PK
Vertical	17355.089	44.88	-2.52	42.36	54	-11.64	AV
Horizontal	4592.156	70.32	-20.42	49.90	74	-24.10	PK
Horizontal	4592.156	59.58	-20.42	39.17	54	-14.83	AV
Horizontal	11570.028	64.84	-8.86	55.98	68.2	-12.22	PK
Horizontal	11570.028	49.55	-8.86	40.69	54	-13.31	AV
Horizontal	17355.169	59.21	-2.52	56.69	68.2	-11.51	PK
Horizontal	17355.169	44.15	-2.52	41.63	54	-12.37	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.161	73.77	-18.93	54.84	68.2	-13.36	PK
Vertical	6039.161	59.97	-18.93	41.04	54	-12.96	AV
Vertical	11650.120	62.19	-8.92	53.27	74	-20.73	PK
Vertical	11650.120	49.10	-8.92	40.18	54	-13.82	AV
Vertical	17475.034	58.11	-1.86	56.25	68.2	-11.95	PK
Vertical	17475.034	44.09	-1.86	42.23	54	-11.77	AV
Horizontal	6039.064	74.92	-18.93	55.98	68.2	-12.22	PK
Horizontal	6039.064	59.98	-18.93	41.05	54	-12.95	AV
Horizontal	11650.187	62.41	-8.92	53.49	74	-20.51	PK
Horizontal	11650.187	49.50	-8.92	40.58	54	-13.42	AV
Horizontal	17475.172	56.87	-1.86	55.01	68.2	-13.19	PK
Horizontal	17475.172	44.50	-1.86	42.64	54	-11.36	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11ac-HT40
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.171	71.53	-20.24	51.29	74	-22.71	PK
Vertical	4679.171	59.89	-20.24	39.65	54	-14.35	AV
Vertical	11510.183	61.55	-8.81	52.74	74	-21.26	PK
Vertical	11510.183	49.24	-8.81	40.43	54	-13.57	AV
Vertical	17265.101	56.24	-3.01	53.23	68.2	-14.97	PK
Vertical	17265.101	44.28	-3.01	41.27	54	-12.73	AV
Horizontal	4679.100	72.81	-20.24	52.57	74	-21.43	PK
Horizontal	4679.100	59.24	-20.24	39.00	54	-15.00	AV
Horizontal	11510.043	62.72	-8.81	53.91	74	-20.09	PK
Horizontal	11510.043	49.13	-8.81	40.32	54	-13.68	AV
Horizontal	17265.064	57.67	-3.01	54.66	68.2	-13.54	PK
Horizontal	17265.064	44.10	-3.01	41.09	54	-12.91	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.057	74.42	-18.93	55.48	68.2	-12.72	PK
Vertical	6039.057	59.05	-18.93	40.12	54	-13.88	AV
Vertical	11590.187	60.14	-8.87	51.27	74	-22.73	PK
Vertical	11590.187	49.93	-8.87	41.06	54	-12.94	AV
Vertical	17385.083	56.24	-2.35	53.89	68.2	-14.31	PK
Vertical	17385.083	44.17	-2.35	41.82	54	-12.18	AV
Horizontal	6039.114	73.75	-18.93	54.82	68.2	-13.38	PK
Horizontal	6039.114	59.99	-18.93	41.06	54	-12.94	AV
Horizontal	11590.151	62.68	-8.87	53.81	74	-20.19	PK
Horizontal	11590.151	49.99	-8.87	41.12	54	-12.88	AV
Horizontal	17385.100	59.79	-2.35	57.44	68.2	-10.76	PK
Horizontal	17385.100	44.43	-2.35	42.08	54	-11.92	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11ac-HT80
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5775 MHz)-Above 1G							
Vertical	4679.172	70.22	-20.24	49.98	74	-24.02	PK
Vertical	4679.172	59.54	-20.24	39.30	54	-14.70	AV
Vertical	11550.124	60.70	-8.84	51.86	74	-22.14	PK
Vertical	11550.124	49.24	-8.84	40.40	54	-13.60	AV
Vertical	17325.045	58.91	-2.68	56.23	68.2	-11.97	PK
Vertical	17325.045	44.95	-2.68	42.27	54	-11.73	AV
Horizontal	4679.123	70.37	-20.24	50.13	74	-23.87	PK
Horizontal	4679.123	59.01	-20.24	38.77	54	-15.23	AV
Horizontal	11550.142	62.10	-8.84	53.26	74	-20.74	PK
Horizontal	11550.142	49.95	-8.84	41.11	54	-12.89	AV
Horizontal	17325.114	55.15	-2.68	52.47	68.2	-15.73	PK
Horizontal	17325.114	44.94	-2.68	42.26	54	-11.74	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ax-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.073	74.13	-20.24	53.88	74	-20.12	PK
Vertical	4679.073	59.21	-20.24	38.97	54	-15.03	AV
Vertical	11490.044	64.98	-8.79	56.19	68.2	-12.01	PK
Vertical	11490.044	49.77	-8.79	40.98	54	-13.02	AV
Vertical	17235.086	56.38	-3.18	53.20	68.2	-15.00	PK
Vertical	17235.086	44.57	-3.18	41.39	54	-12.61	AV
Horizontal	4679.177	72.55	-20.24	52.31	74	-21.69	PK
Horizontal	4679.177	59.41	-20.24	39.17	54	-14.83	AV
Horizontal	11490.045	62.08	-8.79	53.29	68.2	-14.91	PK
Horizontal	11490.045	49.23	-8.79	40.44	54	-13.56	AV
Horizontal	17235.003	56.39	-3.18	53.21	68.2	-14.99	PK
Horizontal	17235.003	44.59	-3.18	41.41	54	-12.59	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.101	73.45	-20.42	53.04	74	-20.96	PK
Vertical	4592.101	59.37	-20.42	38.95	54	-15.05	AV
Vertical	11570.112	63.05	-8.86	54.19	68.2	-14.01	PK
Vertical	11570.112	49.66	-8.86	40.80	54	-13.20	AV
Vertical	17355.038	56.25	-2.52	53.73	68.2	-14.47	PK
Vertical	17355.038	44.07	-2.52	41.55	54	-12.45	AV
Horizontal	4592.121	72.26	-20.42	51.84	74	-22.16	PK
Horizontal	4592.121	59.37	-20.42	38.96	54	-15.04	AV
Horizontal	11570.154	61.89	-8.86	53.03	68.2	-15.17	PK
Horizontal	11570.154	49.24	-8.86	40.38	54	-13.62	AV
Horizontal	17355.146	55.55	-2.52	53.03	68.2	-15.17	PK
Horizontal	17355.146	44.97	-2.52	42.45	54	-11.55	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.100	71.48	-18.93	52.55	68.2	-15.65	PK
Vertical	6039.100	59.47	-18.93	40.54	54	-13.46	AV
Vertical	11650.090	62.31	-8.92	53.39	74	-20.61	PK
Vertical	11650.090	49.80	-8.92	40.88	54	-13.12	AV
Vertical	17475.003	59.49	-1.86	57.63	68.2	-10.57	PK
Vertical	17475.003	44.61	-1.86	42.75	54	-11.25	AV
Horizontal	6039.045	70.67	-18.93	51.74	68.2	-16.46	PK
Horizontal	6039.045	59.28	-18.93	40.35	54	-13.65	AV
Horizontal	11650.042	63.32	-8.92	54.40	74	-19.60	PK
Horizontal	11650.042	49.26	-8.92	40.34	54	-13.66	AV
Horizontal	17475.112	59.92	-1.86	58.06	68.2	-10.14	PK
Horizontal	17475.112	44.88	-1.86	43.02	54	-10.98	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11ax-HT40
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.047	72.90	-20.24	52.65	74	-21.35	PK
Vertical	4679.047	59.65	-20.24	39.41	54	-14.59	AV
Vertical	11510.088	61.36	-8.81	52.55	74	-21.45	PK
Vertical	11510.088	49.64	-8.81	40.83	54	-13.17	AV
Vertical	17265.006	56.59	-3.01	53.58	68.2	-14.62	PK
Vertical	17265.006	44.68	-3.01	41.67	54	-12.33	AV
Horizontal	4679.001	73.62	-20.24	53.38	74	-20.62	PK
Horizontal	4679.001	59.79	-20.24	39.55	54	-14.45	AV
Horizontal	11510.149	62.61	-8.81	53.80	74	-20.20	PK
Horizontal	11510.149	49.82	-8.81	41.01	54	-12.99	AV
Horizontal	17265.189	59.75	-3.01	56.74	68.2	-11.46	PK
Horizontal	17265.189	44.93	-3.01	41.92	54	-12.08	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.116	71.50	-18.93	52.57	68.2	-15.63	PK
Vertical	6039.116	59.33	-18.93	40.40	54	-13.60	AV
Vertical	11590.073	64.75	-8.87	55.88	74	-18.12	PK
Vertical	11590.073	49.71	-8.87	40.84	54	-13.16	AV
Vertical	17385.003	59.13	-2.35	56.78	68.2	-11.42	PK
Vertical	17385.003	44.63	-2.35	42.28	54	-11.72	AV
Horizontal	6039.048	71.55	-18.93	52.62	68.2	-15.58	PK
Horizontal	6039.048	59.97	-18.93	41.04	54	-12.96	AV
Horizontal	11590.146	62.16	-8.87	53.29	74	-20.71	PK
Horizontal	11590.146	49.84	-8.87	40.97	54	-13.03	AV
Horizontal	17385.122	57.02	-2.35	54.67	68.2	-13.53	PK
Horizontal	17385.122	44.28	-2.35	41.93	54	-12.07	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11ax-HT80
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5775 MHz)-Above 1G							
Vertical	4679.080	71.24	-20.24	51.00	74	-23.00	PK
Vertical	4679.080	59.87	-20.24	39.63	54	-14.37	AV
Vertical	11550.009	64.09	-8.84	55.25	74	-18.75	PK
Vertical	11550.009	49.28	-8.84	40.44	54	-13.56	AV
Vertical	17325.042	56.22	-2.68	53.54	68.2	-14.66	PK
Vertical	17325.042	44.55	-2.68	41.87	54	-12.13	AV
Horizontal	4679.005	70.16	-20.24	49.91	74	-24.09	PK
Horizontal	4679.005	59.52	-20.24	39.28	54	-14.72	AV
Horizontal	11550.120	60.88	-8.84	52.04	74	-21.96	PK
Horizontal	11550.120	49.33	-8.84	40.49	54	-13.51	AV
Horizontal	17325.138	56.22	-2.68	53.54	68.2	-14.66	PK
Horizontal	17325.138	44.62	-2.68	41.94	54	-12.06	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Between 1GHz – 40GHz

ANT 4

Test Mode:	TX(5.1G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.055	74.48	-20.73	53.75	68.2	-14.45	PK
Vertical	4434.055	59.50	-20.73	38.77	54	-15.23	AV
Vertical	10360.189	62.29	-9.36	52.93	68.2	-15.27	PK
Vertical	10360.189	49.33	-9.36	39.97	54	-14.03	AV
Vertical	15540.160	60.26	-7.84	52.42	74	-21.58	PK
Vertical	15540.160	49.16	-7.84	41.32	54	-12.68	AV
Horizontal	4434.142	73.95	-20.73	53.22	68.2	-14.98	PK
Horizontal	4434.142	59.31	-20.73	38.58	54	-15.42	AV
Horizontal	10360.170	62.69	-9.36	53.33	68.2	-14.87	PK
Horizontal	10360.170	49.38	-9.36	40.02	54	-13.98	AV
Horizontal	15540.058	61.49	-7.84	53.65	74	-20.35	PK
Horizontal	15540.058	49.17	-7.84	41.33	54	-12.67	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.178	70.90	-20.42	50.48	74	-23.52	PK
Vertical	4592.178	59.72	-20.42	39.31	54	-14.69	AV
Vertical	10400.187	63.00	-9.30	53.70	68.2	-14.50	PK
Vertical	10400.187	49.94	-9.30	40.64	54	-13.36	AV
Vertical	15600.153	62.77	-7.82	54.95	74	-19.05	PK
Vertical	15600.153	49.04	-7.82	41.22	54	-12.78	AV
Horizontal	4592.045	73.26	-20.42	52.84	74	-21.16	PK
Horizontal	4592.045	59.57	-20.42	39.15	54	-14.85	AV
Horizontal	10400.040	64.47	-9.30	55.17	68.2	-13.03	PK
Horizontal	10400.040	49.96	-9.30	40.66	54	-13.34	AV
Horizontal	15600.040	64.02	-7.82	56.20	74	-17.80	PK
Horizontal	15600.040	49.97	-7.82	42.15	54	-11.85	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.034	70.85	-20.12	50.73	74	-23.27	PK
Vertical	4739.034	59.71	-20.12	39.58	54	-14.42	AV
Vertical	10480.007	60.49	-9.18	51.31	68.2	-16.89	PK
Vertical	10480.007	49.80	-9.18	40.62	54	-13.38	AV
Vertical	15720.192	61.63	-7.78	53.85	74	-20.15	PK
Vertical	15720.192	49.11	-7.78	41.33	54	-12.67	AV
Horizontal	4739.167	72.29	-20.12	52.17	74	-21.83	PK
Horizontal	4739.167	59.10	-20.12	38.98	54	-15.02	AV
Horizontal	10480.039	63.10	-9.18	53.92	68.2	-14.28	PK
Horizontal	10480.039	49.89	-9.18	40.71	54	-13.29	AV
Horizontal	15720.053	61.50	-7.78	53.72	74	-20.28	PK
Horizontal	15720.053	49.66	-7.78	41.88	54	-12.12	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.006	74.64	-20.73	53.91	68.2	-14.29	PK
Vertical	4434.006	59.12	-20.73	38.39	54	-15.61	AV
Vertical	10360.097	60.08	-9.36	50.72	68.2	-17.48	PK
Vertical	10360.097	49.88	-9.36	40.52	54	-13.48	AV
Vertical	15540.151	62.87	-7.84	55.03	74	-18.97	PK
Vertical	15540.151	49.59	-7.84	41.75	54	-12.25	AV
Horizontal	4434.107	71.43	-20.73	50.70	68.2	-17.50	PK
Horizontal	4434.107	59.40	-20.73	38.67	54	-15.33	AV
Horizontal	10360.129	61.76	-9.36	52.40	68.2	-15.80	PK
Horizontal	10360.129	49.97	-9.36	40.61	54	-13.39	AV
Horizontal	15540.015	60.45	-7.84	52.61	74	-21.39	PK
Horizontal	15540.015	49.06	-7.84	41.22	54	-12.78	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.151	71.54	-20.42	51.12	74	-22.88	PK
Vertical	4592.151	59.72	-20.42	39.31	54	-14.69	AV
Vertical	10400.126	64.03	-9.30	54.73	68.2	-13.47	PK
Vertical	10400.126	49.18	-9.30	39.88	54	-14.12	AV
Vertical	15600.075	61.13	-7.82	53.31	74	-20.69	PK
Vertical	15600.075	49.41	-7.82	41.59	54	-12.41	AV
Horizontal	4592.175	74.25	-20.42	53.83	74	-20.17	PK
Horizontal	4592.175	59.53	-20.42	39.11	54	-14.89	AV
Horizontal	10400.128	60.25	-9.30	50.95	68.2	-17.25	PK
Horizontal	10400.128	49.56	-9.30	40.26	54	-13.74	AV
Horizontal	15600.019	61.28	-7.82	53.46	74	-20.54	PK
Horizontal	15600.019	49.68	-7.82	41.86	54	-12.14	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.175	71.83	-20.12	51.70	74	-22.30	PK
Vertical	4739.175	59.77	-20.12	39.65	54	-14.35	AV
Vertical	10480.165	64.45	-9.18	55.27	68.2	-12.93	PK
Vertical	10480.165	49.55	-9.18	40.37	54	-13.63	AV
Vertical	15720.103	62.71	-7.78	54.93	74	-19.07	PK
Vertical	15720.103	49.36	-7.78	41.58	54	-12.42	AV
Horizontal	4739.023	71.27	-20.12	51.14	74	-22.86	PK
Horizontal	4739.023	59.03	-20.12	38.90	54	-15.10	AV
Horizontal	10480.196	60.03	-9.18	50.85	68.2	-17.35	PK
Horizontal	10480.196	49.98	-9.18	40.80	54	-13.20	AV
Horizontal	15720.115	64.27	-7.78	56.49	74	-17.51	PK
Horizontal	15720.115	49.39	-7.78	41.61	54	-12.39	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.114	74.49	-20.73	53.76	68.2	-14.44	PK
Vertical	4434.114	59.91	-20.73	39.18	54	-14.82	AV
Vertical	10380.050	63.12	-9.33	53.79	68.2	-14.41	PK
Vertical	10380.050	49.17	-9.33	39.84	54	-14.16	AV
Vertical	15570.077	60.68	-7.83	52.85	74	-21.15	PK
Vertical	15570.077	49.86	-7.83	42.03	54	-11.97	AV
Horizontal	4434.139	73.48	-20.73	52.75	74	-21.25	PK
Horizontal	4434.139	59.16	-20.73	38.43	54	-15.57	AV
Horizontal	10380.147	63.11	-9.33	53.78	68.2	-14.42	PK
Horizontal	10380.147	49.08	-9.33	39.75	54	-14.25	AV
Horizontal	15570.032	60.97	-7.83	53.14	74	-20.86	PK
Horizontal	15570.032	49.84	-7.83	42.01	54	-11.99	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.058	72.08	-20.12	51.96	68.2	-16.24	PK
Vertical	4739.058	59.41	-20.12	39.29	54	-14.71	AV
Vertical	10460.193	61.92	-9.21	52.71	68.2	-15.49	PK
Vertical	10460.193	49.25	-9.21	40.04	54	-13.96	AV
Vertical	15690.109	63.06	-7.79	55.27	74	-18.73	PK
Vertical	15690.109	49.10	-7.79	41.31	54	-12.69	AV
Horizontal	4739.109	71.06	-20.12	50.94	68.2	-17.26	PK
Horizontal	4739.109	59.92	-20.12	39.80	54	-14.20	AV
Horizontal	10460.061	63.97	-9.21	54.76	68.2	-13.44	PK
Horizontal	10460.061	49.70	-9.21	40.49	54	-13.51	AV
Horizontal	15690.091	60.55	-7.79	52.76	74	-21.24	PK
Horizontal	15690.091	49.33	-7.79	41.54	54	-12.46	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.162	70.02	-20.73	49.28	68.2	-18.92	PK
Vertical	4434.162	59.35	-20.73	38.62	54	-15.38	AV
Vertical	10360.095	64.19	-9.36	54.83	68.2	-13.37	PK
Vertical	10360.095	49.64	-9.36	40.28	54	-13.72	AV
Vertical	15540.007	62.59	-7.84	54.75	74	-19.25	PK
Vertical	15540.007	49.82	-7.84	41.98	54	-12.02	AV
Horizontal	4434.184	72.87	-20.73	52.14	68.2	-16.06	PK
Horizontal	4434.184	59.08	-20.73	38.35	54	-15.65	AV
Horizontal	10360.056	62.08	-9.36	52.72	68.2	-15.48	PK
Horizontal	10360.056	49.87	-9.36	40.51	54	-13.49	AV
Horizontal	15540.008	63.97	-7.84	56.13	74	-17.87	PK
Horizontal	15540.008	49.63	-7.84	41.79	54	-12.21	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.039	72.54	-20.42	52.13	74	-21.87	PK
Vertical	4592.039	59.28	-20.42	38.87	54	-15.13	AV
Vertical	10400.114	64.76	-9.30	55.46	68.2	-12.74	PK
Vertical	10400.114	49.99	-9.30	40.69	54	-13.31	AV
Vertical	15600.082	62.31	-7.82	54.49	74	-19.51	PK
Vertical	15600.082	49.35	-7.82	41.53	54	-12.47	AV
Horizontal	4592.038	72.68	-20.42	52.26	74	-21.74	PK
Horizontal	4592.038	59.39	-20.42	38.97	54	-15.03	AV
Horizontal	10400.193	60.98	-9.30	51.68	68.2	-16.52	PK
Horizontal	10400.193	49.61	-9.30	40.31	54	-13.69	AV
Horizontal	15600.068	64.26	-7.82	56.44	74	-17.56	PK
Horizontal	15600.068	49.36	-7.82	41.54	54	-12.46	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.074	74.87	-20.12	54.75	74	-19.25	PK
Vertical	4739.074	59.54	-20.12	39.42	54	-14.58	AV
Vertical	10480.189	61.58	-9.18	52.40	68.2	-15.80	PK
Vertical	10480.189	49.80	-9.18	40.62	54	-13.38	AV
Vertical	15720.166	61.88	-7.78	54.10	74	-19.90	PK
Vertical	15720.166	49.49	-7.78	41.71	54	-12.29	AV
Horizontal	4739.077	74.02	-20.12	53.90	74	-20.10	PK
Horizontal	4739.077	59.24	-20.12	39.11	54	-14.89	AV
Horizontal	10480.179	62.03	-9.18	52.85	68.2	-15.35	PK
Horizontal	10480.179	49.60	-9.18	40.42	54	-13.58	AV
Horizontal	15720.015	61.54	-7.78	53.76	74	-20.24	PK
Horizontal	15720.015	49.36	-7.78	41.58	54	-12.42	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.078	72.18	-20.73	51.45	68.2	-16.75	PK
Vertical	4434.078	59.13	-20.73	38.40	54	-15.60	AV
Vertical	10380.188	63.49	-9.33	54.16	68.2	-14.04	PK
Vertical	10380.188	49.46	-9.33	40.13	54	-13.87	AV
Vertical	15570.025	63.68	-7.83	55.85	74	-18.15	PK
Vertical	15570.025	49.08	-7.83	41.25	54	-12.75	AV
Horizontal	4434.053	71.11	-20.73	50.38	74	-23.62	PK
Horizontal	4434.053	59.26	-20.73	38.52	54	-15.48	AV
Horizontal	10380.010	63.62	-9.33	54.29	68.2	-13.91	PK
Horizontal	10380.010	49.57	-9.33	40.24	54	-13.76	AV
Horizontal	15570.118	61.14	-7.83	53.31	74	-20.69	PK
Horizontal	15570.118	49.51	-7.83	41.68	54	-12.32	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.078	74.96	-20.12	54.84	68.2	-13.36	PK
Vertical	4739.078	59.63	-20.12	39.51	54	-14.49	AV
Vertical	10460.014	64.93	-9.21	55.72	68.2	-12.48	PK
Vertical	10460.014	49.45	-9.21	40.24	54	-13.76	AV
Vertical	15690.176	62.99	-7.79	55.20	74	-18.80	PK
Vertical	15690.176	49.39	-7.79	41.60	54	-12.40	AV
Horizontal	4739.193	71.09	-20.12	50.97	68.2	-17.23	PK
Horizontal	4739.193	59.04	-20.12	38.92	54	-15.08	AV
Horizontal	10460.171	62.99	-9.21	53.78	68.2	-14.42	PK
Horizontal	10460.171	49.37	-9.21	40.16	54	-13.84	AV
Horizontal	15690.033	64.01	-7.79	56.22	74	-17.78	PK
Horizontal	15690.033	49.76	-7.79	41.97	54	-12.03	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5210 MHz)-Above 1G							
Vertical	4434.051	70.52	-20.73	49.79	68.2	-18.41	PK
Vertical	4434.051	59.60	-20.73	38.87	54	-15.13	AV
Vertical	10420.197	64.83	-9.27	55.56	68.2	-12.64	PK
Vertical	10420.197	49.98	-9.27	40.71	54	-13.29	AV
Vertical	15630.090	62.15	-7.81	54.34	74	-19.66	PK
Vertical	15630.090	49.59	-7.81	41.78	54	-12.22	AV
Horizontal	4434.028	70.98	-20.73	50.25	68.2	-17.95	PK
Horizontal	4434.028	59.58	-20.73	38.84	54	-15.16	AV
Horizontal	10420.012	43.85	9.27	53.12	68.2	-15.08	PK
Horizontal	10420.012	29.25	9.27	38.52	54	-15.48	AV
Horizontal	15630.066	64.85	-7.81	57.04	74	-16.96	PK
Horizontal	15630.066	49.27	-7.81	41.46	54	-12.54	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.011	70.21	-20.73	49.48	68.2	-18.72	PK
Vertical	4434.011	59.03	-20.73	38.29	54	-15.71	AV
Vertical	10360.185	63.91	-9.36	54.55	68.2	-13.65	PK
Vertical	10360.185	49.00	-9.36	39.64	54	-14.36	AV
Vertical	15540.032	64.30	-7.84	56.46	74	-17.54	PK
Vertical	15540.032	49.82	-7.84	41.98	54	-12.02	AV
Horizontal	4434.022	71.60	-20.73	50.87	68.2	-17.33	PK
Horizontal	4434.022	59.80	-20.73	39.07	54	-14.93	AV
Horizontal	10360.003	62.82	-9.36	53.46	68.2	-14.74	PK
Horizontal	10360.003	49.56	-9.36	40.20	54	-13.80	AV
Horizontal	15540.024	61.06	-7.84	53.22	74	-20.78	PK
Horizontal	15540.024	49.68	-7.84	41.84	54	-12.16	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.048	73.40	-20.42	52.99	74	-21.01	PK
Vertical	4592.048	59.34	-20.42	38.92	54	-15.08	AV
Vertical	10400.070	60.60	-9.30	51.30	68.2	-16.90	PK
Vertical	10400.070	49.85	-9.30	40.55	54	-13.45	AV
Vertical	15600.109	60.31	-7.82	52.49	74	-21.51	PK
Vertical	15600.109	49.40	-7.82	41.58	54	-12.42	AV
Horizontal	4592.121	73.52	-20.42	53.11	74	-20.89	PK
Horizontal	4592.121	59.94	-20.42	39.52	54	-14.48	AV
Horizontal	10400.140	64.94	-9.30	55.64	68.2	-12.56	PK
Horizontal	10400.140	49.22	-9.30	39.92	54	-14.08	AV
Horizontal	15600.073	60.75	-7.82	52.93	74	-21.07	PK
Horizontal	15600.073	49.93	-7.82	42.11	54	-11.89	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.075	71.22	-20.12	51.10	74	-22.90	PK
Vertical	4739.075	59.48	-20.12	39.36	54	-14.64	AV
Vertical	10480.057	61.70	-9.18	52.52	68.2	-15.68	PK
Vertical	10480.057	49.03	-9.18	39.85	54	-14.15	AV
Vertical	15720.005	62.51	-7.78	54.73	74	-19.27	PK
Vertical	15720.005	49.20	-7.78	41.42	54	-12.58	AV
Horizontal	4739.145	71.60	-20.12	51.48	74	-22.52	PK
Horizontal	4739.145	59.52	-20.12	39.39	54	-14.61	AV
Horizontal	10480.084	61.92	-9.18	52.74	68.2	-15.46	PK
Horizontal	10480.084	49.29	-9.18	40.11	54	-13.89	AV
Horizontal	15720.163	64.76	-7.78	56.98	74	-17.02	PK
Horizontal	15720.163	49.76	-7.78	41.98	54	-12.02	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.154	70.05	-20.73	49.32	68.2	-18.88	PK
Vertical	4434.154	59.09	-20.73	38.36	54	-15.64	AV
Vertical	10380.165	61.33	-9.33	52.00	68.2	-16.20	PK
Vertical	10380.165	49.02	-9.33	39.69	54	-14.31	AV
Vertical	15570.090	60.27	-7.83	52.44	74	-21.56	PK
Vertical	15570.090	49.82	-7.83	41.99	54	-12.01	AV
Horizontal	4434.156	73.57	-20.73	52.84	74	-21.16	PK
Horizontal	4434.156	59.35	-20.73	38.62	54	-15.38	AV
Horizontal	10380.016	61.68	-9.33	52.35	68.2	-15.85	PK
Horizontal	10380.016	49.22	-9.33	39.89	54	-14.11	AV
Horizontal	15570.089	62.92	-7.83	55.09	74	-18.91	PK
Horizontal	15570.089	49.28	-7.83	41.45	54	-12.55	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.159	71.60	-20.12	51.48	68.2	-16.72	PK
Vertical	4739.159	59.62	-20.12	39.50	54	-14.50	AV
Vertical	10460.186	63.74	-9.21	54.53	68.2	-13.67	PK
Vertical	10460.186	49.45	-9.21	40.24	54	-13.76	AV
Vertical	15690.126	63.66	-7.79	55.87	74	-18.13	PK
Vertical	15690.126	49.73	-7.79	41.94	54	-12.06	AV
Horizontal	4739.139	70.19	-20.12	50.06	68.2	-18.14	PK
Horizontal	4739.139	59.89	-20.12	39.77	54	-14.23	AV
Horizontal	10460.079	60.23	-9.21	51.02	68.2	-17.18	PK
Horizontal	10460.079	49.89	-9.21	40.68	54	-13.32	AV
Horizontal	15690.076	61.21	-7.79	53.42	74	-20.58	PK
Horizontal	15690.076	49.13	-7.79	41.34	54	-12.66	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ax-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5210 MHz)-Above 1G							
Vertical	4434.143	73.66	-20.73	52.93	68.2	-15.27	PK
Vertical	4434.143	59.66	-20.73	38.93	54	-15.07	AV
Vertical	10420.046	63.73	-9.27	54.46	68.2	-13.74	PK
Vertical	10420.046	49.83	-9.27	40.56	54	-13.44	AV
Vertical	15630.008	61.91	-7.81	54.10	74	-19.90	PK
Vertical	15630.008	49.08	-7.81	41.27	54	-12.73	AV
Horizontal	4434.060	70.19	-20.73	49.46	68.2	-18.74	PK
Horizontal	4434.060	59.82	-20.73	39.09	54	-14.91	AV
Horizontal	10420.142	42.05	9.27	51.32	68.2	-16.88	PK
Horizontal	10420.142	29.15	9.27	38.42	54	-15.58	AV
Horizontal	15630.039	60.34	-7.81	52.53	74	-21.47	PK
Horizontal	15630.039	49.52	-7.81	41.71	54	-12.29	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.194	73.51	-20.73	52.78	68.2	-15.42	PK
Vertical	4434.194	59.81	-20.73	39.08	54	-14.92	AV
Vertical	10520.020	61.13	-9.12	52.01	68.2	-16.19	PK
Vertical	10520.020	49.36	-9.12	40.24	54	-13.76	AV
Vertical	15780.133	60.52	-7.77	52.75	74	-21.25	PK
Vertical	15780.133	49.49	-7.77	41.72	54	-12.28	AV
Horizontal	4434.007	73.53	-20.73	52.80	68.2	-15.40	PK
Horizontal	4434.007	59.64	-20.73	38.91	54	-15.09	AV
Horizontal	10520.052	61.47	-9.12	52.35	68.2	-15.85	PK
Horizontal	10520.052	49.50	-9.12	40.38	54	-13.62	AV
Horizontal	15780.049	61.27	-7.77	53.50	74	-20.50	PK
Horizontal	15780.049	49.05	-7.77	41.28	54	-12.72	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.082	70.56	-20.42	50.14	74	-23.86	PK
Vertical	4592.082	59.02	-20.42	38.60	54	-15.40	AV
Vertical	10560.098	64.61	-9.06	55.55	68.2	-12.65	PK
Vertical	10560.098	49.92	-9.06	40.86	54	-13.14	AV
Vertical	15840.076	61.45	-7.75	53.70	74	-20.30	PK
Vertical	15840.076	49.66	-7.75	41.91	54	-12.09	AV
Horizontal	4592.150	72.39	-20.42	51.98	74	-22.02	PK
Horizontal	4592.150	59.58	-20.42	39.17	54	-14.83	AV
Horizontal	10560.162	64.27	-9.06	55.21	68.2	-12.99	PK
Horizontal	10560.162	49.81	-9.06	40.75	54	-13.25	AV
Horizontal	15840.067	62.03	-7.75	54.28	74	-19.72	PK
Horizontal	15840.067	49.48	-7.75	41.73	54	-12.27	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.024	72.68	-20.12	52.56	74	-21.44	PK
Vertical	4739.024	59.44	-20.12	39.31	54	-14.69	AV
Vertical	10640.019	60.52	-8.94	51.58	68.2	-16.62	PK
Vertical	10640.019	49.42	-8.94	40.48	54	-13.52	AV
Vertical	15960.135	63.23	-7.71	55.52	74	-18.48	PK
Vertical	15960.135	49.85	-7.71	42.14	54	-11.86	AV
Horizontal	4739.163	70.13	-20.12	50.01	74	-23.99	PK
Horizontal	4739.163	59.39	-20.12	39.27	54	-14.73	AV
Horizontal	10640.088	63.67	-8.94	54.73	68.2	-13.47	PK
Horizontal	10640.088	49.02	-8.94	40.08	54	-13.92	AV
Horizontal	15960.101	63.10	-7.71	55.39	74	-18.61	PK
Horizontal	15960.101	49.60	-7.71	41.89	54	-12.11	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.006	73.43	-20.73	52.70	68.2	-15.50	PK
Vertical	4434.006	59.65	-20.73	38.92	54	-15.08	AV
Vertical	10520.033	62.61	-9.12	53.49	68.2	-14.71	PK
Vertical	10520.033	49.41	-9.12	40.29	54	-13.71	AV
Vertical	15780.100	60.43	-7.77	52.66	74	-21.34	PK
Vertical	15780.100	49.22	-7.77	41.45	54	-12.55	AV
Horizontal	4434.049	70.62	-20.73	49.89	68.2	-18.31	PK
Horizontal	4434.049	59.46	-20.73	38.73	54	-15.27	AV
Horizontal	10520.035	64.97	-9.12	55.85	68.2	-12.35	PK
Horizontal	10520.035	49.22	-9.12	40.10	54	-13.90	AV
Horizontal	15780.017	61.87	-7.77	54.10	74	-19.90	PK
Horizontal	15780.017	49.63	-7.77	41.86	54	-12.14	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.104	70.95	-20.42	50.53	74	-23.47	PK
Vertical	4592.104	60.00	-20.42	39.58	54	-14.42	AV
Vertical	10560.034	63.59	-9.06	54.53	68.2	-13.67	PK
Vertical	10560.034	49.90	-9.06	40.84	54	-13.16	AV
Vertical	15840.120	60.93	-7.75	53.18	74	-20.82	PK
Vertical	15840.120	49.61	-7.75	41.86	54	-12.14	AV
Horizontal	4592.011	71.96	-20.42	51.54	74	-22.46	PK
Horizontal	4592.011	59.42	-20.42	39.00	54	-15.00	AV
Horizontal	10560.181	64.43	-9.06	55.37	68.2	-12.83	PK
Horizontal	10560.181	49.19	-9.06	40.13	54	-13.87	AV
Horizontal	15840.140	62.20	-7.75	54.45	74	-19.55	PK
Horizontal	15840.140	49.30	-7.75	41.55	54	-12.45	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.089	72.04	-20.12	51.91	74	-22.09	PK
Vertical	4739.089	59.33	-20.12	39.21	54	-14.79	AV
Vertical	10640.088	64.14	-8.94	55.20	68.2	-13.00	PK
Vertical	10640.088	49.59	-8.94	40.65	54	-13.35	AV
Vertical	15960.010	63.68	-7.71	55.97	74	-18.03	PK
Vertical	15960.010	49.03	-7.71	41.32	54	-12.68	AV
Horizontal	4739.074	71.56	-20.12	51.44	74	-22.56	PK
Horizontal	4739.074	59.08	-20.12	38.96	54	-15.04	AV
Horizontal	10640.005	61.35	-8.94	52.41	68.2	-15.79	PK
Horizontal	10640.005	49.75	-8.94	40.81	54	-13.19	AV
Horizontal	15960.052	62.91	-7.71	55.20	74	-18.80	PK
Horizontal	15960.052	49.83	-7.71	42.12	54	-11.88	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.121	71.82	-20.73	51.09	68.2	-17.11	PK
Vertical	4434.121	59.85	-20.73	39.11	54	-14.89	AV
Vertical	10540.188	63.06	-9.09	53.97	68.2	-14.23	PK
Vertical	10540.188	49.54	-9.09	40.45	54	-13.55	AV
Vertical	15810.078	62.02	-7.76	54.26	74	-19.74	PK
Vertical	15810.078	49.78	-7.76	42.02	54	-11.98	AV
Horizontal	4434.063	73.19	-20.73	52.46	74	-21.54	PK
Horizontal	4434.063	59.30	-20.73	38.57	54	-15.43	AV
Horizontal	10540.056	63.89	-9.09	54.80	68.2	-13.40	PK
Horizontal	10540.056	49.02	-9.09	39.93	54	-14.07	AV
Horizontal	15810.122	63.26	-7.76	55.50	74	-18.50	PK
Horizontal	15810.122	49.62	-7.76	41.86	54	-12.14	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.063	72.41	-20.12	52.28	68.2	-15.92	PK
Vertical	4739.063	59.98	-20.12	39.86	54	-14.14	AV
Vertical	10620.008	63.86	-8.97	54.89	68.2	-13.31	PK
Vertical	10620.008	49.39	-8.97	40.42	54	-13.58	AV
Vertical	15930.085	60.41	-7.72	52.69	74	-21.31	PK
Vertical	15930.085	49.36	-7.72	41.64	54	-12.36	AV
Horizontal	4739.171	70.23	-20.12	50.11	68.2	-18.09	PK
Horizontal	4739.171	59.23	-20.12	39.11	54	-14.89	AV
Horizontal	10620.079	62.80	-8.97	53.83	68.2	-14.37	PK
Horizontal	10620.079	49.58	-8.97	40.61	54	-13.39	AV
Horizontal	15930.102	61.99	-7.72	54.27	74	-19.73	PK
Horizontal	15930.102	49.16	-7.72	41.44	54	-12.56	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.000	73.63	-20.73	52.90	68.2	-15.30	PK
Vertical	4434.000	59.08	-20.73	38.35	54	-15.65	AV
Vertical	10520.007	60.60	-9.12	51.48	68.2	-16.72	PK
Vertical	10520.007	49.16	-9.12	40.04	54	-13.96	AV
Vertical	15780.166	64.89	-7.77	57.12	74	-16.88	PK
Vertical	15780.166	49.94	-7.77	42.17	54	-11.83	AV
Horizontal	4434.029	73.72	-20.73	52.99	68.2	-15.21	PK
Horizontal	4434.029	59.15	-20.73	38.42	54	-15.58	AV
Horizontal	10520.012	62.57	-9.12	53.45	68.2	-14.75	PK
Horizontal	10520.012	49.34	-9.12	40.22	54	-13.78	AV
Horizontal	15780.001	63.59	-7.77	55.82	74	-18.18	PK
Horizontal	15780.001	49.66	-7.77	41.89	54	-12.11	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.124	71.79	-20.42	51.38	74	-22.62	PK
Vertical	4592.124	59.38	-20.42	38.96	54	-15.04	AV
Vertical	10560.051	64.83	-9.06	55.77	68.2	-12.43	PK
Vertical	10560.051	49.78	-9.06	40.72	54	-13.28	AV
Vertical	15840.127	61.86	-7.75	54.11	74	-19.89	PK
Vertical	15840.127	49.28	-7.75	41.53	54	-12.47	AV
Horizontal	4592.040	71.29	-20.42	50.87	74	-23.13	PK
Horizontal	4592.040	59.06	-20.42	38.64	54	-15.36	AV
Horizontal	10560.070	62.69	-9.06	53.63	68.2	-14.57	PK
Horizontal	10560.070	49.03	-9.06	39.97	54	-14.03	AV
Horizontal	15840.186	62.51	-7.75	54.76	74	-19.24	PK
Horizontal	15840.186	49.58	-7.75	41.83	54	-12.17	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.032	73.91	-20.12	53.79	74	-20.21	PK
Vertical	4739.032	59.90	-20.12	39.78	54	-14.22	AV
Vertical	10640.035	63.08	-8.94	54.14	68.2	-14.06	PK
Vertical	10640.035	49.26	-8.94	40.32	54	-13.68	AV
Vertical	15960.089	61.69	-7.71	53.98	74	-20.02	PK
Vertical	15960.089	49.71	-7.71	42.00	54	-12.00	AV
Horizontal	4739.023	73.50	-20.12	53.37	74	-20.63	PK
Horizontal	4739.023	59.07	-20.12	38.95	54	-15.05	AV
Horizontal	10640.167	61.69	-8.94	52.75	68.2	-15.45	PK
Horizontal	10640.167	49.29	-8.94	40.35	54	-13.65	AV
Horizontal	15960.123	64.48	-7.71	56.77	74	-17.23	PK
Horizontal	15960.123	49.34	-7.71	41.63	54	-12.37	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.068	70.28	-20.73	49.54	68.2	-18.66	PK
Vertical	4434.068	59.08	-20.73	38.35	54	-15.65	AV
Vertical	10540.031	63.49	-9.09	54.40	68.2	-13.80	PK
Vertical	10540.031	49.34	-9.09	40.25	54	-13.75	AV
Vertical	15810.130	64.70	-7.76	56.94	74	-17.06	PK
Vertical	15810.130	49.12	-7.76	41.36	54	-12.64	AV
Horizontal	4434.006	71.33	-20.73	50.60	74	-23.40	PK
Horizontal	4434.006	59.77	-20.73	39.04	54	-14.96	AV
Horizontal	10540.031	60.33	-9.09	51.24	68.2	-16.96	PK
Horizontal	10540.031	49.55	-9.09	40.46	54	-13.54	AV
Horizontal	15810.065	64.80	-7.76	57.04	74	-16.96	PK
Horizontal	15810.065	49.48	-7.76	41.72	54	-12.28	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.148	74.31	-20.12	54.19	68.2	-14.01	PK
Vertical	4739.148	59.93	-20.12	39.81	54	-14.19	AV
Vertical	10620.092	64.24	-8.97	55.27	68.2	-12.93	PK
Vertical	10620.092	49.32	-8.97	40.35	54	-13.65	AV
Vertical	15930.095	64.15	-7.72	56.43	74	-17.57	PK
Vertical	15930.095	49.03	-7.72	41.31	54	-12.69	AV
Horizontal	4739.134	71.48	-20.12	51.36	68.2	-16.84	PK
Horizontal	4739.134	59.39	-20.12	39.27	54	-14.73	AV
Horizontal	10620.003	62.28	-8.97	53.31	68.2	-14.89	PK
Horizontal	10620.003	49.18	-8.97	40.21	54	-13.79	AV
Horizontal	15930.042	62.25	-7.72	54.53	74	-19.47	PK
Horizontal	15930.042	49.88	-7.72	42.16	54	-11.84	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5290 MHz)-Above 1G							
Vertical	4434.033	74.90	-20.73	54.16	68.2	-14.04	PK
Vertical	4434.033	59.36	-20.73	38.63	54	-15.37	AV
Vertical	10580.173	62.73	-9.03	53.70	68.2	-14.50	PK
Vertical	10580.173	49.48	-9.03	40.45	54	-13.55	AV
Vertical	15870.141	64.48	-7.74	56.74	74	-17.26	PK
Vertical	15870.141	49.25	-7.74	41.51	54	-12.49	AV
Horizontal	4434.082	70.26	-20.73	49.52	68.2	-18.68	PK
Horizontal	4434.082	59.38	-20.73	38.65	54	-15.35	AV
Horizontal	10580.123	62.89	-9.03	53.86	68.2	-14.34	PK
Horizontal	10580.123	49.64	-9.03	40.61	54	-13.39	AV
Horizontal	15870.171	64.66	-7.74	56.92	74	-17.08	PK
Horizontal	15870.171	49.98	-7.74	42.24	54	-11.76	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.181	71.77	-20.73	51.04	68.2	-17.16	PK
Vertical	4434.181	59.74	-20.73	39.01	54	-14.99	AV
Vertical	10520.080	64.22	-9.12	55.10	68.2	-13.10	PK
Vertical	10520.080	49.92	-9.12	40.80	54	-13.20	AV
Vertical	15780.124	64.07	-7.77	56.30	74	-17.70	PK
Vertical	15780.124	49.51	-7.77	41.74	54	-12.26	AV
Horizontal	4434.189	74.65	-20.73	53.92	68.2	-14.28	PK
Horizontal	4434.189	59.26	-20.73	38.53	54	-15.47	AV
Horizontal	10520.160	60.79	-9.12	51.67	68.2	-16.53	PK
Horizontal	10520.160	49.55	-9.12	40.43	54	-13.57	AV
Horizontal	15780.036	62.93	-7.77	55.16	74	-18.84	PK
Horizontal	15780.036	49.80	-7.77	42.03	54	-11.97	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.117	70.79	-20.42	50.37	74	-23.63	PK
Vertical	4592.117	59.22	-20.42	38.80	54	-15.20	AV
Vertical	10560.032	61.67	-9.06	52.61	68.2	-15.59	PK
Vertical	10560.032	49.79	-9.06	40.73	54	-13.27	AV
Vertical	15840.123	61.95	-7.75	54.20	74	-19.80	PK
Vertical	15840.123	49.32	-7.75	41.57	54	-12.43	AV
Horizontal	4592.190	73.62	-20.42	53.21	74	-20.79	PK
Horizontal	4592.190	59.09	-20.42	38.67	54	-15.33	AV
Horizontal	10560.012	61.32	-9.06	52.26	68.2	-15.94	PK
Horizontal	10560.012	49.63	-9.06	40.57	54	-13.43	AV
Horizontal	15840.018	63.02	-7.75	55.27	74	-18.73	PK
Horizontal	15840.018	49.22	-7.75	41.47	54	-12.53	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.012	70.67	-20.12	50.55	74	-23.45	PK
Vertical	4739.012	59.68	-20.12	39.56	54	-14.44	AV
Vertical	10640.121	63.88	-8.94	54.94	68.2	-13.26	PK
Vertical	10640.121	49.17	-8.94	40.23	54	-13.77	AV
Vertical	15960.178	61.34	-7.71	53.63	74	-20.37	PK
Vertical	15960.178	49.37	-7.71	41.66	54	-12.34	AV
Horizontal	4739.156	72.18	-20.12	52.06	74	-21.94	PK
Horizontal	4739.156	59.07	-20.12	38.95	54	-15.05	AV
Horizontal	10640.175	61.25	-8.94	52.31	68.2	-15.89	PK
Horizontal	10640.175	49.30	-8.94	40.36	54	-13.64	AV
Horizontal	15960.059	62.16	-7.71	54.45	74	-19.55	PK
Horizontal	15960.059	49.27	-7.71	41.56	54	-12.44	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.125	70.14	-20.73	49.41	68.2	-18.79	PK
Vertical	4434.125	59.50	-20.73	38.77	54	-15.23	AV
Vertical	10540.037	63.64	-9.09	54.55	68.2	-13.65	PK
Vertical	10540.037	49.49	-9.09	40.40	54	-13.60	AV
Vertical	15810.059	62.00	-7.76	54.24	74	-19.76	PK
Vertical	15810.059	49.97	-7.76	42.21	54	-11.79	AV
Horizontal	4434.071	73.68	-20.73	52.95	74	-21.05	PK
Horizontal	4434.071	59.03	-20.73	38.30	54	-15.70	AV
Horizontal	10540.038	60.98	-9.09	51.89	68.2	-16.31	PK
Horizontal	10540.038	49.64	-9.09	40.55	54	-13.45	AV
Horizontal	15810.062	61.74	-7.76	53.98	74	-20.02	PK
Horizontal	15810.062	49.24	-7.76	41.48	54	-12.52	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.118	74.48	-20.12	54.36	68.2	-13.84	PK
Vertical	4739.118	59.02	-20.12	38.90	54	-15.10	AV
Vertical	10620.010	62.32	-8.97	53.35	68.2	-14.85	PK
Vertical	10620.010	49.94	-8.97	40.97	54	-13.03	AV
Vertical	15930.089	61.21	-7.72	53.49	74	-20.51	PK
Vertical	15930.089	49.17	-7.72	41.45	54	-12.55	AV
Horizontal	4739.172	73.87	-20.12	53.75	68.2	-14.45	PK
Horizontal	4739.172	59.60	-20.12	39.48	54	-14.52	AV
Horizontal	10620.122	61.87	-8.97	52.90	68.2	-15.30	PK
Horizontal	10620.122	49.49	-8.97	40.52	54	-13.48	AV
Horizontal	15930.006	61.28	-7.72	53.56	74	-20.44	PK
Horizontal	15930.006	49.28	-7.72	41.56	54	-12.44	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.3G) - 802.11ax-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5290 MHz)-Above 1G							
Vertical	4434.076	72.54	-20.73	51.81	68.2	-16.39	PK
Vertical	4434.076	59.22	-20.73	38.48	54	-15.52	AV
Vertical	10580.075	62.36	-9.03	53.33	68.2	-14.87	PK
Vertical	10580.075	49.12	-9.03	40.09	54	-13.91	AV
Vertical	15870.141	63.09	-7.74	55.35	74	-18.65	PK
Vertical	15870.141	49.01	-7.74	41.27	54	-12.73	AV
Horizontal	4434.177	73.75	-20.73	53.01	68.2	-15.19	PK
Horizontal	4434.177	59.24	-20.73	38.51	54	-15.49	AV
Horizontal	10580.165	61.45	-9.03	52.42	68.2	-15.78	PK
Horizontal	10580.165	49.64	-9.03	40.61	54	-13.39	AV
Horizontal	15870.104	62.17	-7.74	54.43	74	-19.57	PK
Horizontal	15870.104	49.42	-7.74	41.68	54	-12.32	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11a
------------	--------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.151	73.30	-20.73	52.57	68.2	-15.63	PK
Vertical	4434.151	59.38	-20.73	38.65	54	-15.35	AV
Vertical	11000.144	63.73	-8.40	55.33	68.2	-12.87	PK
Vertical	11000.144	49.27	-8.40	40.87	54	-13.13	AV
Vertical	16500.186	62.99	-6.09	56.90	74	-17.10	PK
Vertical	16500.186	49.89	-6.09	43.80	54	-10.20	AV
Horizontal	4434.122	70.95	-20.73	50.22	68.2	-17.98	PK
Horizontal	4434.122	59.91	-20.73	39.18	54	-14.82	AV
Horizontal	11000.140	62.60	-8.40	54.20	68.2	-14.00	PK
Horizontal	11000.140	49.54	-8.40	41.14	54	-12.86	AV
Horizontal	16500.176	62.00	-6.09	55.91	74	-18.09	PK
Horizontal	16500.176	49.05	-6.09	42.96	54	-11.04	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.030	74.65	-20.42	54.23	74	-19.77	PK
Vertical	4592.030	59.68	-20.42	39.26	54	-14.74	AV
Vertical	11160.196	62.75	-8.53	54.22	68.2	-13.98	PK
Vertical	11160.196	49.95	-8.53	41.42	54	-12.58	AV
Vertical	16740.041	60.92	-5.31	55.61	74	-18.39	PK
Vertical	16740.041	49.30	-5.31	43.99	54	-10.01	AV
Horizontal	4592.136	70.97	-20.42	50.56	74	-23.44	PK
Horizontal	4592.136	59.76	-20.42	39.34	54	-14.66	AV
Horizontal	11160.064	62.44	-8.53	53.91	68.2	-14.29	PK
Horizontal	11160.064	49.09	-8.53	40.56	54	-13.44	AV
Horizontal	16740.028	63.87	-5.31	58.56	74	-15.44	PK
Horizontal	16740.028	49.38	-5.31	44.07	54	-9.93	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.022	71.40	-20.12	51.28	74	-22.72	PK
Vertical	4739.022	59.44	-20.12	39.31	54	-14.69	AV
Vertical	11400.167	60.51	-8.72	51.79	68.2	-16.41	PK
Vertical	11400.167	49.34	-8.72	40.62	54	-13.38	AV
Vertical	17100.167	63.88	-3.92	59.96	74	-14.04	PK
Vertical	17100.167	49.97	-3.92	46.05	54	-7.95	AV
Horizontal	4739.139	72.65	-20.12	52.53	74	-21.47	PK
Horizontal	4739.139	59.66	-20.12	39.53	54	-14.47	AV
Horizontal	11400.004	64.73	-8.72	56.01	68.2	-12.19	PK
Horizontal	11400.004	49.89	-8.72	41.17	54	-12.83	AV
Horizontal	17100.145	63.49	-3.92	59.57	74	-14.43	PK
Horizontal	17100.145	49.01	-3.92	45.09	54	-8.91	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11n-HT20
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.178	70.46	-20.73	49.73	68.2	-18.47	PK
Vertical	4434.178	59.66	-20.73	38.92	54	-15.08	AV
Vertical	11000.085	63.47	-8.40	55.07	68.2	-13.13	PK
Vertical	11000.085	49.07	-8.40	40.67	54	-13.33	AV
Vertical	16500.193	61.17	-6.09	55.08	74	-18.92	PK
Vertical	16500.193	49.09	-6.09	43.00	54	-11.00	AV
Horizontal	4434.139	71.37	-20.73	50.64	68.2	-17.56	PK
Horizontal	4434.139	59.04	-20.73	38.31	54	-15.69	AV
Horizontal	11000.129	63.52	-8.40	55.12	68.2	-13.08	PK
Horizontal	11000.129	49.53	-8.40	41.13	54	-12.87	AV
Horizontal	16500.137	64.36	-6.09	58.27	74	-15.73	PK
Horizontal	16500.137	49.41	-6.09	43.32	54	-10.68	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.086	71.01	-20.42	50.60	74	-23.40	PK
Vertical	4592.086	59.93	-20.42	39.51	54	-14.49	AV
Vertical	11160.139	61.94	-8.53	53.41	68.2	-14.79	PK
Vertical	11160.139	49.87	-8.53	41.34	54	-12.66	AV
Vertical	16740.165	61.18	-5.31	55.87	74	-18.13	PK
Vertical	16740.165	49.99	-5.31	44.68	54	-9.32	AV
Horizontal	4592.179	73.07	-20.42	52.66	74	-21.34	PK
Horizontal	4592.179	59.82	-20.42	39.41	54	-14.59	AV
Horizontal	11160.014	63.38	-8.53	54.85	68.2	-13.35	PK
Horizontal	11160.014	49.97	-8.53	41.44	54	-12.56	AV
Horizontal	16740.135	60.12	-5.31	54.81	74	-19.19	PK
Horizontal	16740.135	49.84	-5.31	44.53	54	-9.47	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.170	73.07	-20.12	52.95	74	-21.05	PK
Vertical	4739.170	59.45	-20.12	39.32	54	-14.68	AV
Vertical	11400.110	61.06	-8.72	52.34	68.2	-15.86	PK
Vertical	11400.110	49.73	-8.72	41.01	54	-12.99	AV
Vertical	17100.105	62.04	-3.92	58.12	74	-15.88	PK
Vertical	17100.105	49.40	-3.92	45.48	54	-8.52	AV
Horizontal	4739.164	72.40	-20.12	52.27	74	-21.73	PK
Horizontal	4739.164	59.70	-20.12	39.58	54	-14.42	AV
Horizontal	11400.171	61.84	-8.72	53.12	68.2	-15.08	PK
Horizontal	11400.171	49.66	-8.72	40.94	54	-13.06	AV
Horizontal	17100.005	63.46	-3.92	59.54	74	-14.46	PK
Horizontal	17100.005	49.47	-3.92	45.55	54	-8.45	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11n-HT40
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.015	64.83	-20.73	44.10	68.2	-24.10	PK
Vertical	4434.015	43.52	-20.73	22.79	54	-31.21	AV
Vertical	11020.037	62.41	-8.42	53.99	68.2	-14.21	PK
Vertical	11020.037	43.59	-8.42	35.17	54	-18.83	AV
Vertical	16530.121	64.90	-5.99	58.91	74	-15.09	PK
Vertical	16530.121	43.74	-5.99	37.75	54	-16.25	AV
Horizontal	4434.005	64.88	-20.73	44.15	74	-29.85	PK
Horizontal	4434.005	43.38	-20.73	22.65	54	-31.35	AV
Horizontal	11020.003	54.86	-8.42	46.44	68.2	-21.76	PK
Horizontal	11020.003	42.54	-8.42	34.12	54	-19.88	AV
Horizontal	16530.125	50.08	-5.99	44.09	74	-29.91	PK
Horizontal	16530.125	43.16	-5.99	37.17	54	-16.83	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.044	63.70	-20.42	43.28	74	-30.72	PK
Vertical	4592.044	43.19	-20.42	22.77	54	-31.23	AV
Vertical	11100.146	64.78	-8.40	56.38	68.2	-11.82	PK
Vertical	11100.146	43.95	-8.40	35.55	54	-18.45	AV
Vertical	16650.098	64.16	-5.60	58.56	74	-15.44	PK
Vertical	16650.098	43.34	-5.60	37.74	54	-16.26	AV
Horizontal	4592.086	61.14	-20.42	40.73	74	-33.27	PK
Horizontal	4592.086	43.31	-20.42	22.89	54	-31.11	AV
Horizontal	11100.038	51.11	-8.40	42.71	68.2	-25.49	PK
Horizontal	11100.038	44.35	-8.40	35.95	54	-18.05	AV
Horizontal	16650.168	54.35	-5.60	48.75	74	-25.25	PK
Horizontal	16650.168	44.41	-5.60	38.81	54	-15.19	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.158	63.40	-20.12	43.28	68.2	-24.92	PK
Vertical	4739.158	43.34	-20.12	23.22	54	-30.78	AV
Vertical	11340.060	63.72	-8.67	55.05	68.2	-13.15	PK
Vertical	11340.060	43.10	-8.67	34.43	54	-19.57	AV
Vertical	17010.181	64.79	-4.41	60.38	74	-13.62	PK
Vertical	17010.181	43.86	-4.41	39.45	54	-14.55	AV
Horizontal	4739.071	62.08	-20.12	41.96	68.2	-26.24	PK
Horizontal	4739.071	43.90	-20.12	23.78	54	-30.22	AV
Horizontal	11340.134	50.27	-8.67	41.60	68.2	-26.60	PK
Horizontal	11340.134	42.68	-8.67	34.01	54	-19.99	AV
Horizontal	17010.027	50.15	-4.41	45.74	74	-28.26	PK
Horizontal	17010.027	42.79	-4.41	38.38	54	-15.62	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.059	71.95	-20.73	51.22	68.2	-16.98	PK
Vertical	4434.059	59.88	-20.73	39.15	54	-14.85	AV
Vertical	11000.062	64.18	-8.40	55.78	68.2	-12.42	PK
Vertical	11000.062	49.65	-8.40	41.25	54	-12.75	AV
Vertical	16500.089	62.41	-6.09	56.32	74	-17.68	PK
Vertical	16500.089	49.73	-6.09	43.64	54	-10.36	AV
Horizontal	4434.032	74.00	-20.73	53.27	68.2	-14.93	PK
Horizontal	4434.032	59.14	-20.73	38.41	54	-15.59	AV
Horizontal	11000.047	60.23	-8.40	51.83	68.2	-16.37	PK
Horizontal	11000.047	49.60	-8.40	41.20	54	-12.80	AV
Horizontal	16500.180	61.82	-6.09	55.73	74	-18.27	PK
Horizontal	16500.180	49.99	-6.09	43.90	54	-10.10	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.062	74.78	-20.42	54.37	74	-19.63	PK
Vertical	4592.062	59.50	-20.42	39.09	54	-14.91	AV
Vertical	11160.020	63.78	-8.53	55.25	68.2	-12.95	PK
Vertical	11160.020	49.12	-8.53	40.59	54	-13.41	AV
Vertical	16740.182	64.74	-5.31	59.43	74	-14.57	PK
Vertical	16740.182	49.14	-5.31	43.83	54	-10.17	AV
Horizontal	4592.026	70.82	-20.42	50.40	74	-23.60	PK
Horizontal	4592.026	59.15	-20.42	38.73	54	-15.27	AV
Horizontal	11160.057	62.84	-8.53	54.31	68.2	-13.89	PK
Horizontal	11160.057	49.52	-8.53	40.99	54	-13.01	AV
Horizontal	16740.194	64.14	-5.31	58.83	74	-15.17	PK
Horizontal	16740.194	49.02	-5.31	43.71	54	-10.29	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.159	70.48	-20.12	50.36	74	-23.64	PK
Vertical	4739.159	59.92	-20.12	39.80	54	-14.20	AV
Vertical	11400.161	62.34	-8.72	53.62	68.2	-14.58	PK
Vertical	11400.161	49.86	-8.72	41.14	54	-12.86	AV
Vertical	17100.041	62.24	-3.92	58.32	74	-15.68	PK
Vertical	17100.041	49.43	-3.92	45.51	54	-8.49	AV
Horizontal	4739.058	73.35	-20.12	53.22	74	-20.78	PK
Horizontal	4739.058	59.74	-20.12	39.62	54	-14.38	AV
Horizontal	11400.173	60.82	-8.72	52.10	68.2	-16.10	PK
Horizontal	11400.173	49.64	-8.72	40.92	54	-13.08	AV
Horizontal	17100.091	62.34	-3.92	58.42	74	-15.58	PK
Horizontal	17100.091	49.49	-3.92	45.57	54	-8.43	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.150	63.11	-20.73	42.38	68.2	-25.82	PK
Vertical	4434.150	43.94	-20.73	23.21	54	-30.79	AV
Vertical	11020.020	62.04	-8.42	53.62	68.2	-14.58	PK
Vertical	11020.020	43.05	-8.42	34.63	54	-19.37	AV
Vertical	16530.165	64.40	-5.99	58.41	74	-15.59	PK
Vertical	16530.165	43.60	-5.99	37.61	54	-16.39	AV
Horizontal	4434.013	64.00	-20.73	43.27	74	-30.73	PK
Horizontal	4434.013	43.47	-20.73	22.73	54	-31.27	AV
Horizontal	11020.191	52.02	-8.42	43.60	68.2	-24.60	PK
Horizontal	11020.191	40.40	-8.42	31.98	54	-22.02	AV
Horizontal	16530.003	54.03	-5.99	48.04	74	-25.96	PK
Horizontal	16530.003	40.26	-5.99	34.27	54	-19.73	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.018	61.25	-20.42	40.83	74	-33.17	PK
Vertical	4592.018	43.84	-20.42	23.42	54	-30.58	AV
Vertical	11100.195	62.15	-8.40	53.75	68.2	-14.45	PK
Vertical	11100.195	43.83	-8.40	35.43	54	-18.57	AV
Vertical	16650.167	63.68	-5.60	58.08	74	-15.92	PK
Vertical	16650.167	43.71	-5.60	38.11	54	-15.89	AV
Horizontal	4592.076	62.29	-20.42	41.87	74	-32.13	PK
Horizontal	4592.076	43.75	-20.42	23.33	54	-30.67	AV
Horizontal	11100.162	54.00	-8.40	45.60	68.2	-22.60	PK
Horizontal	11100.162	43.96	-8.40	35.56	54	-18.44	AV
Horizontal	16650.109	51.11	-5.60	45.51	74	-28.49	PK
Horizontal	16650.109	41.26	-5.60	35.66	54	-18.34	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.030	61.39	-20.12	41.26	68.2	-26.94	PK
Vertical	4739.030	43.47	-20.12	23.35	54	-30.65	AV
Vertical	11340.032	63.63	-8.67	54.96	68.2	-13.24	PK
Vertical	11340.032	43.86	-8.67	35.19	54	-18.81	AV
Vertical	17010.016	64.22	-4.41	59.81	74	-14.19	PK
Vertical	17010.016	43.25	-4.41	38.84	54	-15.16	AV
Horizontal	4739.046	60.92	-20.12	40.80	68.2	-27.40	PK
Horizontal	4739.046	43.79	-20.12	23.66	54	-30.34	AV
Horizontal	11340.195	52.03	-8.67	43.36	68.2	-24.84	PK
Horizontal	11340.195	44.83	-8.67	36.16	54	-17.84	AV
Horizontal	17010.020	54.05	-4.41	49.64	74	-24.36	PK
Horizontal	17010.020	42.47	-4.41	38.06	54	-15.94	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ac-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.010	64.83	-20.73	44.10	68.2	-24.10	PK
Vertical	4434.010	43.77	-20.73	23.04	54	-30.96	AV
Vertical	11060.191	60.20	-8.45	51.75	68.2	-16.45	PK
Vertical	11060.191	43.94	-8.45	35.49	54	-18.51	AV
Vertical	16590.196	61.94	-5.79	56.15	74	-17.85	PK
Vertical	16590.196	43.02	-5.79	37.23	54	-16.77	AV
Horizontal	4434.023	62.08	-20.73	41.35	68.2	-26.85	PK
Horizontal	4434.023	43.67	-20.73	22.93	54	-31.07	AV
Horizontal	11060.095	52.13	-8.45	43.68	68.2	-24.52	PK
Horizontal	11060.095	43.39	-8.45	34.94	54	-19.06	AV
Horizontal	16590.162	53.81	-5.79	48.02	74	-25.98	PK
Horizontal	16590.162	44.05	-5.79	38.26	54	-15.74	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.164	71.71	-20.73	50.98	68.2	-17.22	PK
Vertical	4434.164	59.60	-20.73	38.87	54	-15.13	AV
Vertical	11000.075	63.50	-8.40	55.10	68.2	-13.10	PK
Vertical	11000.075	49.35	-8.40	40.95	54	-13.05	AV
Vertical	16500.135	61.15	-6.09	55.06	74	-18.94	PK
Vertical	16500.135	49.12	-6.09	43.03	54	-10.97	AV
Horizontal	4434.073	70.92	-20.73	50.19	68.2	-18.01	PK
Horizontal	4434.073	59.12	-20.73	38.39	54	-15.61	AV
Horizontal	11000.156	60.90	-8.40	52.50	68.2	-15.70	PK
Horizontal	11000.156	49.10	-8.40	40.70	54	-13.30	AV
Horizontal	16500.100	62.72	-6.09	56.63	74	-17.37	PK
Horizontal	16500.100	49.13	-6.09	43.04	54	-10.96	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.090	71.26	-20.42	50.84	74	-23.16	PK
Vertical	4592.090	59.94	-20.42	39.53	54	-14.47	AV
Vertical	11160.160	61.86	-8.53	53.33	68.2	-14.87	PK
Vertical	11160.160	49.76	-8.53	41.23	54	-12.77	AV
Vertical	16740.090	62.93	-5.31	57.62	74	-16.38	PK
Vertical	16740.090	49.54	-5.31	44.23	54	-9.77	AV
Horizontal	4592.005	74.63	-20.42	54.22	74	-19.78	PK
Horizontal	4592.005	59.49	-20.42	39.07	54	-14.93	AV
Horizontal	11160.186	62.54	-8.53	54.01	68.2	-14.19	PK
Horizontal	11160.186	49.14	-8.53	40.61	54	-13.39	AV
Horizontal	16740.054	63.93	-5.31	58.62	74	-15.38	PK
Horizontal	16740.054	49.73	-5.31	44.42	54	-9.58	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.051	73.78	-20.12	53.66	74	-20.34	PK
Vertical	4739.051	59.22	-20.12	39.10	54	-14.90	AV
Vertical	11400.025	64.63	-8.72	55.91	68.2	-12.29	PK
Vertical	11400.025	49.51	-8.72	40.79	54	-13.21	AV
Vertical	17100.025	64.94	-3.92	61.02	74	-12.98	PK
Vertical	17100.025	49.23	-3.92	45.31	54	-8.69	AV
Horizontal	4739.025	70.19	-20.12	50.07	74	-23.93	PK
Horizontal	4739.025	59.07	-20.12	38.94	54	-15.06	AV
Horizontal	11400.086	61.98	-8.72	53.26	68.2	-14.94	PK
Horizontal	11400.086	49.38	-8.72	40.66	54	-13.34	AV
Horizontal	17100.036	64.78	-3.92	60.86	74	-13.14	PK
Horizontal	17100.036	49.55	-3.92	45.63	54	-8.37	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.6G) - 802.11ax-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.068	63.51	-20.73	42.78	68.2	-25.42	PK
Vertical	4434.068	43.70	-20.73	22.96	54	-31.04	AV
Vertical	11020.143	62.32	-8.42	53.90	68.2	-14.30	PK
Vertical	11020.143	43.72	-8.42	35.30	54	-18.70	AV
Vertical	16530.084	62.36	-5.99	56.37	74	-17.63	PK
Vertical	16530.084	43.98	-5.99	37.99	54	-16.01	AV
Horizontal	4434.195	62.66	-20.73	41.92	74	-32.08	PK
Horizontal	4434.195	43.43	-20.73	22.70	54	-31.30	AV
Horizontal	11020.031	54.14	-8.42	45.72	68.2	-22.48	PK
Horizontal	11020.031	42.67	-8.42	34.25	54	-19.75	AV
Horizontal	16530.149	52.13	-5.99	46.14	74	-27.86	PK
Horizontal	16530.149	40.15	-5.99	34.16	54	-19.84	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.068	64.79	-20.42	44.37	74	-29.63	PK
Vertical	4592.068	43.90	-20.42	23.48	54	-30.52	AV
Vertical	11100.085	61.85	-8.40	53.45	68.2	-14.75	PK
Vertical	11100.085	43.66	-8.40	35.26	54	-18.74	AV
Vertical	16650.104	63.70	-5.60	58.10	74	-15.90	PK
Vertical	16650.104	43.99	-5.60	38.39	54	-15.61	AV
Horizontal	4592.065	60.33	-20.42	39.92	74	-34.08	PK
Horizontal	4592.065	43.25	-20.42	22.84	54	-31.16	AV
Horizontal	11100.138	51.11	-8.40	42.71	68.2	-25.49	PK
Horizontal	11100.138	44.60	-8.40	36.20	54	-17.80	AV
Horizontal	16650.101	52.40	-5.60	46.80	74	-27.20	PK
Horizontal	16650.101	42.44	-5.60	36.84	54	-17.16	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.063	60.60	-20.12	40.48	68.2	-27.72	PK
Vertical	4739.063	43.83	-20.12	23.71	54	-30.29	AV
Vertical	11340.006	61.61	-8.67	52.94	68.2	-15.26	PK
Vertical	11340.006	43.25	-8.67	34.58	54	-19.42	AV
Vertical	17010.019	60.48	-4.41	56.07	74	-17.93	PK
Vertical	17010.019	43.26	-4.41	38.85	54	-15.15	AV
Horizontal	4739.135	64.69	-20.12	44.57	68.2	-23.63	PK
Horizontal	4739.135	43.30	-20.12	23.18	54	-30.82	AV
Horizontal	11340.098	51.37	-8.67	42.70	68.2	-25.50	PK
Horizontal	11340.098	42.16	-8.67	33.49	54	-20.51	AV
Horizontal	17010.147	50.60	-4.41	46.19	74	-27.81	PK
Horizontal	17010.147	42.74	-4.41	38.33	54	-15.67	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.