

TEST REPORT

Applicant: REOLINK TECHNOLOGY PTE. LTD.
Address: 31 KAKI BUKIT ROAD 3, #06-02, TECHLINK,
SINGAPORE 417818
Equipment Type: WiFi module
Model Name: WL1NM1001
Brand Name: Reolink
FCC ID: 2BN5S-2503H
ISED Number: 33667-2503H
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-247 Issue 3
(refer to section 3.1)
Sample Arrival Date: Apr. 22, 2025
Test Date: May 08, 2025 - May 14, 2025
Date of Issue: Jun. 17, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie Zhu**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jun. 17, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Test Software List	9
4.4	Measurement Uncertainty	10
4.5	Description of Test Setup	10
4.6	Measurement Results Explanation Example	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.2	Output Power	15
5.3	Occupied Bandwidth	17
5.4	Conducted Spurious Emission	18
5.5	Band Edge (Authorized-band band-edge)	20

5.6	Conducted Emission	22
5.7	Radiated Spurious Emission	23
5.8	Band Edge (Restricted-band band-edge).....	28
5.9	Power Spectral density (PSD).....	29
ANNEX A	TEST RESULT	30
A.1	Output Power, E.I.R.P	30
A.2	Occupied Bandwidth	33
A.3	Conducted Spurious Emissions	37
A.4	Band Edge (Authorized-band band-edge).....	42
A.5	Conducted Emissions.....	45
A.6	Radiated Spurious Emission	56
A.7	Band Edge (Restricted-band band-edge).....	76
A.8	Power Spectral Density (PSD)	79
ANNEX B	TEST SETUP PHOTOS	82
ANNEX C	EUT EXTERNAL PHOTOS	82
ANNEX D	EUT INTERNAL PHOTOS	82

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	REOLINK TECHNOLOGY PTE. LTD.
Address	31 KAKI BUKIT ROAD 3, #06-02, TECHLINK, SINGAPORE 417818

2.2 Manufacturer Information

Manufacturer	REOLINK TECHNOLOGY PTE. LTD.
Address	31 KAKI BUKIT ROAD 3, #06-02, TECHLINK, SINGAPORE 417818

2.3 General Description for Equipment under Test (EUT)

EUT Name	WiFi module
Model Name Under Test	WL1NM1001
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	952700Y006OCBLOR
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac and 802.11ax
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology		DTS
Modulation Type		GFSK
Product Type		☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate		1 Mbps, 2 Mbps
Frequency Range		The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel		40 (at intervals of 2 MHz) ^{Note 1}
Tested Channel		1 Mbps: 0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz) 2 Mbps: 1 (2404 MHz), 19 (2440 MHz), 38 (2478 MHz)
Antenna Type	ANT1	FPC Antenna
	ANT2	Dipole Antenna
	ANT3	Dipole Antenna
	ANT4	Dipole Antenna
	ANT5	Dipole Antenna
Antenna Gain	ANT1	3.3 dBi
	ANT2	2.89 dBi
	ANT3	4.4 dBi
	ANT4	3.81 dBi
	ANT5	3.05 dBi
Antenna Impedance		50Ω
Note 1: 2 Mbps does not support Channel 0, Channel 12, and Channel 39.		

Antenna Information:

Serial Number	Antenna Name	Antenna Manufacturer	Model	Antenna Type
ANT1	Argus 4 Pro Argus 4	SHENZHEN LINRONG TECHNOLOGY CO., LTD	03.10.03.003	FPC Antenna
ANT2	Argus PT Ultra@Reolink Argus PT	SHENZHENYINGJIACHUANG ELECTRONICTECHNOLOGY CO. LTD.	54.07.001.0147	Dipole Antenna
ANT3	Reolink Altas PT Ultra	Shenzhen Be-Comfortable Technology Co. Ltd	53.05.004.0014	Dipole Antenna
ANT4	Reolink Altas	SHENZHEN LINRONG TECHNOLOGY CO., LTD	03.14.03.001	Dipole Antenna
ANT5	Reolink TrackMix	Shenzhen Be-Comfortable Technology Co. Ltd	62.04.042.0055	Dipole Antenna
Note: All antenna model are alternative antenna, the max gain antenna is chosen for all test.				

All channel was listed on the following table:

BLE 1M:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

BLE 2M:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
\	\	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	\	\	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	\	\

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 3	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exemp Local Area Network (LE-LAN) Devices
4	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
5	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	--	Pass ^{Note1}
2	Output Power	15.247(b)	RSS-247, 5.4 (d)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	RSS-GEN, 6.7; RSS-247, 5.2 (a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	RSS-247, 5.5;	Low/High	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/High	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Low/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (b)	Low/Middle/High	ANNEX A.8	Pass
10	Receiver Spurious Emissions	--	RSS-Gen, 7.4	--	N/A	N/A ^{Note2}

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	49% to 65%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+21.6℃ to +25.1℃
Working Voltage of the EUT	NV (Normal Voltage)	5V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2024.07.04	2025.07.03
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2024.12.16	2025.12.15
Power Sensor	KEYSIGHT	U2063XA	MY58000247	2024.07.04	2025.07.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY50531259	2024.08.01	2025.07.31
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	02460	2024.05.16	2027.05.15
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	140	2024.07.28	2027.07.27
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2024.08.01	2025.07.31
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2024.08.01	2025.07.31
Amplifier	COM-MV	KA LNA18 40G-01	18050001	2024.12.05	2025.12.04
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8℃
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is External in the product.	The antenna is the unique connector with a wire antenna.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW $\geq$ DTS bandwidth.

Set VBW $\geq 3 \times$ RBW.

Set span $\geq 3 \times$ RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW $\geq$ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.2 (a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dB $\mu\text{V/m}$) = $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu\text{V/m}$ @3m (AV) and 74dB $\mu\text{V/m}$ @3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements

for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.

- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
- 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the

Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.10; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.5.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power, E.I.R.P

Note: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data

ANT3

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low Channel	4.09	2.56	30	1000	Pass
Middle Channel	4.26	2.67			Pass
High Channel	4.22	2.64			Pass

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low Channel	4.31	2.70	30	1000	Pass
Middle Channel	4.35	2.72			Pass
High Channel	4.40	2.75			Pass

E.I.R.P Test Data (For ISSED)

Channel	E.I.R.P		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low Channel	8.49	7.06	36	4000	Pass
Middle Channel	8.66	7.35			Pass
High Channel	8.62	7.28			Pass

Channel	E.I.R.P		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low Channel	8.71	7.43	36	4000	Pass
Middle Channel	8.75	7.50			Pass
High Channel	8.80	7.59			Pass

Test Plots

ANT3


GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



A.2 Occupied Bandwidth

Note: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data

ANT3

Test Mode	GFSK (BLE 1Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	689.900	1051.300	≥500
Middle Channel	667.500	1041.800	≥500
High Channel	720.000	1039.700	≥500

Test Mode	GFSK (BLE 2Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	1200.000	2092.700	≥500
Middle Channel	1215.000	2089.900	≥500
High Channel	1395.000	2070.800	≥500

Test Plots

ANT3

6 dB Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



99% Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



A.3 Conducted Spurious Emissions

Note: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data

ANT3

GFSK (BLE 1Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-37.39	3.59	-16.41	Pass
Middle Channel	-37.03	3.75	-16.25	Pass
High Channel	-36.92	4.10	-15.90	Pass

GFSK (BLE 2Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-36.54	3.07	-16.93	Pass
Middle Channel	-36.66	2.99	-17.01	Pass
High Channel	-37.31	2.78	-17.22	Pass


Test Plots

ANT3

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 1Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 1Mbps) MIDDLE CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 1Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) MIDDLE CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 2Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data

ANT3


GFSK (BLE 1Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-48.98	3.59	-16.41	Pass
High Channel	-48.25	4.10	-15.90	Pass

GFSK (BLE 2Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-49.11	3.07	-16.93	Pass
High Channel	-48.13	2.78	-17.22	Pass


Test Plots

ANT3

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL




GFSK (BLE 1Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL




GFSK (BLE 1Mbps) HIGH CHANNEL, BAND EDGE




GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER
LEVELGFSK (BLE 2Mbps) HIGH CHANNEL, BAND
EDGE

A.5 Conducted Emissions

Note ¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

ANT3

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.188	51.91	9.83	64.12	12.21	Peak	L	Pass
1**	0.188	31.32	9.83	54.12	22.80	AV	L	Pass
2	0.216	52.98	9.83	62.97	9.99	Peak	L	Pass
2**	0.216	42.38	9.83	52.97	10.59	AV	L	Pass
3	0.320	47.01	10.21	59.71	12.70	Peak	L	Pass
3**	0.320	36.27	10.21	49.71	13.44	AV	L	Pass
4	0.360	46.67	10.76	58.73	12.06	Peak	L	Pass
4**	0.360	32.96	10.76	48.73	15.77	AV	L	Pass
5	9.326	42.55	10.34	60.00	17.45	Peak	L	Pass
5**	9.326	31.51	10.34	50.00	18.49	AV	L	Pass
6	13.762	39.12	10.62	60.00	20.88	Peak	L	Pass
6**	13.762	26.09	10.62	50.00	23.91	AV	L	Pass

PHASE N


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.208	53.43	9.83	63.28	9.85	Peak	N	Pass
1**	0.208	42.13	9.83	53.28	11.15	AV	N	Pass
2	0.260	47.43	9.82	61.43	14.00	Peak	N	Pass
2**	0.260	32.67	9.82	51.43	18.76	AV	N	Pass
3	0.386	46.10	10.65	58.15	12.05	Peak	N	Pass
3**	0.386	30.16	10.65	48.15	17.99	AV	N	Pass
4	0.442	43.22	10.13	57.02	13.80	Peak	N	Pass
4**	0.442	29.94	10.13	47.02	17.08	AV	N	Pass
5	4.492	42.37	10.44	56.00	13.63	Peak	N	Pass
5**	4.492	27.39	10.44	46.00	18.61	AV	N	Pass
6	9.756	38.19	10.39	60.00	21.81	Peak	N	Pass
6**	9.756	26.59	10.39	50.00	23.41	AV	N	Pass

ANT1**PHASE L**


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	56.92	9.83	65.89	8.97	Peak	L	Pass
1**	0.152	40.18	9.83	55.89	15.71	AV	L	Pass
2	0.208	52.09	9.83	63.28	11.19	Peak	L	Pass
2**	0.208	35.97	9.83	53.28	17.31	AV	L	Pass
3	0.316	45.64	10.14	59.81	14.17	Peak	L	Pass
3**	0.316	33.61	10.14	49.81	16.20	AV	L	Pass
4	0.472	45.28	10.02	56.48	11.20	Peak	L	Pass
4**	0.472	29.60	10.02	46.48	16.88	AV	L	Pass
5	4.540	38.84	10.41	56.00	17.16	Peak	L	Pass
5**	4.540	26.33	10.41	46.00	19.67	AV	L	Pass
6	9.600	41.66	10.21	60.00	18.34	Peak	L	Pass
6**	9.600	27.59	10.21	50.00	22.41	AV	L	Pass

PHASE N


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	54.02	9.83	65.89	11.87	Peak	N	Pass
1**	0.152	36.90	9.83	55.89	18.99	AV	N	Pass
2	0.192	51.36	9.83	63.95	12.59	Peak	N	Pass
2**	0.192	36.51	9.83	53.95	17.44	AV	N	Pass
3	0.230	51.46	9.82	62.45	10.99	Peak	N	Pass
3**	0.230	36.33	9.82	52.45	16.12	AV	N	Pass
4	0.374	45.86	10.70	58.41	12.55	Peak	N	Pass
4**	0.374	35.15	10.70	48.41	13.26	AV	N	Pass
5	0.498	41.70	9.99	56.03	14.33	Peak	N	Pass
5**	0.498	28.33	9.99	46.03	17.70	AV	N	Pass
6	4.536	42.36	10.41	56.00	13.64	Peak	N	Pass
6**	4.536	27.74	10.41	46.00	18.26	AV	N	Pass

ANT2**PHASE L**


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	53.89	9.83	65.89	12.00	Peak	L	Pass
1**	0.152	34.96	9.83	55.89	20.93	AV	L	Pass
2	0.214	52.11	9.83	63.05	10.94	Peak	L	Pass
2**	0.214	39.98	9.83	53.05	13.07	AV	L	Pass
3	0.322	46.90	10.25	59.66	12.76	Peak	L	Pass
3**	0.322	33.37	10.25	49.66	16.29	AV	L	Pass
4	0.438	43.93	10.18	57.10	13.17	Peak	L	Pass
4**	0.438	31.27	10.18	47.10	15.83	AV	L	Pass
5	4.688	39.36	10.14	56.00	16.64	Peak	L	Pass
5**	4.688	25.71	10.14	46.00	20.29	AV	L	Pass
6	9.646	41.78	10.25	60.00	18.22	Peak	L	Pass
6**	9.646	31.59	10.25	50.00	18.41	AV	L	Pass

PHASE N


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.196	52.51	9.83	63.78	11.27	Peak	N	Pass
1**	0.196	36.93	9.83	53.78	16.85	AV	N	Pass
2	0.220	52.74	9.83	62.82	10.08	Peak	N	Pass
2**	0.220	41.46	9.83	52.82	11.36	AV	N	Pass
3	0.382	45.63	10.67	58.24	12.61	Peak	N	Pass
3**	0.382	35.85	10.67	48.24	12.39	AV	N	Pass
4	0.450	44.64	10.05	56.88	12.24	Peak	N	Pass
4**	0.450	33.07	10.05	46.88	13.81	AV	N	Pass
5	4.592	42.47	10.59	56.00	13.53	Peak	N	Pass
5**	4.592	26.62	10.59	46.00	19.38	AV	N	Pass
6	9.478	38.94	10.32	60.00	21.06	Peak	N	Pass
6**	9.478	26.38	10.32	50.00	23.62	AV	N	Pass

ANT4**PHASE L**


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.192	53.05	9.83	63.95	10.90	Peak	L	Pass
1**	0.192	34.24	9.83	53.95	19.71	AV	L	Pass
2	0.208	53.07	9.83	63.28	10.21	Peak	L	Pass
2**	0.208	41.89	9.83	53.28	11.39	AV	L	Pass
3	0.248	50.66	9.82	61.82	11.16	Peak	L	Pass
3**	0.248	38.61	9.82	51.82	13.21	AV	L	Pass
4	0.378	45.28	10.68	58.32	13.04	Peak	L	Pass
4**	0.378	33.04	10.68	48.32	15.28	AV	L	Pass
5	0.468	43.08	10.03	56.55	13.47	Peak	L	Pass
5**	0.468	27.44	10.03	46.55	19.11	AV	L	Pass
6	9.594	42.03	10.21	60.00	17.97	Peak	L	Pass
6**	9.594	31.38	10.21	50.00	18.62	AV	L	Pass

PHASE N


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.194	51.88	9.83	63.86	11.98	Peak	N	Pass
1**	0.194	33.59	9.83	53.86	20.27	AV	N	Pass
2	0.216	52.83	9.83	62.97	10.14	Peak	N	Pass
2**	0.216	42.01	9.83	52.97	10.96	AV	N	Pass
3	0.370	46.10	10.72	58.50	12.40	Peak	N	Pass
3**	0.370	27.89	10.72	48.50	20.61	AV	N	Pass
4	0.448	43.35	10.07	56.91	13.56	Peak	N	Pass
4**	0.448	29.08	10.07	46.91	17.83	AV	N	Pass
5	4.546	41.91	10.41	56.00	14.09	Peak	N	Pass
5**	4.546	27.55	10.41	46.00	18.45	AV	N	Pass
6	9.944	38.83	10.59	60.00	21.17	Peak	N	Pass
6**	9.944	28.63	10.59	50.00	21.37	AV	N	Pass

ANT5**PHASE L**


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.228	46.88	9.82	62.52	15.64	Peak	L	Pass
1**	0.228	36.09	9.82	52.52	16.43	AV	L	Pass
2	0.380	43.92	10.68	58.28	14.36	Peak	L	Pass
2**	0.380	30.21	10.68	48.28	18.07	AV	L	Pass
3	0.470	47.54	10.03	56.51	8.97	Peak	L	Pass
3**	0.470	41.96	10.03	46.51	4.55	AV	L	Pass
4	0.482	45.77	10.01	56.30	10.53	Peak	L	Pass
4**	0.482	25.94	10.01	46.30	20.36	AV	L	Pass
5	3.866	37.94	10.32	56.00	18.06	Peak	L	Pass
5**	3.866	26.05	10.32	46.00	19.95	AV	L	Pass
6	9.976	40.54	10.49	60.00	19.46	Peak	L	Pass
6**	9.976	29.29	10.49	50.00	20.71	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.228	47.88	9.82	62.52	14.64	Peak	N	Pass
1**	0.228	36.47	9.82	52.52	16.05	AV	N	Pass
2	0.404	44.04	10.54	57.77	13.73	Peak	N	Pass
2**	0.404	31.14	10.54	47.77	16.63	AV	N	Pass
3	0.458	46.72	10.04	56.73	10.01	Peak	N	Pass
3**	0.458	37.12	10.04	46.73	9.61	AV	N	Pass
4	0.496	45.21	10.00	56.07	10.86	Peak	N	Pass
4**	0.496	33.88	10.00	46.07	12.19	AV	N	Pass
5	4.572	39.54	10.51	56.00	16.46	Peak	N	Pass
5**	4.572	25.92	10.51	46.00	20.08	AV	N	Pass
6	9.718	38.46	10.51	60.00	21.54	Peak	N	Pass
6**	9.718	26.79	10.51	50.00	23.21	AV	N	Pass

A.6 Radiated Spurious Emission

Note ¹: The symbol of “--” in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note ⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 2M-High channel mode is the worst.


Note ⁵: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots.

ANT3

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.729	17.76	-27.13	29.5	11.74	Peak	84.00	100	Horizontal	Pass
2	132.309	18.12	-27.19	33.0	14.88	Peak	206.00	100	Horizontal	Pass
3	150.007	25.35	-26.28	33.0	7.65	Peak	128.00	100	Horizontal	Pass
4	154.614	23.96	-26.18	33.0	9.04	Peak	128.00	100	Horizontal	Pass
5	175.949	28.95	-27.44	33.0	4.05	Peak	212.00	100	Horizontal	Pass
6	178.858	28.80	-27.57	33.0	4.20	Peak	212.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBUV/m)	Factor (dB)	Limit (dBUV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.002	17.71	-27.08	29.5	11.79	Peak	267.00	100	Vertical	Pass
2	144.431	19.14	-26.53	33.0	13.86	Peak	134.00	100	Vertical	Pass
3	167.948	20.18	-26.68	33.0	12.82	Peak	109.00	100	Vertical	Pass
4	191.950	22.06	-28.80	33.0	10.94	Peak	112.00	100	Vertical	Pass
5	201.890	25.47	-29.23	33.0	7.53	Peak	177.00	100	Vertical	Pass
6	262.499	19.30	-26.87	35.5	16.20	Peak	31.00	100	Vertical	Pass

ANT1**30 MHz to 1 GHz, ANT H**


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBUV/m)	Factor (dB)	Limit (dBUV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.244	17.57	-27.10	29.5	11.93	Peak	254.00	100	Horizontal	Pass
2	127.946	15.07	-27.47	33.0	17.93	Peak	77.00	100	Horizontal	Pass
3	168.190	20.27	-26.73	33.0	12.73	Peak	183.00	100	Horizontal	Pass
4	190.737	25.63	-28.81	33.0	7.37	Peak	223.00	100	Horizontal	Pass
5	207.466	25.97	-29.37	33.0	7.03	Peak	59.00	100	Horizontal	Pass
6	424.449	19.93	-22.04	35.5	15.57	Peak	264.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.244	16.47	-27.10	29.5	13.03	Peak	78.00	100	Vertical	Pass
2	114.854	23.62	-28.64	33.0	9.38	Peak	121.00	100	Vertical	Pass
3	144.431	19.86	-26.53	33.0	13.14	Peak	109.00	100	Vertical	Pass
4	167.706	20.72	-26.62	33.0	12.28	Peak	140.00	100	Vertical	Pass
5	190.737	20.31	-28.81	33.0	12.69	Peak	301.00	100	Vertical	Pass
6	237.043	21.12	-28.43	35.5	14.38	Peak	155.00	100	Vertical	Pass

ANT2**30 MHz to 1 GHz, ANT H**


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	53.759	17.44	-27.06	29.5	12.06	Peak	243.00	100	Horizontal	Pass
2	132.552	14.86	-27.20	33.0	18.14	Peak	202.00	100	Horizontal	Pass
3	168.433	20.35	-26.75	33.0	12.65	Peak	181.00	100	Horizontal	Pass
4	174.979	26.06	-27.40	33.0	6.94	Peak	332.00	100	Horizontal	Pass
5	180.555	27.39	-27.60	33.0	5.61	Peak	332.00	100	Horizontal	Pass
6	340.807	17.26	-24.44	35.5	18.24	Peak	34.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	53.759	16.83	-27.06	29.5	12.67	Peak	276.00	100	Vertical	Pass
2	144.189	19.83	-26.55	33.0	13.17	Peak	96.00	100	Vertical	Pass
3	167.463	19.40	-26.56	33.0	13.60	Peak	71.00	100	Vertical	Pass
4	191.950	20.93	-28.80	33.0	12.07	Peak	93.00	100	Vertical	Pass
5	213.769	22.90	-29.27	33.0	10.10	Peak	199.00	100	Vertical	Pass
6	238.013	20.53	-28.25	35.5	14.97	Peak	149.00	100	Vertical	Pass

ANT4**30 MHz to 1 GHz, ANT H**


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.002	17.93	-27.08	29.5	11.57	Peak	177.00	100	Horizontal	Pass
2	131.340	16.51	-27.33	33.0	16.49	Peak	164.00	100	Horizontal	Pass
3	167.706	20.44	-26.62	33.0	12.56	Peak	201.00	100	Horizontal	Pass
4	185.161	29.54	-28.20	33.0	3.46	Peak	195.00	100	Horizontal	Pass
5	200.192	28.20	-29.18	33.0	4.80	Peak	28.00	100	Horizontal	Pass
6	326.503	18.91	-24.70	35.5	16.59	Peak	50.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	53.759	17.22	-27.06	29.5	12.28	Peak	18.00	100	Vertical	Pass
2	152.917	29.55	-26.31	33.0	3.45	Peak	111.00	100	Vertical	Pass
3	158.250	29.91	-26.21	33.0	3.09	Peak	111.00	100	Vertical	Pass
4	181.525	27.99	-27.68	33.0	5.01	Peak	30.00	100	Vertical	Pass
5	238.255	21.13	-28.21	35.5	14.37	Peak	211.00	100	Vertical	Pass
6	305.411	20.10	-25.30	35.5	15.40	Peak	353.00	100	Vertical	Pass

ANT5**30 MHz to 1 GHz, ANT H**


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.244	18.18	-27.10	29.5	11.32	Peak	52.00	100	Horizontal	Pass
2	133.279	16.31	-27.20	33.0	16.69	Peak	198.00	100	Horizontal	Pass
3	167.706	20.68	-26.62	33.0	12.32	Peak	170.00	100	Horizontal	Pass
4	191.465	18.08	-28.81	33.0	14.92	Peak	9.00	100	Horizontal	Pass
5	235.346	19.28	-28.53	35.5	16.22	Peak	6.00	100	Horizontal	Pass
6	326.988	17.64	-24.64	35.5	17.86	Peak	34.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.486	17.73	-27.12	29.5	11.77	Peak	152.00	100	Vertical	Pass
2	143.947	19.33	-26.57	33.0	13.67	Peak	65.00	100	Vertical	Pass
3	167.948	20.69	-26.68	33.0	12.31	Peak	140.00	100	Vertical	Pass
4	191.950	21.34	-28.80	33.0	11.66	Peak	131.00	100	Vertical	Pass
5	210.375	28.26	-29.27	33.0	4.74	Peak	131.00	100	Vertical	Pass
6	214.739	27.86	-29.32	33.0	5.14	Peak	131.00	100	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

ANT3

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1333.270	45.70	74.0	28.30	Peak	28.00	100	Horizontal	Pass
1**	1333.270	29.83	54.0	24.17	AV	28.00	100	Horizontal	Pass
2	2974.091	48.05	74.0	25.95	Peak	339.00	400	Horizontal	Pass
2**	2974.091	40.47	54.0	13.53	AV	339.00	400	Horizontal	Pass
3	4912.148	52.29	74.0	21.71	Peak	40.00	200	Horizontal	Pass
3**	4912.148	44.30	54.0	9.70	AV	40.00	200	Horizontal	Pass
4	7629.528	54.79	74.0	19.21	Peak	53.00	400	Horizontal	Pass
4**	7629.528	37.40	54.0	16.60	AV	53.00	400	Horizontal	Pass
5	12476.641	54.27	74.0	19.73	Peak	281.00	100	Horizontal	Pass
5**	12476.641	42.53	54.0	11.47	AV	281.00	100	Horizontal	Pass
6	16854.380	54.62	74.0	19.38	Peak	320.00	400	Horizontal	Pass
6**	16854.380	41.05	54.0	12.95	AV	320.00	400	Horizontal	Pass

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1469.901	42.51	74.0	31.49	Peak	262.00	100	Vertical	Pass
1**	1469.901	28.25	54.0	25.75	AV	262.00	100	Vertical	Pass
2	2993.718	52.92	74.0	21.08	Peak	174.00	400	Vertical	Pass
2**	2993.718	40.79	54.0	13.21	AV	174.00	400	Vertical	Pass
3	4820.548	53.70	74.0	20.30	Peak	266.00	200	Vertical	Pass
3**	4820.548	39.07	54.0	14.93	AV	266.00	200	Vertical	Pass
4	7965.255	54.02	74.0	19.98	Peak	325.00	100	Vertical	Pass
4**	7965.255	44.75	54.0	9.25	AV	325.00	100	Vertical	Pass
5	12439.188	48.39	74.0	25.61	Peak	198.00	200	Vertical	Pass
5**	12439.188	43.30	54.0	10.70	AV	198.00	200	Vertical	Pass
6	17456.460	55.57	74.0	18.43	Peak	15.00	300	Vertical	Pass
6**	17456.460	46.49	54.0	7.51	AV	15.00	300	Vertical	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.882	44.15	74.0	29.85	Peak	119.00	300	Horizontal	Pass
1**	1330.882	28.88	54.0	25.12	AV	119.00	300	Horizontal	Pass
2	2969.680	47.92	74.0	26.08	Peak	285.00	400	Horizontal	Pass
2**	2969.680	39.03	54.0	14.97	AV	285.00	400	Horizontal	Pass
3	4916.345	50.93	74.0	23.07	Peak	159.00	200	Horizontal	Pass
3**	4916.345	42.69	54.0	11.31	AV	159.00	200	Horizontal	Pass
4	7628.876	51.16	74.0	22.84	Peak	249.00	200	Horizontal	Pass
4**	7628.876	42.00	54.0	12.00	AV	249.00	200	Horizontal	Pass
5	12477.327	50.91	74.0	23.09	Peak	65.00	400	Horizontal	Pass
5**	12477.327	42.78	54.0	11.22	AV	65.00	400	Horizontal	Pass
6	16857.497	56.46	74.0	17.54	Peak	142.00	100	Horizontal	Pass
6**	16857.497	41.84	54.0	12.16	AV	142.00	100	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1465.610	41.80	74.0	32.20	Peak	75.00	400	Vertical	Pass
1**	1465.610	32.99	54.0	21.01	AV	75.00	400	Vertical	Pass
2	2991.354	52.83	74.0	21.17	Peak	91.00	300	Vertical	Pass
2**	2991.354	40.42	54.0	13.58	AV	91.00	300	Vertical	Pass
3	4825.812	51.01	74.0	22.99	Peak	188.00	200	Vertical	Pass
3**	4825.812	40.39	54.0	13.61	AV	188.00	200	Vertical	Pass
4	7967.540	58.13	74.0	15.87	Peak	249.00	100	Vertical	Pass
4**	7967.540	44.08	54.0	9.92	AV	249.00	100	Vertical	Pass
5	12440.128	48.38	74.0	25.62	Peak	205.00	400	Vertical	Pass
5**	12440.128	43.28	54.0	10.72	AV	205.00	400	Vertical	Pass
6	17455.847	56.30	74.0	17.70	Peak	71.00	100	Vertical	Pass
6**	17455.847	47.31	54.0	6.69	AV	71.00	100	Vertical	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1337.297	43.26	74.0	30.74	Peak	354.00	100	Horizontal	Pass
1**	1337.297	30.23	54.0	23.77	AV	354.00	100	Horizontal	Pass
2	2975.997	49.32	74.0	24.68	Peak	126.00	400	Horizontal	Pass
2**	2975.997	42.36	54.0	11.64	AV	126.00	400	Horizontal	Pass
3	4916.789	53.85	74.0	20.15	Peak	129.00	200	Horizontal	Pass
3**	4916.789	41.58	54.0	12.42	AV	129.00	200	Horizontal	Pass
4	7629.309	55.65	74.0	18.35	Peak	352.00	200	Horizontal	Pass
4**	7629.309	41.78	54.0	12.22	AV	352.00	200	Horizontal	Pass
5	12471.255	54.64	74.0	19.36	Peak	42.00	100	Horizontal	Pass
5**	12471.255	45.99	54.0	8.01	AV	42.00	100	Horizontal	Pass
6	16857.477	56.21	74.0	17.79	Peak	31.00	200	Horizontal	Pass
6**	16857.477	43.34	54.0	10.66	AV	31.00	200	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1469.972	40.77	74.0	33.23	Peak	193.00	400	Vertical	Pass
1**	1469.972	30.42	54.0	23.58	AV	193.00	400	Vertical	Pass
2	2990.919	47.85	74.0	26.15	Peak	278.00	300	Vertical	Pass
2**	2990.919	41.82	54.0	12.18	AV	278.00	300	Vertical	Pass
3	4819.450	49.88	74.0	24.12	Peak	310.00	200	Vertical	Pass
3**	4819.450	43.35	54.0	10.65	AV	310.00	200	Vertical	Pass
4	7963.457	56.58	74.0	17.42	Peak	221.00	300	Vertical	Pass
4**	7963.457	40.65	54.0	13.35	AV	221.00	300	Vertical	Pass
5	12444.567	51.48	74.0	22.52	Peak	281.00	100	Vertical	Pass
5**	12444.567	46.68	54.0	7.32	AV	281.00	100	Vertical	Pass
6	17453.421	53.40	74.0	20.60	Peak	253.00	300	Vertical	Pass
6**	17453.421	46.34	54.0	7.66	AV	253.00	300	Vertical	Pass

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1285.554	41.17	74.0	32.83	Peak	124.00	200	Horizontal	Pass
1**	1285.554	31.66	54.0	22.34	AV	124.00	200	Horizontal	Pass
2	2768.945	51.41	74.0	22.59	Peak	39.00	400	Horizontal	Pass
2**	2768.945	41.13	54.0	12.87	AV	39.00	400	Horizontal	Pass
3	5170.136	54.62	74.0	19.38	Peak	247.00	200	Horizontal	Pass
3**	5170.136	40.31	54.0	13.69	AV	247.00	200	Horizontal	Pass
4	6805.095	55.61	74.0	18.39	Peak	107.00	200	Horizontal	Pass
4**	6805.095	44.72	54.0	9.28	AV	107.00	200	Horizontal	Pass
5	13464.153	57.27	74.0	16.73	Peak	190.00	200	Horizontal	Pass
5**	13464.153	42.67	54.0	11.33	AV	190.00	200	Horizontal	Pass
6	17470.258	57.73	74.0	16.27	Peak	85.00	400	Horizontal	Pass
6**	17470.258	46.40	54.0	7.60	AV	85.00	400	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1284.937	40.57	74.0	33.43	Peak	180.00	100	Vertical	Pass
1**	1284.937	32.15	54.0	21.85	AV	180.00	100	Vertical	Pass
2	2773.587	52.97	74.0	21.03	Peak	92.00	300	Vertical	Pass
2**	2773.587	45.65	54.0	8.35	AV	92.00	300	Vertical	Pass
3	5164.298	53.42	74.0	20.58	Peak	238.00	200	Vertical	Pass
3**	5164.298	45.47	54.0	8.53	AV	238.00	200	Vertical	Pass
4	6805.588	57.48	74.0	16.52	Peak	124.00	200	Vertical	Pass
4**	6805.588	43.20	54.0	10.80	AV	124.00	200	Vertical	Pass
5	13467.181	57.42	74.0	16.58	Peak	214.00	300	Vertical	Pass
5**	13467.181	43.45	54.0	10.55	AV	214.00	300	Vertical	Pass
6	17463.348	58.86	74.0	15.14	Peak	187.00	100	Vertical	Pass
6**	17463.348	48.56	54.0	5.44	AV	187.00	100	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1283.662	43.87	74.0	30.13	Peak	235.00	400	Horizontal	Pass
1**	1283.662	31.35	54.0	22.65	AV	235.00	400	Horizontal	Pass
2	2770.964	52.15	74.0	21.85	Peak	164.00	200	Horizontal	Pass
2**	2770.964	42.09	54.0	11.91	AV	164.00	200	Horizontal	Pass
3	5170.537	54.32	74.0	19.68	Peak	191.00	200	Horizontal	Pass
3**	5170.537	43.24	54.0	10.76	AV	191.00	200	Horizontal	Pass
4	6807.875	52.86	74.0	21.14	Peak	292.00	400	Horizontal	Pass
4**	6807.875	47.95	54.0	6.05	AV	292.00	400	Horizontal	Pass
5	13463.809	53.48	74.0	20.52	Peak	248.00	400	Horizontal	Pass
5**	13463.809	46.63	54.0	7.37	AV	248.00	400	Horizontal	Pass
6	17469.912	54.17	74.0	19.83	Peak	16.00	300	Horizontal	Pass
6**	17469.912	49.25	54.0	4.75	AV	16.00	300	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1289.410	40.84	74.0	33.16	Peak	119.00	100	Vertical	Pass
1**	1289.410	35.20	54.0	18.80	AV	119.00	100	Vertical	Pass
2	2773.233	53.44	74.0	20.56	Peak	68.00	400	Vertical	Pass
2**	2773.233	40.36	54.0	13.64	AV	68.00	400	Vertical	Pass
3	5163.605	53.96	74.0	20.04	Peak	30.00	200	Vertical	Pass
3**	5163.605	45.31	54.0	8.69	AV	30.00	200	Vertical	Pass
4	6805.562	52.52	74.0	21.48	Peak	59.00	300	Vertical	Pass
4**	6805.562	45.45	54.0	8.55	AV	59.00	300	Vertical	Pass
5	13469.300	56.14	74.0	17.86	Peak	133.00	200	Vertical	Pass
5**	13469.300	46.05	54.0	7.95	AV	133.00	200	Vertical	Pass
6	17469.368	54.54	74.0	19.46	Peak	236.00	100	Vertical	Pass
6**	17469.368	49.40	54.0	4.60	AV	236.00	100	Vertical	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.232	43.63	74.0	30.37	Peak	195.00	300	Horizontal	Pass
1**	1287.232	30.86	54.0	23.14	AV	195.00	300	Horizontal	Pass
2	2766.861	51.37	74.0	22.63	Peak	287.00	400	Horizontal	Pass
2**	2766.861	44.27	54.0	9.73	AV	287.00	400	Horizontal	Pass
3	5393.918	50.49	74.0	23.51	Peak	292.00	200	Horizontal	Pass
3**	5393.918	46.33	54.0	7.67	AV	292.00	200	Horizontal	Pass
4	6517.257	54.19	74.0	19.81	Peak	306.00	300	Horizontal	Pass
4**	6517.257	47.45	54.0	6.55	AV	306.00	300	Horizontal	Pass
5	13352.275	54.29	74.0	19.71	Peak	8.00	300	Horizontal	Pass
5**	13352.275	47.03	54.0	6.97	AV	8.00	300	Horizontal	Pass
6	17438.378	56.08	74.0	17.92	Peak	132.00	400	Horizontal	Pass
6**	17438.378	44.82	54.0	9.18	AV	132.00	400	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1288.006	44.74	74.0	29.26	Peak	158.00	100	Vertical	Pass
1**	1288.006	33.68	54.0	20.32	AV	158.00	100	Vertical	Pass
2	2768.513	50.97	74.0	23.03	Peak	110.00	300	Vertical	Pass
2**	2768.513	44.04	54.0	9.96	AV	110.00	300	Vertical	Pass
3	5290.154	54.28	74.0	19.72	Peak	205.00	200	Vertical	Pass
3**	5290.154	40.10	54.0	13.90	AV	205.00	200	Vertical	Pass
4	6652.323	55.45	74.0	18.55	Peak	168.00	400	Vertical	Pass
4**	6652.323	45.90	54.0	8.10	AV	168.00	400	Vertical	Pass
5	13311.206	54.48	74.0	19.52	Peak	123.00	300	Vertical	Pass
5**	13311.206	44.63	54.0	9.37	AV	123.00	300	Vertical	Pass
6	17415.939	56.87	74.0	17.13	Peak	125.00	400	Vertical	Pass
6**	17415.939	45.53	54.0	8.47	AV	125.00	400	Vertical	Pass

ANT1**GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.961	41.68	74.0	32.32	Peak	72.00	200	Horizontal	Pass
1**	1287.961	33.88	54.0	20.12	AV	72.00	200	Horizontal	Pass
2	2773.957	52.24	74.0	21.76	Peak	126.00	400	Horizontal	Pass
2**	2773.957	41.32	54.0	12.68	AV	126.00	400	Horizontal	Pass
3	5391.638	50.98	74.0	23.02	Peak	322.00	200	Horizontal	Pass
3**	5391.638	44.40	54.0	9.60	AV	322.00	200	Horizontal	Pass
4	6512.770	53.12	74.0	20.88	Peak	201.00	400	Horizontal	Pass
4**	6512.770	43.97	54.0	10.03	AV	201.00	400	Horizontal	Pass
5	13353.478	56.61	74.0	17.39	Peak	153.00	100	Horizontal	Pass
5**	13353.478	45.47	54.0	8.53	AV	153.00	100	Horizontal	Pass
6	17441.166	58.12	74.0	15.88	Peak	253.00	300	Horizontal	Pass
6**	17441.166	45.10	54.0	8.90	AV	253.00	300	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1288.365	42.65	74.0	31.35	Peak	291.00	300	Vertical	Pass
1**	1288.365	32.14	54.0	21.86	AV	291.00	300	Vertical	Pass
2	2770.975	52.77	74.0	21.23	Peak	359.00	200	Vertical	Pass
2**	2770.975	46.01	54.0	7.99	AV	359.00	200	Vertical	Pass
3	5290.668	55.17	74.0	18.83	Peak	115.00	200	Vertical	Pass
3**	5290.668	40.75	54.0	13.25	AV	115.00	200	Vertical	Pass
4	6658.731	51.73	74.0	22.27	Peak	232.00	400	Vertical	Pass
4**	6658.731	47.71	54.0	6.29	AV	232.00	400	Vertical	Pass
5	13303.683	54.91	74.0	19.09	Peak	83.00	300	Vertical	Pass
5**	13303.683	48.93	54.0	5.07	AV	83.00	300	Vertical	Pass
6	17417.351	55.73	74.0	18.27	Peak	17.00	300	Vertical	Pass
6**	17417.351	48.92	54.0	5.08	AV	17.00	300	Vertical	Pass

ANT2**GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.589	43.51	74.0	30.49	Peak	151.00	200	Horizontal	Pass
1**	1287.589	32.88	54.0	21.12	AV	151.00	200	Horizontal	Pass
2	2769.222	49.09	74.0	24.91	Peak	21.00	200	Horizontal	Pass
2**	2769.222	44.78	54.0	9.22	AV	21.00	200	Horizontal	Pass
3	5391.186	54.76	74.0	19.24	Peak	44.00	200	Horizontal	Pass
3**	5391.186	44.27	54.0	9.73	AV	44.00	200	Horizontal	Pass
4	6515.412	53.84	74.0	20.16	Peak	176.00	300	Horizontal	Pass
4**	6515.412	42.83	54.0	11.17	AV	176.00	300	Horizontal	Pass
5	13355.818	57.37	74.0	16.63	Peak	135.00	200	Horizontal	Pass
5**	13355.818	49.88	54.0	4.12	AV	135.00	200	Horizontal	Pass
6	17442.335	58.78	74.0	15.22	Peak	44.00	300	Horizontal	Pass
6**	17442.335	45.47	54.0	8.53	AV	44.00	300	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1288.832	42.23	74.0	31.77	Peak	99.00	100	Vertical	Pass
1**	1288.832	32.62	54.0	21.38	AV	99.00	100	Vertical	Pass
2	2772.145	52.48	74.0	21.52	Peak	357.00	400	Vertical	Pass
2**	2772.145	43.86	54.0	10.14	AV	357.00	400	Vertical	Pass
3	5284.557	51.54	74.0	22.46	Peak	59.00	200	Vertical	Pass
3**	5284.557	44.96	54.0	9.04	AV	59.00	200	Vertical	Pass
4	6654.425	53.02	74.0	20.98	Peak	184.00	100	Vertical	Pass
4**	6654.425	43.04	54.0	10.96	AV	184.00	100	Vertical	Pass
5	13305.325	55.76	74.0	18.24	Peak	342.00	100	Vertical	Pass
5**	13305.325	49.24	54.0	4.76	AV	342.00	100	Vertical	Pass
6	17421.930	56.44	74.0	17.56	Peak	183.00	400	Vertical	Pass
6**	17421.930	44.73	54.0	9.27	AV	183.00	400	Vertical	Pass

ANT4**GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1289.118	39.60	74.0	34.40	Peak	312.00	300	Horizontal	Pass
1**	1289.118	33.52	54.0	20.48	AV	312.00	300	Horizontal	Pass
2	2770.163	53.90	74.0	20.10	Peak	150.00	300	Horizontal	Pass
2**	2770.163	43.13	54.0	10.87	AV	150.00	300	Horizontal	Pass
3	5390.614	55.40	74.0	18.60	Peak	121.00	200	Horizontal	Pass
3**	5390.614	44.48	54.0	9.52	AV	121.00	200	Horizontal	Pass
4	6513.290	53.81	74.0	20.19	Peak	274.00	100	Horizontal	Pass
4**	6513.290	45.86	54.0	8.14	AV	274.00	100	Horizontal	Pass
5	13350.982	54.62	74.0	19.38	Peak	164.00	400	Horizontal	Pass
5**	13350.982	49.35	54.0	4.65	AV	164.00	400	Horizontal	Pass
6	17441.608	55.13	74.0	18.87	Peak	98.00	300	Horizontal	Pass
6**	17441.608	48.99	54.0	5.01	AV	98.00	300	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1289.038	43.23	74.0	30.77	Peak	116.00	100	Vertical	Pass
1**	1289.038	33.98	54.0	20.02	AV	116.00	100	Vertical	Pass
2	2771.633	53.53	74.0	20.47	Peak	119.00	400	Vertical	Pass
2**	2771.633	44.99	54.0	9.01	AV	119.00	400	Vertical	Pass
3	5283.422	49.66	74.0	24.34	Peak	214.00	200	Vertical	Pass
3**	5283.422	41.79	54.0	12.21	AV	214.00	200	Vertical	Pass
4	6657.096	55.79	74.0	18.21	Peak	188.00	200	Vertical	Pass
4**	6657.096	42.26	54.0	11.74	AV	188.00	200	Vertical	Pass
5	13308.409	58.77	74.0	15.23	Peak	242.00	200	Vertical	Pass
5**	13308.409	45.11	54.0	8.89	AV	242.00	200	Vertical	Pass
6	17416.379	55.12	74.0	18.88	Peak	79.00	100	Vertical	Pass
6**	17416.379	44.45	54.0	9.55	AV	79.00	100	Vertical	Pass

ANT5**GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.348	44.22	74.0	29.78	Peak	141.00	100	Horizontal	Pass
1**	1287.348	32.73	54.0	21.27	AV	141.00	100	Horizontal	Pass
2	2766.848	52.04	74.0	21.96	Peak	134.00	400	Horizontal	Pass
2**	2766.848	40.52	54.0	13.48	AV	134.00	400	Horizontal	Pass
3	5390.565	54.51	74.0	19.49	Peak	144.00	200	Horizontal	Pass
3**	5390.565	46.39	54.0	7.61	AV	144.00	200	Horizontal	Pass
4	6514.185	54.51	74.0	19.49	Peak	216.00	300	Horizontal	Pass
4**	6514.185	43.91	54.0	10.09	AV	216.00	300	Horizontal	Pass
5	13353.118	52.60	74.0	21.40	Peak	208.00	100	Horizontal	Pass
5**	13353.118	46.57	54.0	7.43	AV	208.00	100	Horizontal	Pass
6	17439.243	54.29	74.0	19.71	Peak	302.00	200	Horizontal	Pass
6**	17439.243	50.51	54.0	3.49	AV	302.00	200	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1286.548	41.46	74.0	32.54	Peak	108.00	200	Vertical	Pass
1**	1286.548	31.33	54.0	22.67	AV	108.00	200	Vertical	Pass
2	2772.658	52.22	74.0	21.78	Peak	90.00	400	Vertical	Pass
2**	2772.658	43.38	54.0	10.62	AV	90.00	400	Vertical	Pass
3	5287.300	53.51	74.0	20.49	Peak	16.00	200	Vertical	Pass
3**	5287.300	43.76	54.0	10.24	AV	16.00	200	Vertical	Pass
4	6657.204	53.26	74.0	20.74	Peak	82.00	300	Vertical	Pass
4**	6657.204	45.80	54.0	8.20	AV	82.00	300	Vertical	Pass
5	13310.595	53.12	74.0	20.88	Peak	182.00	100	Vertical	Pass
5**	13310.595	44.61	54.0	9.39	AV	182.00	100	Vertical	Pass
6	17419.966	54.28	74.0	19.72	Peak	180.00	100	Vertical	Pass
6**	17419.966	49.14	54.0	4.86	AV	180.00	100	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Test Data**ANT3****GFSK (BLE 1Mbps) LOW CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2321.171	56.68	74.0	17.32	Peak	249.00	100	Horizontal	Pass
1**	2321.171	45.34	54.0	8.66	AV	249.00	100	Horizontal	Pass
2	2390.000	51.71	74.0	22.29	Peak	75.00	200	Horizontal	Pass
2**	2390.000	45.73	54.0	8.27	AV	75.00	200	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.43	74.0	17.57	Peak	324.00	100	Horizontal	Pass
1**	2483.500	45.35	54.0	8.65	AV	324.00	100	Horizontal	Pass
2	2494.799	54.63	74.0	19.37	Peak	188.00	100	Horizontal	Pass
2**	2494.799	46.09	54.0	7.91	AV	188.00	100	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2318.334	55.39	74.0	18.61	Peak	268.00	300	Horizontal	Pass
1**	2318.334	44.84	54.0	9.16	AV	268.00	300	Horizontal	Pass
2	2390.000	51.96	74.0	22.04	Peak	309.00	100	Horizontal	Pass
2**	2390.000	44.43	54.0	9.57	AV	309.00	100	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.56	74.0	19.44	Peak	85.00	200	Horizontal	Pass
1**	2483.500	43.87	54.0	10.13	AV	85.00	200	Horizontal	Pass
2	2492.789	56.55	74.0	17.45	Peak	83.00	100	Horizontal	Pass
2**	2492.789	45.15	54.0	8.85	AV	83.00	100	Horizontal	Pass

ANT1**GFSK (BLE 2Mbps) HIGH CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	55.76	74.0	18.24	Peak	338.00	200	Horizontal	Pass
1**	2483.500	42.99	54.0	11.01	AV	338.00	200	Horizontal	Pass
2	2493.603	54.93	74.0	19.07	Peak	79.00	300	Horizontal	Pass
2**	2493.603	44.37	54.0	9.63	AV	79.00	300	Horizontal	Pass

ANT2**GFSK (BLE 2Mbps) HIGH CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.71	74.0	20.29	Peak	88.00	300	Horizontal	Pass
1**	2483.500	44.67	54.0	9.33	AV	88.00	300	Horizontal	Pass
2	2494.838	54.68	74.0	19.32	Peak	348.00	200	Horizontal	Pass
2**	2494.838	45.42	54.0	8.58	AV	348.00	200	Horizontal	Pass

ANT4**GFSK (BLE 2Mbps) HIGH CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.77	74.0	20.23	Peak	321.00	200	Horizontal	Pass
1**	2483.500	42.69	54.0	11.31	AV	321.00	200	Horizontal	Pass
2	2494.053	56.35	74.0	17.65	Peak	334.00	200	Horizontal	Pass
2**	2494.053	42.52	54.0	11.48	AV	334.00	200	Horizontal	Pass

ANT5**GFSK (BLE 2Mbps) HIGH CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.67	74.0	20.33	Peak	149.00	200	Horizontal	Pass
1**	2483.500	44.45	54.0	9.55	AV	149.00	200	Horizontal	Pass
2	2493.290	58.5	74.0	15.50	Peak	74.00	100	Horizontal	Pass
2**	2493.290	42.96	54.0	11.04	AV	74.00	100	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Note: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data

ANT3

GFSK (BLE 1Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-12.35	8	Pass
Middle Channel	-12.16	8	Pass
High Channel	-11.99	8	Pass

GFSK (BLE 2Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-14.54	8	Pass
Middle Channel	-14.31	8	Pass
High Channel	-14.36	8	Pass

Test Plots

ANT3

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2541261-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2541261-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2541261-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--