

TEST REPORT

Applicant: REOLINK TECHNOLOGY PTE. LTD.
Address: 31 KAKI BUKIT ROAD 3, #06-02, TECHLINK,
SINGAPORE 417818
Equipment Type: Video Doorbell
Model Name: Reolink Video Doorbell (refer to section 2.3)
Brand Name: Reolink
FCC ID: 2BN5S-2601A
ISED Number: 33667-2601A
HVIN: Reolink Video Doorbell V02, D340B V02
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-210 Issue 11
(refer to section 3.1)
Sample Arrival Date: Apr. 01, 2026
Test Date: Apr. 03, 2026 - Apr. 08, 2026
Date of Issue: May 07, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie Zhu**Checked by:** Li Ganming**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Apr. 22, 2026</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Apr. 29, 2026</u>	<u>Page 21&22, updated the test data.</u>
<u>Rev. 03</u>	<u>May 07, 2026</u>	<u>Added the HVIN on the home page.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards	7
3.2	Test Verdict	7
4	GENERAL TEST CONFIGURATIONS	8
4.1	Test Environments	8
4.2	Test Equipment List	8
4.3	Test Software List	8
4.4	Measurement Uncertainty	9
4.5	Description of Test Setup	9
5	TEST ITEMS	12
5.1	Antenna Requirements	12
5.2	20 dB and 99% Bandwidth	13
5.3	AC Conducted Emission	14
5.4	Radiated Spurious Emission	15
5.5	Band Edge (Restricted-band band-edge)	17
ANNEX A	TEST RESULT	18

A.1	20 dB and 99% Bandwidth.....	18
A.2	AC Conducted Emissions	19
A.3	Radiated Emission.....	21
A.4	Band Edge (Restricted-band band-edge).....	25
ANNEX B	TEST SETUP PHOTOS	28
ANNEX C	EUT EXTERNAL PHOTOS.....	28
ANNEX D	EUT INTERNAL PHOTOS.....	28

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☒ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No. 55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The CAB identifier number is CN0030.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	REOLINK TECHNOLOGY PTE. LTD.
Address	251 Little Falls Drive, Wilmington, New Castle County, Delaware 19808

2.2 Manufacturer Information

Manufacturer	REOLINK TECHNOLOGY PTE. LTD.
Address	31 KAKI BUKIT ROAD 3, #06-02, TECHLINK, SINGAPORE 417818

2.3 General Description for Equipment under Test (EUT)

EUT Name	Video Doorbell
Model Name Under Test	Reolink Video Doorbell
Series Model Name	D340B
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Serial Number	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	915 MHz
-----------------------------------	---------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	GFSK
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate	1 Mbps
Number of Channel	1
Tested Channel	915 MHz
Antenna Type	FPC Antenna
Antenna Gain	0.6 dBi

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-210 Issue 11	Licence-Exempt Radio Apparatus: Category I Equipment
4	ANSI C63.10-2020+ Cor. 1-2023+ C63.10a-2024 + Errata to C63.10a-2024	American National Standard for Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	RSS-Gen 6.8	--	Pass	Note ¹
2	20 dB and 99% Bandwidth	15.215(c)	RSS-Gen 6.7	ANNEX A.1	Pass	--
3	AC Conducted Emission	15.207	RSS-Gen 8.8	ANNEX A.2	Pass	--
4	Radiated Spurious Emission	15.249(a)	RSS-210 B.10 RSS-Gen 8.9	ANNEX A.3	Pass	--
5	Band Edge(Restricted-band band-edge)	15.249(a)	RSS-210 B.10 RSS-Gen 8.10	ANNEX A.4	Pass	--
Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.						

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	50% to 63%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+21.5°C to +24.3°C
Working Voltage of the EUT	NV (Normal Voltage)	3.6 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2025.06.16	2026.06.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY52510065	2025.06.16	2026.06.15
Signaling Unit	ROHDE&SCHWARZ	CMW500	171150	2025.04.28	2026.04.27
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	00884	2025.03.01	2028.02.29
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	01631	2025.02.22	2028.02.21
Anechoic Chamber	RAINFORD	9m*6m*6m	144	2025.01.04	2028.01.03
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2025.06.17	2026.06.16
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2025.06.17	2026.06.16
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2025.06.16	2026.06.15
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8 m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-Gen 6.8

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 20 dB and 99% Bandwidth

5.2.1 Limit

FCC §15.215(c); RSS-Gen 6.7

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

RSS-Gen 6.7

The emission bandwidth (×dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated × dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3× the resolution bandwidth.

When the occupied bandwidth limit is not stated in the applicable RSS or reference measurement method, the transmitted signal bandwidth shall be reported as the 99% emission bandwidth, as calculated or measured

5.2.2 Test Setups

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW ≥ 1% of the 20 dB bandwidth

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 AC Conducted Emission

5.3.1 Limit

FCC §15.207; RSS-Gen 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.3.2 Test Setups

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Radiated Spurious Emission

5.4.1 Limit

FCC §15.249(a); RSS-210 B.10& RSS-Gen 8.9

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.4.2 Test Setups

See section 4.5.2-4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Restricted-band band-edge)

5.5.1 Limit

FCC §15.249(a); RSS-210 B.10&RSS-Gen 8.10

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.5.2 Test Setups

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.5.4 Test Result

Please refer to ANNEX A.4.

ANNEX A TEST RESULT


A.1 20 dB and 99% Bandwidth

Test Data


Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
915	0.080017	0.079321

Test Plots

20 dB Bandwidth



99% Bandwidth



A.2 AC Conducted Emissions

Note ¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.


Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.282	44.59	9.82	60.76	16.17	Peak	L	Pass
1**	0.282	26.71	9.82	50.76	24.05	AV	L	Pass
2	0.330	44.09	10.42	59.45	15.36	Peak	L	Pass
2**	0.330	29.68	10.42	49.45	19.77	AV	L	Pass
3	0.732	40.71	10.39	56.00	15.29	Peak	L	Pass
3**	0.732	26.66	10.39	46.00	19.34	AV	L	Pass
4	2.626	36.75	10.04	56.00	19.25	Peak	L	Pass
4**	2.626	24.44	10.04	46.00	21.56	AV	L	Pass
5	10.522	40.39	10.23	60.00	19.61	Peak	L	Pass
5**	10.522	25.03	10.23	50.00	24.97	AV	L	Pass
6	18.716	43.78	11.19	60.00	16.22	Peak	L	Pass
6**	18.716	27.58	11.19	50.00	22.42	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.168	46.66	9.85	65.06	18.40	Peak	N	Pass
1**	0.168	33.26	9.85	55.06	21.80	AV	N	Pass
2	0.336	44.32	10.54	59.30	14.98	Peak	N	Pass
2**	0.336	31.73	10.54	49.30	17.57	AV	N	Pass
3	0.722	39.06	10.49	56.00	16.94	Peak	N	Pass
3**	0.722	27.60	10.49	46.00	18.40	AV	N	Pass
4	1.230	36.69	10.30	56.00	19.31	Peak	N	Pass
4**	1.230	25.81	10.30	46.00	20.19	AV	N	Pass
5	10.366	38.56	10.47	60.00	21.44	Peak	N	Pass
5**	10.366	27.32	10.47	50.00	22.68	AV	N	Pass
6	20.132	41.79	11.06	60.00	18.21	Peak	N	Pass
6**	20.132	28.30	11.06	50.00	21.70	AV	N	Pass

A.3 Radiated Emission

Note ¹: The symbol of “--” in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note ⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Note ⁵: The center channel Average Results (dBuV/m) = Peak Results(dBuV/m) + Factor (dB); Duty cycle correction factor=20*log(Duty Cycle) (dB)

Note ⁶: The marked spikes near 915 MHz with circle should be ignored because they are Fundamental signal.

Test Data and Plots


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	36.596	8.42	40.0	31.58	Peak	309.00	150	Horizontal	Pass
2	202.126	9.09	43.5	34.41	Peak	360.00	150	Horizontal	Pass
3	445.645	17.08	46.0	28.92	Peak	118.00	150	Horizontal	Pass
4	654.971	28.44	46.0	17.56	Peak	360.00	150	Horizontal	Pass
5	865.510	43.15	46.0	2.85	Peak	4.00	150	Horizontal	Pass
6	915.028	89.82	94	4.18	Peak	170.00	150	Horizontal	N/A

30 MHz to 1 GHz, ANT V

3#_RE Test case_FCC Part 15C_FCC 15.247_30MHz-1GHz - LORA




No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	42.222	7.47	40.0	32.53	Peak	166.00	150	Vertical	Pass
2	71.273	10.48	40.0	29.52	Peak	118.00	150	Vertical	Pass
3	159.834	11.97	43.5	31.53	Peak	289.00	150	Vertical	Pass
4	240.005	12.68	46.0	33.32	Peak	360.00	150	Vertical	Pass
5	827.146	29.20	46.0	16.80	Peak	88.00	150	Vertical	Pass
6	915.028	75.14	94	18.86	Peak	189.00	150	Vertical	N/A

Note: The spurious above 10G is noise only, do not show on the report.

915 MHz 1 GHz to 10 GHz, ANT H


3#_RE_Test case_FCC Part 15C_FCC 15.247_1GHz-10GHz



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1293.500	44.66	74.0	29.34	Peak	360.00	150	Horizontal	Pass
1**	1293.500	34.87	54.0	19.13	AV	360.00	150	Horizontal	Pass
2	2762.700	52.96	74.0	21.04	Peak	139.00	150	Horizontal	Pass
2**	2762.700	43.22	54.0	10.78	AV	139.00	150	Horizontal	Pass
3	3660.000	44.20	74.0	29.80	Peak	121.00	150	Horizontal	Pass
3**	3660.000	39.19	54.0	14.81	AV	121.00	150	Horizontal	Pass
4	4575.200	51.73	74.0	22.27	Peak	266.00	150	Horizontal	Pass
4**	4575.200	49.89	54.0	4.11	AV	266.00	150	Horizontal	Pass
5	6499.600	50.13	74.0	23.87	Peak	121.00	150	Horizontal	Pass
5**	6499.600	40.59	54.0	13.41	AV	121.00	150	Horizontal	Pass
6	9404.349	46.42	74.0	27.58	Peak	35.00	150	Horizontal	Pass
6**	9404.349	37.76	54.0	16.24	AV	35.00	150	Horizontal	Pass

915 MHz 1 GHz to 10 GHz, ANT V

3#_RE Test case_FCC Part 15C_FCC 15.247_1GHz-10GHz



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1403.700	44.43	74.0	29.57	Peak	270.00	150	Vertical	Pass
1**	1403.700	34.82	54.0	19.18	AV	270.00	150	Vertical	Pass
2	2649.100	53.39	74.0	20.61	Peak	231.00	150	Vertical	Pass
2**	2649.100	44.15	54.0	9.85	AV	231.00	150	Vertical	Pass
3	3660.400	44.08	74.0	29.92	Peak	341.00	150	Vertical	Pass
3**	3660.400	40.35	54.0	13.65	AV	341.00	150	Vertical	Pass
4	4575.000	51.68	74.0	22.32	Peak	140.00	150	Vertical	Pass
4**	4575.000	49.64	54.0	4.36	AV	140.00	150	Vertical	Pass
5	6488.000	49.82	74.0	24.18	Peak	140.00	150	Vertical	Pass
5**	6488.000	41.42	54.0	12.58	AV	140.00	150	Vertical	Pass
6	9016.450	46.82	74.0	27.18	Peak	47.00	150	Vertical	Pass
6**	9016.450	37.74	54.0	16.26	AV	47.00	150	Vertical	Pass

A.4 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ⁴: The Level (dBuV/m) has been corrected by factor.

Note ⁵: Both horizontal and vertical directions were pre tested, only the worst configuration has been reported in this report.

Test Data and Plots

608 MHz to 614 MHz


3#_Bandedge - ATT_FCC_lora_Left below 1G



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	609.730	43.45	46.0	2.55	Peak	91.00	150	Horizontal	Pass
2	613.450	43.80	46.0	2.20	Peak	323.00	150	Horizontal	Pass

960 MHz to 1000 MHz


3#_Bandedge - ATT_FCC_lora_Right below 1G



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	968.400	45.96	54.0	8.04	Peak	91.00	150	Horizontal	Pass
2	987.800	46.15	54.0	7.85	Peak	282.00	150	Horizontal	Pass

1000 MHz to 1240 MHz

3#_Bandedge - ATT_FCC_lora_Right above 1G



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1021.600	42.16	54.0	11.84	Peak	350.00	150	Horizontal	Pass
2	1187.200	42.13	54.0	11.87	Peak	194.00	150	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “Ti-EE26030766-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “Ti-EE26030766-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “Ti-EE26030766-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--