

TEST REPORT

Product Name : ROBOTIC LAWNMOWER
Model Number : TYM V3, Yardcare V3, Lebosbo V3, V3
FCC ID : 2BN5V-V3

Prepared for : Nanjing Toua Robot Technology Co.,Ltd
Address : Room 501, No. 69, Shang Qinhuai Street, Jiangning
District, Nanjing City, Jiangsu Province, China

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : 1&2/F., Building 2, Zone A, Zhongda Marine
Biotechnology Research and Development Base, No.9,
Xincheng Avenue, Songshanhu High-technology
Industrial Development Zone, Dongguan, Guangdong,
China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2604080020E00103R
Date of sample receipt : Apr 08, 2025
Date(s) of Tests : Apr 08, 2025 to May 18, 2025
Date of issue : May 19, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Nanjing Toua Robot Technology Co.,Ltd
Address : Room 501, No. 69, Shang Qinhuai Street, Jiangning District, Nanjing City, Jiangsu Province, China
Manufacturer : Nanjing Toua Robot Technology Co.,Ltd
Address : Room 501, No. 69, Shang Qinhuai Street, Jiangning District, Nanjing City, Jiangsu Province, China
Factory : Anhui Toua Robotics Co., Ltd
Address : Building 4, No. 29, Runzhou Road, Danyang Town, Bowang District, Ma'anshan City, Anhui Province, China
EUT : ROBOTIC LAWNMOWER
Model Name : TYM V3, Yardcare V3, Lebosbo V3, V3
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1091	PASS

The above equipment was tested by EMTEK (DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1091.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Apr 08, 2025 to May 18, 2025


Prepared by :


Jessica Zhang /Editor

Reviewer :


Warren Deng /Supervisor

Approve & Authorized Signer :


Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2604080020E00103R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	ROBOTIC LAWNMOWER
Model Number:	TYM V3, Yardcare V3, Lebosbo V3, V3 (Note: These models are the same, except for the model number, color and appearance; TYM V3 was selected for full test.)
Sample:	1#
Device Type:	BLE 2.4G WIFI
Data Rate:	802.11b 802.11g 802.11n(20MHz channel bandwidth) 1Mbps for GFSK modulation
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; GFSK
Operating Frequency Range(s) :	2412-2462MHz for 802.11b/g/n(HT20); 2402-2480MHz
Number of Channels:	11 channels for 802.11b/g/n(HT20); BLE:40 channels
Transmit Power Max:	BLE:4.37 dBm(0.002735 W) 2.4G WIFI:15.39 dBm(0.034594 W)
Antenna Type:	FPC Antenna
Antenna Gain:	4.42 dBi
Power supply:	DC 18.0V built-in battery
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

4. Measurement Result

Antenna gain:

2.4G: 4.42 dBi

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2412	11B	15.14	15±1	16	39.811	4.42	2.767	0.0219	1
2437		14.79	15±1	16	39.811	4.42	2.767	0.0219	1
2462		14.77	15±1	16	39.811	4.42	2.767	0.0219	1
2412	11G	15.32	15±1	16	39.811	4.42	2.767	0.0219	1
2437		15.39	15±1	16	39.811	4.42	2.767	0.0219	1
2462		15.30	15±1	16	39.811	4.42	2.767	0.0219	1
2412	11N20SISO	15.12	15±1	16	39.811	4.42	2.767	0.0219	1
2437		15.32	15±1	16	39.811	4.42	2.767	0.0219	1
2462		15.20	15±1	16	39.811	4.42	2.767	0.0219	1

Antenna gain:

BLE: 4.42 dBi

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK (1M)	3.20	3±1	4	2.512	4.42	2.767	0.0014	1
2440		3.74	3±1	4	2.512	4.42	2.767	0.0014	1
2480		4.37	4±1	5	3.162	4.42	2.767	0.0017	1

According to KDB 447498, no stand-alone required for WIFI/BLE antenna, and no simultaneous SAR measurement is required.

*** End of Report ***