

Antenna specification

Antenna Sample Confirmation From

Name of supplier	ShenZhen Aihui Technology Co. , Ltd				
Customer name	Yi Gao				
Sample name	1068				
model	Tablet				
Sample size	Main antenna: 160mm 3rd generation terminal Tri-Phase One-Day Line: 225mm 3rd Generation Terminal NFC Antenna: 65mm 3rd Generation Terminal				
Inspection item	Performance test	Visual inspection	Structure	In the news	Test results
Notes					
Quality Audit		Project Audit		Business confirmation	
The following is to be completed by the client					
Customer feedback					

Customer signature/seal	date:
-------------------------	-------

Antenna Test Report

Test Unit: Shenzhen Aihui Technology Co. , Ltd.			
Materials	FPC coaxial line		
Antenna type	MonopoleType	Polarization mode	Linear
Application scenario			
Working band	GSM/LTE/WIFI /BT /GPS	VSWR	≤2
Power	Max: 2W	Impedance	50Ω

dBi	
Test Equipment	HPE5071C、Shielding Room、3D automatic turntable
Antenna Description:: 1. Grounding processing and picture description: no 2. Need to change the motherboard to match: no ● Test voltage: 3.6V, check the antenna contact is good before testing. ● The RF cable of the integrated tester is kept in a natural state and can not be curled. Specification:test the specified power level, all indicators must conform to the specifications.	

1. Project Image
2. Test Fixture
3. Antenna matching circuit
4. S11 test
5. Antenna passive efficiency and gain
6. Darkroom test equipment and data
7. Schematic diagram of antenna assembly
8. Antenna environment handling
9. Antenna mass production index
10. Structural drawing


1.Project Image

The final verification antenna performance prototype in our company for at least one year, easy to analyze and solve the problem of antenna mass production, to ensure the quality of antenna shipment

2.Test Fixture

Objective: to test the passive parameters of antenna as accurately as possible. Making Method: the handset is made of a 50 ohm coaxial cable, one end of which is connected to the test point of the back end of the matching circuit of the handset motherboard (front end of the RF test hole) , and the other end is connected to the SMA joint. The diagram is as follows:

3、 Antenna matching circuit




Modify

E01	E02	E03
No	No	No

Note: The match is unmodified.

4.S11 test

4.0 4.0s11 test method description of test equipment: Network Analyzer (E5071C) test method: a 50 ohm CABLE is used to export from the instrument test port. The SMA connector for connecting the handset is calibrated using a calibration piece, record the echo loss and standing wave ratio corresponding to the relevant frequency points. The test schematic is as follows:




6.Test Equipment

Test system: shielded darkroom

The temperature was $22^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and the humidity was $50\% \pm 15\%$


Test equipment: when testing passive data, use the Network analyzer AGILENT E5071C
to test active data, use the omnibus CMW500



7.Antenna Passive Test Data

Main Antenna:


Gain&Efficiency 增益和效率			
frequency 频率(Hz)	gain 增益(dBi)	efficiency 效率(dB)	efficiency 效率
690M	-0.15	-4.05	29.89%
710M	0.28	-3.22	33.43%
740M	0.62	-3.06	34.23%
770M	0.73	-3.19	34.11%
800M	0.69	-3.24	36.18%
830M	0.91	-3.01	36.56%
860M	0.84	-3.13	35.43%
890M	0.77	-3.19	34.11%
920M	0.67	-3.21	33.64%
950M	0.58	-3.52	34.26%
980M	0.46	-3.76	35.36%



Shenzhen Aihui Technology Co. , Ltd.


Gain&Efficiency 增益和效率			
frequency 频率(Hz)	gain 增益(dBi)	efficiency 效率(dB)	efficiency 效率
1710M	1.13	-3.56	40.25%
1743M	1.17	-3.46	41.52%
1777M	0.92	-3.72	39.58%
1811M	0.86	-3.94	38.95%
1845M	1.23	-4.27	41.51%
1878M	1.34	-3.94	38.76%
1912M	1.49	-3.05	40.91%
1946M	1.36	-3.16	39.82%
1980M	1.15	-3.37	42.71%
2014M	1.24	-3.31	46.53%
2047M	0.96	-4.01	45.48%
2081M	1.08	-3.62	42.51%
2115M	1.19	-3.39	40.53%
2149M	1.05	-3.49	43.26%
2183M	0.97	-3.91	45.26%
2216M	0.73	-3.85	38.18%
2250M	0.13	-4.72	34.26%
2284M	0.61	-4.56	31.23%
2318M	0.52	-4.55	30.52%
2352M	0.71	-4.37	36.25%
2385M	0.08	-5.09	35.37%
2419M	0.16	-4.96	38.76%
2453M	0.36	-4.83	38.94%
2487M	0.56	-4.19	35.83%
2521M	0.87	-4.27	37.43%
2554M	1.01	-3.96	39.22%
2588M	1.12	-3.49	42.36%
2622M	1.31	-3.42	43.16%
2656M	0.94	-3.86	40.17%
2690M	0.84	-3.91	38.69%

Address: 402TEL: 0755-23203435fax: 0755-23203435, Block C, Juxin Science and Technology Industrial Park, Nanchang community, xixiang, Baoan District, Shenzhen




Three-in-one: 2.4G WIFI

Gain&Efficiency 增益和效率			
frequency 频率(Hz)	gain 增益(dBi)	efficiency 效率(dB)	efficiency 效率
2400M	1.35	-3.19	46.36%
2410M	1.16	-3.23	45.58%
2420M	1.47	-2.98	46.11%
2430M	1.29	-3.21	45.21%
2440M	1.09	-3.45	47.03%
2450M	1.13	-3.34	43.63%
2460M	1.04	-3.51	45.28%
2470M	1.26	-3.19	45.11%
2480M	1.33	-3.09	43.63%
2490M	1.41	-3.01	42.85%
2500M	1.27	-3.18	40.32%







GPS

Gain&Efficiency 增益和效率			
frequency 频率(Hz)	gain 增益(dBi)	efficiency 效率(dB)	efficiency 效率
1560M	0.95	-3.58	40.11%
1565M	0.82	-3.67	41.16%
1575M	1.02	-3.19	42.28%
1580M	0.99	-3.55	39.03%



5.8GWIFI

Gain&Efficiency			
frequency 频率(Hz)	gain 增益(dBi)	efficiency 效率(dB)	efficiency 效率
5050M	1.04	-3.69	43.59%
5100M	1.1	-3.61	44.39%
5150M	1.13	-3.65	43.58%
5200M	1.08	-3.74	45.15%
5250M	1.17	-3.62	42.76%
5300M	0.97	-3.71	43.62%
5350M	0.88	-3.75	45.27%
5400M	1.01	-3.63	41.79%
5450M	1.21	-3.58	40.63%
5500M	1.33	-3.51	43.29%
5550M	1.17	-3.62	43.35%
5600M	1.42	-3.46	45.79%
5650M	1.61	-3.34	46.12%
5700M	1.35	-3.49	46.75%
5750M	1.50	-3.39	47.19%
5800M	1.37	-3.41	45.17%
5850M	1.42	-3.44	44.11%





8.Antenna environment handling

9.Antenna mass production index

When the antenna is mass-produced, the standing wave ratio is taken as the mass-produced test standard. Based on the differences of the project itself, the following criteria are given:	Standard for volume production
680MHZ-2700Mhz	VSWR (Mass Production performance) & LT; VSWR(recognition performance) 0.5


10.1 Structural drawings

Shenzhen Aihui Technology Co. , Ltd.



Address: 402TEL: 0755-23203435fax: 0755-23203435, Block C, Juxin Science and Technology Industrial Park, Nanchang community, xixiang, Baoan District, Shenzhen

Shenzhen Aihui Technology Co. , Ltd.



Address: 402TEL: 0755-23203435fax: 0755-23203435, Block C, Juxin Science and Technology Industrial Park, Nanchang community, xixiang, Baoan District, Shenzhen