

RF EXPOSURE EVALUATION

FCC ID: 2BN6J-POP4

According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b):

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{GHz}}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$$

- f_{GHz} is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (dBm)	Distance (mm)	Calculation results	Limit	Operating Mode
2412	6.92	6.92 ± 1	7.920	5	1.924	3	DSSS
2412	6.82	6.82 ± 1	7.820	5	1.880	3	
2437	7.13	7.13 ± 1	8.130	5	2.030	3	
2437	6.88	6.88 ± 1	7.880	5	1.916	3	DSSS
2462	7.44	7.44 ± 1	8.440	5	2.191	3	
2462	7.27	7.27 ± 1	8.270	5	2.107	3	
2412	6.91	6.91 ± 1	7.910	5	1.920	3	OFDM
2412	6.83	6.83 ± 1	7.830	5	1.885	3	
2437	7.11	7.11 ± 1	8.110	5	2.020	3	
2437	6.79	6.79 ± 1	7.790	5	1.877	3	OFDM
2462	6.97	6.97 ± 1	7.970	5	1.966	3	
2462	6.74	6.74 ± 1	7.740	5	1.865	3	
2412	4.84	4.84 ± 1	5.840	5	1.192	3	OFDM
2412	4.83	4.83 ± 1	5.830	5	1.189	3	

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

2412	7.85	7.85 ± 1	8.850	5	2.384	3	
2437	5.04	5.04 ± 1	6.040	5	1.254	3	OFDM
2437	5.08	5.08 ± 1	6.080	5	1.266	3	
2437	8.07	8.07 ± 1	9.070	5	2.520	3	
2462	5.25	5.25 ± 1	6.250	5	1.323	3	OFDM
2462	5.24	5.24 ± 1	6.240	5	1.320	3	
2462	8.26	8.26 ± 1	9.260	5	2.647	3	
2412	5.33	5.33 ± 1	6.330	5	1.334	3	OFDMA
2412	5.34	5.34 ± 1	6.340	5	1.337	3	
2412	8.35	8.35 ± 1	9.350	5	2.674	3	
2437	5.52	5.52 ± 1	6.520	5	1.401	3	OFDMA
2437	5.52	5.52 ± 1	6.520	5	1.401	3	
2437	8.53	8.53 ± 1	9.530	5	2.802	3	
2462	5.61	5.61 ± 1	6.610	5	1.438	3	OFDMA
2462	5.62	5.62 ± 1	6.620	5	1.441	3	
2462	8.63	8.63 ± 1	9.630	5	2.882	3	
5210	3.77	3.77 ± 1	4.770	5	1.369	3	OFDM
5210	1.90	1.90 ± 1	2.900	5	0.890	3	
5210	5.95	5.95 ± 1	6.950	5	2.262	3	
5210	4.20	4.20 ± 1	5.200	5	1.512	3	OFDMA
5210	1.88	1.88 ± 1	2.880	5	0.886	3	
5210	6.20	6.20 ± 1	7.200	5	2.396	3	

Note: WIFI5.2G&WiFi 2.4G cannot support simultaneous transmission.

Result: No Standalone SAR test is required.