

EMF TEST REPORT

Test Report No. : OT-264-RWD-060
Reception No. : 2602000614
Applicant : TELICA Inc.
Address : Tower A-411, 40 Imi-ro, Uiwang-Si, Gyeonggi-do, 16006, South Korea
Manufacturer : AMPAK Technology Inc.
Address : 6F., No.23, Hunake 1st Rd., Zubei City, Hsinchu Country 302047, Taiwan
Type of Equipment : WLAN Module
FCC ID. : 2BN7U-AP6256
Model Name : TE-AP6256
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 7 pages (including this page)
Date of Incoming : March 16, 2026
Date of issue : April 24, 2026


SUMMARY

The equipment complies with the regulation; **CFR §2.1091**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This test report is not associated with the accreditation granted by the Korean Laboratory Accreditation Scheme (KOLAS).





Tested by
 Ye-Bhin, Park / Project Engineer
 ONETECH Corp.

Reviewed by
 Tae-Ho, Kim / Chief Engineer
 ONETECH Corp.

Approved by
 Jae-Ho, Lee / Director
 ONETECH Corp.

CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. MAXIMUM PERMISSIBLE EXPOSURE	6
3.1 LIMIT AND CALCULATION METHOD	6
4. MPE Calculations	7
5. CALCULATED RESULTS	7
5.1 LIMIT AND CALCULATION	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-264-RWD-060	April 24, 2026	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : TELICA Inc.

Address : Tower A-411, 40 Imi-ro, Uiwang-Si, Gyeonggi-do, 16006, South Korea

Contact Person : Aaron, Kim / Principal Research Engineer

Telephone No. : +82-10-9580-1067

FCC ID : 2BN7U-AP6256

Model Name : TE-AP6256

Brand Name : -

Serial Number : N/A

Date : April 24, 2026

E.U.T. DESCRIPTION	Modular Transmitter, WLAN Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
Modifications on the Equipment to Achieve Compliance	None

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The TELICA Inc., Model TE-AP6256 (referred to as the EUT in this report) is a WLAN Module. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	WLAN Module	
Temperature Range	-30 °C ~ 85 °C	
OPERATING FREQUENCY	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
MODULATION TYPE	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
ANTENNA TYPE	PCB Antenna	
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32.768 kHz, 37.4 MHz	

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. MAXIMUM PERMISSIBLE EXPOSURE

3.1 LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with FCC 47 CFR Part 2 Subpart J, section 2.1091 and FCC 47 CFR Part 1.1310(e)(1) this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF permissible Exposure limit shall comply with, Limits for General Population/Uncontrolled Exposure.

Frequency range	Electric field strength	Magnetic field strength	Power density	Averaging time
(MHz)	(V/m)	(A/m)	(mW/cm ²)	(minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			<u>1</u>	<30

f = frequency in MHz

* = Plane-wave equivalent power density

4. MPE Calculations

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below

$$\text{EIRP} = \text{P} + \text{G}$$

Where,

P = Power input to the antenna (mW) G = Numeric power gain of the antenna

G= Power Gain of the Antenna (dBi)

Power density at the specific separation:

$$\text{S} = \text{PG} / (4\text{R}^2\pi)$$

Where,

S = Maximum power density (mW/cm²)

P = Power input to the antenna (mW) G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna

(20cm = limit for MPE)

Estimated safe separation:

$$\text{R} = \sqrt{\text{PG} / 4\pi}$$

Where,

P = Power input to the antenna (mW)

G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna

(20cm = limit for MPE)

5. CALCULATED RESULTS

5.1 LIMIT AND CALCULATION

Operating Mode	Measured Power	P*	G	EIRP	EIRP	Power Density	LIMIT
	(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	
802.11 b	15.38	16.38	4.98	21.36	136.77	0.027 2	1
802.11 g	12.33	13.33	4.98	18.31	67.76	0.013 5	1
802.11 n(HT20)	11.75	12.75	4.98	17.73	59.29	0.011 8	1

Note: P = Max Tune up Power

Tolerance = Target power ± 1.0