# Appendix A

## RF Test Data for BT LE(Conducted Measurement)

**Product Name: RF Bluetooth APP controller**

**Test Model: KJ-RF-BT-APP-001**

**Environmental Conditions**

| | |
|---|---|
| Temperature: | 23.8°C |
| Relative Humidity: | 52.1% |
| ATM Pressure: | 100.0 kPa |
| Test Engineer: | Jay Luo |
| Supervised by: | Nick Peng |

# A.1 -6dB Bandwidth

| Condition | Mode | Frequency (MHz) | Antenna | -6 dB Bandwidth (MHz) | Limit -6 dB Bandwidth (MHz) | Verdict |
|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | 0.661 | >=0.5 | Pass |
| NVNT | BLE 1M | 2440 | Ant1 | 0.653 | >=0.5 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 0.651 | >=0.5 | Pass |

Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



# A.2 Maximum Peak Conducted Output Power

| Condition | Mode | Frequency (MHz) | Antenna | Conducted Power (dBm) | Limit (dBm) | Verdict |
|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | 0.56 | 30 | Pass |
| NVNT | BLE 1M | 2440 | Ant1 | 0.61 | 30 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | -0.46 | 30 | Pass |

Test Graphs

Power NVNT BLE 1M 2402MHz Ant1




Power NVNT BLE 1M 2440MHz Ant1



Power NVNT BLE 1M 2480MHz Ant1



# A.3 Maximum Power Spectral Density Level

| Condition | Mode | Frequency (MHz) | Antenna | Conducted PSD (dBm/3kHz) | Limit (dBm/3kHz) | Verdict |
|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | -16.07 | 8 | Pass |
| NVNT | BLE 1M | 2440 | Ant1 | -16.04 | 8 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | -16.95 | 8 | Pass |

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2440MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1



## A.4 Band Edge

| Condition | Mode | Frequency (MHz) | Antenna | Max Value (dBc) | Limit (dBc) | Verdict |
|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | -57.08 | -20 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | -55.53 | -20 | Pass |

Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



# A.5 Conducted RF Spurious Emission

| Condition | Mode | Frequency (MHz) | Antenna | Max Value (dBc) | Limit (dBc) | Verdict |
|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | -55.96 | -20 | Pass |
| NVNT | BLE 1M | 2440 | Ant1 | -54.82 | -20 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | -54.94 | -20 | Pass |

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



# A.6 Duty Cycle

| Condition | Mode | Frequency (MHz) | Antenna | Duty Cycle (%) | Correction Factor (dB) | 1/T (kHz) |
|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | 87.39 | 0.59 | 0.61 |
| NVNT | BLE 1M | 2440 | Ant1 | 87.41 | 0.58 | 0.61 |
| NVNT | BLE 1M | 2480 | Ant1 | 87.39 | 0.59 | 0.61 |

Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant1




Duty Cycle NVNT BLE 1M 2440MHz Ant1



Duty Cycle NVNT BLE 1M 2480MHz Ant1



## A.7 Restrict Band

| Condition | Mode | Frequency (MHz) | Antenna | Spur Freq (MHz) | Power (dBm) | Gain (dBi) | Duty Factor (dB) | E (dBuV/m) | Detector | Limit (dBuV/m) | Verdict |
|---|---|---|---|---|---|---|---|---|---|---|---|
| NVNT | BLE 1M | 2402 | Ant1 | 2310 | -51.85 | 2 | - | 45.41 | Peak | 74 | Pass |
| NVNT | BLE 1M | 2402 | Ant1 | 2310 | -58.57 | 2 | 0.59 | 39.28 | Average | 54 | Pass |
| NVNT | BLE 1M | 2402 | Ant1 | 2358.768 | -47.65 | 2 | - | 49.61 | Peak | 74 | Pass |
| NVNT | BLE 1M | 2402 | Ant1 | 2366.352 | -58.03 | 2 | 0.59 | 39.82 | Average | 54 | Pass |
| NVNT | BLE 1M | 2402 | Ant1 | 2390 | -49.71 | 2 | - | 47.55 | Peak | 74 | Pass |
| NVNT | BLE 1M | 2402 | Ant1 | 2390 | -58.37 | 2 | 0.59 | 39.48 | Average | 54 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 2483.5 | -46.97 | 2 | - | 50.29 | Peak | 74 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 2483.5 | -57.29 | 2 | 0.59 | 40.56 | Average | 54 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 2486.632 | -45.3 | 2 | - | 51.96 | Peak | 74 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 2483.512 | -57.29 | 2 | 0.59 | 40.56 | Average | 54 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 2500 | -49.4 | 2 | - | 47.86 | Peak | 74 | Pass |
| NVNT | BLE 1M | 2480 | Ant1 | 2500 | -57.77 | 2 | 0.59 | 40.08 | Average | 54 | Pass |

Test Graphs

Restrict Band NVNT BLE 1M 2402MHz Ant1 Peak




Restrict Band NVNT BLE 1M 2402MHz Ant1 Average



Restrict Band NVNT BLE 1M 2480MHz Ant1 Peak




Restrict Band NVNT BLE 1M 2480MHz Ant1 Average