

RADIO TEST REPORT

Product : Inspiren Link
Model Name : IN6L001
FCC ID : 2BNIV-LNK-1
Test Regulation : FCC 47 CFR Part 15 Subpart C (Section 15.247)
Received Date : 2025/12/22
Test Date : 2025/12/22 ~ 2026/01/07
Issued Date : 2026/1/20

Applicant : All Inspire Health
19 Morris Avenue, Building 128, Brooklyn, NY 11205

Issued By : Underwriters Laboratories Taiwan Co., Ltd.
Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd.,
Zhudong Township, Hsinchu County, Taiwan




The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



Original Test Report No.: 4792081030A-US-R3-V0

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Table of Contents

1. Attestation of Test Results	4
2. Summary of Test Results	5
3. Test Methodology and Reference Procedures.....	6
4. Facilities and Accreditation	6
5. Measurement Uncertainty	7
6. Equipment under Test.....	8
6.1. Description of EUT	8
6.2. Channel List	9
6.3. Test Condition.....	10
6.4. Description of Available Antennas	11
6.5. Test Mode Applicability and Tested Channel Detail.....	12
6.6. Duty cycle	13
7. Test Equipment	14
8. Description of Test Setup	16
9. Test Results	18
9.1. Channel Bandwidth.....	18
9.2. Conducted Output Power	21
9.3. Hopping Channel Separation	23
9.4. Number of Hopping Frequency Used	26
9.5. Dwell Time on Each Channel	28
9.6. Conducted Out of Band Emission.....	31
9.7. Radiated Spurious Emission	36
9.8. AC Power Line Conducted Emission	68

1. Attestation of Test Results

APPLICANT: All Inspire Health
19 Morris Avenue, Building 128, Brooklyn, NY 11205

MANUFACTURER: InnoComm Mobile Technology Corporation
3F, No. 6, Hsin Ann Rd., Hsinchu Science Park, Hsinchu 300092,
Taiwan

EUT DESCRIPTION: Inspiren Link

BRAND: All Inspire Health

MODEL: IN6L001

SAMPLE STAGE: Engineering Verification Test Sample

DATE of TESTED: 2025/12/22 ~ 2026/01/07

APPLICABLE STANDARDS	
STANDARD	Test Results
FCC 47 CFR PART 15 Subpart C (Section 15.247)	PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:



Sally Lu
Project Handler

Date : 2026/1/20

Approved and Authorized By:



Eric Lee
Senior Laboratory Engineer

Date : 2026/1/20

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

2. Summary of Test Results

Summary of Test Results		
FCC Clause	Test Items	Result
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS
15.247(b)	Conducted Output Power	PASS
15.247(d)	Antenna Port Emission	PASS
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS
15.207	AC Power Conducted Emission	PASS
15.203	Antenna Requirement	PASS

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

3. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2, KDB558074 D01 Meas Guidance v05r02, KDB414788 D01 Radiated Test Site v01r01, ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024.

4. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.
Address	Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

5. Measurement Uncertainty

For statement of conformity, Simple acceptance (Section 3.1.4 of IEC Guide 115) was applied as decision rule for measurement in this test report.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k=2$.

Determining compliance based on the results of the compliance measurement, not considering measurement instrumentation uncertainty.

Measurement	Frequency	Uncertainty
Conducted disturbance at mains terminals ports	150kHz ~ 30MHz	3.0 dB
RF Conducted	9 kHz - 40GHz	2.4 dB
Radiated disturbance below 30MHz	9 kHz - 30 MHz	1.9 dB
Radiated disturbance below 1 GHz	30MHz ~ 1GHz	5.6 dB
Radiated disturbance above 1 GHz	1GHz ~ 40GHz	4.6 dB

6. Equipment under Test

6.1. Description of EUT

Product	Inspiren Link
Brand Name	All Inspire Health
Model Name	IN6L001
Normal Voltage	120Vac/60Hz 3.2Vdc from Battery

Operating Frequency	2402MHz ~ 2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK and 8DPSK
Transfer Rate	Up to 3 Mbps
Maximum Output Power	10.23 dBm
Sample ID	Conducted Test:9266372
	Radiated Test:9266370

Note:

1. EUT is equipped with a built-in rechargeable battery with the following table:

Brand	Model	Description
UTL	14500	3.2Vdc, 1.92Wh, 20250707/600mAh

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual, the laboratory shall not be held responsible.
3. The EUT contains three modules, namely module 1 (BT+WLAN 2.4GHz+WLAN 5GHz), module 2 (BLE), and module 3 (LoRa). This test report is the BT test result of module 1 (BT+WLAN 2.4GHz+WLAN 5GHz).

6.2. Channel List

79 channels are provided for BT-BR/EDR mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	-	-

6.3. Test Condition

Test Item	Test Site No.	Environmental	Input Power	Test Date	Tested by
Antenna Port Conducted Measurement	SR4	19~22°C/ 58~69%RH	120Vac/ 60Hz	2025/12/22~ 2026/01/07	WaterNil Guan
Radiated Spurious Emission	966-2	22~26°C/ 62~68%RH	120Vac/ 60Hz	2025/12/24~ 2026/01/03	Rex Chen
AC power Line Conducted Emission	SR1	24°C/ 62%RH	120Vac/ 60Hz	2026/01/06	Rex Chen

Sample Calculation:

Antenna Port Conducted Measurement:

- Where relevant, the follow sample calculation is provided:
Result Value (dBm) = Reading Value (dBm) + Attenuator Factor (dB) + Cable Loss (dB).
Example: Result Value (10dBm) = Reading Value (-2dBm) + Attenuator Factor (10dB) + Cable Loss(2dB).
*Test plot only shown the “Result Value”.

Radiated Spurious Emission:

- Where relevant, the follow sample calculation is provided:
Result Value (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB).
Example: Result Value (34.5dBuV/m) = Reading Value (40.1dBuV) + Antenna Factor (18.7dB/m) + Cable Loss (4.2dB) - Preamp Factor (28.5dB).

AC power Line Conducted Emission:

- Where relevant, the follow sample calculation is provided:
Result Value (dBuV) = Reading Value (dBuV) + Correction Factor (dB).
Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).
Example: Result Value (53.7dBuV) = Reading Value (35.1dBuV) + Insertion loss(18.1dB) + Cable loss(0.5dB).

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

6.4. Description of Available Antennas

Ant. No.	Transmitter Circuit	Frequency Range	Brand Name	Model Name	Maximum Gain (dBi)	Ant. Type	Connector Type
BT/WIFI 1	Chain0	2412~2472MHz	Innocomm	Ext_WIFI1	2.38	Monopole	i-Pex

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual, the laboratory shall not be held responsible.

6.5. Test Mode Applicability and Tested Channel Detail

Test Item	Modulation Type	Available Channel	Test Channel	Packet Type
Radiated Emissions (Above 1GHz)	GFSK	0 to 78	0,39,78	DH5
	8DPSK	0 to 78	0,39,78	3DH5
Radiated Emissions (Below 1GHz)	GFSK	0 to 78	78	3DH5
AC Power Line Conducted Emission	GFSK	0 to 78	78	3DH5
Antenna Port Conducted Measurement	GFSK	0 to 78	0,39,78	DH1*,DH3*,DH5
	8DPSK	0 to 78	0,39,78	3DH1*,3DH3*,3DH5

* Only for Dwell Time on Each Channel test

- The EUT was examined in three orthogonal axes (X-Y, Y-Z, X-Z), and the X-Y plane was confirmed as the worst-case orientation. All final radiated emission tests were conducted with the EUT positioned accordingly.
- The EUT operates on a rechargeable battery. A pre-scan was conducted at 0%, 50%, and 100% battery capacity. The worst-case emissions occurred at 100% capacity, so only the corresponding test data is documented in this report.
- In the transmit mode, GFSK 3DH5 channel 78 has the highest RF output power. Therefore, the AC conduction was performed using this worst-case mode.
- In the transmit mode, GFSK 3DH5 channel 78 has the highest RF output power. Therefore, all final tests for the spurious emission (below 1GHz) were performed using this worst-case mode.
- The Packet Type for DH1, DH3, and DH5 have all been pre-tested, the fundamental worst case of the Packet Type was found in the DH5. Therefore, only DH5 Packet Type is recorded in the report. (Except Dwell Time).
- The modulation and bandwidth are similar for $\pi/4$ -DQPSK mode and 8DPSK mode, therefore investigated 8DPSK mode to representative mode in test report.
- For Antenna Port Conducted Measurement, this item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Since the DUT is a Bluetooth device, the AFH mode and non-AFH mode follow the Bluetooth timing protocol, and the same timing level has the same time interval, but the non-AFH mode has worse results, therefore only the test data of this type were recorded in this report.

Simultaneously transmission condition:

Condition	Technology				
1	Module1			Module2	Module3
	BT	WLAN (2.4GHz)	WLAN (5GHz)	BT LE	LoRa

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

6.6. Duty cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle	Duty Factor (dB)	VBW Set (above 1GHz)
GFSK(DH5)	2.870	3.750	0.7653	1.16	510Hz
8DPSK(3DH5)	2.870	3.750	0.7653	1.16	510Hz



7. Test Equipment

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
Radiated Spurious Emission					
Spectrum Analyzer	Keysight	N9010A	MY56070818	2025/3/12	2026/3/11
EMI Test Receiver	Rohde & Schwarz	ESR7	101754	2024/12/24	2025/12/23
				2025/12/9	2026/12/8
Loop Antenna	ETS lindgren	6502	00213440	2025/11/14	2026/11/13
Trilog-Broadband Antenna with 5dB Attenuator	Schwarzbeck & EMCI	VULB 9168 & N-6-05	774 & AT-N0538	2024/12/30	2025/12/29
				2025/12/23	2026/12/22
Horn Antenna (1-18 GHz)	Schwarzbeck	BBHA 9120 D	01690	2025/11/18	2026/11/17
Horn Antenna (18-40 GHz)	Schwarzbeck	BBHA 9170	781	2025/12/2	2026/12/1
Preamplifier (30-1000 MHz)	EMCI	EMC330E	980405	2025/5/12	2026/5/11
Preamplifier (1-18 GHz)	EMCI	EMC051835BE	980406	2025/1/13	2026/1/12
Preamplifier (18-40GHz)	EMCI	EMC184040SEE	980426	2025/4/7	2026/4/6
Cables (9k-18 GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-4 & 170425-2	2025/11/21	2026/11/20
Cables (18-40GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-1 & 170214-2	2025/11/21	2026/11/20

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
Antenna Port Conducted Measurement					
Signal Analyzer	Rohde & Schwarz	FSVA3044	101281	2025/3/5	2026/3/4
Signal Analyzer	Rohde & Schwarz	FSV40	101490	2025/6/17	2026/6/16
Attenuator	EMCI	EMC-40ATK2W10	17002	2025/10/28	2026/10/27
USB Power Sensor	Anritsu	MA24408A	12031	2025/6/24	2026/6/23
Temperature & Humidity Test Chamber	GIANT FORCE	GTH-150-40-CP-AR	MAA1701-010	2025/2/25	2026/2/24
AC power Line Conducted Emission					
EMI Test Receiver	Rohde & Schwarz	ESR7	101753	2025/9/18	2026/9/17
Two-Line V-Network	Rohde & Schwarz	ENV216	102136	2025/5/27	2026/5/26
Impuls-Begrenzer Pulse Limiter	Rohde & Schwarz	ESH3-Z2	102219-Qt	2025/8/27	2026/8/26
Cables	TITAN	CFD200	T0732ACFD 20020A300-2	2025/4/21	2026/4/20

UL Software		
Description	Name	Version
Radiated measurement	e3	6.191211 (V6)
Conducted measurement	RF-Conducted-FCC 15247	ver 1.0
AC power Line Conducted Emission	EZ_EMG	UL-3A1.2

8. Description of Test Setup

Tx Mode

Support Equipment


ID	Equipment	Brand Name	Model Name	S/N	Remark
A	Battery	UTL	14500	N/A	Provide by Client 3.2Vdc

Test Setup

Controlled using a bespoke application (ADB interface version 1.0.32) on a test Notebook.
The application was used to enable a continuous transmission mode and to select the test channels, data rates, modulation schemes and power setting as required.

Setup Diagram for Test

Tx Mode



Under Table

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

9. Test Results

9.1. Channel Bandwidth


Requirements

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data

Mode	CH	Freq (MHz)	Chain	20dB BW (MHz)	Limit (MHz)	Result
GFSK(DH5)	0	2402	Chain 0	0.968	N/A	Pass
GFSK(DH5)	39	2441	Chain 0	0.968	N/A	Pass
GFSK(DH5)	78	2480	Chain 0	0.972	N/A	Pass
8DPSK(3DH5)	0	2402	Chain 0	1.302	N/A	Pass
8DPSK(3DH5)	39	2441	Chain 0	1.302	N/A	Pass
8DPSK(3DH5)	78	2480	Chain 0	1.301	N/A	Pass


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



9.2. Conducted Output Power


Requirements

The Maximum Output Power Measurement is 125mW.

Test Procedure

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Test Setup



The loss between RF output port of the EUT and the input port of the Power Meter has been taken into consideration.

Test Data

Mode	CH	Freq. (MHz)	Peak Power (dBm)	Total Power (mW)	Total Power (dBm)	AVG Power (dBm)	Total Power (mW)	Total Power (dBm)	Limit (dBm)	Result
			Chain 0			Chain 0				
BT-GFSK	0	2402	8.43	6.966	8.43	8.06	6.397	8.06	20.97	Pass
	39	2441	8.9	7.762	8.9	8.45	6.998	8.45	20.97	Pass
	78	2480	8.71	7.43	8.71	8.3	6.761	8.3	20.97	Pass
BT-8DPSK	0	2402	9.29	8.492	9.29	6.18	4.15	6.18	20.97	Pass
	39	2441	9.64	9.204	9.64	6.62	4.592	6.62	20.97	Pass
	78	2480	10.23	10.544	10.23	7.34	5.42	7.34	20.97	Pass

Note: Average Power is for reference Only.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

9.3. Hopping Channel Separation


Requirements

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- By using the MaxHold function record the separation of two adjacent channels.
- Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data

Mode	CH	Freq (MHz)	Chain	Channel Separation (MHz)	> Limit (MHz)
GFSK(DH5)	0	2402	Chain 0	1	0.645
GFSK(DH5)	39	2441	Chain 0	0.999	0.645
GFSK(DH5)	78	2480	Chain 0	1.002	0.648
8DPSK(3DH5)	0	2402	Chain 0	0.997	0.868
8DPSK(3DH5)	39	2441	Chain 0	0.999	0.868
8DPSK(3DH5)	78	2480	Chain 0	1.003	0.867


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



9.4. Number of Hopping Frequency Used


Requirements

At least 15 channels frequencies, and should be equally spaced.

Test procedure

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.


Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data

There are 79 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

9.5. Dwell Time on Each Channel

Requirements

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test procedure

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.
- Measure the maximum time duration of one single pulse.

A Period Time = (channel number)*0.4

For normal mode:

DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)

DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)

DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)


For AFH mode:

DH1 Time Slot: Reading * (800/2)*31.6/(channel number)

DH3 Time Slot: Reading * (800/4)*31.6/(channel number)

DH5 Time Slot: Reading * (800/6)*31.6/(channel number)

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Test Data

Mode	Freq (MHz)	Chain	Length of transmission time (ms)	Dwell Time (ms)	Limit (ms)	Result
GFSK(DH1)	2441	Chain 0	0.380	121.600	400	PASS
GFSK(DH3)	2441	Chain 0	1.640	262.400	400	PASS
GFSK(DH5)	2441	Chain 0	2.870	306.133	400	PASS
8DPSK(3DH1)	2441	Chain 0	0.380	121.600	400	PASS
8DPSK(3DH3)	2441	Chain 0	1.640	262.400	400	PASS
8DPSK(3DH5)	2441	Chain 0	2.870	306.133	400	PASS

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



9.6. Conducted Out of Band Emission


Requirements

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b) (3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209 (a) is not required.

Test procedure


The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.


Test Setup





The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data









9.7. Radiated Spurious Emission

Requirements

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Test Procedures

[For 9 kHz ~ 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 30MHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

[For above 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

Configuration	Average	
	RBW	VBW
Bluetooth	1MHz	Refer to section 6.6 for duty cycle.

4. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
5. Test data of Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
6. Test data of Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
7. Test data of Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB).
8. Test data of Notation "@" = Fundamental Frequency
9. Test data of Notation " * " = The peak result under 20 dB above and complies with AVG limit, AVG result is deemed to comply with AVG limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Test Setup

<Frequency Range 9 kHz ~ 30 MHz>



<Frequency Range 30 MHz ~ 1 GHz >



Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the Setup Configurations.

Test Data

Above 1 GHz

Mode	GFSK	Channel	0
------	------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2340.4	30.47	11.23	41.7	54	-12.3	AVG
		2358.83	43	11.21	54.21	74	-19.79	PK
	@	2402	86.21	11.13	97.34	N/A	N/A	PK
	@	2402	85.96	11.13	97.09	N/A	N/A	AVG
Vertical		2320.64	42.25	11.23	53.48	74	-20.52	PK
		2340.02	30.79	11.22	42.01	54	-11.99	AVG
	@	2402	89.01	11.13	100.14	N/A	N/A	PK
	@	2402	88.78	11.13	99.91	N/A	N/A	AVG





Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

TX, GFSK (Ch 0)
Band Edge (Average), Horizontal

TX, GFSK (Ch 0)
Band Edge (Average), Vertical

TX, GFSK (Ch 0)
Band Edge (Peak), Horizontal

TX, GFSK (Ch 0)
Band Edge (Peak), Vertical


Mode	GFSK	Channel	39
------	------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2315.89	42.48	11.23	53.71	74	-20.29	PK
		2339.45	30.44	11.22	41.66	54	-12.34	AVG
	@	2441	83.16	10.96	94.12	N/A	N/A	PK
	@	2441	82.83	10.96	93.79	N/A	N/A	AVG
		2490.69	30.27	11.01	41.28	54	-12.72	AVG
		2492.78	41.79	11.02	52.81	74	-21.19	PK
Vertical		2339.45	42.65	11.22	53.87	74	-20.13	PK
		2339.83	30.77	11.22	41.99	54	-12.01	AVG
	@	2441	88.87	10.96	99.83	N/A	N/A	PK
	@	2441	88.45	10.96	99.41	N/A	N/A	AVG
		2490.69	30.3	11.01	41.31	54	-12.69	AVG
		2499.81	41.71	11.03	52.74	74	-21.26	PK





Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

TX, GFSK (Ch 39)
Band Edge (Average), Horizontal

TX, GFSK (Ch 39)
Band Edge (Average), Vertical

TX, GFSK (Ch 39)
Band Edge (Peak), Horizontal

TX, GFSK (Ch 39)
Band Edge (Peak), Vertical


Mode	GFSK	Channel	78
------	------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2480	84.59	10.99	95.58	N/A	N/A	PK
	@	2480	84.37	10.99	95.36	N/A	N/A	AVG
		2483.66	30.43	11	41.43	54	-12.57	AVG
		2495.63	41.21	11.02	52.23	74	-21.77	PK
Vertical	@	2480	89.65	10.99	100.64	N/A	N/A	PK
	@	2480	89.51	10.99	100.5	N/A	N/A	AVG
		2483.66	31.78	11	42.78	54	-11.22	AVG
		2488.41	42.23	11.01	53.24	74	-20.76	PK


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



Mode	GFSK - Emission	Channel	0
------	-----------------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		1750	60.07	-8.42	51.65	74	-22.35	PK
		3205	48.73	-1.84	46.89	74	-27.11	PK
	*	4804	37.95	5.06	43.01	74	-30.99	PK
		14500	27.83	28.9	56.73	74	-17.27	PK
		14500	19.56	28.9	48.46	54	-5.54	AVG
		15385	28.62	26.17	54.79	74	-19.21	PK
		15385	19.79	26.17	45.96	54	-8.04	AVG
	*	16814	34.24	5.41	39.65	74	-34.35	PK
	*	19216	33.08	3.58	36.66	74	-37.34	PK
	*	21618	32.68	6.16	38.84	74	-35.16	PK
	*	24020	32.41	10.74	43.15	74	-30.85	PK
Vertical		1750	59.16	-8.42	50.74	74	-23.26	PK
		3205	54.12	-1.84	52.28	74	-21.72	PK
	*	4804	39.93	5.06	44.99	74	-29.01	PK
		14500	27.74	28.9	56.64	74	-17.36	PK
		14500	19.47	28.9	48.37	54	-5.63	AVG
		15340	27.96	26.5	54.46	74	-19.54	PK
		15340	19.13	26.5	45.63	54	-8.37	AVG
	*	16814	33.67	5.41	39.08	74	-34.92	PK
	*	19216	33.63	3.58	37.21	74	-36.79	PK
	*	21618	32.83	6.16	38.99	74	-35.01	PK
	*	24020	32.75	10.74	43.49	74	-30.51	PK

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Horizontal




TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Vertical




TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Horizontal



TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Vertical



Mode	GFSK - Emission	Channel	39
------	-----------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		1750	58.83	-8.42	50.41	74	-23.59	PK
		3250	42.83	-1.91	40.92	74	-33.08	PK
	*	4882	35.06	5.55	40.61	74	-33.39	PK
		14500	27.98	28.9	56.88	74	-17.12	PK
		14500	19.71	28.9	48.61	54	-5.39	AVG
		15310	27.57	26.72	54.29	74	-19.71	PK
		15310	18.74	26.72	45.46	54	-8.54	AVG
	*	17087	34.55	5.41	39.96	74	-34.04	PK
	*	19528	34.51	3.99	38.5	74	-35.5	PK
	*	21969	32.42	6.25	38.67	74	-35.33	PK
	*	24410	32.55	11.97	44.52	74	-29.48	PK
Vertical		1750	59.21	-8.42	50.79	74	-23.21	PK
		3250	49.63	-1.91	47.72	74	-26.28	PK
	*	4882	36.21	5.55	41.76	74	-32.24	PK
		14500	27.55	28.9	56.45	74	-17.55	PK
		14500	19.28	28.9	48.18	54	-5.82	AVG
		15370	27.68	26.28	53.96	74	-20.04	PK
		15370	18.85	26.28	45.13	54	-8.87	AVG
	*	17087	33.85	5.41	39.26	74	-34.74	PK
	*	19528	33.75	3.99	37.74	74	-36.26	PK
	*	21969	33.17	6.25	39.42	74	-34.58	PK
	*	24410	32.25	11.97	44.22	74	-29.78	PK

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000


Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, GFSK - Emission (Ch 39)
Radiated Spurious Emission, Horizontal




TX, GFSK - Emission (Ch 39)
Radiated Spurious Emission, Vertical



TX, GFSK - Emission (Ch 39)
Radiated Spurious Emission, Horizontal



TX, GFSK - Emission (Ch 39)
Radiated Spurious Emission, Vertical



Mode	GFSK - Emission	Channel	78
------	-----------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		1750	58.72	-8.42	50.3	74	-23.7	PK
		3310	47.62	-2	45.62	74	-28.38	PK
	*	4960	34.65	5.88	40.53	74	-33.47	PK
		14500	28.02	28.9	56.92	74	-17.08	PK
		14500	19.75	28.9	48.65	54	-5.35	AVG
		15355	28.39	26.38	54.77	74	-19.23	PK
		15355	19.56	26.38	45.94	54	-8.06	AVG
	*	17360	33.6	4.89	38.49	74	-35.51	PK
	*	19840	33.41	4.06	37.47	74	-36.53	PK
	*	22320	33.45	6.93	40.38	74	-33.62	PK
	*	24800	32.2	12.44	44.64	74	-29.36	PK
Vertical		1750	58.68	-8.42	50.26	74	-23.74	PK
		3310	43.86	-2	41.86	74	-32.14	PK
	*	4960	34.21	5.88	40.09	74	-33.91	PK
		14470	27.85	28.86	56.71	74	-17.29	PK
		14470	19.58	28.86	48.44	54	-5.56	AVG
		15355	28.74	26.38	55.12	74	-18.88	PK
		15355	19.91	26.38	46.29	54	-7.71	AVG
	*	17360	33.95	4.89	38.84	74	-35.16	PK
	*	19840	33.47	4.06	37.53	74	-36.47	PK
	*	22320	32.93	6.93	39.86	74	-34.14	PK
	*	24800	31.76	12.44	44.2	74	-29.8	PK

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000


Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, GFSK - Emission (Ch 78)
Radiated Spurious Emission, Horizontal




TX, GFSK - Emission (Ch 78)
Radiated Spurious Emission, Vertical



TX, GFSK - Emission (Ch 78)
Radiated Spurious Emission, Horizontal



TX, GFSK - Emission (Ch 78)
Radiated Spurious Emission, Vertical



Mode	8DPSK	Channel	0
------	-------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2339.83	30.49	11.22	41.71	54	-12.29	AVG
		2375.74	43.04	11.18	54.22	74	-19.78	PK
	@	2402	85.5	11.13	96.63	N/A	N/A	PK
	@	2402	82.85	11.13	93.98	N/A	N/A	AVG
Vertical		2340.21	30.7	11.23	41.93	54	-12.07	AVG
		2365.86	42.11	11.21	53.32	74	-20.68	PK
	@	2402	88.9	11.13	100.03	N/A	N/A	PK
	@	2402	85.51	11.13	96.64	N/A	N/A	AVG

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, 8DPSK (Ch 0)

Band Edge (Average), Horizontal




TX, 8DPSK (Ch 0)

Band Edge (Average), Vertical




TX, 8DPSK (Ch 0)

Band Edge (Peak), Horizontal



TX, 8DPSK (Ch 0)

Band Edge (Peak), Vertical



Mode	8DPSK	Channel	39
------	-------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2313.42	42.67	11.22	53.89	74	-20.11	PK
		2330.33	30.49	11.23	41.72	54	-12.28	AVG
	@	2441	82.16	10.96	93.12	N/A	N/A	PK
	@	2441	79.26	10.96	90.22	N/A	N/A	AVG
		2485.18	30.25	11	41.25	54	-12.75	AVG
		2490.69	41.14	11.01	52.15	74	-21.85	PK
Vertical		2331.85	42.32	11.23	53.55	74	-20.45	PK
		2340.02	30.7	11.22	41.92	54	-12.08	AVG
	@	2441	88.32	10.96	99.28	N/A	N/A	PK
	@	2441	85.75	10.96	96.71	N/A	N/A	AVG
		2487.27	42.23	11.01	53.24	74	-20.76	PK
		2494.87	30.21	11.02	41.23	54	-12.77	AVG

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, 8DPSK (Ch 39)

Band Edge (Average), Horizontal




TX, 8DPSK (Ch 39)

Band Edge (Average), Vertical




TX, 8DPSK (Ch 39)

Band Edge (Peak), Horizontal



TX, 8DPSK (Ch 39)

Band Edge (Peak), Vertical



Mode	8DPSK	Channel	78
------	-------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2480	84.68	10.99	95.67	N/A	N/A	PK
	@	2480	81.55	10.99	92.54	N/A	N/A	AVG
		2483.66	31.26	11	42.26	54	-11.74	AVG
		2497.91	41.75	11.03	52.78	74	-21.22	PK
Vertical	@	2480	89.45	10.99	100.44	N/A	N/A	PK
	@	2480	87.09	10.99	98.08	N/A	N/A	AVG
		2483.66	33.89	11	44.89	54	-9.11	AVG
		2484.04	42.17	11	53.17	74	-20.83	PK


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



Mode	8DPSK - Emission	Channel	0
------	------------------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		1748	59.38	-8.44	50.94	74	-23.06	PK
		3210	47.3	-1.85	45.45	74	-28.55	PK
	*	4804	35.72	5.06	40.78	74	-33.22	PK
		14481	27.23	28.87	56.1	74	-17.9	PK
		14481	18.96	28.87	47.83	54	-6.17	AVG
		15314	28.59	26.69	55.28	74	-18.72	PK
		15314	19.76	26.69	46.45	54	-7.55	AVG
	*	16814	34.27	5.41	39.68	74	-34.32	PK
	*	19216	33.34	3.58	36.92	74	-37.08	PK
	*	21618	33.13	6.16	39.29	74	-34.71	PK
	*	24020	32.98	10.74	43.72	74	-30.28	PK
Vertical		1748	58.93	-8.44	50.49	74	-23.51	PK
		3210	53.98	-1.85	52.13	74	-21.87	PK
	*	4804	37.72	5.06	42.78	74	-31.22	PK
		14464	28.31	28.85	57.16	74	-16.84	PK
		14464	20.04	28.85	48.89	54	-5.11	AVG
		15399	28.67	26.07	54.74	74	-19.26	PK
		15399	19.83	26.07	45.9	54	-8.1	AVG
	*	16814	33.31	5.41	38.72	74	-35.28	PK
	*	19216	33.18	3.58	36.76	74	-37.24	PK
	*	21618	33.03	6.16	39.19	74	-34.81	PK
	*	24020	33.16	10.74	43.9	74	-30.1	PK

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000


Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, 8DPSK - Emission (Ch 0)
Radiated Spurious Emission, Horizontal




TX, 8DPSK - Emission (Ch 0)
Radiated Spurious Emission, Vertical



TX, 8DPSK - Emission (Ch 0)
Radiated Spurious Emission, Horizontal



TX, 8DPSK - Emission (Ch 0)
Radiated Spurious Emission, Vertical



Mode	8DPSK - Emission	Channel	39
------	------------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		1750	59.41	-8.42	50.99	74	-23.01	PK
	*	4882	35	5.55	40.55	74	-33.45	PK
		14500	27.87	28.9	56.77	74	-17.23	PK
		14500	19.6	28.9	48.5	54	-5.5	AVG
		15310	28.05	26.72	54.77	74	-19.23	PK
		15310	19.22	26.72	45.94	54	-8.06	AVG
	*	17087	33.38	5.41	38.79	74	-35.21	PK
	*	19528	33.1	3.99	37.09	74	-36.91	PK
	*	21969	32.34	6.25	38.59	74	-35.41	PK
	*	24410	32.72	11.97	44.69	74	-29.31	PK
		1750	58.15	-8.42	49.73	74	-24.27	PK
Vertical	*	4882	35.38	5.55	40.93	74	-33.07	PK
		14470	27.97	28.86	56.83	74	-17.17	PK
		14470	19.7	28.86	48.56	54	-5.44	AVG
		15385	28.55	26.17	54.72	74	-19.28	PK
		15385	19.72	26.17	45.89	54	-8.11	AVG
	*	17087	34.71	5.41	40.12	74	-33.88	PK
	*	19528	32.91	3.99	36.9	74	-37.1	PK
	*	21969	31.97	6.25	38.22	74	-35.78	PK
	*	24410	32.65	11.97	44.62	74	-29.38	PK

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


TX, 8DPSK - Emission (Ch 39)

Radiated Spurious Emission, Horizontal




TX, 8DPSK - Emission (Ch 39)

Radiated Spurious Emission, Vertical




TX, 8DPSK - Emission (Ch 39)

Radiated Spurious Emission, Horizontal



TX, 8DPSK - Emission (Ch 39)

Radiated Spurious Emission, Vertical



Mode	8DPSK - Emission	Channel	78
------	------------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		1750	58.94	-8.42	50.52	74	-23.48	PK
		3310	48.47	-2	46.47	74	-27.53	PK
	*	4960	34.92	5.88	40.8	74	-33.2	PK
		14485	28.61	28.88	57.49	74	-16.51	PK
		14485	20.34	28.88	49.22	54	-4.78	AVG
		15385	28.09	26.17	54.26	74	-19.74	PK
		15385	19.26	26.17	45.43	54	-8.57	AVG
	*	17360	33.55	4.89	38.44	74	-35.56	PK
	*	19840	34.02	4.06	38.08	74	-35.92	PK
	*	22320	32.46	6.93	39.39	74	-34.61	PK
	*	24800	32	12.44	44.44	74	-29.56	PK
Vertical		1750	59.19	-8.42	50.77	74	-23.23	PK
		3310	50.84	-2	48.84	74	-25.16	PK
	*	4960	34.28	5.88	40.16	74	-33.84	PK
		14470	28.32	28.86	57.18	74	-16.82	PK
		14470	20.05	28.86	48.91	54	-5.09	AVG
		15310	28.34	26.72	55.06	74	-18.94	PK
		15310	19.51	26.72	46.23	54	-7.77	AVG
	*	17360	33.35	4.89	38.24	74	-35.76	PK
	*	19840	34.13	4.06	38.19	74	-35.81	PK
	*	22320	32.87	6.93	39.8	74	-34.2	PK
	*	24800	32.56	12.44	45	74	-29	PK





Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

TX, 8DPSK - Emission (Ch 78)
Radiated Spurious Emission, Horizontal

TX, 8DPSK - Emission (Ch 78)
Radiated Spurious Emission, Vertical

TX, 8DPSK - Emission (Ch 78)
Radiated Spurious Emission, Horizontal

TX, 8DPSK - Emission (Ch 78)
Radiated Spurious Emission, Vertical


Below 1 GHz

Mode	8DPSK	Channel	78
------	-------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		148.34	40.77	-11.5	29.27	43.5	-14.23	PK
		238.55	44.27	-12.57	31.7	46	-14.3	PK
		320.03	38.91	-9.49	29.42	46	-16.58	PK
		389.87	42.09	-7.55	34.54	46	-11.46	PK
		493.66	44.49	-4.94	39.55	46	-6.45	PK
		766.23	35.4	1.18	36.58	46	-9.42	PK
Vertical		54.25	40.33	-11.91	28.42	40	-11.58	PK
		95.96	42.71	-17	25.71	43.5	-17.79	PK
		159.98	39.1	-11.38	27.72	43.5	-15.78	PK
		494.63	39.66	-4.91	34.75	46	-11.25	PK
		584.84	38.21	-2.63	35.58	46	-10.42	PK
		765.26	33.68	1.19	34.87	46	-11.13	PK


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



9 kHz ~ 30 MHz Data:

For 9 kHz to 30 MHz radiated emission have performed all modes of operation were investigated. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

No non-compliance noted:

KDB 414788 D01 OATS and Chamber Correlation Justification

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

- OATs and chamber correlation testing had been performed and chamber measured test results is the worst case test result.

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

9.8. AC Power Line Conducted Emission

Requirements

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.
2. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
3. Test data of Result value (dB μ V) = Reading value (dB μ V) + Correction Factor (dB).
4. Test data of Margin(dB) = Result value (dB μ V) - Limit value (dB μ V).
5. Test data of Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Test Setup




Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the Setup Configurations.

Test Data

Mode	3DH5_TX2480	Channel	78
------	-------------	---------	----



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1904	56.32	0.08	56.40	64.02	-7.62	QP
2	0.1904	35.91	0.08	35.99	54.02	-18.03	AVG
3	0.1971	56.12	0.08	56.20	63.73	-7.53	QP
4	0.1971	38.64	0.08	38.72	53.73	-15.01	AVG
5	0.2983	48.34	0.09	48.43	60.29	-11.86	QP
6	0.2983	28.67	0.09	28.76	50.29	-21.53	AVG
7	0.3064	47.76	0.10	47.86	60.07	-12.21	QP
8	0.3064	25.11	0.10	25.21	50.07	-24.86	AVG
9	0.3810	42.59	0.10	42.69	58.26	-15.57	QP
10	0.3810	20.80	0.10	20.90	48.26	-27.36	AVG
11	0.6663	39.17	0.13	39.30	56.00	-16.70	QP
12	0.6663	21.23	0.13	21.36	46.00	-24.64	AVG

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	3DH5_TX2480	Channel	78
------	-------------	---------	----



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1899	41.18	9.93	51.11	64.04	-12.93	QP
2	0.1899	22.38	9.93	32.31	54.04	-21.73	AVG
3	0.2850	35.01	9.94	44.95	60.67	-15.72	QP
4	0.2850	17.28	9.94	27.22	50.67	-23.45	AVG
5	0.6134	30.02	9.94	39.96	56.00	-16.04	QP
6	0.6134	12.00	9.94	21.94	46.00	-24.06	AVG
7	0.6663	32.30	9.95	42.25	56.00	-13.75	QP
8	0.6663	15.86	9.95	25.81	46.00	-20.19	AVG
9	0.6875	31.21	9.95	41.16	56.00	-14.84	QP
10	0.6875	15.81	9.95	25.76	46.00	-20.24	AVG
11	0.7675	25.08	9.96	35.04	56.00	-20.96	QP
12	0.7675	8.34	9.96	18.30	46.00	-27.70	AVG

END OF REPORT

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1