

FCC TEST REPORT

FCC ID: 2BNOR-DLH-8802

Report No. : SSP26060572-1

Applicant : SHENZHEN ORICO TECHNOLOGIES CO., LTD.

Product Name : Magnetic Wireless Power Bank

Model Name : DLH-8802

Test Standard : FCC Part 15 Subpart C

Date of Issue : 2026-07-30

Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.zrlklab.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	SHENZHEN ORICO TECHNOLOGIES CO., LTD. 1903-1904,14A, Zhonghaixin Innovation Industrial Park, no.12, GanLee Sixth Address of Applicant.....: Road, Gankeng Community, Jihua Street, Shenzhen, China	
Manufacturer:	SHENZHEN DELE POWER ELECTRONIC CO., LTD Room 302, 3rd floor, Block A No.438, Dong Huan Road, Xinqiao street, Sha Address of Manufacturer.....: Jing Town, Bao'an District, ShenZhen, Guangdong province, china	
Product Name:	Magnetic Wireless Power Bank	
Brand Name:	-	
Main Model:	DLH-8802	
Series Models:	-	
Test Standard:	FCC Part 15 Subpart C ANSI C63.4-2014 ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	
Date of Test	2026-06-30 to 2026-07-10	
Test Result:	PASS	
Tested By	<u>Colin Chen</u> (Colin Chen)	
Reviewed By:	<u>Lorzix Luo</u> (Lorzix Luo)	
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)	
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.		

CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty.....	8
2. Summary of Test Results.....	9
3. Antenna Requirement.....	10
3.1 Standard and Limit.....	10
3.2 Test Result.....	10
4. Conducted Emissions	11
4.1 Standard and Limit.....	11
4.2 Test Procedure.....	11
4.3 Test Data and Results	12
5. Radiated Emissions	17
5.1 Standard and Limit.....	17
5.2 Test Procedure.....	17
5.3 Test Data and Results	19
6. Occupied Bandwidth	32
6.1 Standard and Limit.....	32
6.2 Test Procedure.....	32
6.3 Test Data and Results	32

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2026-07-30	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Magnetic Wireless Power Bank
Trade Name:	-
Test Model:	DLH-8802
Series Models:	-
Rated Voltage:	Type-C Input: 5V=2.4A, 9V=2.22A, 12V=1.67A (20W Max) Type-C Output: 5V=2.4A, 9V=2.22A, 10=2.22A, 12V=1.67A (22.5W Max) Wireless Output: 15W/10W/7.5W/5W/2.5W
Battery:	17.2Wh (5000mAh, 3.44V)
Test Sample No:	SSP26060572-1
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	

Wireless Specification	
Wireless Standard:	WPC (QI)
Operating Frequency:	15W / 10W / 7.5W / 5W: 110.5-205kHz, 2.5W: 310-340kHz
Modulation:	FSK
Antenna Gain:	0dBi
Type of Antenna:	Coil Antenna
Type of Device:	☒ Portable Device ☐ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description		Remark
TM1	Wireless charging 2.5W		310-340kHz
TM2	Wireless charging 5W		110.5-205kHz
TM3	Wireless charging 7.5W		110.5-205kHz
TM4	Wireless charging 10W		110.5-205kHz
TM5	Wireless charging 15W		110.5-205kHz
TM6	Wireless charging 5W+Charging		110.5-205kHz
TM7	Wireless charging 2.5W+Charging		310-340kHz
Note: All modes of the main model and accessory models mentioned above have been tested. The report only shows the worst modes of the main model: TM5 and TM6 and TM7 data.			
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
USB Cable	100	Unshielded	Without Ferrite
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Dummy load(15W)	YBZ	YBZ-001	N/A
Dummy load(2.5W)	YBZ	YBZ-002	N/A
Adapter	CUKTECH Technology Co., Ltd	AD1003	-

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6983.01
FCC Registration No.:	583813
FCC Designation No.:	CN1373
ISED Registration No.:	CN0164

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2025-07-15	2026-07-14
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2025-07-15	2026-07-14
Test Cable	N/A	Cable 5	N/A	2025-07-15	2026-07-14
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2025-07-15	2026-07-14
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2025-07-15	2026-07-14
Amplifier	SCHWARZBECK	BBV 9743B	00251	2025-07-15	2026-07-14
Amplifier	HUABO	YXL0518-2.5-45	--	2025-07-15	2026-07-14
Loop Antenna	DAZE	ZN30900C	21104	2025-07-12	2026-07-11
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2025-07-12	2026-07-11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2025-07-12	2026-07-11
Attenuator	QUANJUDA	6dB	220731	2025-07-15	2026-07-14
Test Cable	N/A	Cable 1	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 2	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 3	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 4	N/A	2025-07-15	2026-07-14
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2025-07-16	2026-07-15
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2025-07-16	2026-07-15

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209	Radiated Emissions	Passed
FCC Part 15.215(c)	Occupied Bandwidth	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an Coil antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.


4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part standard limit for a wireless device, and with the worst case TM6 and TM7 as below:


Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions


Tested Mode:	TM6
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	Wireless charging 5W + Charging




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2580	31.71	9.32	41.03	61.50	-20.47	QP	P	
2 *	0.2580	28.04	9.32	37.36	51.50	-14.14	AVG	P	
3	1.2839	26.94	9.44	36.38	56.00	-19.62	QP	P	
4	1.2839	14.62	9.44	24.06	46.00	-21.94	AVG	P	
5	2.1030	23.41	9.47	32.88	56.00	-23.12	QP	P	
6	2.1030	15.63	9.47	25.10	46.00	-20.90	AVG	P	
7	0.5280	25.05	9.39	34.44	56.00	-21.56	QP	P	
8	0.5280	10.52	9.39	19.91	46.00	-26.09	AVG	P	
9	7.2465	20.14	9.57	29.71	60.00	-30.29	QP	P	
10	7.2465	10.36	9.57	19.93	50.00	-30.07	AVG	P	
11	29.6520	19.38	10.10	29.48	60.00	-30.52	QP	P	
12	29.6520	12.36	10.10	22.46	50.00	-27.54	AVG	P	



Test Plots and Data of Conducted Emissions	
Tested Mode:	TM7
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	Wireless charging 2.5W + Charging



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2625	34.14	9.90	44.04	61.35	-17.31	QP	P	
2 *	0.2625	30.83	9.90	40.73	51.35	-10.62	AVG	P	
3	0.3930	29.71	9.95	39.66	58.00	-18.34	QP	P	
4	0.3930	25.08	9.95	35.03	48.00	-12.97	AVG	P	
5	0.7890	28.68	9.98	38.66	56.00	-17.34	QP	P	
6	0.7890	23.70	9.98	33.68	46.00	-12.32	AVG	P	
7	2.9130	23.70	10.05	33.75	56.00	-22.25	QP	P	
8	2.9130	19.50	10.05	29.55	46.00	-16.45	AVG	P	
9	7.3725	21.36	10.07	31.43	60.00	-28.57	QP	P	
10	7.3725	12.81	10.07	22.88	50.00	-27.12	AVG	P	
11	26.6145	17.43	10.27	27.70	60.00	-32.30	QP	P	
12	26.6145	10.42	10.27	20.69	50.00	-29.31	AVG	P	



5. Radiated Emissions

5.1 Standard and Limit


According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of Emission (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3
Note: The more stringent limit applies at transition frequencies.		


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz


- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

Based on all mode tested data, the EUT complied with the FCC Part 15.209 standard limit for a wireless device, and with the worst case TM5 and TM6 and TM7 as below:


Test Data of Radiated Emissions from 9kHz to 30MHz

Test Mode:	TM5	Phase:	Coplaner
Test Voltage:	DC 3.44V		
Remark:	Wireless charging 15W		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0108	19.17	35.87	55.04	126.92	-71.88	QP	100	0	P	
2	0.0225	15.70	34.66	50.36	120.55	-70.19	QP	100	0	P	
3	0.0388	11.87	31.36	43.23	115.82	-72.59	QP	100	0	P	
4	0.1274	38.16	25.39	63.55	105.49	-41.94	QP	100	0	P	
5	0.2908	22.82	25.81	48.63	98.33	-49.70	QP	100	0	P	
6 *	1.0485	21.49	25.93	47.42	67.19	-19.77	QP	100	0	P	


Test Mode:	TM5	Phase:	Coaxial
Test Voltage:	DC 3.44V		
Remark:	Wireless charging 15W		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0100	22.35	35.95	58.30	127.59	-69.29	QP	100	360	P	
2	0.0240	14.66	34.50	49.16	119.99	-70.83	QP	100	360	P	
3	0.1274	37.66	25.39	63.05	105.49	-42.44	QP	100	360	P	
4	0.1573	25.65	25.76	51.41	103.66	-52.25	QP	100	360	P	
5	0.4686	21.18	25.67	46.85	94.19	-47.34	QP	100	360	P	
6 *	1.0210	21.78	25.92	47.70	67.42	-19.72	QP	100	360	P	




Test Mode:	TM6	Phase:	Coaxial
Test Voltage:	AC 120V/60Hz		
Remark:	Wireless charging 5W + Charging		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0352	15.66	30.02	45.68	116.66	-70.98	QP	100	360	P	
2	0.1141	33.76	23.21	56.97	106.45	-49.48	QP	100	360	P	
3	0.3428	23.18	23.32	46.50	96.90	-50.40	QP	100	360	P	
4 *	1.2554	22.12	23.38	45.50	65.62	-20.12	QP	100	360	P	
5	2.4090	15.35	23.39	38.74	69.50	-30.76	QP	100	360	P	
6	9.9656	10.60	23.41	34.01	69.50	-35.49	QP	100	360	P	



Test Mode:	TM7	Phase:	Coaxial
Test Voltage:	AC 120V/60Hz		
Remark:	Wireless charging 2.5W + Charging		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0158	19.46	32.98	52.44	123.61	-71.17	QP	100	360	P	
2	0.0470	16.59	26.66	43.25	114.15	-70.90	QP	100	360	P	
3	0.0948	16.26	23.43	39.69	108.06	-68.37	QP	100	360	P	
4	0.3251	45.47	23.34	68.81	97.36	-28.55	QP	100	360	P	
5 *	0.9735	24.22	23.36	47.58	67.83	-20.25	QP	100	360	P	
6	5.6531	11.96	23.52	35.48	69.50	-34.02	QP	100	360	P	

Note:

Pre-scan in the all of mode, the worst case in of was recorded.


Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

Margin = Reading - Limit.

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM5
Test Antenna Polarization:	Horizontal
Remark:	Wireless charging 15W



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	50.2324	25.69	-8.44	17.25	40.00	-22.75	QP	100	343	P	
2	84.7019	26.84	-12.96	13.88	40.00	-26.12	QP	100	289	P	
3	151.5972	26.14	-7.75	18.39	43.50	-25.11	QP	100	356	P	
4	289.0021	28.44	-8.62	19.82	46.00	-26.18	QP	100	68	P	
5	497.6765	26.91	-3.31	23.60	46.00	-22.40	QP	100	343	P	
6 *	785.0935	27.49	1.33	28.82	46.00	-17.18	QP	100	219	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM5
Test Antenna Polarization:	Vertical
Remark:	Wireless charging 15W



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	36.7662	27.90	-8.82	19.08	40.00	-20.92	QP	100	10	P	
2	143.8295	31.36	-8.03	23.33	43.50	-20.17	QP	100	86	P	
3	242.5253	30.95	-10.33	20.62	46.00	-25.38	QP	100	156	P	
4	489.0269	26.95	-3.54	23.41	46.00	-22.59	QP	100	0	P	
5	649.6597	26.32	-0.85	25.47	46.00	-20.53	QP	100	349	P	
6 *	881.4067	28.33	2.23	30.56	46.00	-15.44	QP	100	349	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM6
Test Antenna Polarization:	Horizontal
Remark:	Wireless charging 5W + Charging



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	73.3593	31.73	-12.10	19.63	40.00	-20.37	QP	100	183	P	
2 *	143.8295	35.64	-8.03	27.61	43.50	-15.89	QP	100	18	P	
3	185.1379	35.39	-10.88	24.51	43.50	-18.99	QP	100	266	P	
4	250.3012	32.85	-9.99	22.86	46.00	-23.14	QP	100	280	P	
5	287.9904	35.37	-8.67	26.70	46.00	-19.30	QP	100	307	P	
6	457.5073	31.58	-4.34	27.24	46.00	-18.76	QP	100	101	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM6
Test Antenna Polarization:	Vertical
Remark:	Wireless charging 5W + Charging




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	39.2991	35.08	-8.42	26.66	40.00	-13.34	QP	100	84	P	
2	72.0843	43.11	-11.94	31.17	40.00	-8.83	QP	100	12	P	
3 *	143.8295	43.92	-8.03	35.89	43.50	-7.61	QP	100	356	P	
4	186.4409	38.24	-10.96	27.28	43.50	-16.22	QP	100	358	P	
5	287.9904	38.71	-8.67	30.04	46.00	-15.96	QP	100	12	P	
6	601.4265	29.63	-1.59	28.04	46.00	-17.96	QP	100	12	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz

Tested Mode:	TM7
Test Antenna Polarization:	Horizontal
Remark:	Wireless charging 2.5W + Charging



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	40.5591	26.25	-8.30	17.95	40.00	-22.05	QP	100	113	P	
2	57.7962	27.29	-9.62	17.67	40.00	-22.33	QP	100	279	P	
3	143.8295	25.37	-8.03	17.34	43.50	-26.16	QP	100	210	P	
4	299.3158	26.14	-8.08	18.06	46.00	-27.94	QP	100	251	P	
5	434.0651	27.44	-4.85	22.59	46.00	-23.41	QP	100	334	P	
6 *	782.3453	27.25	1.30	28.55	46.00	-17.45	QP	100	348	P	



Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: For 9kHz-30MHz, Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})(\text{dB})$;

Limit line = specific limits (dBuV) + distance extrapolation factor.

Note 4: Level = Reading + Factor, Margin = Level – Limit.

6. Occupied Bandwidth

6.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
 - 2) Set the spectrum analyzer to any one measured frequency within its operating range.
 - 3) Set RBW = 1% ~5% of the 20 dB bandwidth, VBW = RBW.
 - 4) Set Sweep = Auto, Detector function = peak, Trace = max hold.
 - 5) Set a reference level on the measuring instrument equal to the highest peak value.
 - 6) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level.
- Record the frequency difference as the emission bandwidth.

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.




Test Setup Block Diagram

6.3 Test Data and Results


Test Frequency	20dB Bandwidth	99% Bandwidth
128.3kHz	235Hz	205Hz

Test Plots of Occupied Bandwidth



Test Frequency	20dB Bandwidth	99% Bandwidth
325.5kHz	523Hz	478Hz

Test Plots of Occupied Bandwidth



***** END OF REPORT *****