PULLCORD

Third Coast Company IYY00059 single-input universal device is compatible with nearly all standard contacts and sensors.

Product Features

- Compact, lightweight, and waterproof design
- Bright LEDs indicate alarm activation, clearance, and low battery
- Vibration feedback confirms alarm activation
- Alarm clearance via magnetic card or button pattern
- Adjustable lanyard with safety breakaway
- Replaceable silicone wristband with adjustable buckle

Product Specifications

Weight:	17 g
Size:	41x45x45mm
Battery Type:	User-replaceable CR123A lithium battery
Frequency:	902-928 MHz, LORA (Chirp Spread Spectrum (CSS))
Battery Life:	3-5 years
Operating Temperature:	32°F to 140°F (5°C to 50°C)
Operating Environment:	Up to 90% Humidity (non-condensing)
Market:	North America, Australia, New Zealand

Dimensions

1. Overview

The Third Coast single input universal device is specifically designed to work seamlessly with any standard contact that operates in either a normally open or normally closed configuration. This device ensures reliable operation by providing full supervision, which continuously monitors its status and performance. Additionally, it comes equipped with advanced features such as a case tamper mechanism to detect unauthorized access and a long-lasting battery to support uninterrupted functionality. These features make it a versatile and dependable solution for various applications requiring secure and consistent performance.

2. Installation and Startup
    a. Installation Notes
        - These devices are intended to be serviced by qualified technicians only.
        - The products are designed exclusively for indoor applications.
        - Manually test all products weekly
3. Operate the Transmitter
    - Trigger an Alarm
      The N/O-N/C selection slide switch allow you to configure the contact circuit wired to the input terminal as either normally open or normally closed.
      The device triggers an alarm when any of the a, b, or c buttons are pressed.
    - Reset an Alarm
      An authorized person should come and disable the alarm using an NFC-enabled phone.

      FCC statements:
    - This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
    - NOTE: The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications or changes to this equipment. Such modifications or changes could void the user's authority to operate the equipment.
    -
    - NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not

occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- - Reorient or relocate the receiving antenna.
- - Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -Consult the dealer or an experienced radio/TV technician for help.

- The device has been evaluated to meet general RF exposure requirement, The device can be used in portable exposure condition without restriction. Federal Communication Commission (FCC) Radiation Exposure Statement Power is so low that no RF exposure calculation is needed.