

Promosmart Marketing SPA

TEST REPORT

SCOPE OF WORK

EMC TESTING—DZ-017

REPORT NUMBER

250113074GZU-002

ISSUE DATE

21-March-2025

[REVISED DATE]

[-----]

PAGES

68

DOCUMENT CONTROL NUMBER

FCC BT 3.0

© 2017 INTERTEK



TEST REPORT

Applicant Name & : Promosmart Marketing SPA
Address Avenida Las Condes 11700, Torre A, Oficina 404-A. Vitacura,
Santiago, Chile
Manufacturing Site : Guangzhou L-TEK Enterprise Co., Ltd
#3 Quan Shui Street Jie Fang Zhuang Yong Ping Road, Bai Yun Area
GuangZhou, China
Intertek Report No: 250113074GZU-002
FCC ID: 2BNTP-DZ-017


Test standards

47 CFR PART 15 Subpart C: 2023 section 15.247

Sample Description

Product : Super Bass Speaker
Model No. : DZ-017
Electrical Rating : Adapter input: 5V, 3W
Serial No. : Not Labeled
Date Received : 13 January 2025
Date Test : 12 February 2025-24 February 2025
Conducted

Prepared and Checked By



Ace Yao

Engineer

Approved By:



Dean Liu

Sr. Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

CONTENT

TEST REPORT	1
CONTENT	3
1.0 TEST RESULT SUMMARY	4
2.0 GENERAL DESCRIPTION.....	5
2.1 PRODUCT DESCRIPTION	5
2.2 RELATED SUBMITTAL(S) GRANTS	6
2.3 TEST METHODOLOGY	6
2.4 TEST FACILITY.....	7
3.0 SYSTEM TEST CONFIGURATION.....	7
3.1 JUSTIFICATION	7
3.2 EUT EXERCISING SOFTWARE.....	8
3.3 SPECIAL ACCESSORIES.....	8
3.4 MEASUREMENT UNCERTAINTY.....	8
3.5 EQUIPMENT MODIFICATION	9
3.6 SUPPORT EQUIPMENT LIST AND DESCRIPTION	9
4.0 MEASUREMENT RESULTS.....	11
4.1 ANTENNA REQUIREMENT	11
4.2 20 DB BANDWIDTH	12
4.3 CARRIER FREQUENCIES SEPARATED.....	18
4.4 HOPPING CHANNEL NUMBER	21
4.5 DWELL TIME	25
4.6 PSEUDO RANDOM FREQUENCY HOPPING SEQUENCE	29
4.6.1 <i>Standard requirement</i>	29
4.6.2 <i>EUT Pseudo random Frequency Hopping Sequence</i>	29
4.7 MAXIMUM PEAK CONDUCTED OUTPUT POWER	30
4.8 OUT OF BAND CONDUCTED EMISSIONS	36
4.9 RADIATED EMISSIONS	39
4.10 BAND EDGES REQUIREMENT	57
4.11 CONDUCTED EMISSION TEST.....	65
5.0 TEST EQUIPMENT LIST	68

TEST REPORT

1.0 TEST RESULT SUMMARY

Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC PART 15 C Clause 15.247 (c) and Clause 15.203	FCC PART 15 C Clause 15.247 (c) and Clause 15.203	PASS
20 dB Bandwidth	FCC PART 15 C Clause 15.247 (a)(1)	ANSI C63.10: Clause 7.8.7 & 6.9.2	PASS
Carrier Frequencies Separated	FCC PART 15 C Clause 15.247(a)(1)	ANSI C63.10: Clause 7.8.2	PASS
Hopping Channel Number	FCC PART 15 C Clause 15.247(a)(1)(iii)	ANSI C63.10: Clause 7.8.3	PASS
Dwell Time	FCC PART 15 C Clause 15.247(a)(1)(iii)	ANSI C63.10: Clause 7.8.4	PASS
Pseudorandom Frequency Hopping Sequence	FCC PART 15 C Clause 15.247(a)(1)	FCC PART 15 C Clause 15.247(a)(1)	PASS
Maximum Peak Conducted Output Power	FCC PART 15 C Clause 15.247(b)(1)	ANSI C63.10: Clause 7.8.5	PASS
Out of Band Conducted Emissions	FCC PART 15 C Clause 15.247(d)	ANSI C63.10: Clause 7.8.8	PASS
Radiated Emissions in Restricted Bands	FCC PART 15 C Clause 15.209 & 15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C Clause 15.247 (d) & 15.205	ANSI C63.10: Clause 7.8.6 & 6.10	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C Clause 15.207	ANSI C63.10: Clause 6.2	PASS

Remark:

N/A: not applicable. Refer to the relative section for the details.

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report.

TEST REPORT

2.0 General Description

2.1 Product Description

Operating Frequency:	2402 MHz – 2480MHz
Type of Modulation:	GFSK, ($\pi/4$)-DQPSK, 8-DPSK
Number of Channels:	79 Channels
Channel Separation:	1 MHz
Dwell Time:	Per channel is less than 0.4s
Antenna Type:	Integral
Antenna Gain:	3.97 dBi
Function:	Super Bass Speaker with BT function to transmit and receive audio signal
Power Supply:	Adapter input: 5V, 3W

Remark: The device meets the requirements stated within Parts 15.247(g) & (h) in that they were developed under the Bluetooth protocol and operate as a true frequency hopping system. The device does not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

EUT modulation and data packet during test:

For BDR mode:

The EUT has been tested on the Modulation of GFSK with DH1, DH3 and DH5 data packet.

For EDR mode:

1. The EUT has been tested on the Modulation of ($\pi/4$)-DQPSK with 2DH1, 2DH3 and 2DH5 data packet.
2. The EUT has been tested on the Modulation of 8-DPSK with 3DH1, 3DH3 and 3DH5 data packet.

TEST REPORT

EUT channels and frequencies list:

Test frequencies are lowest channel 0: 2402 MHz, middle channel 39: 2441 MHz and highest channel 78: 2480 MHz.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	/	/
26	2428	53	2455	/	/

2.2 Related Submittal(s) Grants

This is an application for certification of Super Bass Speaker which has BT function.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10:2013. Radiated emission measurement was

TEST REPORT

performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans and final tests were performed in the semi-anechoic chamber to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise.

2.4 Test Facility

All tests were performed at:

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China

Except Conducted Emissions was performed at:

Room101/301/401/102/202/302/402/502/602/702/802, No. 7-2, Caipin Road, Huangpu District, Guangzhou, Guangdong, China

A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, AC power line was manipulated to produce worst case emissions. It was powered by AC 120V/60Hz supply.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. The spurious emissions more than 20 dB below the permissible value are not reported.

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Frequency range of radiated emission measurements

Lowest frequency generated in the	Upper frequency range of measurement
-----------------------------------	--------------------------------------

TEST REPORT

device	
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

3.2 EUT Exercising Software

Description	Manufacturer	Model No.	SN/Version	Supplied by
For fixing frequency	--	BT_Tool	V1.1.2	Client

3.3 Special Accessories

No special accessories used

3.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	20 dB Bandwidth	2.3%
	6dB Bandwidth	
	99% Bandwidth	
2	Carrier Frequencies Separated	2.3%
3	Dwell Time	1.2%
4	Maximum Peak Conducted Output Power	1.5dB
5	Peak Power Spectral Density	1.5dB
6	Out of Band Conducted Emissions	1.5dB
7	Band edges measurement	1.5dB

TEST REPORT

8	Radiated Emissions	3.6 dB (9 kHz-30 MHz)
		4.7 dB (30 MHz-1 GHz)
		4.8 dB (1 GHz-18 GHz)
		5.2 dB (18GHz-26GHz)
9	Conducted Emissions at Mains Terminals	2.58dB
10	Temperature	0.5 °C
11	Humidity	0.4 %
12	Time	1.2%

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT.

Measurement uncertainty is calculated in accordance with ETSI TR 100 028-2001.

The measurement uncertainty is given with a confidence of 95%, k=2.

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value

3.5 Equipment Modification

Any modifications installed previous to testing by Promosmart Marketing SPA will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

3.6 Support Equipment List and Description

This product was tested with corresponding support equipment as below:

Support Equipment

Cable

Description	Model No.	Connector type	Cable length/type	Supplied by
Antenna cable	RF-01	SMA	0.2 m(shielded)	Intertek

TEST REPORT

Support equipment

Description	Model No.	Rating	Supplied by
NoteBook	Latitude 5420	100-240VAC,50/60Hz	Intertek
Adapter	CH-P002	100-240~, 50/60Hz, 0.2A	Intertek

Remark:

After the frequency was fixed, Notebook and Fix board were removed out of the Chamber before test.

TEST REPORT

4.0 Measurement Results

4.1 Antenna Requirement

Standard requirement:

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna


The antenna is an integral antenna and no consideration of replacement. The best case gain of the antenna is 3.97 dBi

TEST REPORT

4.2 20 dB Bandwidth

Test Requirement:	FCC Part 15 C section 15.247 (a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Test Method:	ANSI C63.10: Clause 7.8.7 & 6.9.2
Test Status:	Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channels with different data package. Compliance test in BDR (DH1) and EDR mode (2DH1, 3DH1) as the worst case was found.

Test Configuration:



Test Procedure:

Removed the antenna from the EUT and then connect a low RF cable (cable loss =1 dB, with 10dB attenuator) from the antenna port to the spectrum. The transmitter was operated at its maximum carrier power measured under normal test conditions.

1. The instrument center frequency was set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer was between two times and five times the OBW(20 dB Bandwidth).
2. The nominal IF filter bandwidth (3 dB RBW) was in the range of 1% to 5% of the OBW, and VBW was approximately three times the RBW.
3. Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope was more than $[10 \log (OBW/RBW)]$ below the reference

TEST REPORT

- level.
4. Step 1) through step 3) might require iteration to adjust within the specified range.
 5. The dynamic range of the instrument at the selected RBW was more than 10 dB below the target “-20 dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW was at least 30 dB below the reference value.
 6. Peak detection and max hold mode (until the trace stabilizes) was used.
 7. Used the 20dB bandwidth function of the instrument and reported the measured bandwidth.
 8. The occupied bandwidth was reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division was clearly labeled. Tabular data was reported in addition to the plot(s).

Used Test Equipment List

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.

Test result:

BDR (DH1):

Test Channel	Bandwidth(MHz)	2/3 bandwidth(MHz)
Lowest	0.938	0.625
Middle	0.933	0.622
Highest	0.933	0.622

EDR mode (2DH1):

Test Channel	bandwidth	2/3 bandwidth
Lowest	1.261	0.841
Middle	1.281	0.854
Highest	1.281	0.854

EDR mode (3DH1):

Test Channel	bandwidth	2/3 bandwidth
Lowest	1.248	0.832
Middle	1.250	0.833
Highest	1.242	0.828


Test result: The unit does meet the FCC requirements.

TEST REPORT


Result plot as follows:

BDR (DH1):

Lowest Channel(2.402 GHz):




Middle Channel(2.441 GHz):




TEST REPORT

Highest Channel(2.480 GHz):




EDR mode (2DH1):

Lowest channel(2.402 GHz):




TEST REPORT

Middle channel(2.441 GHz):




Highest channel(2.480 GHz):




TEST REPORT

EDR mode (3DH1):

Lowest channel(2.402 GHz):




Middle channel(2.441 GHz):



TEST REPORT

Highest channel(2.480 GHz):



4.3 Carrier Frequencies Separated

Test Requirement:

FCC Part 15 C section 15.247

(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Method:


ANSI C63.10: Clause 7.8.2

Test Status:

Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel and hopping mode with different data packet. Compliance test in hopping with BDR (DH1) as the worst case was found.

Test Configuration:

TEST REPORT



Test Procedure:

1. Removed the antenna from the EUT and then connect a low attenuation RF cable(cable loss =1 dB, with 10dB attenuator) from the antenna port to the spectrum.
2. Span: Wide enough to capture the peaks of two adjacent channels.
3. Set the spectrum analyzer: RBW $\geq$ 1% of the span, VBW $\geq$ RBW, Sweep = auto; Detector Function = Peak. Trace = Max hold.
4. Allowed the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Used Test Equipment List

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.

Test result:

Test Channel	Carrier Frequencies Separated	Pass/Fail
Lower Channels (channel 0 and channel 1)	1.003	Pass
Middle Channels (channel 38 and channel 39)	0.999	Pass
Upper Channels (channel 77 and channel 78)	0.999	Pass


Remark:

The limit is the maximum two-thirds of the 20 dB bandwidth: 854 KHz.


Result plot as follows:

Lowest Channels: Carrier Frequencies Separated:

TEST REPORT




Middle Channels: Carrier Frequencies Separated:



TEST REPORT

Highest Channels: Carrier Frequencies Separated:



Test result: The unit does meet the FCC requirements.

4.4 Hopping Channel Number

Test Requirement:

FCC Part15 C section 15.247

(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test Method:


NSI C63.10: Clause 7.8.3

Test Status:

Pre-test the EUT in hopping mode with different data packet. Compliance test in BDR (DH1) and EDR mode (2DH1,3DH1) as the worst case was found.

Test Configuration:

TEST REPORT



Test Procedure:

1. Removed the antenna from the EUT and then connect a low attenuation RF cable(cable loss =1 dB, with 10dB attenuator) from the antenna port to the spectrum.
2. Span: The frequency band of operation
3. Set the spectrum analyzer: RBW = 300 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
4. Allowed the trace to stabilize.
5. Set the spectrum analyzer: start frequency = 2400 MHz, stop frequency = 2483.5 MHz. Submit the test result graph.


Used Test Equipment List

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.


Test result: Total channels are 79 channels.

BDR mode (DH1):

TEST REPORT




EDR mode (2DH1):



TEST REPORT

EDR mode (3DH1):



Test result: The unit does meet the FCC requirements.

TEST REPORT


4.5 Dwell Time

Test Requirement: FCC Part 15 C section 15.247
(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Method: ANSI C63.10: Clause 7.8.4

Test Status: Test the EUT in hopping mode at the middle (2441 MHz) with different data packet. Compliance test in hopping mode with BDR(DH5), EDR mode (2DH5, 3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Removed the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0, centered on a hopping channel.
3. Set RBW = 3 MHz and VBW = 3 MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = Max hold;
4. Used the marker-delta function to determine the dwell time.

Used Test Equipment List

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.

TEST REPORT

Test Result:

The test period: $T = 0.4 \text{ s} \times 79 \text{ Channel} = 31.6 \text{ s}$

Channel 39: 2.441 GHz									
DH5 time slot	=	2.928	(ms)	*	6	*	(31.6/3.16)	=	175.68 ms
2DH5 time slot	=	2.935	(ms)	*	10	*	(31.6/3.16)	=	293.50 ms
3DH5 time slot	=	2.935	(ms)	*	11	*	(31.6/3.16)	=	322.85 ms

The average time of occupancy in the specified 31.6 second period is equal to pulse width x (number of pulse in observation period) x (test period / observation period).

The results are not greater than 0.4 seconds.


The unit does meet the FCC requirements.

Result plot as follows:

The Middle channel: 2441MHz


DH5

Pulse Width:




TEST REPORT

Number of Pulses in 3.16 S observation period:




2DH5

Pulse Width:




TEST REPORT

Number of Pulses in 3.16 S observation period:




3DH5

Pulse Width:



TEST REPORT

Number of Pulses in 3.16 S observation period:



4.6 Pseudo random Frequency Hopping Sequence

4.6.1 Standard requirement

15.247(a)(1) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudo random ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


4.6.2 EUT Pseudo random Frequency Hopping Sequence

Bluetooth protocol is utilized by the EUT. It is shown that each frequency used equally on the average by the transmitter. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

TEST REPORT

4.7 Maximum Peak Conducted Output Power

Test Requirement:	FCC Part 15 C section 15.247 (b)(1)For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. Refer to the result “Hopping channel number” of this report. The 1 watt (30.0 dBm) limit applies.
Test Method:	ANSI C63.10: Clause 7.8.5
Test Status:	Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with BDR mode (DH1) and EDR mode (2DH1,3DH1) as the worst case was found.
Test Configuration:	



Test Procedure:

1. Removed the antenna from the EUT and then connect a low attenuation RF cable (cable loss=1.5 dB) from the antenna port to the spectrum.
2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
3. Set the spectrum analyzer: RBW = 3 MHz (RBW > 20 dB bandwidth of the emission being measured) , VBW = 3 MHz. Sweep = auto; Detector Function = Peak. Trace: Max hold.
4. Kept the EUT in transmitting at lowest, medium and highest channel with different data packet individually. Record the max value.

Used Test Equipment List:

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.

TEST REPORT

Test result:


BDR (DH1):				
Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	6.48	30.0	Pass
Middle	2441	6.42	30.0	Pass
Highest	2480	6.05	30.0	Pass
EDR mode(2DH1):				
Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	7.03	30.0	Pass
Middle	2441	6.88	30.0	Pass
Highest	2480	6.53	30.0	Pass
EDR mode(3DH1):				
Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	7.77	30.0	Pass
Middle	2441	7.61	30.0	Pass
Highest	2480	7.30	30.0	Pass
Remark: Cable lose=1.0 dB Level = Read Level + Cable Loss.				

Result plot as follows:


BDR(DH1):

The Lowest Channel(2.402 MHz):

TEST REPORT




Middle Channel(2.441 GHz):




TEST REPORT

The Highest Channel (2.480 GHz):




EDR mode (2DH1):

The Lowest channel (2.402 GHz):




TEST REPORT

Middle channel (2.441 GHz):




The Highest channel (2.480 GHz):




TEST REPORT

EDR mode (3DH1):

The Lowest channel (2.402 GHz):




Middle channel (2.441 GHz):



TEST REPORT

The Highest channel (2.480 GHz):



4.8 Out of Band Conducted Emissions

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 7.8.8

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with BDR mode (DH1) as the worst case was found.

Test Configuration:

TEST REPORT



Test Procedure:

1. Removed the antenna from the EUT and then connect a low RF cable (cable loss =1dB, with 10dB attenuator) from the antenna port to the spectrum analyser.
2. Set the spectrum analyzer: RBW=100 kHz, VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measured the Conducted unwanted Emissions of the test frequency with special test status.
4. Repeated until all the test status was investigated.


Used Test Equipment List:

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details


Result plot as follows:

The Lowest Channel 2402MHz: 9 kHz to 25 GHz

TEST REPORT




Middle Channel 2441MHz: 9 kHz to 25 GHz



TEST REPORT

The Highest Channel 2480MHz: 9 kHz to 25 GHz



4.9 Radiated Emissions

Test Requirement:

FCC Part 15 C section 15.247

section 15.247: (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Test Method:

ANSI C63.10: Clause 6.4, 6.5 and 6.6

TEST REPORT

Test Status:	Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with normal (DH1) and EDR mode (2DH1,3DH1) as the worst case was found.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Limit:	Section 15.209 40.0 dB μ V/m between 30MHz & 88MHz; 43.5 dB μ V/m between 88MHz & 216MHz; 46.0 dB μ V/m between 216MHz & 960MHz; 54.0 dB μ V/m above 960MHz.
Detector:	For Peak and Quasi-Peak value: RBW = 1 MHz for $f \geq 1$ GHz, 200 Hz for 9 kHz to 150 kHz 9 kHz for 150 kHz to 30 MHz 120 kHz for 30 MHz to 1GHz VBW $\geq$ RBW Sweep = auto Detector function = peak for $f \geq 1$ GHz, QP for $f < 1$ GHz Trace = max hold For AV value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW=10 Hz Sweep = auto Trace = max hold
Field Strength Calculation:	The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below: $FS = RA + AF + CF - AG + PD + AV$ $FS = RA + \text{Correct Factor} + AV$ $FS = \text{Field Strength in dB}\mu\text{V/m}$ $RA = \text{Receiver Amplitude (including preamplifier) in dB}\mu\text{V}$ $AF = \text{Antenna Factor in dB}$ $CF = \text{Cable Attenuation Factor in dB}$ $AG = \text{Amplifier Gain in dB}$ $PD = \text{Pulse Desensitization in dB}$ $AV = \text{Average Factor in -dB}$ $\text{Correct Factor} = AF + CF - AG + PD$

Where:

In the radiated emission table which follows, the reading shown

TEST REPORT

on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dBμV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added.

The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dBμV/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$\text{Correct Factor} = 7.4 + 1.6 - 29.0 + 0 = -20 \text{ dB}$$

$$FS = 62 + (-20) + (-10) = 32 \text{ dB}\mu\text{V/m}$$

Section 15.205 Restricted bands of operation.


MHz	MHz	MHz	GHz
-----	-----	-----	-----

TEST REPORT

0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
10.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		


Test Configuration:

1) 9 kHz to 30 MHz emissions:




2) 30 MHz to 1 GHz emissions:

TEST REPORT



3) 1 GHz to 40 GHz emissions:



Test Procedure:

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the special distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2) 30 MHz to 1 GHz emissions:

TEST REPORT

For testing performed with the bi-log type antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

3) 1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2010 was used to perform radiated emission test above 1 GHz.

For testing performed with the horn antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

4) The receiver was scanned from 9 kHz to 25 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

Used Test Equipment List:

3m Semi-Anechoic Chamber, EMI Test Receiver (9 kHz~7 GHz), Signal and Spectrum Analyzer (10 Hz~40 GHz), Loop antenna (9 kHz-30 MHz). TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX), Bouble-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX) and High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX). Refer to Clause 5 Test Equipment List for details.

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Pre-scan all modes, worst case as below

DH1 mode with 1Mbps data rate Test at Channel 0 (2.402 GHz) in transmitting status


Horizontal:

TEST REPORT



All emission levels are more than 6dB below the limit.

Vertical:



All emission levels are more than 6dB below the limit.

TEST REPORT

1~25 GHz Radiated Emissions.

DH1 mode data as below

Test at Channel 0 (2.402 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4803.8	56.4	-1.1	55.3	74	H
4803.8	51.2	-1.1	50.1	74	V

AV Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4803.8	37.3	-1.1	36.2	54	H
4803.8	/	-1.1	/	54	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

Test at Channel 39 (2.441 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4882.3	56.0	-1.0	55.0	74	H
4882.3	49.0	-1.0	48.0	74	V

AV Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4882.3	38.3	-1.0	37.3	54	H
4882.3	/	-1.0	/	54	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

TEST REPORT

Test at Channel 78 (2.480 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
7440.9	49.8	2.6	52.4	74	H
10197.0	40.2	6.7	46.9	74	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

2DH1 mode data as below

Test at Channel 0 (2.402 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4803.8	55.8	-1.1	54.7	74	H
4803.8	50.2	-1.1	49.1	74	V

AV Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4803.8	37.6	-1.1	36.5	54	H
4803.8	/	-1.1	/	54	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

Test at Channel 39 (2.441 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4882.3	55.6	-1.0	54.6	74	H
4882.3	47.3	-1.0	46.3	74	V

TEST REPORT

AV Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4882.3	37.9	-1.0	36.9	54	H
4882.3	/	-1.0	/	54	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

Test at Channel 78 (2.480 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
7440.9	43.9	2.6	46.5	74	H
9942.0	40.8	6.4	47.2	74	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

3DH1 mode data as below

Test at Channel 0 (2.402 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4803.8	56.5	-1.1	55.4	74	H
4803.8	49.8	-1.1	48.7	74	V

AV Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4803.8	37.4	-1.1	36.3	54	H
4803.8	/	-1.1	/	54	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

TEST REPORT

Test at Channel 39 (2.441 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4882.1	55.0	-1.0	54.0	74	H
10388.3	40.9	6.8	47.7	74	V

AV Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4882.1	36.5	-1.0	35.5	54	H
10388.3	/	6.8	/	54	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.

Test at Channel 78 (2.480 GHz) in transmitting status

PK Measurement:

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
7438.8	46.7	2.6	49.3	74	H
9920.8	39.9	6.3	46.2	74	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be record.


TEST REPORT

Band Edges Emission


DH1 mode data:

Test at Channel 0 (2.402 GHz) in transmitting status

Horizontal



Vertical



Peak Measurement:


Frequency (MHz)	Reading Level (dBμV)	Correct Factor	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2376.0	59.4	-8.2	51.2	74	H

TEST REPORT


2376.1	53.2	-8.2	45.0	74	V
--------	------	------	------	----	---

Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

Test at Channel 78 (2.480 GHz) in transmitting status
Horizontal



Vertical



Peak Measurement:


Frequency (MHz)	Reading Level (dBμV)	Correct Factor	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2485.7	49.8	-7.8	42.0	74	H
2489.8	50.8	-7.8	43.0	74	V

TEST REPORT


Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

2DH1 mode data:

Test at Channel 0 (2.402 GHz) in transmitting status
Horizontal



Vertical




TEST REPORT

Peak Measurement:


Frequency (MHz)	Reading Level (dBμV)	Correct Factor	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2375.5	57.8	-8.2	49.6	74	H
2376.2	54.0	-8.2	45.8	74	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

Test at Channel 78 (2.480 GHz) in transmitting status
Horizontal



Vertical



TEST REPORT

Peak Measurement:


Frequency (MHz)	Reading Level (dB μ V)	Correct Factor	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2481.2	54.5	-7.8	46.7	74	H
2485.0	49.3	-7.8	41.5	74	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

3DH1 mode data:


Test at Channel 0 (2.402 GHz) in transmitting status

Horizontal



Vertical

TEST REPORT




Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2376.0	59.0	-8.2	50.8	74	H
2389.0	54.6	-8.2	46.4	74	V


Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

Test at Channel 78 (2.480 GHz) in transmitting status
Horizontal



TEST REPORT

Vertical



Peak Measurement:


Frequency (MHz)	Reading Level (dB μ V)	Correct Factor	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2483.7	53.2	-7.8	45.4	74	H
2485.5	50.0	-7.8	42.2	74	V

Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

TEST REPORT

4.10 Band Edges Requirement

Test Requirement:	FCC Part 15 C section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.
Frequency Band:	2400 MHz to 2483.5 MHz
Test Method:	ANSI C63.10: Clause 7.8.6 & 6.10
Test Status:	Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with BDR mode (DH1) and EDR mode (2DH1,3DH1) as the worst case was found.
Test Configuration:	For Band Edges Emission in Radiated mode, Please refer to clause 4.7



Test Procedure: For Band Edges Emission in Radiated mode, Please refer to clause 4.7

1. Removed the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set RBW of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 100 kHz bandwidth from band edge.
3. Repeated until all the test status was investigated.
4. Reported the worst case.

Used Test Equipment List:

3m Semi-Anechoic Chamber, EMI Test Receiver (9 kHz~7 GHz), Signal and Spectrum Analyzer (10 Hz~40 GHz), Loop antenna (9 kHz-30 MHz). TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX), Bouble-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX) and High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX). Refer to Clause 5 Test Equipment List for details.

TEST REPORT

Test result with plots as follows:

For conducted mode:

The band edges was measured and recorded Result:


The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.


Result plot as follows:

DH1 mode


Lowest channel: 2.402 GHz




TEST REPORT



Highest Channel: 2.480 GHz:




TEST REPORT




2DH1 mode


Lowest channel: 2.402 GHz




TEST REPORT



Highest Channel: 2.480 GHz:




TEST REPORT




3DH1 mode


Lowest channel: 2.402 GHz




TEST REPORT



Highest Channel: 2.480 GHz:




TEST REPORT



TEST REPORT

4.11 Conducted Emission Test

Test Configuration:



Test Setup and Procedure:

Test was performed according to ANSI C63.10 Clause 6.2. The EUT was set to achieve the maximum emission level. The mains terminal disturbance voltage was measured with the EUT in a shielded room. The EUT was connected to AC power source through an Artificial Mains Network which provides a 50Ω linear impedance Artificial hand is used if appropriate (for handheld apparatus). The load/control terminal disturbance voltage was measured with passive voltage probe if appropriate.

The table-top EUT was placed on a 0.8m high non-metallic table above earthed ground plane (Ground Reference Plane). And for floor standing EUT, was placed on a 0.1m high non-metallic supported on GRP. The EUT keeps a distance of at least 0.8m from any other of the metallic surface. The Artificial Mains Network is situated at a distance of 0.8m from the EUT.

During the test, mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m

The bandwidth of test receiver was set at 9 kHz. The frequency range from 150 kHz to 30MHz was checked.

TEST REPORT


Test Data and Curve

At main terminal: Pass

Tested Wire: Live

Operation Mode: transmitting

Full Spectrum




All emission levels are more than 10 dB below the limit.

TEST REPORT

Tested Wire: Neutral

Operation Mode: transmitting

Full Spectrum



All emission levels are more than 10 dB below the limit.

TEST REPORT

5.0 Test Equipment List

Radiated Emission/Radio					
Equipment No.	Equipment	Model	Manufacturer	Cal. Due date (YYYY-MM-DD)	Calibration Interval
EM030-04	3m Semi-Anechoic Chamber	9×6×6 m ³	ETS•LINDGRE N	2025-04-09	1Y
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	2025-11-10	1Y
EM031-03	Signal and Spectrum Analyzer (10 Hz~40 GHz)	R&S FSV40	R&S	2025-11-10	1Y
EM011-04	Loop antenna (9 kHz-30 MHz)	HFH2-Z2	R&S	2025-07-07	1Y
EM033-01	TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX)	VULB 9163	SCHWARZBECK	2025-12-08	1Y
EM033-02	Bouble-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX)	R&S HF907	R&S	2025-07-02	1Y
EM033-03	High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX)	R&S SCU-26	R&S	2025-04-22	1Y
EM033-04	High Frequency Antenna & preamplifier (26 GHz-40 GHz)	R&S SCU-40	R&S	2025-04-22	1Y
EM031-02-01	Coaxial cable(9 kHz-1 GHz)	N/A	R&S	2025-04-09	1Y
EM033-02-02	Coaxial cable(1 GHz-18 GHz)	N/A	R&S	2025-04-09	1Y
EM033-04-02	Coaxial cable(18 GHz~40 GHz)	N/A	R&S	2025-04-25	1Y
EM031-01	Signal Generator (9 kHz~6 GHz)	SMB100A	R&S	2025-03-17	1Y
EM040-01	Band Reject/Notch Filter	WRHFV	Wainwright	N/A	1Y
EM040-02	Band Reject/Notch Filter	WRCGV	Wainwright	N/A	1Y
EM040-03	Band Reject/Notch Filter	WRCGV	Wainwright	N/A	1Y
EM022-03	2.45 GHz Filter	BRM50702	Micro-Tronics	2025-05-15	1Y
SA016-29	Climatic Test Chamber	MHU-80L	JIANQIAO	2026-01-05	1Y
EM046-05	Power meter	NPR6A	R&S	2025-04-22	1Y
EM046-06	Power meter	NPR6A	R&S	2025-05-09	1Y
EM031-04-01	EMC32	V10.01.00	R&S	N/A	N/A
EM045-01-10	10dB Attenuator	N/A	R&S	2025-12-24	1Y
Conducted Disturbance-Mains Terminal (2)					
Equipment No.	Equipment	Model	Manufacturer	Cal. Due date (DD-MM-YYYY)	Calibration Interval
EM031-04	EMI receiver	ESR3	R&S	05/01/2026	1Y
EM006-06	LISN	ENV216	R&S	01/09/2025	1Y
SA047-111	Digital Temperature-Humidity Recorder	RS210	YIJIE	20/10/2025	1Y
EM004-03	EMC shield Room	8m×4m×3m	Zhongyu	05/01/2026	1Y
EM031-04-01	EMC32	V10.01.00	R&S	N/A	1Y

*****End of the test report*****