

东莞市德欣达电子科技有限公司

Dongguan Dexinda Electronic Technology Co.,Ltd

客户/Client	中山市古镇洛奥灯饰厂 Zhongshan Guzhen Luoa Lighting Factory
名称/TYPE	发射线圈transmitting coil
产品型号	
Model NO	A11/G43.5*0.6MM 单孔双槽背胶线长150MM 0.15*15*10TS 6.3UH Single-hole double-slot adhesive tape length
产品编号	
Part numbering systey	
客户料号	
Client p/NO	
工程编号	
Enginrer NO	
日期/Date	2025-6-24

本公司工程部/For Enginer Departner Only	
修改内容/Rrvised Content	认可日期/APProved Date

编制/Prepared	审核/Checked	认可/Approved
RAO	谢 良Xie Liang	

客户认可回签/Authorixed Signaturure Company Chop		
工程/ Enginrer	认可/QC APProved	认可日期/APProved

东莞市德欣达电子科技有限公司

Dongguan Dexinda Electronic Technology Co.,Ltd

一、线圈工艺/Winding Procese:

NO	winding	guage	number	direction	remark
1	N1	2UEW-B-0.15*15P	10TS	CCW	
2					

二 . 电气性能/FEATURES:

1.测试条件 (Test conditions) : 25°C,65%RH@100KHz/1V

1.1 电感量 (Inductance)

1.11 L0A (单独线圈) =3.8uH±20%

1.12 L0A(线圈+磁片)=6.3uH±10%

1.2 Q 值=35MIN

1.3 直流电阻 (DCR) : 55mΩ MAX

1.4 工作温度(Operating Temperature) : -25°C~85°C

2.测试仪器(Test instrument) : L:创达 1068+1310;DCR:502BC;SIZE:Callipers

3.材料清单 bill of materials

NO	project	materials
1	WIRE	φ 0.15*15P 2UEW
2	FERRITE	43.5*5.3*0.6mm L Double-slot ferrite hard magnetic material
3	GLUE	white glues
4	SOLDER	QD-107H
5	Adhesive	single-sided adhesive
6	High temperature adhesive	7MM high-temperature tape
7		
8		


东莞市德欣达电子科技有限公司

Dongguan Dexinda Electronic Technology Co.,Ltd


三．实物图/CIRCUIT DIAGRAM



单位：



四．外形图/OUTSIDE DIAGRA



Note: The outlet position of the coil is wrapped with 8MM (ref) heat-resistant adhesive tape.

标准	A	B	C	D	E	F	I	T
STD	43.5±1	20.5±1	5.3±0.5	150±3	4±1	39±1	0.6±0.2	2.2Max


单位： MM

东莞市德欣达电子科技有限公司

Dongguan Dexinda Electronic Technology Co.,Ltd

五．包装/PACKAGE

5.1 包装图片 Packing pictures:



5.2 包装数量及规格 Packing Quantity:

项目 Item	数量 Quantity	材料规格 Material
盒 Box	350 Pcs	345*330*50 mm
箱 Big Carton	1400 Pcs	360*340*280 mm

5.3 包装以现有包装盘为参照标准，以实际出货包装为准，如有特要求可以定制。

The packaging shall be based on the exusting packing plate and the actual delivery package shall prevail .If there is any requirement,we can customize it.

东莞市德欣达电子科技有限公司

Dongguan Dexinda Electronic Technology Co.,Ltd

六、贮存和使用条件 Storage and Use condition

6.1 贮存条件 Storage condition

6.1.1 建议贮存条件：温度 $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ ，湿度 70% (Max.)

Recommended keeping conditions: $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$, 70%RH (Max.)

6.1.2 贮存期限：自生产之日起六个月内

Storage life : Within the limits of six months from being produced.

6.2 使用条件 Use condition

使用条件限制：温度 $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ ，湿度 $\leq 90\%$

Use condition limit: $T=-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$, $\text{RH} \leq 90\%$.