



Appendix A.5

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 Band5_ERP

Band: 5								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	ERP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	22.50	2.53	22.88	<=38.45	Pass
			836.6	22.62	2.53	23.00	<=38.45	Pass
			846.6	22.61	2.53	22.99	<=38.45	Pass
Note1: ERP=Conducted Power+Antenna Gain-2.15								

2. Frequency Stability

2.1 Test Result

2.1.1 Band5

Band: 5							
Network	Frequency (MHz)	Temp. (°C)	Voltage (VDC)	Freq. Error (Hz)	Freq. vs. Rated (ppm)		Verdict
					Result	Limit	
RMC	826.4	20	3.30	-1.681	-0.0020	-2.5 to 2.5	Pass
			3.80	-1.645	-0.0020	-2.5 to 2.5	Pass
			4.30	-1.452	-0.0018	-2.5 to 2.5	Pass
		-30	3.80	-1.473	-0.0018	-2.5 to 2.5	Pass
		-20	3.80	-1.402	-0.0017	-2.5 to 2.5	Pass
		-10	3.80	-1.523	-0.0018	-2.5 to 2.5	Pass
		0	3.80	-0.944	-0.0011	-2.5 to 2.5	Pass
		10	3.80	-1.259	-0.0015	-2.5 to 2.5	Pass
		30	3.80	-0.916	-0.0011	-2.5 to 2.5	Pass
		40	3.80	-1.087	-0.0013	-2.5 to 2.5	Pass
		50	3.80	-0.579	-0.0007	-2.5 to 2.5	Pass
	836.6	20	3.27	-0.165	-0.0002	-2.5 to 2.5	Pass
			3.85	-0.315	-0.0004	-2.5 to 2.5	Pass
			4.43	-0.257	-0.0003	-2.5 to 2.5	Pass
		-30	3.30	-0.193	-0.0002	-2.5 to 2.5	Pass
		-20	3.80	-0.243	-0.0003	-2.5 to 2.5	Pass
		-10	4.30	-0.029	0.0000	-2.5 to 2.5	Pass
		0	3.80	0.086	0.0001	-2.5 to 2.5	Pass
		10	3.80	-0.393	-0.0005	-2.5 to 2.5	Pass
		30	3.80	-0.315	-0.0004	-2.5 to 2.5	Pass
		40	3.80	0.193	0.0002	-2.5 to 2.5	Pass



Report No.: SUCR260500041102

Page: 2 of 18

	846.6	50	3.80	-0.257	-0.0003	-2.5 to 2.5	Pass
		20	3.30	0.472	0.0006	-2.5 to 2.5	Pass
			3.80	0.579	0.0007	-2.5 to 2.5	Pass
			4.30	0.615	0.0007	-2.5 to 2.5	Pass
		-30	3.80	0.780	0.0009	-2.5 to 2.5	Pass
		-20	3.80	0.844	0.0010	-2.5 to 2.5	Pass
		-10	3.80	0.694	0.0008	-2.5 to 2.5	Pass
		0	3.80	0.701	0.0008	-2.5 to 2.5	Pass
		10	3.80	0.858	0.0010	-2.5 to 2.5	Pass
		30	3.80	0.544	0.0006	-2.5 to 2.5	Pass
		40	3.80	0.901	0.0011	-2.5 to 2.5	Pass
		50	3.80	0.551	0.0007	-2.5 to 2.5	Pass



Report No.: SUCR260500041102

Page: 3 of 18

3. 99% & 26dB Bandwidth

3.1 Test Result

3.1.1 Band5_OBW


Band: 5						
ENV	Mode		Frequency (MHz)	99% Occupied Bandwidth (MHz)		Verdict
	Network	Subset		Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	4.152	/	Pass
			836.6	4.186	/	Pass
			846.6	4.163	/	Pass


3.1.2 Band5_XDB


Band: 5						
ENV	Mode		Frequency (MHz)	26dB Bandwidth (MHz)		Verdict
	Network	Subset		Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	4.752	/	Pass
			836.6	4.760	/	Pass
			846.6	4.762	/	Pass

3.2 Test Graph


3.2.1 Band5_OBW









3.2.2 Band5_XDB









4. Peak-Average Ratio

4.1 Test Result


4.1.1 Band5


Band: 5						
ENV	Mode		Frequency (MHz)	Peak-Average Ratio (dB)		Verdict
	Network	Subset		Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	2.83	<=13	Pass
			836.6	2.76	<=13	Pass
			846.6	2.79	<=13	Pass




4.2 Test Graph

4.2.1 Band5









Report No.: SUCR260500041102
Page: 14 of 18

5. Spurious Emission

5.1 Test Result


5.1.1 Band5


Band: 5						
ENV	Mode		Frequency (MHz)	Spurious Emission		Verdict
	Network	Subset		Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	Refer To Test Graph	Pass	
			836.6	Refer To Test Graph	Pass	
			846.6	Refer To Test Graph	Pass	




5.2 Test Graph

5.2.1 Band5







Band5_RMC_MCH_836.6MHz_12.2kbps RMC_NTNV



Band5_RMC_HCH_846.6MHz_12.2kbps RMC_NTNV





- End of the Appendix -