


RF Test Report

Applicant: Eagle Electronics Inc.
Address: 114 Venture Dr Paraskala, OH 43062-9239 United States
Product: LTE Cat 1 module
Model No.: I421-GLGA
Brand Name: Eagle
FCC ID: 2BNX7I421GLGAA
Standards: 47 CFR Part 22
47 CFR Part 24
47 CFR Part 27
47 CFR Part 90
Report No.: PD20250032-R3A
Issue Date: 2025/04/03
Test Result: PASS *

* Testing performed at Hefei Panwin Technology Co., Ltd. on the above equipment indicates the product meets the requirements of the relevant standards.



Reviewed By: Charlie Wang



Approved By: Alec Yang

Hefei Panwin Technology Co., Ltd.

Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin
Avenue, High-tech Zone, Hefei City, Anhui Province, China
TEL: +86-0551-63811775

Revision History

Report No.	Version	Description	Issue Date	Note
PD20250032-R3A	01	Initial Report	2025/04/03	Valid

Remark:

Model I425-GLGA(LTE Cat4 with Data and Voice), and I421-GLGA(LTE Cat1 with Data and Voice) all use Qualcomm 9207 chipset and share the same chipset baseline and hardware/software design. The differences between them are that they support different LTE UE Category.

Model I421-GLGA have two packaged types: LGA and MINIPCIE.

MINIPCIE is make up with I421-GLGA LGA module and PCIe carrier board.

There are no any other internal changes in these modules.

We hereby state that they are identical in interior structure and components, and just connector interface is different for the marketing requirement.

After evaluation, RF Output Power & Effective Radiated Power was tested for GSM and WCDMA. RF Output Power & Effective Radiated Power, Occupied Bandwidth and Peak-to-Average Ratio was tested for LTE. This report spot check the Radiated Spurious Emission of worst bands, and the data results did not deteriorate. Test data is referenced from the original report (Report No.: PD20250026-R3A) issued on 2025/04/03.

CONTENTS

1 General Information	14
1.1 Notes of the Test Report	14
1.2 Test Facility	14
1.3 Testing Laboratory	14
2 General Description of Equipment under Test	14
2.1 Details of Application	14
2.2 Details of EUT	15
2.3 Frequency List of Low/Middle/High Channels	17
2.4 Application Standards	22
3 Test Condition	23
3.1 Test Environmental Conditions	23
3.2 Test Configuration	23
3.3 Equipment List	25
3.4 Test Uncertainty	26
4 Test Items Description	27
4.1 RF Output Power & Effective (Isotropic) Radiated Power	27
4.2 EIRP Power Density	28
4.3 Peak-to-Average Ratio	29
4.4 Occupied Bandwidth	30
4.5 Conducted Band Edge Measurement	31
4.6 Spurious Emissions at Antenna Terminals	32
4.7 Frequency Stability	33
4.8 Radiated Spurious Emission	34
ANNEX A: Test Results	36
ANNEX B: The EUT Appearance	37
ANNEX C: Test Setup Photographs	38

Test Summary

GSM1900 / UMTS Band II

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §24.232(c)	EIRP ≤2 Watt	PASS
2	Peak-to-Average Ratio	§24.232(d)	≤13 dB	Reference report: PD20250026-R3A
3	Occupied Bandwidth	§2.1049	No limit.	
4	Conducted Band Edge Measurement	§2.1051, §24.238(a)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	
5	Spurious Emissions at Antenna Terminals	§2.1051, §24.238(a)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053, §24.238(a)	≤ -13 dBm/1 MHz.	
7	Frequency Stability	§2.1055 §24.235	Within authorized bands of operation/frequency block.	

LTE Band 2 / 25

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §24.232(c)	EIRP $\leq$ 2 Watt	PASS
2	Peak-to-Average Ratio	§24.232(d)	$\leq$ 13 dB	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Conducted Band Edge Measurement	§2.1051, §24.238(a)	$\leq$ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051, §24.238(a)	$\leq$ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053, §24.238(a)	$\leq$ -13 dBm/1 MHz.	
7	Frequency Stability	§2.1055 §24.235	Within authorized bands of operation/frequency block.	

UMTS Band IV

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §27.50(d)(4)	EIRP ≤ 1 Watt	PASS
2	Peak-to-Average Ratio	§27.50(d)(5)	≤13 dB	Reference report: PD20250026-R3A
3	Occupied Bandwidth	§2.1049	No limit.	
4	Conducted Band Edge Measurement	§2.1051, §27.53(h)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	
5	Spurious Emissions at Antenna Terminals	§2.1051, §27.53(h)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053, §27.53(h)	≤ -13 dBm/1 MHz.	
7	Frequency Stability	§2.1055 §27.54	Within authorized bands of operation/frequency block.	

LTE Band 4 / 66

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §27.50(d)(4)	EIRP ≤ 1 Watt	PASS
2	Peak-to-Average Ratio	§27.50(d)(5)	≤13 dB	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Conducted Band Edge Measurement	§2.1051, §27.53(h)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051, §27.53(h)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053, §27.53(h)	≤ -13 dBm/1 MHz.	
7	Frequency Stability	§2.1055 §27.54	Within authorized bands of operation/frequency block.	

GSM850 / UMTS Band V

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046 §22.913 (a)(5)	ERP ≤ 7 Watt	PASS
2	Peak-to-Average Ratio	§22.913 (d)	≤13 dB	Reference report: PD20250026-R3A
3	Occupied Bandwidth	§2.1049	No limit.	
4	Conducted Band Edge Measurement	§2.1051 §22.917 (a)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	
5	Spurious Emissions at Antenna Terminals	§2.1051 §22.917(a)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053 §22.917(a)	FCC: ≤ -13 dBm/100 kHz.	
7	Frequency Stability	§2.1055 §22.355	< ±2.5 ppm	

LTE Band 5 / 26(824~849 MHz)

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046 §22.913 (a)(5)	ERP ≤ 7 Watt	PASS
2	Peak-to-Average Ratio	§22.913 (d)	≤13 dB	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Conducted Band Edge Measurement	§2.1051 §22.917 (a)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051 §22.917(a)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053 §22.917(a)	FCC: ≤ -13 dBm/100 kHz.	
7	Frequency Stability	§2.1055 §22.355	< ±2.5 ppm	

LTE Band 26(814~824 MHz)

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §90.635(b)	< 100 W	PASS
2	Peak-to-Average Ratio	--	≤13 dB	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Emission Mask	§2.1051 § 90.691(a)	For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log10(f/6.1) decibels or 50 + 10 Log10(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051, §90.691	< 43 + 10Log10(P[Watts]) for all out-of- band emissions	
6	Radiated Spurious Emission	§2.1053, §90.691		
7	Frequency Stability	§2.1055 §90.213	Within authorized bands of operation/frequency block.	


LTE Band 13

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §27.50(b)(10)	ERP ≤ 3 Watt	PASS
2	Peak-to-Average Ratio	--	≤13 dB	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Conducted Band Edge Measurement	§2.1051, §27.53(c)	On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051, §27.53(c) §27.53(f)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges. On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations; For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.	
6	Radiated Spurious Emission	§2.1053, §27.53(c) §27.53(f)	FCC: ≤ -13 dBm/100 kHz. For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.	
7	Frequency Stability	§2.1055 §27.54	Within authorized bands of operation/frequency block.	

LTE Band 12

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §27.50(c)(10)	ERP ≤ 3 Watt	PASS
2	Peak-to-Average Ratio	--	≤13 dB	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Conducted Band Edge Measurement	§2.1051, §27.53(g)	For operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051, §27.53(g)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	
6	Radiated Spurious Emission	§2.1053, §27.53(g)	FCC: ≤ -13 dBm/100 kHz.	
7	Frequency Stability	§2.1055 §27.54	Within authorized bands of operation/frequency block.	

LTE Band 7 / 38 / 41

No.	Test Case	FCC Rules	Limit	Verdict
1	RF Output Power & Effective Radiated Power	§2.1046, §27.50(h)(2)	$EIRP \leq 2 \text{ Watt}$	PASS
2	Peak-to-Average Ratio	--	$\leq 13 \text{ dB}$	PASS
3	Occupied Bandwidth	§2.1049	No limit.	Report Only
4	Conducted Band Edge Measurement	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P) \text{ dB}$ on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P) \text{ dB}$ on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P) \text{ dB}$ on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P) \text{ dB}$ on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P) \text{ dB}$ at or below 2490.5 MHz.	Reference report: PD20250026-R3A
5	Spurious Emissions at Antenna Terminals	§2.1051, §27.53(m)		
6	Radiated Spurious Emission	§2.1053, §27.53(m)		
7	Frequency Stability	§2.1055 §27.54	Within authorized bands of operation/frequency block.	

Conducted detection date: 2025/03/06 to 2025/03/17

Date of sample received: 2025/03/06

- The samples tested have been evaluated in accordance with the procedures given in the application standards in **Section 2.4** of this report and have been shown to comply with the applicable technical standards.
- All indications of PASS/FAIL in this report are based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

1 General Information

1.1 Notes of the Test Report

This report is invalid without signature of auditor and approver or with any alterations. The report shall not be partially reproduced without written approval of the testing company. Entrusted test results are only responsible for incoming samples. If there is any objection to the testing report, it shall be raised to the testing company within 15 days from the date of receiving the report. In the test results, "NA" means "not applicable", and the test items marked with "Δ" are subcontracted projects.

1.2 Test Facility

A2LA (Certificate Number: 6849.01)

Hefei Panwin Technology Co., Ltd. has been accredited by American Association for Laboratory Accreditation to perform measurement.

FCC (Designation Number: CN1361, Test Firm Registration Number: 473156)

Hefei Panwin Technology Co., Ltd. has been accredited on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Laboratory

Company Name	Hefei Panwin Technology Co., Ltd.
Address	Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China
Telephone	+86-0551-63811775
Post Code	230031

2 General Description of Equipment under Test

2.1 Details of Application

Applicant	Eagle Electronics Inc.
Applicant Address	114 Venture Dr Paraskala, OH 43062-9239 United States
Manufacturer	Eagle Electronics Inc.
Manufacturer Address	114 Venture Dr Paraskala, OH 43062-9239 United States

2.2 Details of EUT

Product		LTE Cat 1 module							
Model		I421-GLGA							
Hardware Version		R1.0							
Software Version		I421GLGAR07A01M1G							
GSM Specification									
Single Band		GSM850, GSM1900							
Multi-slot class		GPRS: 33/ EGPRS: 33							
Type of Modulation		GMSK(GSM, GPRS),8PSK (EGPRS)							
UMTS Specification									
Single Band		WCDMA Band II, IV, V							
Power Class for UMTS		PC3							
Type of Modulation		Supports QPSK, 16QAM and 64QAM modulations							
E-UTRA Specification									
Single Band		FDD Band: 2, 4, 5, 7, 12, 13, 25, 26, 66 TDD Band: 38, 41							
Power Class for LTE		PC3							
Type of Modulation		UL: QPSK, 16QAM DL: QPSK, 16QAM, 64QAM							
Antenna Type		☒ External ☐ Integrated							
Antenna Gain		GSM850: 2.13dBi GSM1900: 1.59dBi WCDMA Band II: 1.59dBi WCDMA Band IV: 2.00dBi WCDMA Band V: 2.13dBi LTE Band 2: 1.59dBi LTE Band 4: 2.00dBi LTE Band 5: 2.13dBi LTE Band 7: 3.00dBi				LTE Band 12: 3.26dBi LTE Band 13: 4.45dBi LTE Band 25: 1.59dBi LTE Band 26(814 to 824MHz): 2.53dBi LTE Band 26(824 to 849MHz): 2.13dBi LTE Band 38: 2.06dBi LTE Band 41: 3.00dBi LTE Band 66: 2.00dBi			
GSM Frequency Range(s)		Band		Tx (MHz)				Rx (MHz)	
		GSM 850		824 to 849				869 to 894	
		GSM 1900		1850 to 1910				1930 to 1990	
Frequency Band(s)	SISO Band	Supported Channel Bandwidth (MHz)						Tx (MHz)	Rx (MHz)
		1.4	3	5	10	15	20		
	WCDMA Band II	-	-	v	-	-	-	1850 to 1910	1930 to 1990
	WCDMA Band IV	-	-	v	-	-	-	1710 to 1755	2110 to 2155

	WCDMA Band V	-	-	v	-	-	-	824 to 849	869 to 894
	LTE Band 2	v	v	v	v	v	v	1850 to 1910	1930 to 1990
	LTE Band 4	v	v	v	v	v	v	1710 to 1755	2110 to 2155
	LTE Band 5	v	v	v	v	-	-	824 to 849	869 to 894
	LTE Band 7	-	-	v	v	v	v	2500 to 2570	2620 to 2690
	LTE Band 12	v	v	v	v	-	-	699 to 716	729 to 746
	LTE Band 13	-	-	v	v	-	-	777 to 787	746 to 756
	LTE Band 25	v	v	v	v	v	v	1850 to 1915	1930 to 1995
	LTE Band 26	v	v	v	v	v	-	814 to 849	859 to 894
	LTE Band 38	-	-	v	v	v	v	2570 to 2620	2570 to 2620
	LTE Band 41	-	-	v	v	v	v	2496 to 2690	2496 to 2690
	LTE Band 66	v	v	v	v	v	v	1710 to 1780	2110 to 2180

Note: The declared of product specification for EUT and/or Antenna presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Support Equipment

Equipment	Manufacturer	Description	Model	Serial Number
EVb	Eagle Electronics Inc.	-	Q1-A0770	MP825AK0Y000553
Adapter	Shenzhen Keyu Power Technology Co., LTD	AC to DC power supply to EVb	KA1801A-0503000DE	-

2.3 Frequency List of Low/Middle/High Channels

GSM850 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
0.2	Channel	128	190	251
	Frequency	824.2	836.6	848.8

GSM1900 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
0.2	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8

WCDMA Band II Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6

WCDMA Band IV Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

WCDMA Band V Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745

LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
10	Channel	20450	20525	20600
	Frequency	829	836.5	844

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
10	Channel	23060	23095	23130
	Frequency	704	707.5	711

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5
10	Channel	23230	23230	23230
	Frequency	782	782	782

LTE Band 25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	26047	26365	26683
	Frequency	1850.7	1882.5	1914.3
3	Channel	26055	26365	26675
	Frequency	1851.5	1882.5	1913.5
5	Channel	26065	26365	26665
	Frequency	1852.5	1882.5	1912.5
10	Channel	26090	26365	26640
	Frequency	1855	1882.5	1910
15	Channel	26115	26365	26615
	Frequency	1857.5	1882.5	1907.5
20	Channel	26140	26365	26590
	Frequency	1860	1882.5	1905

LTE Band 26 (814 to 824MHz) Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
10	Channel	26740	26740	26740

	Frequency	819	819	819
--	-----------	-----	-----	-----

LTE Band 26 (824 to 849MHz) Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	26797	26915	27033
	Frequency	824.7	836.5	848.3
3	Channel	26805	26915	27025
	Frequency	825.5	836.5	847.5
5	Channel	26815	26915	27015
	Frequency	826.5	836.5	846.5
10	Channel	26840	26915	26990
	Frequency	829.0	836.5	844.0
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610

LTE Band 41 (2496 to 2690MHz) Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
5	Channel	39675	40620	41565
	Frequency	2498.5	2593	2687.5
10	Channel	39700	40620	41540
	Frequency	2501	2593	2685
15	Channel	39725	40620	41515
	Frequency	2503.5	2593	2682.5
20	Channel	39750	40620	41490
	Frequency	2506	2593	2680

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770

2.4 Application Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

47 CFR Part 2

47 CFR Part 22

47 CFR Part 24

47 CFR Part 27

47 CFR Part 90

ANSI C63.26-2015

FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

3 Test Condition

3.1 Test Environmental Conditions

During testing, environmental conditions are described below.

Normal Configuration		Extreme Configuration		
Voltage	3.8V	Voltage	High: 4.3V	Low: 3.3V

3.2 Test Configuration

GSM										
Test Case	BW (MHz)	Modulation				RB		CH		
		GMSK		8PSK		1	full	L	M	H
RF Output Power & Effective (Isotropic) Radiated	0.2	v		v		-	-	v	v	v
Occupied Bandwidth	-	-		-		-	-	-	-	-
Conducted Band Edge	-	-		-		-	-	-	-	-
Spurious Emissions at Antenna Terminals	-	-		-		-	-	-	-	-
Peak-to-Average Ratio	-	-		-		-	-	-	-	-
Frequency Stability	-	-		-		-	-	-	-	-
Radiated Spurious Emission	Spot check									
WCDMA										
Test Case	BW (MHz)	Modulation				RB		CH		
		QPSK	16QAM	64QAM	256QAM	1	full	L	M	H
RF Output Power & Effective (Isotropic) Radiated	5	v	--	--	--	--	--	v	v	v
Occupied Bandwidth	-	-	-	-	-	-	-	-	-	-
Conducted Band Edge	-	-	-	-	-	-	-	-	-	-
Spurious Emissions at Antenna Terminals	-	-	-	-	-	-	-	-	-	-
Peak-to-Average Ratio	-	-	-	-	-	-	-	-	-	-
Frequency Stability	-	-	-	-	-	-	-	-	-	-
Radiated Spurious Emission	Spot check									
LTE										
Test Case	BW	Modulation				RB		CH		
		QPSK	16QAM	64QAM	256QAM	1	full	L	M	H
RF Output Power & Effective (Isotropic) Radiated	all	v	v	-	-	v	v	v	v	v

Occupied Bandwidth	all	v	v	-	-	-	v	-	v	-
Conducted Band Edge	-	-	-	-	-	-	-	-	-	-
Spurious Emissions at Antenna Terminals	-	-	-	-	-	-	-	-	-	-
Peak-to-Average Ratio	all	v	v	-	-	-	v	-	v	-
Frequency Stability	-	-	-	-	-	-	-	-	-	-
Radiated Spurious Emission	Spot check									

Note:

- 1.The mark " V " means that this configuration is chosen for testing.
- 2.The mark " -- " means that this bandwidth is not supported.
- 3.The device is investigated from 30Hz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.
- 4.Frequency Stability : Normal Voltage = 3.8V ; Low Voltage =3.3V. ; High Voltage =4.3V

3.3 Equipment List

Instrument	Manufacturer	Model	Asset No.	Cal. Interval	Cal. Due Date
Conducted					
Base Station Simulator	R&S	CMW500	PWC0052	1 Year	2025/09/12
Spectrum Analyzer	KEYSIGHT	N9020B	PWC0047	1 Year	2025/09/11
DC Power	KEYSIGHT	E3640A	PWC0043	1 Year	2025/09/12
Climate Chamber	Boyi	B-T-48C	PWC0051	1 Year	2025/09/12
Shielded Chamber	Mao Rui	MR534	PWC0041	3 Years	2026/08/26
RF cable	TIMES Microwave Systems	SFT205PUR-NMSWSM-1.50M	PWD0165	1 Year	2025/09/12
RF cable	TIMES Microwave Systems	HF160-KMKMR-1.50M	PWD0166	1 Year	2025/09/12
Coupling unit	COM-MW	ZDC6-10M1	PWD0167	1 Year	2025/09/12
Trigger cable	-	ZT06-BNCJ-BNCJ-1M	-	-	-
Test Software	Tonscend	JS1120 V3.1.46	-	-	-
Radiated					
Receiver	R&S	ESR7	PWB0023	1 Year	2025/09/11
Spectrum Analyzer	R&S	FSV3044	PWB0024	1 Year	2025/09/11
Loop Antenna	R&S	HFH2-Z2E	PWB0026	1 Year	2025/09/13
TRILOG Broadband Antenna	Schwarzbeck	VULB9162	PWB0029	1 Year	2025/09/09
Double-Ridged Guide Antenna	ETS-Lindgren	3117	PWB0031	1 Year	2025/09/26
k Type Horn Antenna	Steatite Antennas	QMS-00880	PWB0035	1 Year	2025/09/08
Pre-Amplifier	R&S	OSP220 (OSP-B155G)	PWB0042	1 Year	2025/09/11
Pre-Amplifier	COM-MW	DLNA8	PWB0094	1 Year	2025/09/11
Pre-Amplifier	R&S	SCU18F	PWB0034	1 Year	2025/09/11
Pre-Amplifier	R&S	SCU40F1	PWB0036	1 Year	2025/09/11
Anechoic Chamber	ETS-Lindgren	Fact 3-2m	PWB0003	3 Years	2026/06/05
Test Software	Tonscend	JS36	-	-	-

3.4 Test Uncertainty

No.	Parameter	Uncertainty
1	Maximum transmit power	0.677dB
2	Frequency error	37.064Hz
3	Bandwidth occupied	5.9kHz
4	Emission spurious, Band edge and PAPR	10Hz-3.5GHz: 0.982dB 3.5GHz-18GHz: 1dB 18GHz-26.5GHz: 0.777dB 26.5GHz-40GHz: 1.066dB
5	Radiated Spurious Emission	Below 1GHz: 4.88 dB Above 1GH: 5.06 dB
6	Temperature	3°C
7	Humidity	1.3 %
8	Supply voltages	0.006 V

4 Test Items Description

Ambient condition

Shielded Chamber

Temperature [°C]	22.4 to 25.7
Humidity [%RH]	33 to 46
Pressure [kPa]	101.6 to 104.6

4.1 RF Output Power & Effective (Isotropic) Radiated Power

Methods of Measurement

Base Station Simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

According to KDB 412172 D01 Power Approach,


$EIRP = PT + GT - LC$, $ERP = EIRP - 2.15$, where

PT = transmitter output power in dBm

GT = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

Test Setup




- 1.The testing follows ANSI C63.26 Section 5.2.
- 2.The transmitter output port was connected to the base station simulator.
- 3.Set EUT at maximum power through the base station simulator
- 4.Select lowest, middle, and highest channels for each band and different modulation.
- 5.Measure and record the power level from the system simulator.

4.2 EIRP Power Density

Methods of Measurement

Measurement Procedure: C63.26 -2015 section 5.2.4

Test Setup




- 1.Set instrument center frequency to OBW center frequency.
- 2.Set span to at least 1.5 times the OBW.
- 3.Set the RBW to the specified reference bandwidth (often 1 MHz).
- 4.Set VBW $\geq 3 \times$ RBW.
- 5.Detector = RMS (power averaging).
- 6.Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- 7.Sweep time = auto couple.
- 8.Employ trace averaging (RMS) mode over a minimum of 100 traces.
- 9.Use the peak marker function to determine the maximum amplitude level within the reference bandwidth (PSD).

4.3 Peak-to-Average Ratio

Methods of Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth.

Test Setup



- 1.The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
- 2.The EUT was connected to spectrum and system simulator via a coupling unit.
- 3.Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- 4.The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
- 5.Record the deviation as Peak to Average Ratio.


4.4 Occupied Bandwidth

Methods of Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

Test Setup



The testing follows ANSI C63.26 Section 5.4.

The EUT was connected to spectrum analyzer and system simulator via a coupling unit.

The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.

The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.

Set the detection mode to peak, and the trace mode to max hold.

Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.

(this is the reference value).

Determine the '-26 dB down amplitude' as equal to (Reference Value – X).

Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the '-X dB down amplitude' determined in step 6. If a marker is below this '-X dB down amplitude' value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.


4.5 Conducted Band Edge Measurement

Methods of Measurement

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel). In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to RMS.

Test Setup



- 1.The testing follows ANSI C63.26 section 5.7
- 2.The EUT was connected to spectrum analyzer and system simulator via a coupling unit.
- 3.The band edges of low and high channels for the highest RF powers were measured.
- 4.Set RBW $\geq$ 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
- 5.Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
- 6.Set spectrum analyzer with RMS detector.
- 7.The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


4.6 Spurious Emissions at Antenna Terminals

Methods of Measurement

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Test Setup



- 1.The testing follows ANSI C63.26 section 5.7
- 2.The EUT was connected to spectrum analyzer and system simulator via a coupling unit.
- 3.The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4.The middle channel for the highest RF power within the transmitting frequency was measured.
- 5.The conducted spurious emission for the whole frequency range was taken.
- 6.Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
- 7.Set spectrum analyzer with RMS detector.
- 8.Taking the record of maximum spurious emission.
- 9.The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


Note: As described in Section C63.26 4.2.3: Generally, the measurement must be corrected by adding $10 \log [(reference\ bandwidth) / (resolution\ or\ measurement\ bandwidth)]$ to the measured value (such bandwidth scaling is limited to cases where the measurement bandwidth used to perform the measurement is less than the reference bandwidth). Therefore, the converted limit value is the standard limit value minus the conversion factor.

4.7 Frequency Stability

Methods of Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

Test Setup



Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20 \pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4.8 Radiated Spurious Emission

Methods of Measurement


The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


Test Setup



For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz

- 1.The testing follows ANSI C63.26 Section 5.5
- 2.The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
- 3.The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
- 4.The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 5.The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
- 6.During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
- 7.Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 8.A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 9.Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 10.EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
- 11.ERP (dBm) = EIRP - 2.15
- 12.The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

Remark: The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

----- THE END -----

ANNEX A: Test Results

Test Results of Conducted Test

GSM850	Refer to ANNEX A.1
GSM1900	Refer to ANNEX A.2
WCDMA Band II	Refer to ANNEX A.3
WCDMA Band IV	Refer to ANNEX A.4
WCDMA Band V	Refer to ANNEX A.5
LTE Band 2	Refer to ANNEX A.6
LTE Band 4	Refer to ANNEX A.7
LTE Band 5	Refer to ANNEX A.8
LTE Band 7	Refer to ANNEX A.9
LTE Band 12	Refer to ANNEX A.10
LTE Band 13	Refer to ANNEX A.11
LTE Band 25	Refer to ANNEX A.12
LTE Band 26 (814 to 824MHz)	Refer to ANNEX A.13
LTE Band 26 (824 to 849MHz)	Refer to ANNEX A.14
LTE Band 38	Refer to ANNEX A.15
LTE Band 41	Refer to ANNEX A.16
LTE Band 66	Refer to ANNEX A.17

ANNEX B: The EUT Appearance

The EUT Appearance (internal and external photographs) are submitted separately.

ANNEX C: Test Setup Photographs

The Test Setup Photographs are submitted separately.