



Report No.: SUCR260400030104

Page: 1 of 712

TEST REPORT

Application No.: SUCR2604000301MO
FCC ID: 2BNX7S5560DNAA
Applicant: Eagle Wireless Inc.
Address of Applicant: 1974 E. 66th St., Suite 200-B Cleveland, OH 44103 USA
Manufacturer: Eagle Wireless Inc.
Address of Manufacturer: 1974 E. 66th St., Suite 200-B Cleveland, OH 44103 USA
Equipment Under Test (EUT):
EUT Name: 5G Sub-6 GHz Smart Module with Wi-Fi 6E & Bluetooth
Model No.: S5560D-NA
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2026-03-30
Date of Test: 2026-03-30 to 2026-05-30
Date of Issue: 2026-06-08

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record			
Version	Description	Date	Remark
00	Original	2026-06-08	/

Authorized for issue by:				
Prepared By		Nature Shen		
		Nature_Shen/Project Engineer		
Approved By		Cedar cheng		
		Cedar Cheng /Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Customer Declaration
Transmission in the Absence of Data		N/A	47 CFR Part 15, Subpart E 15.407 (c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions (Below 1GHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		ANSI C63.10 (2020) Section 6.6 & 12.7	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5 & 12.7.2	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Duty Cycle		ANSI C63.10 (2020) Section 12.2	ANSI C63.10 (2020) Section 12.2	Pass
99% Bandwidth		ANSI C63.10 (2020) Section 12.5.3	ANSI C63.10 (2020) Section 12.5.3	Pass
26dB Emission Bandwidth		ANSI C63.10 (2020) Section 12.5.2	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Minimum 6 dB Bandwidth (5.725-5.85 GHz band)		ANSI C63.10 (2020) Section 12.5.1	47 CFR Part 15, Subpart E 15.407 (e)	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 12.4	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Non-occupancy Period		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Channel Availability Check Time		KDB 905462 D02 Section 7.8.2	KDB 905462 D02 Section 5.1	Pass
Channel Move Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Channel Closing Transmission Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
U-NII Detection Bandwidth		KDB 905462 D02 Section 7.8.1	KDB 905462 D02 Section 5.1	Pass

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Environment Parameter	6
4.3 Description of Support Units	6
4.4 Measurement Uncertainty & Decision Rule	6
4.5 Test Location	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
6.2 Transmission in the Absence of Data	11
7 Radio Spectrum Matter Test Results	12
7.1 Radiated Emissions (Below 1GHz)	12
7.2 Radiated Emissions (Above 1GHz).....	17
7.3 Radiated Emissions which fall in the restricted bands	192
7.4 Duty Cycle	343
7.5 99% Bandwidth	344
7.6 26dB Emission Bandwidth.....	345
7.7 Minimum 6 dB Bandwidth (5.725-5.85 GHz band)	346
7.8 Maximum Conducted Output Power	347
7.9 Power Spectral Density	349
7.10 Non-occupancy Period	351
7.11 Channel Availability Check Time.....	354
7.12 Channel Move Time	357
7.13 Channel Closing Transmission Time	359
7.14 U-NII Detection Bandwidth	361
8 Test Setup Photo	363
9 EUT Constructional Details (EUT Photos).....	363
10 Appendix.....	364

4 General Information

4.1 Details of E.U.T.

Hardware Version:	R1.0
Software Version:	S5560DNAPAR04A01
SN:	P1Y25CJ43000041/ P1Y25CJ43000053/ P1Y25CJ43000026
Power supply:	12V
Operation Frequency/Number of channels (20MHz):	U-NII-1: 5180-5240MHz (4 Channels); U-NII-2A: 5260-5320MHz (4 Channels); U-NII-2C: 5500-5720MHz (12 Channels); U-NII-3: 5745-5825MHz (5 Channels)
Operation Frequency/Number of channels/(40MHz):	U-NII-1: 5190-5230MHz (2 Channels); U-NII-2A: 5270-5310MHz (2 Channels); U-NII-2C: 5510-5710MHz (6 Channels); U-NII-3: 5755-5795MHz (2 Channels)
Operation Frequency/Number of channels (80MHz):	U-NII-1: 5210MHz (1 Channel); U-NII-2A: 5290MHz (1 Channels); U-NII-2C: 5530-5690MHz (3 Channels); U-NII-3: 5775MHz (1 Channel)
Operation Frequency/Number of channels (160MHz):	U-NII-1&2A: 5250MHz (1 Channel); U-NII-2C: 5570MHz (1 Channels)
Modulation Type:	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM, 4096-QAM)
Channel Spacing:	802.11a/n/ac/ax 20: 20MHz; 802.11n/ac/ax 40: 40MHz; 802.11ac/ax 80: 80MHz; 802.11ax 160: 160MHz
DFS Function:	Master
TPC Function:	Support TPC function
Antenna Type:	Dipole Antenna
Antenna Gain:	Ant1:U-NII-1: -0.7dBi;U-NII-2A: -0.8dBi;U-NII-2C: -1.2dBi;U-NII-3: -1.5dBi (Provided by the manufacturer) Ant2:U-NII-1: -0.7dBi;U-NII-2A: -0.8dBi;U-NII-2C: -1.2dBi;U-NII-3: -1.5dBi (Provided by the manufacturer)
Antenna Number:	2

4.2 Environment Parameter

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	25	4
Note: NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature		

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Computer	Lenovo	T14	2YK6GR
Mouse	Lenovo	3D optical Mouse	N/A
Router	Smauwave Technology Co.,Ltd	SRT 421	RT421X02211300001

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
5	RF conducted power	$\pm 0.75\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 1.56\text{dB}$ (9KHz-30MHz)
		$\pm 4.80\text{dB}$ (30MHz-1GHz)
		$\pm 4.80\text{dB}$ (1GHz-18GHz)
		$\pm 4.80\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

Note:

1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).

2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).

3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 6336.01)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.is accredited by the American Association for Laboratory Accreditation (A2LA).

• **FCC (Designation Number: CN1312)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number:717327

• **ISED (CAB Identifier: CN0120)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
RF Conducted Test						
1	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
2	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-15	11/21/2025	11/20/2026
3	MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/14/2026	1/13/2027
4	Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-08-01	1/14/2026	1/13/2027
6	MXG Vector Signal Generator	ROHDE&SCHWARZ	SMR20	SUWI-01-33-01	11/21/2025	11/20/2026
7	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-13	5/8/2025	5/7/2026
					4/22/2026	4/21/2027
8	Wideband Radio Communication Test Station	Anritsu	MT8000A	SUWI-01-34-02	11/21/2025	11/20/2026
9	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/21/2025	11/20/2026
10	Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/21/2025	11/20/2026
11	Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/21/2025	11/20/2026
12	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
13	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/11/2026	2/10/2027
14	Temperature Chamber	GIANT FORCE	ICT-017-40-SP-SD	SUWI-01-13-02	5/7/2025	5/6/2026
					5/7/2026	5/6/2027
15	Measurement Software	TST	TST 272 V2.02	SUWI-03-55-03	NCR	NCR
16	RF Control unit	TST	TSCB3023R2	SUWI-02-20-01	NCR	NCR
17	RFCables	Tonscend	NA	SUWI-01-03-01	1/15/2026	1/14/2027
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/2/2026
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	11/20/2025	11/19/2026
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	1/14/2026	1/13/2027
6	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	11/29/2025	11/28/2027
7	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
8	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
9	Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027

10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/14/2026	1/13/2027
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/14/2026	1/13/2027
12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/14/2026	1/13/2027
13	Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	8/25/2025	8/24/2026
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	8/25/2025	8/24/2026
15	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	8/26/2025	8/25/2026
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-06	11/21/2025	11/20/2026
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	1/14/2026	1/13/2027
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/11/2026	2/10/2027
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR
21	RF Control unit	Tonscend	JS0806-1	SUWI-02-20-01	NCR	NCR
22	RFCables	Tonscend	NA	SUWI-01-03-02	1/15/2026	1/14/2027

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Dipole Antenna and no consideration of replacement. The best case gain of the

Ant1:U-NII-1: -0.7dBi;U-NII-2A: -0.8dBi;U-NII-2C: -1.2dBi;U-NII-3: -1.5dBi

Ant2:U-NII-1: -0.7dBi;U-NII-2A: -0.8dBi;U-NII-2C: -1.2dBi;U-NII-3: -1.5dBi

Antenna location: Refer to internal photo.



6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart E 15.407 (c)

6.2.2 Conclusion

6.2.2 Conclusion Standard Requirement: The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met. EUT Details: WIFI chip support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.

7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1. The above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C

Humidity: 41 % RH


Atmospheric Pressure: 1001 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.
Pre-scan	08	TX mode (U-NII-2A)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.

Pre-scan	09	TX mode (U-NII-2C)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-3)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.


EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.

Test Mode: 07; Polarity: Horizontal



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	34.365	50.89	12.76	-33.96	29.70	40.00	10.30	Horizontal
2	71.225	43.61	10.09	-33.41	20.29	40.00	19.71	Horizontal
3	196.1125	41.86	9.97	-32.28	19.55	43.50	23.95	Horizontal
4	294.325	46.34	12.69	-31.65	27.37	46.00	18.63	Horizontal
5	478.3825	36.24	17.05	-30.67	22.62	46.00	23.38	Horizontal
6	1000	27.29	24.50	-27.80	23.99	54.00	30.01	Horizontal

Test Mode: 07; Polarity: Vertical



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	49.1575	49.3	13.47	-33.70	29.07	40.00	10.93	Vertical
2	78.985	46.45	9.39	-33.35	22.49	40.00	17.51	Vertical
3	107.8425	47.76	10.10	-33.02	24.84	43.50	18.66	Vertical
4	188.8375	43.84	10.30	-32.34	21.81	43.50	21.69	Vertical
5	294.325	44.05	12.69	-31.65	25.08	46.00	20.92	Vertical
6	983.2675	27.33	24.37	-27.95	23.74	54.00	30.26	Vertical

7.2 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.6 & 12.7

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark:

1. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

2. Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C


Humidity: 43 % RH

Atmospheric Pressure: 1001 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	07	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-2A)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.
Final test	09	TX mode (U-NII-2C)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-3)_Keep the EUT in continuously transmitting mode with all modulation types.Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 40GHz, The points marked on below plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the below harmonics were the highest point could be found when testing, so only the below harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq$ 98%) for Average detection (AV) at frequency above 1GHz.

11a_TX_CH_36_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17984.6667	34.32	41.66	-30.96	45.01	54.00	8.99	Horizontal
2	5759.7917	41.34	33.78	-17.14	57.97	68.20	10.23	Horizontal
3	6906.7167	59.23	36.15	-42.63	52.75	68.20	15.45	Horizontal
4	9478.8833	48.78	38.05	-38.52	48.31	74.00	25.69	Horizontal
5	12881.35	45.02	39.76	-34.52	50.26	68.20	17.94	Horizontal
6	13619.2667	44.89	40.21	-34.29	50.81	68.20	17.39	Horizontal
7	17988.5	41.37	41.67	-30.95	52.08	74.00	21.92	Horizontal

11a_TX_CH_36_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17957.0667	34.41	41.58	-31.02	44.97	54.00	9.03	Vertical
2	6050.8333	40.87	34.60	-16.90	58.58	68.20	9.62	Vertical
3	6906.7167	52.08	36.15	-42.63	45.60	68.20	22.60	Vertical
4	9553.6333	49.17	38.06	-38.35	48.88	68.20	19.32	Vertical
5	12948.4333	45.19	39.84	-34.91	50.12	68.20	18.08	Vertical
6	13831.6333	44.80	40.32	-34.72	50.39	68.20	17.81	Vertical
7	17967.4167	42.07	41.61	-31.00	52.68	74.00	21.32	Vertical

11a_TX_CH_40_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17962.4333	34.42	41.59	-31.01	45.01	54.00	8.99	Horizontal
2	5760.25	40.49	33.78	-17.14	57.13	68.20	11.07	Horizontal
3	6933.55	59.20	36.19	-42.63	52.76	68.20	15.44	Horizontal
4	9509.55	48.41	38.05	-38.46	48.00	68.20	20.20	Horizontal
5	12836.8833	45.20	39.70	-34.66	50.24	68.20	17.96	Horizontal
6	14400.1167	44.34	40.16	-33.76	50.74	68.20	17.46	Horizontal
7	17971.6333	43.00	41.62	-30.99	53.63	74.00	20.37	Horizontal

11a_TX_CH_40_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17987.35	34.81	41.66	-30.96	45.52	54.00	8.48	Vertical
2	6140.2083	40.18	34.78	-16.73	58.23	68.20	9.97	Vertical
3	6933.1667	52.18	36.19	-42.63	45.74	68.20	22.46	Vertical
4	9575.1	48.33	38.06	-38.29	48.10	68.20	20.10	Vertical
5	11177.05	45.35	39.19	-35.22	49.33	74.00	24.67	Vertical
6	12859.5	45.09	39.73	-34.59	50.23	68.20	17.97	Vertical
7	17990.0333	42.31	41.67	-30.95	53.03	74.00	20.97	Vertical

11a_TX_CH_48_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17947.1	34.95	41.55	-31.04	45.46	54.00	8.54	Horizontal
2	6267.625	40.46	35.04	-16.97	58.53	68.20	9.67	Horizontal
3	6986.45	59.18	36.28	-42.63	52.83	68.20	15.37	Horizontal
4	9511.0833	49.38	38.05	-38.46	48.97	68.20	19.23	Horizontal
5	12871.7667	46.21	39.75	-34.55	51.41	68.20	16.79	Horizontal
6	14366	44.92	40.18	-34.17	50.93	68.20	17.27	Horizontal
7	17903.0167	42.77	41.42	-31.12	53.06	74.00	20.94	Horizontal

11a_TX_CH_48_Veritical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17947.1	34.58	41.55	-31.04	45.09	54.00	8.91	Vertical
2	6053.5833	40.17	34.61	-16.88	57.89	68.20	10.31	Vertical
3	6986.45	53.34	36.28	-42.63	46.99	68.20	21.21	Vertical
4	9527.95	49.15	38.05	-38.41	48.79	68.20	19.41	Vertical
5	12817.3333	46.44	39.68	-34.72	51.40	68.20	16.80	Vertical
6	13543.3667	45.73	40.17	-34.67	51.23	68.20	16.97	Vertical
7	17990.0333	42.42	41.67	-30.95	53.14	74.00	20.86	Vertical

11a_TX_CH_52_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17964.7333	35.29	41.60	-31.00	45.89	54.00	8.11	Horizontal
2	5760.25	40.78	33.78	-17.14	57.42	68.20	10.78	Horizontal
3	7013.2833	59.63	36.30	-42.61	53.32	68.20	14.88	Horizontal
4	9488.0833	49.20	38.05	-38.51	48.74	74.00	25.26	Horizontal
5	11178.2	44.80	39.19	-35.21	48.78	74.00	25.22	Horizontal
6	12956.1	46.00	39.85	-34.98	50.87	68.20	17.33	Horizontal
7	17981.2167	42.97	41.65	-30.97	53.65	74.00	20.35	Horizontal

11a_TX_CH_52_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17991.1833	34.81	41.67	-30.95	45.54	54.00	8.46	Vertical
2	5693.7917	40.15	33.58	-17.32	56.41	68.20	11.79	Vertical
3	7013.6667	52.82	36.30	-42.61	46.51	68.20	21.69	Vertical
4	9548.2667	48.53	38.05	-38.36	48.23	68.20	19.97	Vertical
5	11183.5667	44.47	39.19	-35.17	48.49	74.00	25.51	Vertical
6	12829.9833	45.87	39.70	-34.68	50.88	68.20	17.32	Vertical
7	17954.3833	42.73	41.57	-31.02	53.28	74.00	20.72	Vertical

11a_TX_CH_60_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17994.25	34.87	41.68	-30.94	45.61	54.00	8.39	Horizontal
2	6260.2917	40.15	35.02	-16.95	58.22	68.20	9.98	Horizontal
3	7066.5667	58.93	36.30	-42.53	52.70	68.20	15.50	Horizontal
4	9523.7333	48.15	38.05	-38.43	47.78	68.20	20.42	Horizontal
5	11182.0333	44.75	39.19	-35.18	48.76	74.00	25.24	Horizontal
6	12926.5833	45.52	39.81	-34.71	50.62	68.20	17.58	Horizontal
7	17972.4	42.88	41.62	-30.99	53.51	74.00	20.49	Horizontal

11a_TX_CH_60_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17976.6167	35.01	41.63	-30.98	45.67	54.00	8.33	Vertical
2	6119.5833	40.13	34.74	-16.71	58.16	68.20	10.04	Vertical
3	7066.5667	52.04	36.30	-42.53	45.81	68.20	22.39	Vertical
4	9481.5667	48.99	38.05	-38.51	48.52	74.00	25.48	Vertical
5	12835.35	45.95	39.70	-34.67	50.99	68.20	17.21	Vertical
6	14294.7	45.30	40.22	-34.99	50.53	68.20	17.67	Vertical
7	17971.6333	42.89	41.62	-30.99	53.52	74.00	20.48	Vertical

11a_TX_CH_64_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17957.45	35.11	41.58	-31.02	45.67	54.00	8.33	Horizontal
2	6220.4167	40.45	34.94	-16.86	58.53	68.20	9.67	Horizontal
3	7093.0167	58.39	36.30	-42.49	52.20	68.20	16.00	Horizontal
4	9446.3	48.93	38.04	-38.56	48.41	74.00	25.59	Horizontal
5	12857.9667	45.67	39.73	-34.59	50.81	68.20	17.39	Horizontal
6	13542.6	45.80	40.17	-34.68	51.29	68.20	16.91	Horizontal
7	17942.5	42.95	41.53	-31.04	53.44	74.00	20.56	Horizontal

11a_TX_CH_64_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17968.1833	35.49	41.61	-30.99	46.10	54.00	7.90	Vertical
2	6150.75	41.20	34.80	-16.75	59.26	68.20	8.94	Vertical
3	7093.4	53.24	36.30	-42.49	47.05	68.20	21.15	Vertical
4	9507.25	49.26	38.05	-38.47	48.84	68.20	19.36	Vertical
5	11134.5	44.93	39.22	-35.51	48.64	74.00	25.36	Vertical
6	12886.7167	45.49	39.76	-34.50	50.75	68.20	17.45	Vertical
7	17939.8167	42.73	41.53	-31.05	53.21	74.00	20.79	Vertical

11a_TX_CH_100_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17911.45	35.40	41.44	-31.11	45.74	54.00	8.26	Horizontal
2	6239.6667	40.12	34.98	-16.90	58.20	68.20	10.00	Horizontal
3	6917.0667	51.08	36.17	-42.63	44.62	68.20	23.58	Horizontal
4	9463.9333	49.29	38.05	-38.54	48.80	74.00	25.20	Horizontal
5	12791.65	46.32	39.65	-34.75	51.22	68.20	16.98	Horizontal
6	14986.2333	44.71	39.81	-34.12	50.39	68.20	17.81	Horizontal
7	17977	43.14	41.63	-30.98	53.80	74.00	20.20	Horizontal

11a_TX_CH_100_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17959.75	35.27	41.58	-31.01	45.84	54.00	8.16	Vertical
2	6225.9167	40.82	34.95	-16.87	58.90	68.20	9.30	Vertical
3	7915.2667	49.81	37.13	-41.45	45.49	68.20	22.71	Vertical
4	9470.0667	48.47	38.05	-38.53	47.99	74.00	26.01	Vertical
5	12799.7	45.79	39.66	-34.78	50.67	68.20	17.53	Vertical
6	13913.2833	44.45	40.36	-34.03	50.78	68.20	17.42	Vertical
7	17971.6333	43.22	41.62	-30.99	53.85	74.00	20.15	Vertical

11a_TX_CH_116_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17926.7833	34.84	41.49	-31.08	45.25	54.00	8.75	Horizontal
2	6139.2917	40.19	34.78	-16.73	58.24	68.20	9.96	Horizontal
3	6691.2833	56.55	35.81	-42.85	49.51	68.20	18.69	Horizontal
4	9460.8667	48.90	38.05	-38.54	48.41	74.00	25.59	Horizontal
5	11391.7167	44.86	39.06	-35.64	48.28	74.00	25.72	Horizontal
6	12798.9333	46.13	39.66	-34.78	51.01	68.20	17.19	Horizontal
7	17980.45	42.49	41.64	-30.97	53.16	74.00	20.84	Horizontal

11a_TX_CH_116_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17926.4	34.81	41.49	-31.08	45.22	54.00	8.78	Vertical
2	6094.8333	40.42	34.69	-16.70	58.41	68.20	9.79	Vertical
3	6749.9333	50.34	35.90	-42.85	43.39	68.20	24.81	Vertical
4	9516.8333	48.74	38.05	-38.44	48.35	68.20	19.85	Vertical
5	12806.6	45.98	39.67	-34.76	50.89	68.20	17.31	Vertical
6	13861.15	45.37	40.33	-34.32	51.38	68.20	16.82	Vertical
7	17934.8333	43.47	41.51	-31.06	53.92	74.00	20.08	Vertical

11a_TX_CH_120_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17983.1333	34.66	41.65	-30.96	45.35	54.00	8.65	Horizontal
2	6143.875	40.45	34.79	-16.74	58.50	68.20	9.70	Horizontal
3	6718.8833	54.63	35.85	-42.85	47.63	68.20	20.57	Horizontal
4	9509.9333	49.08	38.05	-38.46	48.67	68.20	19.53	Horizontal
5	12874.0667	46.26	39.75	-34.54	51.47	68.20	16.73	Horizontal
6	13853.1	45.74	40.33	-34.43	51.63	68.20	16.57	Horizontal
7	17968.5667	42.17	41.61	-30.99	52.79	74.00	21.21	Horizontal

11a_TX_CH_120_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17983.5167	34.70	41.65	-30.96	45.39	54.00	8.61	Vertical
2	6154.4167	40.27	34.81	-16.75	58.33	68.20	9.87	Vertical
3	6718.8833	53.10	35.85	-42.85	46.10	68.20	22.10	Vertical
4	9483.1	49.62	38.05	-38.51	49.16	74.00	24.84	Vertical
5	10186.9	46.61	38.32	-36.39	48.54	68.20	19.66	Vertical
6	12965.6833	45.78	39.86	-35.07	50.57	68.20	17.63	Vertical
7	17996.1667	42.12	41.69	-30.94	52.87	74.00	21.13	Vertical

11a_TX_CH_124_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17961.6667	33.95	41.59	-31.01	44.53	54.00	9.47	Horizontal
2	6096.2083	40.03	34.69	-16.70	58.03	68.20	10.17	Horizontal
3	6750.3167	55.02	35.90	-42.85	48.07	68.20	20.13	Horizontal
4	9467.7667	48.68	38.05	-38.53	48.19	74.00	25.81	Horizontal
5	11193.5333	44.47	39.18	-35.10	48.55	74.00	25.45	Horizontal
6	12803.9167	46.12	39.66	-34.77	51.02	68.20	17.18	Horizontal
7	17977	41.89	41.63	-30.98	52.55	74.00	21.45	Horizontal

11a_TX_CH_124_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17992.3333	33.78	41.68	-30.95	44.51	54.00	9.49	Vertical
2	6141.5833	39.89	34.78	-16.73	57.94	68.20	10.26	Vertical
3	6813.5667	50.17	36.00	-42.82	43.35	68.20	24.85	Vertical
4	9497.2833	49.14	38.05	-38.49	48.70	74.00	25.30	Vertical
5	12870.2333	46.02	39.74	-34.56	51.21	68.20	16.99	Vertical
6	14515.5	45.07	40.09	-34.78	50.38	68.20	17.82	Vertical
7	17984.6667	41.74	41.66	-30.96	52.43	74.00	21.57	Vertical

11a_TX_CH_128_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17976.2333	33.87	41.63	-30.98	44.52	54.00	9.48	Horizontal
2	6328.5833	39.49	35.16	-16.91	57.74	68.20	10.46	Horizontal
3	6768.3333	53.96	35.93	-42.85	47.04	68.20	21.16	Horizontal
4	8478.7667	50.12	37.64	-40.39	47.36	74.00	26.64	Horizontal
5	9518.75	48.31	38.05	-38.44	47.92	68.20	20.28	Horizontal
6	12800.0833	46.75	39.66	-34.78	51.63	68.20	16.57	Horizontal
7	17963.9667	41.48	41.60	-31.00	52.07	74.00	21.93	Horizontal

11a_TX_CH_128_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17928.3167	34.16	41.49	-31.07	44.58	54.00	9.42	Vertical
2	6307.9583	39.65	35.12	-17.00	57.76	68.20	10.44	Vertical
3	7592.8833	50.50	36.49	-41.82	45.17	74.00	28.83	Vertical
4	9568.5833	48.39	38.06	-38.30	48.14	68.20	20.06	Vertical
5	12779.3833	45.24	39.64	-34.71	50.17	68.20	18.03	Vertical
6	14338.4	43.70	40.20	-34.51	49.39	68.20	18.81	Vertical
7	17930.6167	41.82	41.50	-31.07	52.25	74.00	21.75	Vertical

11a_TX_CH_140_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17927.1667	34.90	41.49	-31.08	45.31	54.00	8.69	Horizontal
2	6099.875	40.38	34.70	-16.68	58.40	68.20	9.80	Horizontal
3	6836.95	52.79	36.04	-42.77	46.06	68.20	22.14	Horizontal
4	7868.8833	50.06	37.04	-41.35	45.75	68.20	22.45	Horizontal
5	9473.5167	48.31	38.05	-38.52	47.83	74.00	26.17	Horizontal
6	12948.4333	45.55	39.84	-34.91	50.48	68.20	17.72	Horizontal
7	17996.1667	41.75	41.69	-30.94	52.50	74.00	21.50	Horizontal

11a_TX_CH_140_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17984.2833	34.36	41.65	-30.96	45.05	54.00	8.95	Vertical
2	6243.3333	40.61	34.99	-16.91	58.69	68.20	9.51	Vertical
3	6969.5833	50.94	36.25	-42.63	44.56	68.20	23.64	Vertical
4	9499.5833	48.45	38.05	-38.49	48.01	74.00	25.99	Vertical
5	12757.9167	45.48	39.61	-34.63	50.46	68.20	17.74	Vertical
6	14424.2667	44.12	40.15	-34.02	50.25	68.20	17.95	Vertical
7	17983.9	41.89	41.65	-30.96	52.58	74.00	21.42	Vertical

11a_TX_CH_144_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17970.1	33.93	41.61	-30.99	44.55	54.00	9.45	Horizontal
2	6248.375	40.13	35.00	-16.92	58.21	68.20	9.99	Horizontal
3	6870.3	51.19	36.09	-42.70	44.59	68.20	23.61	Horizontal
4	7996.5333	49.23	37.29	-41.19	45.33	68.20	22.87	Horizontal
5	9545.5833	48.40	38.05	-38.37	48.09	68.20	20.11	Horizontal
6	13401.9167	44.08	40.10	-34.47	49.71	68.20	18.49	Horizontal
7	17973.9333	42.02	41.62	-30.98	52.66	74.00	21.34	Horizontal

11a_TX_CH_144_Veritical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17970.1	34.34	41.61	-30.99	44.96	54.00	9.04	Vertical
2	6075.125	40.02	34.65	-16.79	57.88	68.20	10.32	Vertical
3	7919.1	50.58	37.14	-41.44	46.28	68.20	21.92	Vertical
4	9501.8833	48.38	38.05	-38.48	47.95	68.20	20.25	Vertical
5	10970.4333	44.74	39.26	-36.05	47.95	74.00	26.05	Vertical
6	12958.7833	46.41	39.85	-35.01	51.25	68.20	16.95	Vertical
7	17916.8167	42.01	41.46	-31.10	52.37	74.00	21.63	Vertical

11a_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17996.55	34.28	41.69	-30.94	45.03	54.00	8.97	Horizontal
2	6130.125	40.29	34.76	-16.72	58.33	68.20	9.87	Horizontal
3	6890.2333	51.18	36.12	-42.65	44.65	68.20	23.55	Horizontal
4	8935.3167	48.16	37.95	-39.50	46.61	68.20	21.59	Horizontal
5	9555.9333	47.99	38.06	-38.34	47.71	68.20	20.49	Horizontal
6	13009.3833	46.35	39.90	-35.36	50.90	68.20	17.30	Horizontal
7	17957.45	42.21	41.58	-31.02	52.77	74.00	21.23	Horizontal

11a_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17986.2	34.75	41.66	-30.96	45.45	54.00	8.55	Vertical
2	6192.9167	40.80	34.89	-16.80	58.89	68.20	9.31	Vertical
3	6968.8167	51.03	36.25	-42.63	44.65	68.20	23.55	Vertical
4	8014.55	49.02	37.31	-41.16	45.17	68.20	23.03	Vertical
5	9485.7833	48.50	38.05	-38.51	48.04	74.00	25.96	Vertical
6	12901.2833	45.44	39.78	-34.47	50.75	68.20	17.45	Vertical
7	17972.0167	41.87	41.62	-30.99	52.50	74.00	21.50	Vertical

11a_TX_CH_157_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17932.15	34.49	41.50	-31.07	44.93	54.00	9.07	Horizontal
2	6263.9583	40.29	35.03	-16.96	58.36	68.20	9.84	Horizontal
3	6940.8333	53.03	36.21	-42.63	46.61	68.20	21.59	Horizontal
4	9530.6333	48.56	38.05	-38.41	48.21	68.20	19.99	Horizontal
5	12917	45.44	39.80	-34.62	50.62	68.20	17.58	Horizontal
6	13612.75	45.05	40.21	-34.21	51.05	68.20	17.15	Horizontal
7	17933.6833	42.11	41.51	-31.06	52.56	74.00	21.44	Horizontal

11a_TX_CH_157_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17955.9167	35.14	41.57	-31.02	45.69	54.00	8.31	Vertical
2	6292.8333	39.91	35.09	-17.02	57.97	68.20	10.23	Vertical
3	6982.6167	50.12	36.27	-42.63	43.76	68.20	24.44	Vertical
4	9583.5333	48.06	38.06	-38.26	47.85	68.20	20.35	Vertical
5	11186.25	43.84	39.19	-35.15	47.87	74.00	26.13	Vertical
6	12854.5167	46.05	39.73	-34.61	51.17	68.20	17.03	Vertical
7	17936.3667	42.20	41.52	-31.06	52.66	74.00	21.34	Vertical

11a_TX_CH_165_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17988.5	34.48	41.67	-30.95	45.19	54.00	8.81	Horizontal
2	6251.5833	40.67	35.00	-16.93	58.74	68.20	9.46	Horizontal
3	6974.5667	50.64	36.26	-42.63	44.27	68.20	23.93	Horizontal
4	9514.9167	49.43	38.05	-38.45	49.03	68.20	19.17	Horizontal
5	11141.0167	44.66	39.22	-35.47	48.41	74.00	25.59	Horizontal
6	12948.05	45.74	39.84	-34.91	50.67	68.20	17.53	Horizontal
7	17965.8833	42.46	41.60	-31.00	53.06	74.00	20.94	Horizontal

11a_TX_CH_165_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17934.0667	34.34	41.51	-31.06	44.79	54.00	9.21	Vertical
2	6203.4583	40.41	34.91	-16.82	58.50	68.20	9.70	Vertical
3	6842.7	50.70	36.05	-42.76	43.99	68.20	24.21	Vertical
4	7965.1	49.23	37.23	-41.29	45.17	68.20	23.03	Vertical
5	9577.0167	48.13	38.06	-38.28	47.91	68.20	20.29	Vertical
6	12844.55	45.53	39.71	-34.64	50.61	68.20	17.59	Vertical
7	17987.35	42.14	41.66	-30.96	52.85	74.00	21.15	Vertical

11n(HT20)_TX_CH_36_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17970.4833	34.11	41.61	-30.99	44.74	54.00	9.26	Horizontal
2	6112.25	40.04	34.72	-16.70	58.07	68.20	10.13	Horizontal
3	6906.7167	57.83	36.15	-42.63	51.35	68.20	16.85	Horizontal
4	7901.4667	49.60	37.10	-41.50	45.21	68.20	22.99	Horizontal
5	9499.2	48.17	38.05	-38.49	47.73	74.00	26.27	Horizontal
6	12744.5	45.34	39.59	-34.59	50.35	68.20	17.85	Horizontal
7	17970.1	42.43	41.61	-30.99	53.05	74.00	20.95	Horizontal

11n(HT20)_TX_CH_36_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17985.05	34.25	41.66	-30.96	44.95	54.00	9.05	Vertical
2	6174.5833	40.80	34.85	-16.78	58.87	68.20	9.33	Vertical
3	6906.3333	53.04	36.15	-42.63	46.56	68.20	21.64	Vertical
4	7842.4333	49.58	36.98	-41.22	45.34	68.20	22.86	Vertical
5	9519.1333	48.22	38.05	-38.44	47.83	68.20	20.37	Vertical
6	13143.9333	44.66	39.97	-34.87	49.76	68.20	18.44	Vertical
7	17963.9667	42.03	41.60	-31.00	52.62	74.00	21.38	Vertical

11n(HT20)_TX_CH_40_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17939.8167	34.86	41.53	-31.05	45.34	54.00	8.66	Horizontal
2	6075.125	40.43	34.65	-16.79	58.29	68.20	9.91	Horizontal
3	6933.1667	60.49	36.19	-42.63	54.05	68.20	14.15	Horizontal
4	7991.9333	50.71	37.28	-41.21	46.79	68.20	21.41	Horizontal
5	9521.8167	48.52	38.05	-38.43	48.14	68.20	20.06	Horizontal
6	12787.4333	45.99	39.64	-34.74	50.90	68.20	17.30	Horizontal
7	17987.35	42.30	41.66	-30.96	53.01	74.00	20.99	Horizontal

11n(HT20)_TX_CH_40_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17981.9833	34.50	41.65	-30.97	45.18	54.00	8.82	Vertical
2	6216.2917	40.18	34.93	-16.85	58.27	68.20	9.93	Vertical
3	6933.1667	54.16	36.19	-42.63	47.72	68.20	20.48	Vertical
4	7863.9	49.56	37.03	-41.33	45.26	68.20	22.94	Vertical
5	9517.2167	48.62	38.05	-38.44	48.23	68.20	19.97	Vertical
6	12952.2667	46.32	39.84	-34.95	51.22	68.20	16.98	Vertical
7	17892.2833	42.29	41.39	-31.19	52.49	74.00	21.51	Vertical

11n(HT20)_TX_CH_48_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17996.55	34.16	41.69	-30.94	44.91	54.00	9.09	Horizontal
2	6226.8333	40.92	34.95	-16.87	59.00	68.20	9.20	Horizontal
3	6986.8333	58.49	36.28	-42.63	52.14	68.20	16.06	Horizontal
4	8008.0333	48.82	37.31	-41.17	44.96	68.20	23.24	Horizontal
5	9509.55	48.71	38.05	-38.46	48.30	68.20	19.90	Horizontal
6	12972.9667	46.45	39.87	-35.14	51.18	68.20	17.02	Horizontal
7	17989.65	42.06	41.67	-30.95	52.78	74.00	21.22	Horizontal

11n(HT20)_TX_CH_48_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17934.8333	34.26	41.51	-31.06	44.71	54.00	9.29	Vertical
2	6180.0833	40.56	34.86	-16.78	58.64	68.20	9.56	Vertical
3	6986.8333	53.63	36.28	-42.63	47.28	68.20	20.92	Vertical
4	7864.6667	49.64	37.03	-41.33	45.34	68.20	22.86	Vertical
5	9540.9833	48.14	38.05	-38.38	47.81	68.20	20.39	Vertical
6	12804.6833	45.94	39.67	-34.77	50.84	68.20	17.36	Vertical
7	17949.4	42.16	41.55	-31.03	52.68	74.00	21.32	Vertical

11n(HT20)_TX_CH_52_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17966.2667	34.03	41.60	-31.00	44.63	54.00	9.37	Horizontal
2	6286.4167	39.82	35.07	-17.01	57.88	68.20	10.32	Horizontal
3	7013.2833	58.90	36.30	-42.61	52.59	68.20	15.61	Horizontal
4	9519.1333	48.48	38.05	-38.44	48.09	68.20	20.11	Horizontal
5	11885.8333	43.70	38.77	-34.71	47.75	74.00	26.25	Horizontal
6	12857.5833	45.30	39.73	-34.60	50.43	68.20	17.77	Horizontal
7	17950.9333	42.15	41.56	-31.03	52.68	74.00	21.32	Horizontal

11n(HT20)_TX_CH_52_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5968.3333	39.62	34.40	-17.02	57.00	68.20	11.20	Vertical
2	7012.9	52.35	36.30	-42.61	46.04	68.20	22.16	Vertical
3	9502.65	49.49	38.05	-38.48	49.06	68.20	19.14	Vertical
4	10171.1833	46.31	38.31	-36.59	48.03	68.20	20.17	Vertical
5	12866.4	46.27	39.74	-34.57	51.44	68.20	16.76	Vertical
6	17968.1833	41.92	41.61	-30.99	52.53	74.00	21.47	Vertical

11n(HT20)_TX_CH_60_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17965.1167	34.45	41.60	-31.00	45.05	54.00	8.95	Horizontal
2	5907.375	39.03	34.22	-16.83	56.42	68.20	11.78	Horizontal
3	7066.95	57.70	36.30	-42.53	51.47	68.20	16.73	Horizontal
4	8368.75	47.61	37.56	-40.73	44.44	74.00	29.56	Horizontal
5	9519.9	48.79	38.05	-38.44	48.41	68.20	19.79	Horizontal
6	12921.6	45.08	39.81	-34.66	50.23	68.20	17.97	Horizontal
7	17962.4333	42.67	41.59	-31.01	53.26	74.00	20.74	Horizontal

11n(HT20)_TX_CH_60_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17973.55	34.23	41.62	-30.98	44.87	54.00	9.13	Vertical
2	6063.6667	39.34	34.63	-16.84	57.13	68.20	11.07	Vertical
3	7066.5667	53.26	36.30	-42.53	47.03	68.20	21.17	Vertical
4	8697.2667	47.20	37.79	-39.75	45.24	68.20	22.96	Vertical
5	10195.7167	46.18	38.33	-36.28	48.23	68.20	19.97	Vertical
6	13606.6167	44.68	40.20	-34.13	50.76	68.20	17.44	Vertical
7	17954.3833	41.81	41.57	-31.02	52.36	74.00	21.64	Vertical

11n(HT20)_TX_CH_64_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17969.7167	33.96	41.61	-30.99	44.58	54.00	9.42	Horizontal
2	6254.3333	40.35	35.01	-16.93	58.42	68.20	9.78	Horizontal
3	7093.4	57.31	36.30	-42.49	51.12	68.20	17.08	Horizontal
4	8473.7833	48.90	37.63	-40.42	46.11	74.00	27.89	Horizontal
5	9457.0333	50.02	38.05	-38.55	49.52	74.00	24.48	Horizontal
6	12774.7833	45.34	39.63	-34.69	50.28	68.20	17.92	Horizontal
7	17968.5667	42.26	41.61	-30.99	52.88	74.00	21.12	Horizontal

11n(HT20)_TX_CH_64_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17942.1167	35.63	41.53	-31.05	46.12	54.00	7.88	Vertical
2	6155.3333	39.76	34.81	-16.75	57.82	68.20	10.38	Vertical
3	7093.4	52.16	36.30	-42.49	45.97	68.20	22.23	Vertical
4	9491.5333	48.96	38.05	-38.50	48.51	74.00	25.49	Vertical
5	11178.9667	44.34	39.19	-35.21	48.33	74.00	25.67	Vertical
6	12815.0333	45.69	39.68	-34.73	50.64	68.20	17.56	Vertical
7	17973.9333	41.72	41.62	-30.98	52.36	74.00	21.64	Vertical

11n(HT20)_TX_CH_100_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17955.9167	33.76	41.57	-31.02	44.31	54.00	9.69	Horizontal
2	6236.4583	40.00	34.97	-16.89	58.08	68.20	10.12	Horizontal
3	6599.6667	51.44	35.66	-42.85	44.25	68.20	23.95	Horizontal
4	7945.55	49.80	37.19	-41.35	45.64	68.20	22.56	Horizontal
5	9455.1167	47.98	38.05	-38.55	47.48	74.00	26.52	Horizontal
6	12951.5	45.40	39.84	-34.94	50.30	68.20	17.90	Horizontal
7	17920.2667	42.37	41.47	-31.09	52.75	74.00	21.25	Horizontal

11n(HT20)_TX_CH_100_Veritical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17972.0167	34.29	41.62	-30.99	44.92	54.00	9.08	Vertical
2	6131.0417	39.77	34.76	-16.72	57.81	68.20	10.39	Vertical
3	6853.8167	49.83	36.07	-42.73	43.16	68.20	25.04	Vertical
4	7968.9333	50.14	37.24	-41.28	46.10	68.20	22.10	Vertical
5	9565.5167	48.42	38.06	-38.31	48.16	68.20	20.04	Vertical
6	12938.0833	46.06	39.83	-34.81	51.07	68.20	17.13	Vertical
7	17959.3667	42.83	41.58	-31.01	53.40	74.00	20.60	Vertical

11n(HT20)_TX_CH_116_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17971.25	34.09	41.62	-30.99	44.72	54.00	9.28	Horizontal
2	6043.9583	40.45	34.59	-16.93	58.11	68.20	10.09	Horizontal
3	6690.1333	54.62	35.80	-42.85	47.57	68.20	20.63	Horizontal
4	7809.85	49.68	36.92	-41.07	45.53	68.20	22.67	Horizontal
5	9503.4167	48.31	38.05	-38.48	47.88	68.20	20.32	Horizontal
6	12833.8167	45.82	39.70	-34.67	50.85	68.20	17.35	Horizontal
7	17993.1	41.19	41.68	-30.94	51.93	74.00	22.07	Horizontal

11n(HT20)_TX_CH_116_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17991.1833	33.58	41.67	-30.95	44.31	54.00	9.69	Vertical
2	6137.4583	39.80	34.77	-16.73	57.85	68.20	10.35	Vertical
3	6697.8	51.74	35.82	-42.85	44.71	68.20	23.49	Vertical
4	8547.3833	48.13	37.68	-40.24	45.58	68.20	22.62	Vertical
5	9501.1167	48.68	38.05	-38.49	48.24	68.20	19.96	Vertical
6	12824.6167	45.29	39.69	-34.70	50.28	68.20	17.92	Vertical
7	17963.9667	42.13	41.60	-31.00	52.72	74.00	21.28	Vertical

11n(HT20)_TX_CH_120_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17955.5333	33.95	41.57	-31.02	44.50	54.00	9.50	Horizontal
2	6008.6667	40.24	34.52	-17.08	57.68	68.20	10.52	Horizontal
3	6723.1	56.62	35.86	-42.85	49.63	68.20	18.57	Horizontal
4	8022.9833	48.95	37.32	-41.15	45.12	68.20	23.08	Horizontal
5	9499.5833	48.46	38.05	-38.49	48.02	74.00	25.98	Horizontal
6	12869.85	46.16	39.74	-34.56	51.35	68.20	16.85	Horizontal
7	17962.05	41.96	41.59	-31.01	52.54	74.00	21.46	Horizontal

11n(HT20)_TX_CH_120_Veritical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17905.3167	33.81	41.43	-31.12	44.12	54.00	9.88	Vertical
2	6186.9583	40.31	34.87	-16.79	58.39	68.20	9.81	Vertical
3	6716.2	50.35	35.85	-42.85	43.35	68.20	24.85	Vertical
4	9505.7167	48.38	38.05	-38.47	47.96	68.20	20.24	Vertical
5	11181.65	44.65	39.19	-35.19	48.65	74.00	25.35	Vertical
6	12830.75	45.30	39.70	-34.68	50.32	68.20	17.88	Vertical
7	17955.9167	41.92	41.57	-31.02	52.47	74.00	21.53	Vertical

11n(HT20)_TX_CH_124_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17937.5167	34.02	41.52	-31.05	44.48	54.00	9.52	Horizontal
2	6215.8333	40.24	34.93	-16.85	58.33	68.20	9.87	Horizontal
3	6744.5667	55.08	35.89	-42.85	48.12	68.20	20.08	Horizontal
4	8511.7333	48.33	37.66	-40.28	45.71	68.20	22.49	Horizontal
5	9558.6167	48.91	38.06	-38.33	48.63	68.20	19.57	Horizontal
6	12841.4833	45.25	39.71	-34.65	50.31	68.20	17.89	Horizontal
7	17934.8333	42.85	41.51	-31.06	53.30	74.00	20.70	Horizontal

11n(HT20)_TX_CH_124_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17986.5833	33.77	41.66	-30.96	44.47	54.00	9.53	Vertical
2	6154.4167	40.53	34.81	-16.75	58.59	68.20	9.61	Vertical
3	6740.35	50.37	35.88	-42.85	43.40	68.20	24.80	Vertical
4	7933.6667	49.62	37.17	-41.39	45.40	68.20	22.80	Vertical
5	9516.0667	48.13	38.05	-38.45	47.73	68.20	20.47	Vertical
6	12816.95	45.65	39.68	-34.73	50.60	68.20	17.60	Vertical
7	17908	41.92	41.43	-31.11	52.24	74.00	21.76	Vertical

11n(HT20)_TX_CH_128_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17977.3833	33.99	41.63	-30.98	44.65	54.00	9.35	Horizontal
2	6225.4583	40.15	34.95	-16.87	58.23	68.20	9.97	Horizontal
3	6769.1	55.81	35.93	-42.85	48.89	68.20	19.31	Horizontal
4	7851.6333	49.32	37.00	-41.27	45.06	68.20	23.14	Horizontal
5	9478.1167	48.96	38.05	-38.52	48.49	74.00	25.51	Horizontal
6	12903.2	45.17	39.78	-34.49	50.46	68.20	17.74	Horizontal
7	17961.2833	42.72	41.59	-31.01	53.30	74.00	20.70	Horizontal

11n(HT20)_TX_CH_128_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17969.3333	33.58	41.61	-30.99	44.20	54.00	9.80	Vertical
2	6051.75	40.01	34.60	-16.89	57.72	68.20	10.48	Vertical
3	7208.7833	49.79	36.30	-42.03	44.06	68.20	24.14	Vertical
4	8510.5833	47.90	37.66	-40.28	45.28	68.20	22.92	Vertical
5	9507.6333	48.29	38.05	-38.47	47.87	68.20	20.33	Vertical
6	12929.65	45.13	39.82	-34.74	50.21	68.20	17.99	Vertical
7	17973.1667	41.27	41.62	-30.98	51.91	74.00	22.09	Vertical

11n(HT20)_TX_CH_140_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17969.3333	33.71	41.61	-30.99	44.33	54.00	9.67	Horizontal
2	6207.5833	39.66	34.92	-16.83	57.75	68.20	10.45	Horizontal
3	6840.0167	52.05	36.04	-42.76	45.33	68.20	22.87	Horizontal
4	7924.85	49.01	37.15	-41.42	44.74	68.20	23.46	Horizontal
5	9491.5333	48.15	38.05	-38.50	47.70	74.00	26.30	Horizontal
6	12851.0667	45.46	39.72	-34.62	50.56	68.20	17.64	Horizontal
7	17898.4167	41.93	41.41	-31.14	52.19	74.00	21.81	Horizontal

11n(HT20)_TX_CH_140_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17994.6333	33.83	41.68	-30.94	44.57	54.00	9.43	Vertical
2	6211.7083	40.41	34.92	-16.84	58.50	68.20	9.70	Vertical
3	6986.8333	49.84	36.28	-42.63	43.49	68.20	24.71	Vertical
4	7896.4833	49.47	37.09	-41.48	45.08	68.20	23.12	Vertical
5	9498.4333	48.71	38.05	-38.49	48.27	74.00	25.73	Vertical
6	12920.0667	45.42	39.80	-34.65	50.58	68.20	17.62	Vertical
7	17988.5	41.70	41.67	-30.95	52.41	74.00	21.59	Vertical

11n(HT20)_TX_CH_144_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17930.6167	34.24	41.50	-31.07	44.67	54.00	9.33	Horizontal
2	6296.0417	39.90	35.09	-17.03	57.96	68.20	10.24	Horizontal
3	6866.0833	51.88	36.09	-42.70	45.26	68.20	22.94	Horizontal
4	9542.9	48.57	38.05	-38.37	48.25	68.20	19.95	Horizontal
5	12945.3667	45.39	39.83	-34.88	50.34	68.20	17.86	Horizontal
6	14492.5	43.99	40.10	-34.74	49.35	74.00	24.65	Horizontal
7	17961.2833	41.97	41.59	-31.01	52.55	74.00	21.45	Horizontal

11n(HT20)_TX_CH_144_Veritical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17927.1667	34.22	41.49	-31.08	44.63	54.00	9.37	Vertical
2	6218.5833	40.12	34.94	-16.85	58.20	68.20	10.00	Vertical
3	7046.6333	49.84	36.30	-42.56	43.58	68.20	24.62	Vertical
4	9483.4833	48.69	38.05	-38.51	48.23	74.00	25.77	Vertical
5	12821.9333	45.55	39.69	-34.71	50.53	68.20	17.67	Vertical
6	14842.4833	43.08	39.89	-33.92	49.06	68.20	19.14	Vertical
7	17920.65	42.04	41.47	-31.09	52.42	74.00	21.58	Vertical

11n(HT20)_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17969.7167	33.59	41.61	-30.99	44.21	54.00	9.79	Horizontal
2	6254.3333	40.80	35.01	-16.93	58.87	68.20	9.33	Horizontal
3	7037.05	49.62	36.30	-42.57	43.35	68.20	24.85	Horizontal
4	9459.7167	48.66	38.05	-38.54	48.16	74.00	25.84	Horizontal
5	11140.6333	44.05	39.22	-35.47	47.80	74.00	26.20	Horizontal
6	12798.55	45.40	39.66	-34.77	50.28	68.20	17.92	Horizontal
7	17995.4	41.76	41.69	-30.94	52.51	74.00	21.49	Horizontal

11n(HT20)_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	6109.5	39.76	34.72	-16.69	57.79	68.20	10.41	Vertical
2	7094.55	49.49	36.30	-42.49	43.30	68.20	24.90	Vertical
3	9518.3667	49.64	38.05	-38.44	49.25	68.20	18.95	Vertical
4	12816.5667	45.02	39.68	-34.73	49.97	68.20	18.23	Vertical
5	15087.8167	44.59	39.64	-34.23	50.00	68.20	18.20	Vertical
6	17995.7833	42.39	41.69	-30.94	53.14	74.00	20.86	Vertical

11n(HT20)_TX_CH_157_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17926.4	33.71	41.49	-31.08	44.12	54.00	9.88	Horizontal
2	6227.2917	40.14	34.95	-16.87	58.22	68.20	9.98	Horizontal
3	6939.6833	50.38	36.20	-42.63	43.95	68.20	24.25	Horizontal
4	9463.55	48.74	38.05	-38.54	48.25	74.00	25.75	Horizontal
5	11206.1833	43.90	39.18	-35.12	47.96	74.00	26.04	Horizontal
6	12803.9167	45.10	39.66	-34.77	50.00	68.20	18.20	Horizontal
7	17936.3667	41.81	41.52	-31.06	52.27	74.00	21.73	Horizontal

11n(HT20)_TX_CH_157_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17928.3167	33.84	41.49	-31.07	44.26	54.00	9.74	Vertical
2	6211.7083	39.84	34.92	-16.84	57.93	68.20	10.27	Vertical
3	6841.1667	50.08	36.05	-42.76	43.37	68.20	24.83	Vertical
4	9567.05	47.95	38.06	-38.31	47.70	68.20	20.50	Vertical
5	12844.9333	45.40	39.71	-34.64	50.48	68.20	17.72	Vertical
6	13831.6333	44.52	40.32	-34.72	50.11	68.20	18.09	Vertical
7	17988.5	40.88	41.67	-30.95	51.59	74.00	22.41	Vertical

11n(HT20)_TX_CH_165_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17934.0667	34.12	41.51	-31.06	44.57	54.00	9.43	Horizontal
2	6234.625	39.57	34.97	-16.89	57.65	68.20	10.55	Horizontal
3	7766.5333	48.70	36.83	-41.25	44.28	68.20	23.92	Horizontal
4	9506.4833	49.04	38.05	-38.47	48.62	68.20	19.58	Horizontal
5	11182.4167	44.08	39.19	-35.18	48.09	74.00	25.91	Horizontal
6	12805.45	45.44	39.67	-34.76	50.34	68.20	17.86	Horizontal
7	17933.3	41.30	41.51	-31.06	51.74	74.00	22.26	Horizontal

11n(HT20)_TX_CH_165_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17937.1333	33.51	41.52	-31.06	43.97	54.00	10.03	Vertical
2	6275.875	40.63	35.05	-16.98	58.70	68.20	9.50	Vertical
3	7862.75	48.99	37.03	-41.32	44.69	68.20	23.51	Vertical
4	9498.8167	48.17	38.05	-38.49	47.73	74.00	26.27	Vertical
5	12654.4167	44.97	39.49	-34.97	49.49	74.00	24.51	Vertical
6	13603.1667	45.44	40.20	-34.08	51.56	68.20	16.64	Vertical
7	17938.6667	41.71	41.52	-31.05	52.18	74.00	21.82	Vertical

11n(HT40)_TX_CH_38_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17959.75	34.45	41.58	-31.01	45.02	54.00	8.98	Horizontal
2	6095.2917	40.14	34.69	-16.70	58.13	68.20	10.07	Horizontal
3	6919.75	56.49	36.17	-42.63	50.03	68.20	18.17	Horizontal
4	9473.9	48.27	38.05	-38.52	47.79	74.00	26.21	Horizontal
5	12800.0833	45.44	39.66	-34.78	50.32	68.20	17.88	Horizontal
6	17076.1667	43.45	39.02	-31.34	51.13	68.20	17.07	Horizontal
7	17959.3667	41.93	41.58	-31.01	52.50	74.00	21.50	Horizontal

11n(HT40)_TX_CH_38_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17901.8667	33.93	41.42	-31.13	44.22	54.00	9.78	Vertical
2	5988.5	39.64	34.47	-17.08	57.02	68.20	11.18	Vertical
3	6919.75	52.32	36.17	-42.63	45.86	68.20	22.34	Vertical
4	8001.5167	49.34	37.30	-41.18	45.46	68.20	22.74	Vertical
5	9514.9167	48.72	38.05	-38.45	48.32	68.20	19.88	Vertical
6	12854.5167	45.34	39.73	-34.61	50.46	68.20	17.74	Vertical
7	17974.7	41.30	41.63	-30.98	51.95	74.00	22.05	Vertical

11n(HT40)_TX_CH_46_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17924.1	34.02	41.48	-31.08	44.42	54.00	9.58	Horizontal
2	6043.0417	40.18	34.59	-16.93	57.84	68.20	10.36	Horizontal
3	6973.4167	59.22	36.26	-42.63	52.85	68.20	15.35	Horizontal
4	9522.5833	48.48	38.05	-38.43	48.10	68.20	20.10	Horizontal
5	11149.8333	44.41	39.21	-35.41	48.21	74.00	25.79	Horizontal
6	12905.5	45.65	39.79	-34.51	50.93	68.20	17.27	Horizontal
7	17973.55	42.00	41.62	-30.98	52.64	74.00	21.36	Horizontal

11n(HT40)_TX_CH_46_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17903.4	34.25	41.42	-31.12	44.55	54.00	9.45	Vertical
2	6082	40.28	34.66	-16.76	58.18	68.20	10.02	Vertical
3	6973.0333	50.85	36.26	-42.63	44.48	68.20	23.72	Vertical
4	9437.1	48.13	38.04	-38.57	47.60	74.00	26.40	Vertical
5	11181.2667	45.00	39.19	-35.19	49.00	74.00	25.00	Vertical
6	12829.9833	45.59	39.70	-34.68	50.60	68.20	17.60	Vertical
7	17980.45	41.61	41.64	-30.97	52.28	74.00	21.72	Vertical

11n(HT40)_TX_CH_54_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17995.7833	33.42	41.69	-30.94	44.17	54.00	9.83	Horizontal
2	6202.0833	40.89	34.90	-16.81	58.98	68.20	9.22	Horizontal
3	7026.7	57.05	36.30	-42.59	50.76	68.20	17.44	Horizontal
4	7991.9333	49.23	37.28	-41.21	45.31	68.20	22.89	Horizontal
5	9470.45	48.21	38.05	-38.53	47.73	74.00	26.27	Horizontal
6	12763.2833	45.22	39.62	-34.65	50.18	68.20	18.02	Horizontal
7	17988.5	41.57	41.67	-30.95	52.28	74.00	21.72	Horizontal

11n(HT40)_TX_CH_54_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17770.7667	33.67	41.04	-31.68	43.02	54.00	10.98	Vertical
2	6142.9583	40.01	34.79	-16.74	58.06	68.20	10.14	Vertical
3	7026.7	52.26	36.30	-42.59	45.97	68.20	22.23	Vertical
4	9494.2167	48.16	38.05	-38.50	47.71	74.00	26.29	Vertical
5	11201.2	44.04	39.18	-35.07	48.15	74.00	25.85	Vertical
6	12878.6667	45.61	39.75	-34.53	50.84	68.20	17.36	Vertical
7	17921.0333	41.50	41.47	-31.09	51.88	74.00	22.12	Vertical

11n(HT40)_TX_CH_62_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17965.8833	33.76	41.60	-31.00	44.36	54.00	9.64	Horizontal
2	6180.0833	40.03	34.86	-16.78	58.11	68.20	10.09	Horizontal
3	7079.9833	57.66	36.30	-42.51	51.45	68.20	16.75	Horizontal
4	9509.9333	48.14	38.05	-38.46	47.73	68.20	20.47	Horizontal
5	11204.65	44.43	39.18	-35.10	48.50	74.00	25.50	Horizontal
6	12820.4	45.77	39.68	-34.71	50.74	68.20	17.46	Horizontal
7	17937.5167	41.86	41.52	-31.05	52.32	74.00	21.68	Horizontal

11n(HT40)_TX_CH_62_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17993.4833	33.72	41.68	-30.94	44.46	54.00	9.54	Vertical
2	6087.9583	39.98	34.68	-16.73	57.92	68.20	10.28	Vertical
3	7079.9833	51.61	36.30	-42.51	45.40	68.20	22.80	Vertical
4	9496.5167	48.91	38.05	-38.49	48.47	74.00	25.53	Vertical
5	10242.1	46.40	38.39	-36.64	48.15	68.20	20.05	Vertical
6	13303.7833	43.33	40.05	-34.60	48.78	74.00	25.22	Vertical
7	17960.5167	41.63	41.59	-31.01	52.21	74.00	21.79	Vertical

11n(HT40)_TX_CH_102_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17954.3833	33.62	41.57	-31.02	44.17	54.00	9.83	Horizontal
2	6235.5417	40.31	34.97	-16.89	58.39	68.20	9.81	Horizontal
3	6909.7833	50.16	36.16	-42.63	43.69	68.20	24.51	Horizontal
4	7952.45	49.85	37.20	-41.33	45.72	68.20	22.48	Horizontal
5	9447.8333	48.71	38.04	-38.56	48.20	74.00	25.80	Horizontal
6	12825.3833	46.16	39.69	-34.70	51.15	68.20	17.05	Horizontal
7	17954	41.72	41.57	-31.02	52.26	74.00	21.74	Horizontal

11n(HT40)_TX_CH_102_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17970.8667	33.70	41.62	-30.99	44.33	54.00	9.67	Vertical
2	6238.2917	40.23	34.98	-16.90	58.31	68.20	9.89	Vertical
3	7084.5833	49.93	36.30	-42.50	43.73	68.20	24.47	Vertical
4	9468.9167	48.55	38.05	-38.53	48.07	74.00	25.93	Vertical
5	12919.6833	45.07	39.80	-34.64	50.23	68.20	17.97	Vertical
6	14424.65	44.33	40.15	-34.02	50.45	68.20	17.75	Vertical
7	17970.4833	42.22	41.61	-30.99	52.85	74.00	21.15	Vertical

11n(HT40)_TX_CH_110_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17995.0167	33.60	41.69	-30.94	44.35	54.00	9.65	Horizontal
2	6251.125	39.99	35.00	-16.93	58.06	68.20	10.14	Horizontal
3	6942.75	51.59	36.21	-42.63	45.17	68.20	23.03	Horizontal
4	9513	48.69	38.05	-38.45	48.29	68.20	19.91	Horizontal
5	12824.6167	44.81	39.69	-34.70	49.80	68.20	18.40	Horizontal
6	14302.3667	44.66	40.22	-34.94	49.94	68.20	18.26	Horizontal
7	17968.95	41.09	41.61	-30.99	51.71	74.00	22.29	Horizontal

11n(HT40)_TX_CH_110_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17924.1	34.36	41.48	-31.08	44.76	54.00	9.24	Vertical
2	6261.2083	40.30	35.02	-16.95	58.37	68.20	9.83	Vertical
3	7213.7667	49.64	36.30	-42.04	43.90	68.20	24.30	Vertical
4	9506.1	48.15	38.05	-38.47	47.73	68.20	20.47	Vertical
5	11190.85	44.17	39.19	-35.12	48.23	74.00	25.77	Vertical
6	12818.4833	45.68	39.68	-34.72	50.64	68.20	17.56	Vertical
7	17940.9667	41.16	41.53	-31.05	51.64	74.00	22.36	Vertical

11n(HT40)_TX_CH_118_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17972.0167	34.48	41.62	-30.99	45.11	54.00	8.89	Horizontal
2	6222.7083	39.86	34.95	-16.86	57.94	68.20	10.26	Horizontal
3	6690.1333	54.90	35.80	-42.85	47.85	68.20	20.35	Horizontal
4	9507.25	49.55	38.05	-38.47	49.13	68.20	19.07	Horizontal
5	12902.4333	45.28	39.78	-34.48	50.58	68.20	17.62	Horizontal
6	13875.7167	44.00	40.34	-34.13	50.21	68.20	17.99	Horizontal
7	17979.6833	42.07	41.64	-30.97	52.74	74.00	21.26	Horizontal

11n(HT40)_TX_CH_118_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17962.8167	34.57	41.59	-31.00	45.16	54.00	8.84	Vertical
2	6313	39.85	35.13	-16.98	58.00	68.20	10.20	Vertical
3	6714.6667	50.54	35.84	-42.85	43.53	68.20	24.67	Vertical
4	9502.2667	48.44	38.05	-38.48	48.01	68.20	20.19	Vertical
5	11218.45	44.51	39.17	-35.24	48.44	74.00	25.56	Vertical
6	12941.15	46.07	39.83	-34.84	51.06	68.20	17.14	Vertical
7	17955.5333	42.31	41.57	-31.02	52.86	74.00	21.14	Vertical

11n(HT40)_TX_CH_126_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17972.4	34.40	41.62	-30.99	45.03	54.00	8.97	Horizontal
2	6293.2917	39.81	35.09	-17.02	57.87	68.20	10.33	Horizontal
3	6759.1333	55.14	35.91	-42.85	48.20	68.20	20.00	Horizontal
4	9503.8	48.99	38.05	-38.48	48.56	68.20	19.64	Horizontal
5	10199.1667	47.54	38.34	-36.24	49.64	68.20	18.56	Horizontal
6	12896.6833	45.82	39.78	-34.47	51.13	68.20	17.07	Horizontal
7	17947.1	41.76	41.55	-31.04	52.27	74.00	21.73	Horizontal

11n(HT40)_TX_CH_126_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17975.85	34.82	41.63	-30.98	45.47	54.00	8.53	Vertical
2	6122.7917	40.04	34.75	-16.71	58.08	68.20	10.12	Vertical
3	7796.4333	49.82	36.89	-41.04	45.67	68.20	22.53	Vertical
4	9521.8167	48.77	38.05	-38.43	48.39	68.20	19.81	Vertical
5	11188.9333	46.16	39.19	-35.14	50.21	74.00	23.79	Vertical
6	12839.5667	46.30	39.71	-34.65	51.35	68.20	16.85	Vertical
7	17990.8	42.90	41.67	-30.95	53.62	74.00	20.38	Vertical

11n(HT40)_TX_CH_134_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17934.0667	34.75	41.51	-31.06	45.20	54.00	8.80	Horizontal
2	6386.3333	39.76	35.27	-16.64	58.39	68.20	9.81	Horizontal
3	6815.1	53.40	36.00	-42.82	46.59	68.20	21.61	Horizontal
4	9545.9667	48.39	38.05	-38.37	48.08	68.20	20.12	Horizontal
5	12814.2667	45.95	39.68	-34.73	50.89	68.20	17.31	Horizontal
6	13608.15	45.53	40.20	-34.15	51.59	68.20	16.61	Horizontal
7	17986.5833	42.27	41.66	-30.96	52.97	74.00	21.03	Horizontal

11n(HT40)_TX_CH_134_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17971.6333	34.64	41.62	-30.99	45.27	54.00	8.73	Vertical
2	6043.9583	41.16	34.59	-16.93	58.82	68.20	9.38	Vertical
3	7878.4667	50.38	37.06	-41.40	46.04	68.20	22.16	Vertical
4	9502.65	48.56	38.05	-38.48	48.13	68.20	20.07	Vertical
5	12730.7	44.86	39.58	-34.54	49.90	68.20	18.30	Vertical
6	13602.0167	44.90	40.20	-34.07	51.03	68.20	17.17	Vertical
7	17958.2167	42.71	41.58	-31.01	53.28	74.00	20.72	Vertical

11n(HT40)_TX_CH_142_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17962.05	34.98	41.59	-31.01	45.56	54.00	8.44	Horizontal
2	6266.25	39.95	35.03	-16.96	58.02	68.20	10.18	Horizontal
3	6843.85	51.60	36.05	-42.75	44.90	68.20	23.30	Horizontal
4	9462.7833	48.25	38.05	-38.54	47.76	74.00	26.24	Horizontal
5	12941.5333	46.22	39.83	-34.85	51.20	68.20	17.00	Horizontal
6	13620.4167	45.43	40.21	-34.31	51.33	68.20	16.87	Horizontal
7	17961.6667	42.99	41.59	-31.01	53.57	74.00	20.43	Horizontal

11n(HT40)_TX_CH_142_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17936.3667	34.74	41.52	-31.06	45.20	54.00	8.80	Vertical
2	6208.0417	40.16	34.92	-16.83	58.25	68.20	9.95	Vertical
3	7094.1667	50.93	36.30	-42.49	44.74	68.20	23.46	Vertical
4	9498.8167	49.09	38.05	-38.49	48.65	74.00	25.35	Vertical
5	12811.5833	45.88	39.67	-34.74	50.81	68.20	17.39	Vertical
6	13456.35	46.51	40.13	-34.85	51.79	68.20	16.41	Vertical
7	17935.2167	42.13	41.51	-31.06	52.58	74.00	21.42	Vertical

11n(HT40)_TX_CH_151_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17952.0833	34.79	41.56	-31.03	45.33	54.00	8.67	Horizontal
2	6163.5833	40.76	34.83	-16.76	58.82	68.20	9.38	Horizontal
3	6905.95	52.07	36.15	-42.63	45.59	68.20	22.61	Horizontal
4	9504.5667	49.38	38.05	-38.48	48.95	68.20	19.25	Horizontal
5	12826.9167	46.42	39.69	-34.69	51.42	68.20	16.78	Horizontal
6	13645.3333	45.44	40.22	-34.64	51.02	68.20	17.18	Horizontal
7	17970.1	42.59	41.61	-30.99	53.21	74.00	20.79	Horizontal

11n(HT40)_TX_CH_151_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17990.0333	35.46	41.67	-30.95	46.18	54.00	7.82	Vertical
2	6215.8333	40.13	34.93	-16.85	58.22	68.20	9.98	Vertical
3	6796.7	50.11	35.97	-42.85	43.23	68.20	24.97	Vertical
4	7988.1	49.76	37.28	-41.22	45.82	68.20	22.38	Vertical
5	9550.5667	48.33	38.06	-38.35	48.03	68.20	20.17	Vertical
6	12836.8833	45.96	39.70	-34.66	51.00	68.20	17.20	Vertical
7	17958.6	42.80	41.58	-31.01	53.37	74.00	20.63	Vertical

11n(HT40)_TX_CH_159_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17894.9667	35.31	41.40	-31.17	45.54	54.00	8.46	Horizontal
2	6221.7917	40.14	34.94	-16.86	58.22	68.20	9.98	Horizontal
3	6966.1333	50.85	36.25	-42.63	44.47	68.20	23.73	Horizontal
4	9485.0167	47.61	38.05	-38.51	47.15	74.00	26.85	Horizontal
5	12848	45.72	39.72	-34.63	50.81	68.20	17.39	Horizontal
6	13499.2833	46.28	40.15	-35.15	51.28	68.20	16.92	Horizontal
7	17899.95	43.51	41.41	-31.13	53.79	74.00	20.21	Horizontal

11n(HT40)_TX_CH_159_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17985.05	34.68	41.66	-30.96	45.38	54.00	8.62	Vertical
2	6077.875	39.64	34.66	-16.78	57.52	68.20	10.68	Vertical
3	7236.7667	49.33	36.30	-42.06	43.57	68.20	24.63	Vertical
4	9463.55	48.00	38.05	-38.54	47.51	74.00	26.49	Vertical
5	10642.3	44.86	38.87	-36.34	47.39	74.00	26.61	Vertical
6	12884.0333	46.04	39.76	-34.51	51.29	68.20	16.91	Vertical
7	17919.5	42.88	41.47	-31.09	53.26	74.00	20.74	Vertical

11ac(VHT80)_TX_CH_42_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17963.5833	34.81	41.59	-31.00	45.40	54.00	8.60	Horizontal
2	5759.7917	39.74	33.78	-17.14	56.37	68.20	11.83	Horizontal
3	6946.5833	59.99	36.21	-42.63	53.57	68.20	14.63	Horizontal
4	8021.0667	49.71	37.31	-41.15	45.88	68.20	22.32	Horizontal
5	9516.8333	48.75	38.05	-38.44	48.36	68.20	19.84	Horizontal
6	12871.3833	46.36	39.75	-34.55	51.55	68.20	16.65	Horizontal
7	17988.8833	42.45	41.67	-30.95	53.17	74.00	20.83	Horizontal

11ac(VHT80)_TX_CH_42_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17908.7667	35.52	41.44	-31.11	45.84	54.00	8.16	Vertical
2	5709.8333	39.96	33.63	-17.30	56.29	68.20	11.91	Vertical
3	6946.5833	52.08	36.21	-42.63	45.66	68.20	22.54	Vertical
4	7965.4833	50.13	37.23	-41.29	46.07	68.20	22.13	Vertical
5	9487.7	48.62	38.05	-38.51	48.16	74.00	25.84	Vertical
6	12948.8167	46.78	39.84	-34.91	51.70	68.20	16.50	Vertical
7	17967.4167	43.04	41.61	-31.00	53.65	74.00	20.35	Vertical

11ac(VHT80)_TX_CH_58_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17973.1667	34.56	41.62	-30.98	45.20	54.00	8.80	Horizontal
2	5927.0833	39.56	34.28	-16.89	56.95	68.20	11.25	Horizontal
3	7053.5333	57.05	36.30	-42.55	50.80	68.20	17.40	Horizontal
4	9431.7333	48.36	38.04	-38.58	47.82	74.00	26.18	Horizontal
5	10923.2833	46.07	39.21	-36.15	49.13	74.00	24.87	Horizontal
6	13626.55	46.18	40.21	-34.39	52.00	68.20	16.20	Horizontal
7	17921.0333	42.88	41.47	-31.09	53.26	74.00	20.74	Horizontal