

Test Report

Report No. : MTi250219007-0103E3
Date of issue : 2025-05-28
Applicant : OXAA Corp.
Product : Motorized 5-in-1 Wireless Charging
Stand with Speaker
Model(s) : OXWC1310, OXWC2310
FCC ID : 2BNYA-OXWC1310

Shenzhen Microtest Co., Ltd.

TEST REPORT



Report No.: MTi250219007-0103E3

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	4
1.3	Environmental Conditions	6
1.4	Description of support units	6
1.5	Measurement uncertainty	6
2	Summary of Test Result	7
3	Test Facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Evaluation Results (Evaluation)	10
5.1	Antenna requirement	10
6	Radio Spectrum Matter Test Results (RF)	11
6.1	Conducted Emission at AC power line	11
6.2	20dB Occupied Bandwidth	14
6.3	Emissions in frequency bands (below 30MHz)	21
6.4	Emissions in frequency bands (30MHz - 1GHz)	26
	Photographs of the test setup	30
	Photographs of the EUT	31

TEST REPORT

Report No.: MTi250219007-0103E3

Test Result Certification		
Applicant	OXAA Corp.	
Applicant Address	6-3545 Odyssey Dr, Mississauga, ON L5M 2S4, Canada	
Manufacturer	OXAA Corp.	
Manufacturer Address	6-3545 Odyssey Dr, Mississauga, ON L5M 2S4, Canada	
Factory	Shenzhen Aodehong Electronic Technology Co.,Ltd.	
Factory Address	5th Floor, Elegant Industrial Park, No.8 Liuhe Road, Liuyue,Henggang Street,Longgang District, Shenzhen,China	
Product description		
Product name	Motorized 5-in-1 Wireless Charging Stand with Speaker	
Trademark	OXAA	
Model name	OXWC1310	
Series Model(s)	OXWC2310	
Standards	47 CFR Part 15C	
Test Method	ANSI C63.10-2020	
Testing Information		
Date of test	2025-03-04 to 2025-03-07	
Test result	Pass	
Prepared by:	Maleah Deng	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

TEST REPORT

Report No.: MTi250219007-0103E3

1 General Description

1.1 Description of the EUT

Product name:	Motorized 5-in-1 Wireless Charging Stand with Speaker
Model name:	OXWC1310
Series Model(s):	OXWC2310
Model difference:	All the models are the same circuit and module, except the model name and color.
Electrical rating:	Input: DC 9V 3A Wireless Output: Phone:5W, 7.5W, 10W, 15W; Earbuds: 5W; Watch: 5W Max Battery: DC 3.7V 1000mAh
Accessories:	Cable: USB-C to USB-C cable 100cm
Hardware version:	1.0
Software version:	1.0
Test sample(s) number:	MTi250219007-01-R002
RF specification	
Operating frequency range:	Coil 1(PHONE): 115-205kHz(5W, 7.5W, 10W); 360kHz(15W) Coil 2(EARBUDS): 115-205kHz Coil 3(WATCH): 300-350kHz(2.5W); 1.7-1.778MHz(5W)
Modulation type:	ASK
Antenna(s) type:	Coil Antenna

1.2 Description of test modes

No.	Emission test modes
Mode1	Charging+Wireless output(PHONE(5W)+EARBUDS(5W)+WATCH(2.5W))
Mode2	Charging+Wireless output(PHONE(7.5W)+EARBUDS(5W)+WATCH(2.5W))
Mode3	Charging+Wireless output(PHONE(10W)+EARBUDS(5W)+WATCH(2.5W))
Mode4	Charging+Wireless output(PHONE(15W)+EARBUDS(5W)+WATCH(2.5W))
Mode5	Charging+Wireless output(PHONE(5W)+EARBUDS(5W)+WATCH(5W))
Mode6	Charging+Wireless output(PHONE(7.5W)+EARBUDS(5W)+WATCH(5W))
Mode7	Charging+Wireless output(PHONE(10W)+EARBUDS(5W)+WATCH(5W))
Mode8	Charging+Wireless output(PHONE(15W)+EARBUDS(5W)+WATCH(5W))
Mode9	Charging+Wireless output(PHONE(5W)+EARBUDS(5W))
Mode10	Charging+Wireless output(PHONE(7.5W)+EARBUDS(5W))
Mode11	Charging+Wireless output(PHONE(10W)+EARBUDS(5W))
Mode12	Charging+Wireless output(PHONE(15W)+EARBUDS(5W))
Mode13	Charging+Wireless output(PHONE(5W)+WATCH(2.5W))

TEST REPORT

Report No.: MTi250219007-0103E3

Mode14	Charging+Wireless output(Phone(7.5W)+Watch(2.5W))
Mode15	Charging+Wireless output(Phone(10W)+Watch(2.5W))
Mode16	Charging+Wireless output(Phone(15W)+Watch(2.5W))
Mode17	Charging+Wireless output(Phone(5W)+Watch(5W))
Mode18	Charging+Wireless output(Phone(7.5W)+Watch(5W))
Mode19	Charging+Wireless output(Phone(10W)+Watch(5W))
Mode20	Charging+Wireless output(Phone(15W)+Watch(5W))
Mode21	Charging+Wireless Output(Earbuds(5W)+Watch(2.5W))
Mode22	Charging+Wireless Output(Earbuds(5W)+Watch(5W))
Mode23	Charging+Wireless output(Phone(5W))
Mode24	Charging+Wireless output(Phone(7.5W))
Mode25	Charging+Wireless output(Phone(10W))
Mode26	Charging+Wireless output(Phone(15W))
Mode27	Charging+Wireless Output(Watch(2.5W))
Mode28	Charging+Wireless Output(Watch(5W))
Mode29	Charging+Wireless Output(Earbuds(5W))
Mode30	stand by

TEST REPORT

Report No.: MTi250219007-0103E3

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list

Description	Model	Serial No.	Manufacturer
HUAWEI QUICK CHARGE	HW-200200ZP1	JN67LSN7N03451	HUAWEI
wireless charging load	YBZ1.1	/	YBZ
airpods	airpods 3	/	apple
iWatch	Apple Watch SE	/	Apple
iWatch	Apple Watch S7	/	Apple

Support cable list

Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

TEST REPORT

Report No.: MTi250219007-0103E3

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15C	47 CFR Part 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15C	47 CFR Part 15.207(a)	Pass
3	20dB Occupied Bandwidth	47 CFR Part 15C	47 CFR Part 15.215(c)	Pass
4	Emissions in frequency bands (below 30MHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass
5	Emissions in frequency bands (30MHz - 1GHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass

TEST REPORT

Report No.: MTi250219007-0103E3

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

TEST REPORT

Report No.: MTi250219007-0103E3

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2024-03-20	2025-03-19
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2024-03-21	2025-03-20
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2024-03-20	2025-03-19
20dB Occupied Bandwidth						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2024-03-20	2025-03-19
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2024-03-21	2025-03-20
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2024-03-21	2025-03-20
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2024-03-21	2025-03-20
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2024-03-21	2025-03-20
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2024-03-21	2025-03-20
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2024-03-21	2025-03-20
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2024-03-20	2025-03-19
9	DC Power Supply	Agilent	E3632A	MY40027695	2024-03-21	2025-03-20
Emissions in frequency bands (below 30MHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-03-20	2025-03-19
2	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2025-03-22
3	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-03-20	2025-03-19
Emissions in frequency bands (30MHz - 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-03-20	2025-03-19
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2025-03-22
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-03-20	2025-03-19

TEST REPORT

Report No.: MTi250219007-0103E3

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached.
The EUT complies with the requirement of FCC PART 15.203.

TEST REPORT

Report No.: MTi250219007-0103E3

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			
Test Method:	ANSI C63.10-2020 section 6.2		
Procedure:	Refer to ANSI C63.10-2020 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.9 °C	Humidity:	44 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1-30				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode4) is recorded in the report				

6.1.2 Test Setup Diagram:




TEST REPORT

Report No.: MTi250219007-0103E3

6.1.3 Test Data:


Mode4 / Line: Line / CH: L



TEST REPORT

Report No.: MTi250219007-0103E3

Mode4 / Line: Neutral / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	29.79	10.77	40.56	66.00	-25.44	QP	
2		0.1500	16.13	10.77	26.90	56.00	-29.10	AVG	
3		0.3460	29.45	10.75	40.20	59.06	-18.86	QP	
4	*	0.3540	24.95	10.74	35.69	48.87	-13.18	AVG	
5		0.3771	20.99	10.74	31.73	48.34	-16.61	AVG	
6		0.3780	30.03	10.74	40.77	58.32	-17.55	QP	
7		0.8180	22.57	10.76	33.33	56.00	-22.67	QP	
8		0.8180	13.98	10.76	24.74	46.00	-21.26	AVG	
9		1.1380	22.28	10.76	33.04	56.00	-22.96	QP	
10		1.1380	13.19	10.76	23.95	46.00	-22.05	AVG	
11		4.1180	14.90	10.85	25.75	46.00	-20.25	AVG	
12		4.1979	26.45	10.86	37.31	56.00	-18.69	QP	

TEST REPORT

Report No.: MTi250219007-0103E3

6.2 20dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15.215(c)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2020, section 6.9.2
Procedure:	a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-

TEST REPORT


Report No.: MTi250219007-0103E3

	delta frequency reading at this point is the specified emission bandwidth. k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
--	---

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.7 °C	Humidity:	61 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1-30				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode25, Mode26, Mode27, Mode28, Mode29) is recorded in the report				

6.2.2 Test Setup Diagram:



TEST REPORT


Report No.: MTi250219007-0103E3

6.2.3 Test Data:

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Coil 1(10W)

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
120.62	812	691




TEST REPORT

Report No.: MTi250219007-0103E3

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Coil 1(15W)




TEST REPORT

Report No.: MTi250219007-0103E3

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Coil 2



TEST REPORT

Report No.: MTi250219007-0103E3

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Coil 3(2.5W)




TEST REPORT

Report No.: MTi250219007-0103E3

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Coil 3(5W)



TEST REPORT

Report No.: MTi250219007-0103E3


6.3 Emissions in frequency bands (below 30MHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.			
Test Method:	ANSI C63.10-2020 section 6.4		
Procedure:	ANSI C63.10-2020 section 6.4		

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.5 °C	Humidity:	43 %	Atmospheric Pressure:	101 kPa
Pre test mode:		Mode1-30			
Final test mode:		All of the listed pre-test mode were tested, only the data of the worst mode (Mode3, Mode8) is recorded in the report			

6.3.2 Test Setup Diagram:




TEST REPORT

Report No.: MTi250219007-0103E3

6.3.3 Test Data:


Mode3 / EUT direction: X axis



TEST REPORT

Report No.: MTi250219007-0103E3

Mode3 / EUT direction: X axis




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.3215	37.89	20.99	58.88	117.47	-58.59	peak	
2		0.3215	34.25	20.99	55.24	97.47	-42.23	AVG	
3		0.8217	25.99	22.17	48.16	69.32	-21.16	QP	
4	*	1.0653	28.22	22.74	50.96	67.07	-16.11	QP	
5		1.1534	19.63	22.91	42.54	66.39	-23.85	QP	
6		1.4408	14.76	23.50	38.26	64.46	-26.20	QP	
7		1.7810	16.98	24.20	41.18	69.50	-28.32	QP	

TEST REPORT

Report No.: MTi250219007-0103E3

Mode8 / EUT direction: X axis




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.1386	27.52	20.52	48.04	124.79	-76.75	peak	
2	*	0.1386	24.79	20.52	45.31	104.79	-59.48	AVG	

TEST REPORT

Report No.: MTi250219007-0103E3

Mode4 / EUT direction: X axis



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.3597	52.15	21.08	73.23	116.59	-43.36	peak	
2		0.3597	49.18	21.08	70.26	96.59	-26.33	AVG	
3		0.5265	26.83	21.47	48.30	73.18	-24.88	QP	
4		0.7009	21.62	21.88	43.50	70.70	-27.20	QP	
5		0.8803	20.80	22.31	43.11	68.73	-25.62	QP	
6	*	1.0766	20.82	22.76	43.58	66.98	-23.40	QP	
7		1.7500	15.46	24.24	39.70	69.50	-29.80	QP	

TEST REPORT

Report No.: MTi250219007-0103E3

6.4 Emissions in frequency bands (30MHz - 1GHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.			
Test Method:	ANSI C63.10-2020 section 6.5		
Procedure:	ANSI C63.10-2020 section 6.5		

6.4.1 E.U.T. Operation:


Operating Environment:					
Temperature:	23.2 °C	Humidity:	55 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1-30				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode2) is recorded in the report				

6.4.2 Test Setup Diagram:

--

TEST REPORT

Report No.: MTi250219007-0103E3




TEST REPORT

Report No.: MTi250219007-0103E3

6.4.3 Test Data:

Mode2 / Polarization: Horizontal



TEST REPORT

Report No.: MTi250219007-0103E3

Mode2 / Polarization: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		40.8446	41.60	-8.55	33.05	40.00	-6.95	QP	
2		43.9658	41.71	-8.73	32.98	40.00	-7.02	QP	
3	!	59.4405	45.34	-9.81	35.53	40.00	-4.47	QP	
4	*	62.6507	46.47	-10.09	36.38	40.00	-3.62	QP	
5	!	68.1514	46.43	-10.94	35.49	40.00	-4.51	QP	
6	!	82.3588	47.83	-13.35	34.48	40.00	-5.52	QP	

TEST REPORT

Report No.: MTi250219007-0103E3

Photographs of the test setup

Refer to Appendix - Test Setup Photos

TEST REPORT

Report No.: MTi250219007-0103E3

Photographs of the EUT

Refer to Appendix - EUT Photos

TEST REPORT

Report No.: MTi250219007-0103E3

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****