

惠州启泰电子科技有限公司

Huizhou Qitai Electronic Technology Co., LTD



SPECIFICATIONS SHEET

规格图面

CUSTOMER :	
客户	摩菲
DESCRIPTION :	
品名描述	POWER17/18
CUSTOMER P/N :	
客户品名	
PART NUMBER :	
制造商料号	
DATE OF APPLICATION :	
提出日期	2024-12-17

CLASSIFICATION OF SPEC. PRESENTATION. (Tick the relevant box "√")

规格图面提出区分

- ☐ New application 新规格
- ☒ New part is added to accepted specification 新产品规格追加记录
- ☐ Revision of accepted specification 既存规格图面变更

ACCEPTANCE STAMP (客户受领印)

APPROVAL BY 承认	CHECK BY 审查	PREPARE BY 制作
陈子奇		陈斌

ADDRESS : 3rd Floor, No. 101, Mingyue 2nd Road, Shiwan Town, Boluo County, Huizhou city

TELEPHONE : 0752-6668681

E-MAIL : 839689578@qq.com

Huizhou Qitai Electronic Technology Co., LTD

CUSTOMER P/N :
客 户 品 名
PART NUMBER :
制 造 商 料 号

[illegible]

Specification
规格内容

CUSTOMER P/N : 客 户 品 名	
PART NUMBER : 制 造 商 料 号	

1. DIMENSIONS (外形尺寸) : (Unit: mm)

单位 (Unit) : 毫米 (mm)



A	B	C	D	E	F	G	H	I
42±0.5	39.6±0.5	16.5±1	15±0.5	8±0.5	14±1	2±1	0.65±0.1	1.7Max

- 背胶为白色双面胶。The adhesive is white double-sided tape.
- 线圈贴合位置居中。The coil is centered in its mounting position.
- 磁铁规格: $\phi 7.5\text{mm} \times 1.5\text{mm}$ 2800GS。Magnet specifications $\phi 7.5\text{mm} \times 1.5\text{mm}$ 2800GS.
- 出线间距控制在3Ref。Line spacing control 3Ref.

APPROVED BY 承认	CHECKED BY 审查	PREPARED BY 制作	DATE 日期	PAGE 页码
昆子奇		陈斌	2024-12-17	2 of 3

Huizhou Qitai Electronic Technology Co., LTD

CUSTOMER P/N :
客 户 品 名

PART NUMBER :
制 造 商 料 号

圈数
Turns

线径
Wire Dia

绕线方式疏/密
Wdg. Type
Spred/Close

绕线方向
Wdg.Direction

相交 是/否
Intersect
Yes/Not

11TS

 $0.08 \times 72P$

密绕 (Close)

逆绕Counter-
clockwise rotation

是 (Yes)

温度 TEMPERATURE: $25 \pm 10^{\circ}\text{C}$, 湿度 RELATIVE HUMIDITY: $65 \pm 10\%$

序号 NO.	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
Coil 1					
1.	IND	S-F	6.8uh±10%	100kHz/V	UC2906A
2.	Q	S-F	40Min	100kHz/V	UC2906A
3.	DCR	S-F	80m ΩMax	100kHz/V	UC2906A

APPROVED BY
承认

CHECKED BY
宙查

PREPARED BY
制作

DATE
日期

PAGE
页 码

昆子奇

陈骏

2024-12-17

3 of 3