

TEST REPORT

FCC DTS Test for CBOX-240816
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2512-FC006-R2

DATE OF ISSUE
January 13, 2026

Tested by
Sang Hoon Lee



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO



HCT CO.,LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.
HCT-RF-2512-FC006-R2

DATE OF ISSUE
January 13, 2026

Applicant	LG Electronics Inc. 128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea
Product Name	RF Module
Model Name	CBOX-240816
FCC ID	2BO3L-CBOX-240816
Date of Test	November 25, 2025 ~ December 12, 2025
FCC Classification	Digital Transmission System(DTS)
Test Standard Used	FCC Rule Part(s): Part 15.247
Test Results	PASS
Location of Test	☒ Permanent Testing Lab ☐ On Site Testing Lab (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
Brand	LG

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 16, 2025	Initial Release
1	January 09, 2026	Delete the note on page 8 Revised the note on page 5, 24
2	January 13, 2026	Revised the Model Name. Revised the Product Name. Deleted the data of Additional Model. Revised the note on page 5, 24.

Notice

Content

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. EUT DESCRIPTION	5
2. TEST METHODOLOGY	6
EUT CONFIGURATION	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES	6
3. INSTRUMENT CALIBRATION	7
4. FACILITIES AND ACCREDITATIONS	7
FACILITIES	7
EQUIPMENT	8
5. ANTENNA REQUIREMENTS	8
6. MEASUREMENT UNCERTAINTY	9
7. DESCRIPTION OF TESTS	10
8. SUMMARY TEST OF RESULTS	25
9. TEST RESULT	26
9.1 DUTY CYCLE	26
9.2 6 dB BANDWIDTH	27
9.3 OUTPUT POWER	28
9.4 POWER SPECTRAL DENSITY	29
9.5 BAND EDGE / CONDUCTED SPURIOUS EMISSIONS	30
9.6 RADIATED SPURIOUS EMISSIONS	32
9.7 POWERLINE CONDUCTED EMISSIONS	36
10. LIST OF TEST EQUIPMENT	37
11. ANNEX A_ TEST SETUP PHOTO	39

1. EUT DESCRIPTION

Model	CBOX-240816	
EUT Type	RF Module	
Power Supply	DC 5.0 V	
Frequency Range	922 MHz ~ 926.8 MHz	
Max. RF Output Power	<u>Average Power</u>	13.52 dBm
	<u>Peak Power</u>	20.32 dBm
Wireless specification	IEEE 802.15.4g	
Modulation Type	OFDM	
Number of Channels	7 Channels	
Antenna Information	Please refer to the Antenna Specification document.	
Serial number	Conducted : FC:FD Radiated : FD:92	

Grant Notes :

1. Output Power listed is conducted(Peak)

2. TEST METHODOLOGY

Unlicensed wireless device were tested using the following measurement procedure.

[1] KDB 558074 D01 15.247 Meas Guidance v05r02

[2] ANSI C63.10-2020

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

According to the requirements in Section 6.3 ~ Section 6.6 of ANSI C63.10-2020.

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1 GHz. Above 1 GHz with 1.5 m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes.

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of ANSI C63.5-2017.

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea. The site is constructed in conformance with the requirements of ANSI C63.4-2014 and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated March 11, 2024 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to ANSI/USEMCSC C63.2-2023, "American National Standard for Specifications of Electromagnetic Interference and Field Strength Measuring Instrumentation in the Frequency Range 9 kHz to 40 GHz".

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR § 15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2020.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
X dB, 99% Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)


Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.54 (Confidence level about 95 %, $k=2$)
Conducted Output Power(Power Meter)	0.54 (Confidence level about 95 %, $k=2$)
Conducted Output Power(Signal Analyzer)	0.68 (Confidence level about 95 %, $k=2$)
Power Spectral Density	1.03 (Confidence level about 95 %, $k=2$)
Band Edge (Out of Band Emissions)	0.70 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.68 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.75 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.82 (Confidence level about 95 %, $k=2$)

7. DESCRIPTION OF TESTS

Test Item	Test Procedure
Duty Cycle	- ANSI C63.10-2020 – Section 11.6
6 dB Bandwidth	- ANSI C63.10-2020 – Section 11.8
Output Power	- ANSI C63.10-2020 – Section 11.9.1.2(Peak) & 11.9.2.3(Avg)
Power Spectral Density	- ANSI C63.10-2020 – Section 11.10
Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions	- ANSI C63.10-2020– Section 11.11
Radiated Test	- ANSI C63.10-2020 – Section 6.4 (Below 30 MHz) - ANSI C63.10-2020 – Section 6.5 (30 MHz to 1000 MHz) - ANSI C63.10-2020 – Section 6.6 (1 GHz to 40 GHz) - ANSI C63.10-2020 – Section 6.10 & 11.12 (Restricted frequency bands)
AC Power line Conducted Emissions	- ANSI C63.10-2020– Section 6.2

7.1. Duty Cycle

Test Configuration



Test Procedure

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to :


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz or 50 MHz ($\geq$ RBW)
3. SPAN = 0 Hz
4. Detector = Average
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = $T_{\text{on}} / T_{\text{total}}$ and Duty Cycle Factor = $10\log(1/\text{Duty Cycle})$

7.2. 6 dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to :

- 1) RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = Max hold
- 5) Sweep = No faster than coupled (auto) time.
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set to 6 dB.


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power

: Measure the peak power of the transmitter.

- Average Power

- 1) Measure the duty cycle.
- 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- 3) Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Measured Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Measured Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3 kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the DTS bandwidth.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = No faster than coupled (auto) time.
- 6) Detector = Peak.
- 7) Trace mode = Max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

- Power Spectral Density = Measured Value + ATT loss + Cable loss


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (Peak) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 20 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to :

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = Max hold
- 6) Sweep time = No faster than coupled (auto) time.
- 7) Ensure that the number of measurement points $\geq 2 \times$ Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	11.23
100	11.16
200	11.14
300	11.23
400	11.40
500	11.31
600	11.27
700	11.40
800	11.40
900	11.38
1000	11.42
2000	11.73
2400	11.24
3000	11.81
4000	11.94
5000	12.04
5850	12.07
6000	12.74
7000	12.82
8000	12.52
9000	13.72
10000	12.66
11000	12.28
12000	12.66
13000	12.50
14000	12.96
15000	13.37
16000	13.14
17000	13.69
18000	13.41
19000	13.51
20000	13.62
21000	13.96
22000	13.85
23000	13.77
24000	13.92
25000	13.77
26000	13.87

Note : 1. 902 ~ 928 MHz is fundamental frequency range.

2. Factor = Attenuator loss + Cable loss


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions (Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3 m from the EUT
3. The EUT is placed on a turntable, which is 0.8 m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40\log(3\text{ m}/300\text{ m}) = -80\text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40\log(3\text{ m}/30\text{ m}) = -40\text{ dB}$
Measurement Distance : 3 m
8. Spectrum Analyzer Setting
Measurement Type(Peak):
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 9 kHz
 - VBW $\geq 3 \times$ RBW
9. Total = Measured value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions (Below 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
3. The Hybrid antenna was placed at a location 3 m from the EUT, which is varied from 1 m to 4 m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

6. Spectrum Analyzer Setting**(1) Measurement Type(Peak):**

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Max hold
- RBW = 100 kHz
- VBW $\geq$ 3 x RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

In general, (1) is used mainly

7. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L)
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Spectrum Analyzer Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 10 GHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - (2) Measurement Type(Average): Duty cycle $\geq 98 \%$
 - Measured Frequency Range : 1 GHz – 10 GHz
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
 - (3) Measurement Type(Average): Duty cycle $< 98 \%$, duty cycle variations are less than $\pm 2 \%$
 - Measured Frequency Range : 1 GHz – 10 GHz
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
 - Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
 - Duty Cycle Factor (dB) : Please refer to Duty cycle test result.
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific

emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

9. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)

10. Total(Measurement Type : Peak)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $\geq 98\%$)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle < 98 %)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)

+ Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 0.8m above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Measured Value + Correction Factor

7.8. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
2. EUT Axis
 - Radiated Spurious Emissions : Z
3. Duty cycle factor applies only OFDM Option2 MCS2 (Duty cycle < 98 %).
4. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane
5. Radiated Spurious Emissions
 - All modes of operation were investigated and the worst case results are reported.
6. The results for the highest antenna gain are reported.

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + Notebook Computer
 - Worstcase : Stand alone + Notebook Computer

Conducted test

1. The EUT was configured with data rate of highest power.

8. SUMMARY TEST OF RESULTS

Test Item	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§ 15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§ 15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§ 15.247(e)	< 8 dBm / 3 kHz		PASS
Band Edge (Out of Band Emissions)	§ 15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§ 15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§ 15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§ 15.247(d), 15.205, 15.209	cf. Section 7.6		N/A

Note. The decision rule applies 'simple acceptance'


9. TEST RESULT

9.1 DUTY CYCLE

Data Rate	OFDM Option	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
MCS 2	Option 2	45.020	46.150	0.976	0.108

Test Plots

OFDM Option2 MCS 2, Channel No. 30




9.2 6 dB BANDWIDTH

Mode	Freq. [MHz]	CH.	6dB Bandwidth [kHz]	99% Occupied Bandwidth [kHz]	Limit [MHz]
OFDM Option2	922.0	24	571.5	665.04	> 0.50
MCS 2	926.8	30	572.7	670.68	> 0.50

Test Plots

OFDM Option2 MCS 2, Channel No. 24



OFDM Option2 MCS 2, Channel No. 30



9.3 OUTPUT POWER

Peak Power

Mode	Frequency [MHz]	Channel	Peak Power [dBm]	Limit [dBm]
OFDM Option2	922.0	24	20.31	30
MCS 2	926.8	30	20.32	30

Average Power

Mode	Frequency [MHz]	Channel	Average Power [dBm]			Limit [dBm]
			Measured Power [dBm]	D.C.F [dB]	Total Power [dBm]	
OFDM Option2	922.0	24	13.41	0.11	13.52	30
MCS 2	926.8	30	13.34	0.11	13.45	30

9.4 POWER SPECTRAL DENSITY


Mode	Frequency [MHz]	Channel	Power Spectral Density [dBm/3kHz]	Limit
			Measured PSD	
OFDM Option2	922.0	24	4.619	8 dBm / 3kHz
MCS 2	926.8	30	4.535	

Test Plots

Note :

In order to simplify the report, attached plots were only the worst case PSD channel.

OFDM Option2 MCS 2, Channel No. 24



9.5 BAND EDGE / CONDUCTED SPURIOUS EMISSIONS

Limit : 20 dBc

Band Edge

Mode	Frequency [MHz]	Channel	Measured Position	Band Edge [dBc]
OFDM Option2	922	24	Lowest Bandedge	67.654
MCS 2	926.8	30	Highest Bandedge	54.181


Conducted Spurious Emissions

Mode	Frequency [MHz]	Channel	Conducted Spurious Emission [dBc]
OFDM Option2	922	24	49.599
MCS 2	926.8	30	49.916

Test Plots(Band Edge)

Note: In order to simplify the report, attached plots were only the worst case.


OFDM Option2 MCS 2, Channel No. 30



Test Plots(Conducted Spurious Emission)

Note: In order to simplify the report, attached plots were only the worst case.

OFDM Option2 MCS 2, Channel No. 24



Limit: -7.19 dBm

9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30 MHz

Frequency	Measured Value	A.F+C.L+D.F	ANT. POL	Total	Limit	Margin
[MHz]	[dBμV/m]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]

No Critical peaks found

Note:

1. The Measured value of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBμV) + Distance extrapolation factor

Frequency Range : Below 1 GHz

Frequency	Measured Value	A.F+C.L	ANT. POL	Total	Limit	Margin
[MHz]	[dBμV/m]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]

No Critical peaks found

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Note : Non Restricted Band refer to Conducted Spurious emission test result (20dBc)

Ch. 24, 922 MHz

Frequency	Measured Value	Duty Cycle Factor	A.F+C.L-A.G+D.F	ANT. POL	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
2766	46.94	0.00	-4.87	V	42.07	73.98	31.91	PK
2766	34.11	0.11	-4.87	V	29.35	53.98	24.63	AV
3688	44.16	0.00	-0.52	V	43.64	73.98	30.34	PK
3688	34.03	0.11	-0.52	V	33.62	53.98	20.36	AV
4610	42.25	0.00	3.17	V	45.42	73.98	28.56	PK
4610	30.21	0.11	3.17	V	33.49	53.98	20.49	AV
7376	38.57	0.00	11.98	V	50.55	73.98	23.43	PK
7376	26.49	0.11	11.98	V	38.58	53.98	15.40	AV
8298	37.34	0.00	13.41	V	50.75	73.98	23.23	PK
8298	25.69	0.11	13.41	V	39.21	53.98	14.77	AV

Frequency	Measured Value	Duty Cycle Factor	A.F+C.L-A.G+D.F	ANT. POL	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
2766	46.96	0.00	-4.87	H	42.09	73.98	31.89	PK
2766	34.17	0.11	-4.87	H	29.41	53.98	24.57	AV
3688	44.22	0.00	-0.52	H	43.70	73.98	30.28	PK
3688	34.26	0.11	-0.52	H	33.85	53.98	20.13	AV
4610	42.32	0.00	3.17	H	45.49	73.98	28.49	PK
4610	30.25	0.11	3.17	H	33.53	53.98	20.45	AV
7376	38.59	0.00	11.98	H	50.57	73.98	23.41	PK
7376	26.54	0.11	11.98	H	38.63	53.98	15.35	AV
8298	37.42	0.00	13.41	H	50.83	73.98	23.15	PK
8298	25.75	0.11	13.41	H	39.27	53.98	14.71	AV

Ch. 30, 926.8 MHz


Frequency	Measured Value	Duty Cycle Factor	A.F+C.L-A.G+D.F	ANT. POL	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
2780.4	46.82	0.00	-4.60	V	42.22	73.98	31.76	PK
2780.4	34.49	0.11	-4.60	V	30.00	53.98	23.98	AV
3707.2	43.76	0.00	-0.23	V	43.53	73.98	30.45	PK
3707.2	33.41	0.11	-0.23	V	33.29	53.98	20.69	AV
4634	42.79	0.00	3.17	V	45.96	73.98	28.02	PK
4634	30.33	0.11	3.17	V	33.60	53.98	20.38	AV
7414.4	39.61	0.00	12.00	V	51.61	73.98	22.37	PK
7414.4	26.55	0.11	12.00	V	38.66	53.98	15.32	AV
8341.2	37.42	0.00	13.74	V	51.16	73.98	22.82	PK
8341.2	25.64	0.11	13.74	V	39.49	53.98	14.49	AV

Frequency	Measured Value	Duty Cycle Factor	A.F+C.L-A.G+D.F	ANT. POL	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
2780.4	46.97	0.00	-4.60	H	42.37	73.98	31.61	PK
2780.4	34.54	0.11	-4.60	H	30.05	53.98	23.93	AV
3707.2	43.90	0.00	-0.23	H	43.67	73.98	30.31	PK
3707.2	33.42	0.11	-0.23	H	33.30	53.98	20.68	AV
4634	43.00	0.00	3.17	H	46.17	73.98	27.81	PK
4634	30.37	0.11	3.17	H	33.64	53.98	20.34	AV
7414.4	39.75	0.00	12.00	H	51.75	73.98	22.23	PK
7414.4	26.87	0.11	12.00	H	38.98	53.98	15.00	AV
8341.2	37.55	0.00	13.74	H	51.29	73.98	22.69	PK
8341.2	25.79	0.11	13.74	H	39.64	53.98	14.34	AV


Test Plots

Note: In order to simplify the report, Plots of worst case are only reported.

Radiated Spurious Emissions plot – Average Result (Ch.30 Harmonic, Z-H)



Radiated Spurious Emissions plot – Peak Result (Ch.30 Harmonic, Z-H)



9.7 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions

Test


1 / 1

Test Report

Common Information

EUT : EBR23718203
Operating Conditions : Wi-Sun Mode
Comment :

Full Spectrum



Final Result QPK

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.1500	51.14	66.00	14.86	9.000	L1	9.6
0.1680	58.86	65.06	6.20	9.000	L1	9.6
0.1793	57.05	64.52	7.47	9.000	L1	9.6
4.4578	36.12	56.00	19.88	9.000	L1	9.8
4.4848	35.62	56.00	20.38	9.000	N	9.7
4.6625	30.87	56.00	25.13	9.000	L1	9.8
18.2435	38.47	60.00	21.53	9.000	N	9.9
18.3763	38.45	60.00	21.55	9.000	N	9.9
18.7070	35.46	60.00	24.54	9.000	N	9.9

Final Result CAV

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.1545	39.32	55.75	16.44	9.000	N	9.6
0.1793	38.62	54.52	15.90	9.000	L1	9.6
0.2400	26.86	52.10	25.23	9.000	L1	9.7
4.4240	21.57	46.00	24.43	9.000	L1	9.8
4.4690	20.94	46.00	25.06	9.000	L1	9.8
4.5140	19.95	46.00	26.05	9.000	L1	9.8
17.9105	25.66	50.00	24.34	9.000	N	9.9
18.5765	26.10	50.00	23.90	9.000	N	9.9
19.9715	25.13	50.00	24.87	9.000	N	10.0

2025-11-21

오전 8:48:22

10. LIST OF TEST EQUIPMENT

Conducted Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
LISN	ENV216	Rohde & Schwarz	102245	07/15/2026	Annual
EMI Test Receiver	ESR	Rohde & Schwarz	101910	08/20/2026	Annual
Temperature Chamber	SU-642	ESPEC	0093008124	02/11/2026	Annual
Signal Analyzer	N9030A	Agilent	MY49432108	02/18/2026	Annual
Power Measurement Set	OSP 120	Rohde & Schwarz	100935	07/24/2026	Annual
Power Meter	N1911A	Agilent	MY45100523	02/21/2026	Annual
Power Sensor	N1921A	Agilent	MY57820067	02/04/2026	Annual
Directional Coupler	87300B	Agilent	3116A03621	10/14/2026	Annual
Power Splitter	11667B	Hewlett Packard	10545	01/23/2026	Annual
DC Power Supply	E3632A	Agilent	KR75303243	04/16/2026	Annual
Attenuator(10 dB)(DC-26.5 GHz)	8493C	HP	07560	05/27/2026	Annual
Attenuator(10 dB)(DC-26.5 GHz)	8493C	HP	08285	05/19/2026	Annual
Attenuator(20 dB)	18N-20dB	Rohde & Schwarz	8	02/18/2026	Annual
Software	EMC32	Rohde & Schwarz	N/A	N/A	N/A
Bluetooth Tester	CBT	Rohde & Schwarz	100752	12/27/2025	Annual
Automation Software	FCC WLAN Conducted	HCT CO., LTD	N/A	N/A	N/A

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
Controller	CO3000	Innco system	CO3000-4p	N/A	N/A
Antenna Position Tower	MA4640/800-XP-EP	Innco system	S1AM	07/25/2026	Annual
Turn Table	DS2000-S-1t	Innco system	DS2000/572/54610422/P	N/A	N/A
Amp & Filter Bank Switch Controller	FBSM-01B	T&M system	TM19050002	N/A	N/A
Loop Antenna	1513	Schwarzbeck	1513-175	06/24/2027	Biennial
Hybrid Antenna	VULB 9168	Schwarzbeck	9168-0895	08/28/2026	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-1300	01/03/2026	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-2296	05/16/2026	Biennial
Horn Antenna(15 GHz ~ 40 GHz)	BBHA9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Spectrum Analyzer	FSV(10 Hz ~ 40 GHz)	Rohde & Schwarz	101055	05/07/2026	Annual
Band Reject Filter	WRCJV2400/2483.5-2370/2520-60/12SS	Wainwright Instruments	2	12/26/2025	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	5	05/27/2026	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	6	05/27/2026	Annual
High Pass Filter	F5_HPF1.5G	Wainwright Instruments	F5	05/09/2026	Annual
High Pass Filter(7 GHz ~ 18 GHz)	WHKX10-7150-8000-18000-50SS	Wainwright Instruments	1	02/21/2026	Annual
Power Amplifier	CBL18265035	CERNEX	22966	10/21/2026	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
Bluetooth Tester	TC-3000C	TESCOM	3000C000175	03/12/2026	Annual
RF Switching System	FMSR-05B (HPF(3~18GHz) + LNA1(1~18GHz))	T&M system	S1L1	12/08/2026	Annual
RF Switching System	FMSR-05B (ATT(10dB) + LNA1(1~18GHz))	T&M system	S1L2	12/08/2026	Annual
RF Switching System	FMSR-05B (ATT(3dB) + LNA1(1~18GHz))	T&M system	S1L3	12/08/2026	Annual
RF Switching System	FMSR-05B (LNA1(1~18GHz))	T&M system	S1L4	12/08/2026	Annual
RF Switching System	FMSR-05B (HPF(7~18GHz) + LNA2(6~18GHz))	T&M system	S1L5	12/08/2026	Annual
RF Switching System	FMSR-05B (Thru(30MHz ~ 18GHz))	T&M system	S1L6	12/08/2026	Annual
Automation Software	FCC WLAN Radiated	HCT CO., LTD	N/A	N/A	N/A
Attenuator(3 dB)	18B-03	Api tech.	1	04/21/2026	Annual

Note:

- Equipment whose calibration due date was updated during the test period was not used between the previous due date and the update.
All reported measurements were performed using equipment within valid calibration.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of ANSI C63.5-2017.

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2512-FC006-P