

TEST REPORT

FCC MPE Test for TMCTAW5W
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2607-FC004-R1

DATE OF ISSUE
August 10, 2026

Tested by
Ki Jae Kwon



Technical Manager
Jong Seok Lee



Accredited by KOLAS, Republic of KOREA

HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO



HCT CO.,LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2607-FC004-R1

DATE OF ISSUE

August 10, 2026

Applicant

LG Electronics Inc.

222 LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 17709, South Korea

Product Name

LG Smart Thermostat

Model Name

TMCTAW5W

FCC ID

2BO3L-TMCTAW5W

Date of Test

June 11, 2026 ~ July 08, 2026

Location of Test

■ Permanent Testing Lab □ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

Manufacturer

HYUNDAI HT GLOBAL COMPANY LIMITED

Lot M, Binh Xuyen industrial Zone, Binh Nguyen Commune, Phu Tho Province, Vitenam

Test Standard Used

CFR 47 Part 2.1091

Test Results

PASS

Brand

LG

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 16, 2026	Initial Release
1	August 10, 2026	Revised the Product Name.

Notice

Content
Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance. The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated. The test results have only been applied with the test methods required by the standard(s). The laboratory is not accredited for the test results marked *. Information provided by the applicant is marked **. Test results provided by external providers are marked ***. When confirmation of authenticity of this test report is required, please contact www.hct.co.kr This test report provides test result(s) under the scope accredited by the Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA. (KOLAS (KS Q ISO/IEC 17025) Accreditation No. KT197)

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures				
Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	#)(100)	30
1.34 - 30.....	824/f	2.19/f	#)(180/f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

= Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

EIRP[Radiated Power]	16.50	dBm
EIRP[Radiated Power]	44.67	mW
Prediction distance	20.00	cm
Prediction frequency	61,450	MHz
Power density at prediction frequency (S)	0.0089	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²