SGS Korea Co., Ltd.
4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
Tel. +82 31 428 5700 / Fax. +82 31 427 2370
http://www.sgsgroup.kr



# TEST REPORT

**of**

FCC CFR 47 part 1, 1.1307(b)

FCC ID: 2BO3LCCRCSLIMH

| | | |
|---|---|---|
| Equipment Under Test | : | Rear Seat Entertainment |
| Model Name | : | CCRCSLIMH |
| Variant Model Name(s) | : | - |
| Applicant | : | LG Electronics Inc. |
| Manufacturer | : | LG Electronics Inc. |
| Date of Receipt | : | 2026.04.23 |
| Date of Test(s) | : | 2026.05.22 ~ 2026.06.04 |
| Date of Issue | : | 2026.06.10 |

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

1) The results of this test report are effective only to the items tested.
2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.
We are responsible for all the information of this test report except for the data(※) provided by the customer.

**Tested by:** Dave Kim

**Technical Manager:** Jinhyoung Cho

## SGS Korea Co., Ltd. Gunpo Laboratory

# INDEX

Table of Contents

1. General Information ---------- 3

2. RF Exposure ---------- 6

# 1. General Information

## 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- CAB Identifier: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901
Fax No. : +82 31 688 0921

## 1.2. Details of Applicant

Applicant : LG Electronics Inc.
Address : 222 LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, South Korea, 17709
Contact Person : Kwon, Yong deok
Phone No. : +82 31 8066 5538

## 1.3. Details of Manufacturer

Company : LG Electronics Inc.
Address : 128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea, 07336

## 1.4. Description of EUT

| | |
|---|---|
| **Kind of Product** | Rear Seat Entertainment |
| **Model Name** | CCRCSLIMM |
| **Serial Number** | Conducted: 605KVCL104147<br>Radiated: 605KVYK104146 |
| **Power Supply** | DC 12 V |
| **Frequency Range** | 2 402 ㎒ ~ 2 480 ㎒ (Bluetooth Low Energy)<br>2 412 ㎒ ~ 2 462 ㎒ (11b/g/n_HT20)<br>5 180 ㎒ ~ 5 240 ㎒ (U-NII 1: 11a/n_HT20, 11ac_VHT20)<br>5 190 ㎒ ~ 5 230 ㎒ (U-NII 1: 11n_HT40, 11ac_VHT40)<br>5 210 ㎒ (U-NII 1: 11ac_VHT80)<br>5 745 ㎒ ~ 5 825 ㎒ (U-NII 3: 11a/n_HT20, 11ac_VHT20)<br>5 755 ㎒ ~ 5 795 ㎒ (U-NII 3: 11n_HT40, 11ac_VHT40)<br>5 775 ㎒ (U-NII 3: 11ac_VHT80) |
| **Modulation Technique** | DSSS, OFDM, GFSK |
| **Number of Channels** | 40 channels (Bluetooth Low Energy)<br>11 channels (11b/g/n_HT20)<br>4 channels (U-NII 1: 11a/n_HT20, 11ac_VHT20)<br>2 channels (U-NII 1: 11n_HT40, 11ac_VHT40)<br>1 channel (U-NII 1: 11ac_VHT80)<br>5 channels (U-NII 3: 11a/n_HT20, 11ac_VHT20)<br>2 channels (U-NII 3: 11n_HT40, 11ac_VHT40)<br>1 channel (U-NII 3: 11ac_VHT80) |
| **Antenna Type** | Ant.1: Chip Antenna<br>Ant.2: Chip Antenna |
| **Antenna Gain** ※ | Ant. 1 & Ant. 2<br>BLE: 2 402 ㎒ ~ 2 480 ㎒: 3.61 ㏈i<br>WLAN2: 2 412 ㎒ ~ 2 462 ㎒: 3.61 ㏈i<br>WLAN5: 5 180 ㎒ ~ 5 240 ㎒: 3.10 ㏈i<br>5 745 ㎒ ~ 5 825 ㎒: 3.10 ㏈i |
| **H/W Version** | V1.0 |
| **S/W Version** | V1.0 |

## 1.5. Declarations by the manufacturer

- The EUT does not support transmit power control (TPC).
- The EUT only supports UNII-1 Band and UNII-3 Band.
- WLAN 5G transmits both SISO and MIMO mode.

## 1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 1 | | |
|---|---|---|
| **Section** | **Test Item(s)** | **Result** |
| 1.1307(b)(3) | RF Exposure Evaluation | Pass |

## 1.7. Test Report Revision

| Revision | Report Number | Date of Issue | Description |
|---|---|---|---|
| 0 | F690501-RF-RTL007062 | 2026.06.10 | Initial |

## 1.8. Device Capabilities

| Mode | SISO | | MIMO |
|---|---|---|---|
| | Ant. 1 | Ant. 2 | Ant. 1 + Ant. 2 |
| Bluetooth Low Energy | O | X | X |
| WLAN 2 ㎓ | X | O | X |
| WLAN 5 ㎓ | O | O | O |

# 2. RF Exposure Evaluation

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

## 2.1. Blanket 1 ㎽ Blanket Exemption

The 1 ㎽ Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 ㎽, regardless of separation distance.
The 1 ㎽ blanket exemption applies at separation distances less than 0.5 ㎝, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).
The 1 ㎽ exemption is independent of service type and covers the full range of 100 ㎑ to 100 ㎓, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

## 2.2. MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 ㎑ through 100 ㎓.

**Table 1: THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

| RF Source Frequency | | | Minimum Distance | | | Threshold ERP |
|---|---|---|---|---|---|---|
| $f_L$ (㎒) | | $f_H$ (㎒) | $\lambda_L / 2\pi$ | | $\lambda_H / 2\pi$ | W |
| 0.3 | - | 1.34 | 159 m | - | 35.6 m | 1 920 R2 |
| 1.34 | - | 30 | 35.6 m | - | 1.6 m | 3 450 $R^2/f^2$ |
| 30 | - | 300 | 1.6 m | - | 159 mm | 3.83 $R^2$ |
| 300 | - | 1 500 | 159 mm | - | 31.8 mm | 0.012 8 $R^2f$ |
| 1 500 | - | 100 000 | 31.8 mm | - | 0.5 mm | 19.2 $R^2$ |
| Subscripts L and H are low and high; λ is wavelength.<br>From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns. | | | | | | |

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least λ/2π. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.
For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 ㎝ to 40 ㎝ and in 0.3 ㎓ to 6 ㎓, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP 20 ㎝ in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{\text{th}}\ (\text{mW}) = ERP_{20\ \text{cm}}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases} \qquad \text{(B. 1)}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of λ/4 or if the antenna gain is less than that of a half-wave dipole.
SAR-based exemptions are constant at separation distances between 20 ㎝ and 40 ㎝ to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 ㎝, considering the importance of reflections.

## 2.3. SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.
If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of λ/4.
As for devices with antennas of length greater than λ/4 where the gain is not well defined, but always less than that of a half-wave dipole (length λ/2), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.
The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.
The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold $P_{th}$ (㎽).
This method shall only be used at separation distances from 0.5 ㎝ to 40 ㎝ and at frequencies from 0.3 ㎓ to 6 ㎓ (inclusive). $P_{th}$ is given by Formula (B.2).

$$P_{\text{th}}\ (\text{mW}) = \begin{cases} ERP_{20\ \text{cm}}(d/20\ \text{cm})^x & d \le 20\ \text{cm} \\ ERP_{20\ \text{cm}} & 20\ \text{cm} < d \le 40\ \text{cm} \end{cases} \qquad \text{(B. 2)}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\ \text{cm}}\sqrt{f}}\right)$$

and f is in ㎓, d is the separation distance (㎝), and ERP 20 ㎝ is per Formula (B.1).

## 2.4. Simultaneous Transmission SAR Test Exemption with Respect to Multiple Exemption Criteria

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR ($Evaluated_k$ term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^{a}\frac{P_i}{P_{th,i}} + \sum_{j=1}^{b}\frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c}\frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

# 3. Test Results

## 3.1. RF Exposure Test Exemptions for Single Source

**-MPE-based Exemption**

| Mode | Frequency Range (㎒) | Minimum Separation Distance (㎝) | Maximum Average Target Power (㏈ m) | Maximum Tune up (dB) | Maximum Average Power (㏈ m) | Antenna Gain (㏈ i) | ERP | | Threshold ERP | Ratio | Result |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | (㏈ m) | (㎽) | (㎽) | | |
| Bluetooth Low Energy | 2 402 ~ 2 480 | 20 | 0 | 2 | 2 | 3.61 | 3.46 | 2.22 | 768 | 0.003 | Pass |
| WLAN 2.4G | 2 412 ~ 2462 | 20 | 12 | 1 | 13 | 3.61 | 14.46 | 27.93 | 768 | 0.036 | Pass |
| WLAN 5G | 5 180 ~ 5 240 | 20 | 4.5 | 1 | 5.5 | 3.10 | 6.45 | 4.42 | 768 | 0.006 | Pass |
| WLAN 5G | 5 745 ~ 5 805 | 20 | 7 | 1 | 8 | 3.10 | 8.95 | 7.85 | 768 | 0.010 | Pass |

Note ;

- Maximum average target power is the manufacturer's declared rated power.
- Maximum average power = Maximum average target power (㏈ m) + Maximum tune up (㏈).
- ERP (㏈ m) = Maximum average Power (㏈ m) + Antenna Gain (㏈ i) -2.15

## 3.2. RF Exposure Test Exemptions for Simultaneous Transmission

| Mode | $P_i/P_{th}$ Ratio Mode A | $P_i/P_{th}$ Ratio Mode B | $\Sigma$ $P_i/P_{th}$ Ratio Mode A+B | Result |
|---|---|---|---|---|
| Bluetooth Low Energy +WLAN (5G) | 0.003 | 0.010 | 0.013 | Pass |
| WLAN (2.4G) + WLAN (5G) | 0.036 | 0.010 | 0.046 | Pass |
| WLAN (5G) + WLAN (5G) | 0.010 | 0.010 | 0.020 | Pass |

**Conclusion: No SAR is required.**

**- End of the Test Report -**