

TEST REPORT

of

RF Exposure Evaluation

FCC ID: 2BO3LLANR62

Equipment Under Test : CONT ASSY-CDC
Model Name : LANR62
Variant Model Name(s) : -
Applicant : LG Electronics Inc.
Manufacturer : LG Electronics Inc.
Date of Receipt : 2025.10.24
Date of Test(s) : 2025.11.06 ~ 2026.03.17
Date of Issue : 2026.04.21

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Dave Kim

Technical Manager:



Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory



SGS Korea Co., Ltd.

4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

<http://www.sgsgroup.kr>

Report Number: F690501-RF-RTL006899

Page: 2 of 9

INDEX

Table of Contents

1. General Information -----	3
2. RF Exposure -----	6

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- CAB Identifier: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : LG Electronics Inc.

Address : 222 LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, South Korea, 17709

Contact Person : Kwon, Yong-deok

Phone No. : +82 31 8066 5538

1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea, 07336

Factory 1 : LG Electronics Inc.

Factory 1 Address : 222 LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 17709, Republic of Korea

Factory 2 : LG Electronics Vietnam Haiphong Co., Ltd.

Factory 2 Address : Lots CN2, Trang Due Industrial Park, Le Loi Commune, An Duong District, Hai Phong City, Vietnam

Factory 3 : LG Electronics Reynosa S.A. de C.V.

Factory 3 Address : Av. Olimpia #2342, Parque Industrial Santa Maria 2da Etapa, 25903 Ramos Arizpe, Coahuila, Mexico

1.4. Description of EUT

Kind of Product	CONT ASSY-CDC
Model Name	LANR62
Serial Number	Conducted: 001 Radiated: 002
Power Supply	DC 12 V
Frequency Range	2 402 MHz ~ 2 480 MHz (Bluetooth) 2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy) 2 412 MHz ~ 2 462 MHz (11b/g/n_HT20) 5 180 MHz ~ 5 240 MHz (Band 1: 11a/n_HT20, 11ac_VHT20) 5 190 MHz ~ 5 230 MHz (Band 1: 11n_HT40, 11ac_VHT40) 5 210 MHz (Band 1: 11ac_VHT80) 5 745 MHz ~ 5 805 MHz (Band 3: 11a/n_HT20, 11ac_VHT20) 5 755 MHz ~ 5 795 MHz (Band 3: 11n_HT40, 11ac_VHT40) 5 775 MHz (Band 3: 11ac_VHT80)
Modulation Technique	DSSS, OFDM, GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels	79 channels (Bluetooth) 40 channels (Bluetooth Low Energy) 11 channels (11b/g/n_HT20) 4 channels (Band 1: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 1: 11n_HT40, 11ac_VHT40) 1 channel (Band 1: 11ac_VHT80) 4 channels (Band 3: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 3: 11n_HT40, 11ac_VHT40) 1 channel (Band 3: 11ac_VHT80)
Antenna Type	Ant.1: Internal Chip Antenna Ant.2: External PIFA Ant.3: Internal Chip Antenna
Antenna Gain ※	Ant. 1 BT&BLE: 2 402 MHz ~ 2 480 MHz: 0.99 dB i WLAN5: 5 180 MHz ~ 5 240 MHz: 0.90 dB i 5 745 MHz ~ 5 805 MHz: 0.71 dB i Ant. 2 WLAN2: 2 412 MHz ~ 2 462 MHz: 3.09 dB i WLAN5: 5 180 MHz ~ 5 240 MHz: 2.95 dB i 5 745 MHz ~ 5 805 MHz: 4.04 dB i Ant. 3 WLAN2: 2 412 MHz ~ 2 462 MHz: 0.71 dB i WLAN5: 5 180 MHz ~ 5 240 MHz: 0.68 dB i 5 745 MHz ~ 5 805 MHz: 0.02 dB i
H/W Version	1.0
S/W Version	1.0

1.5. Declarations by the manufacturer

- The EUT supports transmit power control (TPC).
- The EUT only supports UNII-1 and UNII-3 Band.
- The EUT does not support channel 165.
- The EUT has three ports (Port1, Port 2 and Port 3).
- WLAN 5G transmits both SISO and CDD/MIMO mode.

1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 2		
Section	Test Item(s)	Result
2.1091	RF Exposure Evaluation	Complied

1.7. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL006899	2026.04.21	Initial

1.8. Device Capabilities

Mode	SISO			CDD / MIMO	
	Ant. 1	Ant. 2	Ant. 3	Ant. 1 + Ant. 2	Ant. 1 + Ant. 3
Bluetooth Low Energy	O	X	X	X	X
Bluetooth	O	X	X	X	X
WLAN 2 GHz	X	O	O	X	X
WLAN 5 GHz	O	O	O	O	O

2. RF Exposure Evaluation

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

2.1. Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).

The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

2.2. MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

**Table 1: THRESHOLDS FOR SINGLE RF SOURCES
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

RF Source Frequency			Minimum Distance			Threshold ERP
f_L (MHz)		f_H (MHz)	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	-	1.34	159 m	-	35.6 m	1 920 R ²
1.34	-	30	35.6 m	-	1.6 m	3 450 R ² /f ²
30	-	300	1.6 m	-	159 mm	3.83 R ²
300	-	1 500	159 mm	-	31.8 mm	0.012 8 R ² f
1 500	-	100 000	31.8 mm	-	0.5 mm	19.2 R ²
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20 cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

2.3. SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

2.4. Simultaneous Transmission SAR Test Exemption with Respect to Multiple Exemption Criteria

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

3. Test Results

3.1. RF Exposure Test Exemptions for Single Source

-MPE-based Exemption

Mode	Frequency Range (MHz)	Minimum Separation Distance (cm)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Power (dB m)	Antenna Gain (dB i)	ERP		Threshold ERP (mW)	Ratio	Result
							(dB m)	(mW)			
Bluetooth	2 402 ~ 2 480	20	0	2	2	0.99	0.84	1.213	768	0.002	Pass
Bluetooth Low Energy	2 402 ~ 2 480	20	0	2	2	0.99	0.84	1.213	768	0.002	Pass
WLAN (2.4G)	2 412 ~ 2462	20	14	2	16	3.09	16.94	49.43	768	0.064	Pass
WLAN (5G)	5 180 ~ 5 240	20	6.5	2.5	9.0	5.00	11.85	15.31	768	0.020	Pass
WLAN (5G)	5 745 ~ 5 805	20	14	2	16	5.54	19.39	86.90	768	0.113	Pass

Note ;

- Maximum average target power is the manufacturer's declared rated power.
- Maximum average power = Maximum average target power (dB m) + Maximum tune up (dB).
- ERP (dB m) = Maximum average Power (dB m) + Antenna Gain (dB i) -2.15

3.2. RF Exposure Test Exemptions for Simultaneous Transmission

Mode	P_i/P_{th} Ratio Mode A	P_i/P_{th} Ratio Mode B	P_i/P_{th} Ratio Mode C	$\Sigma P_i/P_{th}$ Ratio Mode A+B+C	Result
Bluetooth + Bluetooth Low Energy + WLAN (2.4G)	0.002	0.002	0.064	0.068	Pass
Bluetooth + Bluetooth Low Energy + WLAN (5G)	0.002	0.002	0.113	0.117	Pass

Conclusion: No SAR is required.

- End of the Test Report -