Appendix A

RF Test Data for BT(BDR/EDR) (Conducted Measurement)

Product Name: Wireless earbuds

Trade Mark: N/A

Test Model: Y50

Environmental Conditions

Temperature:	24.6℃
Relative Humidity:	52.7%
ATM Pressure:	101Kpa
Test Engineer:	Emiya lin
Supervised by:	Simba Haung

Contents

Page

COVER PAGE

1 Duty Cycle 3
1.1 Test Result 3
1.2 Test Graphs 4
2 Maximum Conducted Peak Output Power 9
2.1 Test Result 9
2.2 Test Graphs 10
3 20dB Bandwidth 15
3.1 Test Result 15
3.2 Test Graphs 16
4 Carrier Frequency Separation 21
4.1 Test Result 21
4.2 Test Graphs 22
5 Hopping Channel Number 24
5.1 Test Result 24
5.2 Test Graphs 25
6 Dwell Time 27
6.1 Test Result 27
6.2 Test Graphs 28
7 RF Conducted Spurious Emissions 31
7.1 Test Result 31
7.2 Test Graphs 32
8 Band-edge for RF Conducted Emissions 41
8.1 Test Result 41
8.2 Test Graphs 42
9 Restrict-band band-edge measurements 54
9.1 Test Result 54
9.2 Test Graphs 56

1 Duty Cycle

1.1 Test Result

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor	1/T (kHz)
1-DH1	2402	33.61	4.74	2.44
1-DH1	2441	32.94	4.82	2.44
1-DH1	2480	33.6	4.74	2.44
2-DH1	2402	34.4	4.63	2.38
2-DH1	2441	34.41	4.63	2.38
2-DH1	2480	34.4	4.63	2.38
3-DH1	2402	34.4	4.63	2.38
3-DH1	2441	34.4	4.63	2.38
3-DH1	2480	34.12	4.67	2.44

1.2 Test Graphs

Test Graphs
1-DH1 2402MHz



1-DH1 2441MHz



1-DH1 2480MHz



2-DH1 2402MHz



2-DH1 2441MHz



2-DH1 2480MHz



3-DH1 2402MHz



3-DH1 2441MHz



3-DH1 2480MHz



2 Maximum Conducted Peak Output Power

2.1 Test Result

Mode	Channel.	Maximum Peak Output Power [dBm]	Limit [dBm]	Verdict
GFSK	LCH	1.07	21	Pass
	MCH	1.11	21	Pass
	HCH	1.95	21	Pass
π/4DQPSK	LCH	1.07	21	Pass
	MCH	1.23	21	Pass
	HCH	1.88	21	Pass
8DPSK	LCH	1.28	21	Pass
	MCH	1.16	21	Pass
	HCH	1.7	21	Pass

2.2 Test Graphs

Test Graphs	
GFSK/LCH	
GFSK/MCH	

GFSK/HCH	
π/4DQPSK/LCH	

π/4DQPSK/MCH	
π/4DQPSK/HCH	

8DPSK/LCH	
8DPSK/MCH	

8DPSK/HCH	 Spectrum Ref Level 20.00 dBm Offset 2.81 dB RBW 3 MHz Att 30 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT SGL Count 100/100 1Pk Max M1[1] 1.70 dBm 2.479525000 GHz M1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm CF 2.48 GHz 10001 pts Span 10.0 MHz

3 20dB Bandwidth

3.1 Test Result

Mode	Channel.	20dB Bandwidth [MHz]	Limit [MHz]	Verdict
GFSK	LCH	0.825	Not Specified	Pass
	MCH	0.887	Not Specified	Pass
	HCH	0.797	Not Specified	Pass
π/4DQPSK	LCH	1.221	Not Specified	Pass
	MCH	1.196	Not Specified	Pass
	HCH	1.157	Not Specified	Pass
8DPSK	LCH	1.2	Not Specified	Pass
	MCH	1.204	Not Specified	Pass
	HCH	1.206	Not Specified	Pass

3.2 Test Graphs

Test Graphs	
GFSK/LCH	
GFSK/MCH	

GFSK/HCH



π/4DQPSK/LCH



π/4DQPSK/MCH



π/4DQPSK/HCH



8DPSK/LCH



8DPSK/MCH



8DPSK/HCH	

Spectrum
Ref Level 20.00 dBm Offset 2.81 dB RBW 30 kHz
Att 30 dB SWT 63.2 µs VBW 100 kHz Mode Auto FFT
SGL Count 100/100
1Pk Max
M1[1] -0.72 dBm 2.479841620 GHz
M2[1] -20.85 dBm 2.479418000 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
M1
M2
M3
CF 2.48 GHz
10001 pts
Span 2.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.47984162 GHz -0.72 dBm
M2 1 2.479418 GHz -20.85 dBm
M3 1 2.480624 GHz -20.63 dBm

4 Carrier Frequency Separation

4.1 Test Result

Mode	Channel.	Carrier Frequency Separation [MHz]	Limit [MHz]	Verdict
GFSK	MCH	0.998	0.591	Pass
π/4DQPSK	MCH	1	0.797	Pass
8DPSK	MCH	1	0.803	Pass

4.2 Test Graphs

Test Graphs	
GFSK/MCH	
π/4DQPSK/MCH	

8DPSK/MCH	 Spectrum Ref Level 20.00 dBm Offset 2.80 dB RBW 30 kHz Att 30 dB SWT 63.3 µs VBW 100 kHz Mode Auto FFT 1Pk Max M1[1] -8.17 dBm 2.44088900 GHz M2[1] -7.76 dBm 2.44188900 GHz 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm CF 2.4415 GHz 1001 pts Span 2.0 MHz Marker Type Ref Trc X-value Y-value Function Function Result M1 1 2.440889 GHz -8.17 dBm M2 1 2.441889 GHz -7.76 dBm

5 Hopping Channel Number

5.1 Test Result

Mode	Channel.	Number of Hopping Channel [N]	Limit [N]	Verdict
GFSK	Hop	79	>=15	PASS
π/4DQPSK	Hop	79	>=15	PASS
8DPSK	Hop	79	>=15	PASS

5.2 Test Graphs

Test Graphs	
GFSK/Hop	
π/4DQPSK/Hop	

8DPSK/Hop	

Spectrum
Ref Level 20.00 dBm Offset 2.80 dB RBW 100 kHz
Att 30 dB SWT 94.8 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1] -6.41 dBm 2.4015865 GHz
M2[1] -4.08 dBm 2.4804105 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
Start 2.4 GHz 1001 pts Stop 2.4835 GHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.4015865 GHz -6.41 dBm
M2 1 2.4804105 GHz -4.08 dBm

6 Dwell Time

6.1 Test Result

Mode	Packet	Channel	Burst Width [ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[ms]	Limit [s]	Verdict
GFSK	DH5	MCH	2.904	105	304.92	0.4	Pass
π/4DQPSK	2DH5	MCH	2.912	105	305.76	0.4	Pass
8DPSK	3DH5	MCH	2.915	105	306.075	0.4	Pass

6.2 Test Graphs

Test Graphs	
GFSK_DH5/MCH	 

π/4DQPSK
_2DH5/MCH





8DPSK _3DH5/MCH





7 RF Conducted Spurious Emissions

7.1 Test Result

Mode	Channel	Max. Level [dBc]	Limit [dBc]	Verdict
GFSK	LCH	-27.16	-20	Pass
	MCH	-27.54	-20	Pass
	HCH	-31.49	-20	Pass
π/4DQPSK	LCH	-35.99	-20	Pass
	MCH	-29.67	-20	Pass
	HCH	-26.6	-20	Pass
8DPSK	LCH	-28.01	-20	Pass
	MCH	-30.01	-20	Pass
	HCH	-26.96	-20	Pass

7.2 Test Graphs

GFSK_LCH_Graphs	
Pref	
Puw	

GFSK_MCH_Graphs	
Pref	
Puw	

GFSK_HCH_Graphs	
Pref	
Puw	

π/4DQPSK_LCH_Graphs	
Pref	
Puw	

π/4DQPSK_MCH_Graphs	
Pref	
Puw