RF Exposure Evaluation

For

Shenzhen Onail Technology Co.,Ltd

AI Nail Machine

Test Model: Non-harmful to Skin 1

Prepared for	:	Shenzhen Onail Technology Co.,Ltd
Address	:	Room 1903&1905, Xingtong Building, No.88 Baoxing Road, Bao'an District Shenzhen Guangdong China
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	April 30, 2025
Number of tested samples	:	2
Sample No.	:	A250429061-1, A250429061-2
Serial number	:	Prototype
Date of Test	:	April 30, 2025 ~ May 14, 2025
Date of Report	:	May 15, 2025

RF Exposure Evaluation		
Report Reference No.	**:**	**LCSA02105067EB**
Date of Issue	:	May 15, 2025
Testing Laboratory Name	**:**	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address.....	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure.....	:	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name.....	**:**	**Shenzhen Onail Technology Co.,Ltd**
Address.....	:	Room 1903&1905, Xingtong Building, No.88 Baoxing Road, Bao'an District Shenzhen Guangdong China
Test Specification		
Standard	:	FCC KDB publication 447498 D01 General RF Exposure Guidance v06 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1093
Test Report Form No.	**:**	TRF-4-E-215 A/0
TRF Originator.....	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	:	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.	**:**	**AI Nail Machine**
Trade Mark	:	N/A
Test Model	:	Non-harmful to Skin 1
Ratings.....	:	Input: 12V⎓2.5A For Adapter Input: 100-240V~, 50/60Hz, 0.6A(Max.) Adapter Output: 5.0V⎓3.0A 15.0W, 9.0V⎓3.0A 27.0W, 12.0V⎓2.5A 30.0W
Result	:	PASS

Compiled by:	Supervised by:	Approved by:
Nadia Zhou	Jack Liu	Gavin Liang
Nadia Zhou/ Administrator	Jack Liu/ Technique principal	Gavin Liang/ Manager

RF Exposure Evaluation

Test Report No. : LCSA02105067EB	May 15, 2025 Date of issue

EUT.....	:	AI Nail Machine
Test Model.....	:	Non-harmful to Skin 1
Applicant.....	**:**	**Shenzhen Onail Technology Co.,Ltd**
Address.....	:	Room 1903&1905, Xingtong Building, No.88 Baoxing Road, Bao'an District Shenzhen Guangdong China
Telephone.....	:	/
Fax.....	:	/
Manufacturer.....	**:**	**Shenzhen Onail Technology Co.,Ltd**
Address.....	:	Room 1903&1905, Xingtong Building, No.88 Baoxing Road, Bao'an District Shenzhen Guangdong China
Telephone.....	:	/
Fax.....	:	/
Factory.....	**:**	**Zhongshan Sunclean Co.,Ltd**
Address.....	:	F/2, F/5, F/6 #1, F/8 #2, Building G, NO.3 of Huanzhen North 13 RD, XinFeng Village Henglan Town, Zhongshan, Guangdong, P.R. CHINA
Telephone.....	:	/
Fax.....	:	/

Test Result	**PASS**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	May 15, 2025	Initial Issue	---

TABLE OF CONTENTS

Description **Page**

1. PRODUCT INFORMATION 6
2. EVALUATION METHOD AND LIMIT 7
3. REFER EVALUATION METHOD 7
4. CONDUCTED POWER RESULTS 8
5. MANUFACTURING TOLERANCE 9
6. EVALUATION RESULTS 10
7. CONCLUSION 10
8. DESCRIPTION OF TEST FACILITY 10
9. MEASUREMENT UNCERTAINTY 10

1. Product Information

EUT	:	AI Nail Machine
Test Model	:	Non-harmful to Skin 1
Ratings	:	Input: 12V⎓2.5A For Adapter Input: 100-240V~, 50/60Hz, 0.6A(Max.) Adapter Output: 5.0V⎓3.0A 15.0W, 9.0V⎓3.0A 27.0W, 12.0V⎓2.5A 30.0W
Hardware Version	:	V1.0
Software Version	:	/
WIFI(2.4G Band)	:	
Frequency Range	:	2412MHz~2462MHz
Channel Spacing	:	5MHz
Channel Number	:	11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	PCB Antenna, 2.83dBi(Max.)
Exposure category	:	General population/uncontrolled environment
EUT Type	:	Production Unit
Device Type	:	Portable Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.		

2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

[(max. power of channel, including tune-up tolerance, mW)/ (min. test separation distance, mm)] · [√f (GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

a) The [∑ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg] + [∑ of MPE ratios] is ≤ 1.0.

b)The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04, and the [∑ of MPE ratios] is ≤ 1.0.

3. Refer Evaluation Method

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1093: Radiofrequency radiation exposure evaluation: portable devices

4. Conducted Power Results

<2.4G WIFI>

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	15.49
	6	2437	14.66
	11	2462	14.63
IEEE 802.11g	1	2412	14.70
	6	2437	14.77
	11	2462	13.92
IEEE 802.11n HT20	1	2412	14.18
	6	2437	13.21
	11	2462	13.31
IEEE 802.11n HT40	3	2422	13.61
	6	2437	12.41
	9	2452	13.26

Average Power

[2.4G WIFI]

Mode	Channel	Frequency(MHz)	Average Power (dBm)
IEEE 802.11b	1	2412	11.93
	6	2437	11.13
	11	2462	11.04
IEEE 802.11g	1	2412	11.18
	6	2437	11.26
	11	2462	10.38
IEEE 802.11n HT20	1	2412	10.58
	6	2437	9.65
	11	2462	9.76
IEEE 802.11n HT40	3	2422	10.05
	6	2437	8.83
	9	2452	9.69

5. Manufacturing Tolerance

[2.4G WIFI]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20SISO (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	13.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40SISO (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	12.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0

[2.4G WIFI]

11B (AVG)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11G (AVG)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.0	11.0	10.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20SISO (AVG)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	10.0	9.0	9.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40SISO (AVG)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	10.0	8.0	9.0
Tolerance ±(dB)	1.0	1.0	1.0

6. Evaluation Results

6.1 Standalone Evaluation

<BT>

Modulation Type	Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11b	2.462	5	12.0	15.8489	4.9736< 7.5	Yes
IEEE 802.11g	2.437	5	12.0	15.8489	4.9483< 7.5	Yes
IEEE 802.11n HT20	2.412	5	11.0	12.5893	3.9104< 7.5	Yes
IEEE 802.11n HT40	2.422	5	11.0	12.5893	3.9185< 7.5	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

6.2 Simultaneous Transmission for SAR Exclusion

The sample support one transmit modular. No need consider simultaneous transmission.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Test Firm Registration Number: 254912.

9. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Output power	:	1GHz-40GHz	±0.57dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....THE END OF REPORT.....