

RF EXPOSURE Test Report

Product: WiFi Camera

Trade Mark: SecKun

Model Number: AJ19, A24S, A24S-AJ19, AJ19Pro,
AJ19Max, SecKun19

FCC ID: 2BO9Y-AJ19

Prepared for

Shenzhen Photonova Tech Co.,Ltd
Room 205, No. 55 Ainan Road, Longdong Community, Baolong Street,
Longgang District, Shenzhen, China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 DESCRIPTION OF EUT..... 5

1.2 TEST MODE..... 5

1.3 TEST SETUP 5

2 TEST FACILITIES AND ACCREDITATIONS 6

2.1 TEST LABORATORY 6

2.2 ENVIRONMENTAL CONDITIONS 6

2.3 MEASUREMENT UNCERTAINTY 6

2.4 TEST SOFTWARE 6

3 LIST OF TEST EQUIPMENT 7

4 RF EXPOSURE 8

4.1 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS..... 8

Limit..... 8

Test Result 8

TEST RESULT CERTIFICATION

Applicant's Name.....: Shenzhen Photonova Tech Co.,Ltd
Address: Room 205, No. 55 Ainan Road, Longdong Community,
Baolong Street, Longgang District, Shenzhen, China
Manufacturer's Name: Shenzhen Photonova Tech Co.,Ltd
Address: Room 205, No. 55 Ainan Road, Longdong Community,
Baolong Street, Longgang District, Shenzhen, China

Product description

Product name: WiFi Camera
Model Number: AJ19, A24S, A24S-AJ19, AJ19Pro, AJ19Max, SecKun19

Standards.....: FCC CFR 47 PART 1, 1.1310

Test procedure.....: KDB 447498 D01 General RF Exposure Guidance v06

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.


Date of Test.....:

Date (s) of performance of tests.....: Apr 03, 2026~ Apr.20, 2026

Test Result.....: **Pass**

Testing Engineer : 
(Z o e S u)

Technical Manager : 
(G a r y L u)

Authorized Signatory : 
(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	WiFi Camera
Model name:	AJ19
Series Model:	A24S, A24S-AJ19, AJ19Pro, AJ19Max, SecKun19
Different of series model:	All the models are the same circuit and module, except the model No..
Operation frequency:	2.4G WIFI: IEEE 802.11b/g/n20: 2412-2462MHz IEEE 802.11n40: 2422-2452MHz BLE:2402 MHz to 2480 MHz
Modulation type:	2.4G WIFI: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n (HT20/H40): OFDM (BPSK, QPSK, 16QAM, 64QAM) BLE: GFSK
Bit Rate of transmitter:	2.4G WIFI: IEEE 802.11b: 1/2/5.5/11Mbps IEEE 802.11g: 6/9/12/18/24/36/48/54Mbps IEEE 802.11n(20MHz): MCS0-7, up to 150Mbps IEEE 802.11n(40MHz): MCS0-7, up to 300Mbps BLE: 1Mbps
Antenna type:	External Antenna
Antenna gain:	2.4G WIFI: 2.42dBi BLE: 2.47dBi
Battery:	DC 3.7V 8000mAh
Power supply:	DC 3.7V
Adapter information:	N/A

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	TX
2	/
3	/

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
RF Test System	MWRF	MTS 8310	V2.0.0.0

3 List of Test Equipment

RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaio Signal Generator	Agilent	N5181A	MY47070421	2025-05-07	2026-05-06
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2025-05-08	2026-05-07
3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2025-05-08	2026-05-07
4	HB-E044	Signal & spectrum Analyzer	R&S	FSV3044	101264	2025-05-07	2026-05-06
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2025-05-08	2026-05-07
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2025-05-09	2026-05-08

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4 RF Exposure

4.1 Standalone SAR test exclusion considerations

Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm².

If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Test Result

Antenna Type: External Antenna;

WIFI antenna gain: 2.42dBi

R = 20cm

$mW = 10^{(dBm/10)}$

antenna gain Numeric = $10^{(dBi/10)} = 10^{(2.42/10)} = 1.75$

BLE antenna gain: 2.47dBi

R = 20cm

$mW = 10^{(dBm/10)}$

antenna gain Numeric = $10^{(dBi/10)} = 10^{(2.47/10)} = 1.77$

2.4GHz WIFI:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power (dBm)	(mW)	Gain Numeric	Power density(mW/cm ²)	(mW/cm ²)
2412	802.11b	12.88	12±1	13	19.93	1.75	0.0069	1
2437		12.54	12±1	13	19.93	1.75	0.0069	1
2462		12.17	12±1	13	19.93	1.75	0.0069	1
2412	802.11g	12.09	12±1	13	19.93	1.75	0.0069	1
2437		11.55	11±1	12	15.85	1.75	0.0055	1
2462		11.27	11±1	12	15.85	1.75	0.0055	1
2412	802.11n H20	10.86	10±1	11	12.59	1.75	0.0044	1
2437		10.53	10±1	11	12.59	1.75	0.0044	1
2462		10.27	10±1	11	12.59	1.75	0.0044	1
2422	802.11n H40	9.97	9±1	10	10.00	1.75	0.0035	1
2437		9.35	9±1	10	10.00	1.75	0.0035	1
2452		9.17	9±1	10	10.00	1.75	0.0035	1

BLE:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power (dBm)	(mW)	Gain Numeric	Power density(mW/cm ²)	(mW/cm ²)
2402	GFSK	3.986	3±1	4	2.512	1.77	0.0009	1
2440		3.995	3±1	4	2.512	1.77	0.0009	1
2480		3.939	3±1	4	2.512	1.77	0.0009	1

Conclusion:

For the max result: 0.0069≤1g SAR, No SAR is required.

***** END OF REPORT *****