

FCC ID: 2BODM-EGL435

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-2.218	0.60	-2±1	-1.00	0.79	<5	0.24622	3.00	YES
	2.44	-2.309	0.59	-2±1	-1.00	0.79	<5	0.24816	3.00	YES
	2.480	-3.615	0.44	-3±1	-2.00	0.63	<5	0.19873	3.00	YES

2.4GHz SRD:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	7.62	5.78	7±1	8.00	6.31	<5	1.95576	3.00	YES

Note: $\text{dbm} = \text{dbuv/m} - 95.2 = 105.16 - 95.2 = 9.96 \text{ dBm (EIRP)}$, so the conduct peak power = $9.96 - 2.34 = 7.62 \text{ dBm}$

Conclusion:

For the max result : $1.95576 \leq \text{FCC Limit } 3.0$ for 1g SAR.